

```
mysql> INSERT INTO orders VALUES
-> (70001,150.50,'2012-10-05',3005,5002),
-> (70009,270.65,'2012-09-10',3001,5005),
-> (70002,65.26,'2012-10-05',3002,5001),
-> (70004,110.50,'2012-08-17',3009,5003),
-> (70007,940.50,'2012-09-10',3005,5002),
-> (70005,2400.60,'2012-07-27',3007,5001),
-> (70008,5700.00,'2012-09-10',3002,5001),
-> (70010,1903.43,'2012-10-10',3004,5006),
-> (70003,2400.40,'2012-10-10',3009,5003),
-> (70012,250.45,'2012-06-27',3008,5002),
-> (70011,75.29,'2012-08-17',3003,5007),
-> (70013,3045.60,'2012-04-25',3002,5001);
Query OK, 12 rows affected (0.01 sec)
Records: 12 Duplicates: 0 Warnings: 0
```

```
mysql> SELECT * FROM orders;
+-----+-----+-----+-----+-----+
| ord_no | purch_amt | ord_date | customer_id | salesman_id |
+-----+-----+-----+-----+-----+
| 70001 | 150.50 | 2012-10-05 | 3005 | 5002 |
| 70002 | 65.26 | 2012-10-05 | 3002 | 5001 |
| 70003 | 2400.40 | 2012-10-10 | 3009 | 5003 |
| 70004 | 110.50 | 2012-08-17 | 3009 | 5003 |
| 70005 | 2400.60 | 2012-07-27 | 3007 | 5001 |
| 70007 | 940.50 | 2012-09-10 | 3005 | 5002 |
| 70008 | 5700.00 | 2012-09-10 | 3002 | 5001 |
| 70009 | 270.65 | 2012-09-10 | 3001 | 5005 |
| 70010 | 1903.43 | 2012-10-10 | 3004 | 5006 |
| 70011 | 75.29 | 2012-08-17 | 3003 | 5007 |
| 70012 | 250.45 | 2012-06-27 | 3008 | 5002 |
| 70013 | 3045.60 | 2012-04-25 | 3002 | 5001 |
+-----+-----+-----+-----+-----+
12 rows in set (0.00 sec)
```

```
mysql> SELECT *
-> FROM orders
-> WHERE purch_amt > 2000;
+-----+-----+-----+-----+-----+
| ord_no | purch_amt | ord_date | customer_id | salesman_id |
+-----+-----+-----+-----+-----+
| 70003 | 2400.40 | 2012-10-10 | 3009 | 5003 |
| 70005 | 2400.60 | 2012-07-27 | 3007 | 5001 |
| 70008 | 5700.00 | 2012-09-10 | 3002 | 5001 |
| 70013 | 3045.60 | 2012-04-25 | 3002 | 5001 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> SELECT *
-> FROM orders
-> WHERE ord_date = '2012-09-10';
+-----+-----+-----+-----+-----+
| ord_no | purch_amt | ord_date | customer_id | salesman_id |
+-----+-----+-----+-----+-----+
| 70007 | 940.50 | 2012-09-10 | 3005 | 5002 |
| 70008 | 5700.00 | 2012-09-10 | 3002 | 5001 |
| 70009 | 270.65 | 2012-09-10 | 3001 | 5005 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> SELECT *
-> FROM orders
-> ORDER BY purch_amt DESC;
+-----+-----+-----+-----+-----+
| ord_no | purch_amt | ord_date | customer_id | salesman_id |
+-----+-----+-----+-----+-----+
| 70008 | 5700.00 | 2012-09-10 | 3002 | 5001 |
| 70013 | 3045.60 | 2012-04-25 | 3002 | 5001 |
| 70003 | 2400.40 | 2012-10-10 | 3009 | 5003 |
| 70005 | 2400.60 | 2012-07-27 | 3007 | 5001 |
| 70010 | 1903.43 | 2012-10-10 | 3004 | 5006 |
| 70007 | 940.50 | 2012-09-10 | 3005 | 5002 |
| 70009 | 270.65 | 2012-09-10 | 3001 | 5005 |
| 70012 | 250.45 | 2012-06-27 | 3008 | 5002 |
+-----+-----+-----+-----+-----+
```

```
mysql> SELECT SUM(purch_amt) AS total_revenue
-> FROM orders;
+-----+
| total_revenue |
+-----+
| 17541.18 |
+-----+
1 row in set (0.01 sec)
```

```
mysql> SELECT MAX(purch_amt) AS highest_order
-> FROM orders;
+-----+
| highest_order |
+-----+
| 5740.00 |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT MIN(purch_amt) AS lowest_order
-> FROM orders;
+-----+
| lowest_order |
+-----+
| 65.26 |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT COUNT(*) AS total_orders
-> FROM orders;
+-----+
| total_orders |
+-----+
| 12 |
+-----+
1 row in set (0.01 sec)
```

```
mysql> SELECT customer_id,
-> SUM(purch_amt) AS total_purchase
-> FROM orders
-> GROUP BY customer_id;
+-----+-----+
| customer_id | total_purchase |
+-----+-----+
| 3805 | 1899.00 |
| 3802 | 8870.86 |
| 3809 | 2590.90 |
| 3807 | 2400.60 |
| 3801 | 270.65 |
| 3804 | 1983.43 |
| 3803 | 75.29 |
| 3808 | 250.45 |
+-----+-----+
8 rows in set (0.01 sec)
```

```
mysql> SELECT customer_id,
-> MAX(purch_amt) AS highest_purchase
-> FROM orders
-> GROUP BY customer_id;
+-----+-----+
| customer_id | highest_purchase |
+-----+-----+
| 3805 | 948.58 |
| 3802 | 5740.00 |
| 3809 | 2400.40 |
| 3807 | 2400.60 |
| 3801 | 270.65 |
| 3804 | 1983.43 |
| 3803 | 75.29 |
| 3808 | 250.45 |
+-----+-----+
8 rows in set (0.00 sec)
```

```
mysql> SELECT customer_id,
-> SUM(purch_amt) AS total_purchase
```

3002	8870.86
3009	2590.90
3007	2400.60
3001	270.65
3004	1983.43
3003	75.29
3006	250.45

```

+-----+
8 rows in set (0.01 sec)

```

```
mysql> SELECT customer_id,  
->      MAX(purch_amt) AS highest_purchase  
-> FROM orders  
-> GROUP BY customer_id;
```

customer_id	highest_purchase
3005	948.50
3002	5760.00
3009	2480.40
3007	2400.60
3001	270.65
3004	1983.43
3003	75.29
3006	250.45

```
8 rows in set (8.00 sec)
```

```
mysql> SELECT customer_id,  
->      SUM(purch_amt) AS total_purchase  
-> FROM orders  
-> GROUP BY customer_id  
-> HAVING SUM(purch_amt) > 1000  
-> ORDER BY total_purchase DESC;
```

customer_id	total_purchase
3002	8870.86
3009	2590.90
3007	2400.60
3004	1983.43
3005	1099.00

```
5 rows in set (0.00 sec)
```

```
mysql> SELECT salesman_id,  
->      COUNT(*) AS total_orders  
-> FROM orders  
-> GROUP BY salesman_id  
-> HAVING COUNT(*) >= 2;
```

salesman_id	total_orders
5002	3
5001	4
5003	2

```
3 rows in set (0.00 sec)
```

```
mysql> SELECT ord_date,  
->      MAX(purch_amt) AS highest_purchase  
-> FROM orders  
-> GROUP BY ord_date  
-> HAVING MAX(purch_amt) > 2000;
```

ord_date	highest_purchase
2012-10-10	2480.40
2012-07-27	2400.60
2012-09-10	5760.00
2012-04-25	3045.60

```
4 rows in set (0.00 sec)
```

```
mysql>
```