```java
package simpletask;

public class Task11 {

    public static void main(String[] args) {
        byte a=7;
        short b=33;
        int c=44;
        long d=44556677l;
        float e=44.5566f;
        double f=666.7788855;
        char g='r';
        System.out.println(a<b);
        System.out.println(a);
        System.out.println(b);
        System.out.println(c);
        System.out.println(d);
        System.out.println(e);
        System.out.println(f);
        System.out.println(c);System.out.println(g);
    }

}
```

```
<terminated> Task11 [Java Application] C:\Users\STUDENT\.p2\pool\plugins\org.eclipse.justj.open
true
7
33
44
44556677
44.5566
666.7788855
44
r
```

Task2

```java
    public static void main(String[] args) {
        Scanner ss=new Scanner(System.in);
        System.out.print("a=");
        int a=ss.nextInt();
        System.out.print("b=");
        int b=ss.nextInt();
        System.out.println(a+b);
        a+=b;
        System.out.println(a-b);
        a-=b;
        System.out.println(a*b);
        a*=b;
        System.out.println(a/b);
        a/=b;
        System.out.println(a%b);
        System.out.print("x=");
        int x=ss.nextInt();
        System.out.print("y=");
        int y=ss.nextInt();
        System.out.println(x&y);
        System.out.println(x|y);
        System.out.println(x>y);
        System.out.println(x<y);
        System.out.println(x>=y);
        System.out.println(x<=y);
```

```
<terminated> Sample [Java Application] C:\Users\STUDENT\.p2\pool\plugins\org.eclipse.justj.oper
2420
44
44
x=55
y=66
2
119
false
true
```

Task3

```java
package demo;

public class task3 {

    public static void main(String[] args) {
        byte age=18;
        short year=2008;
        System.out.println("age:"+age);
        System.out.println("year:"+year);

    }

}
```

```
<terminated> task3 [Java Application] C:\Users\STUDENT\.p2\pool\plugins\org.eclipse.justj.openjd
age:18
year:2008
```

Task4

```java
package demo;

public class task4 {

    public static void main(String[] args) {
        float a=20.87f;
        float b=33.98f;
        System.out.println(a+b);

    }

}
```

```
<terminated> task3 [Java Application] C:\Users\STUDENT\.p2\pool\plugins\org.eclipse.justj.openjd
54.85
```

Task5

```java
package demo;

public class task5 {

    public static void main(String[] args) {
        double PI=3.146;
        System.out.println(PI);

    }

}
```

```
<terminated> task5 [Java Application] C:\Users\STUDENT\.p2\pool\plugins\or
3.146
```

Task6

```java
package demo;

public class task6 {

    public static void main(String[] args) {
        char a='d';
        int c=a;
        System.out.println(c);

    }

}
```

```
<terminated> task6 [Java Application] C:\Users\STUDENT\.p2\pool\plugins\org.eclipse.justj.openjd
100
```

Task7

```java
package demo;

public class task7 {

    public static void main(String[] args) {
        int a=100;
        int b=190;
        System.out.println(a==b);
        System.out.println(a<b);
        System.out.println(a>b);
        System.out.println(a<=b);
        System.out.println(a>=b);

    }

}
```

```
<terminated> task7 [Java Application] C:\Users\STUDENT\.p2\pool\plugins\
false
true
false
true
false
```

Task8

```java
package demo;

public class task8 {

    public static void main(String[] args) {
        int a=44;
        double g=a;
        System.out.println(g);

    }

}
```

```
<terminated> task7 [Java Application] C:\Users\STUDENT\.p2\pool
44.0
```

Task9

```java
package demo;

public class task9 {

    public static void main(String[] args) {
        String name="kumaran";
        int age=20;
        int salary=20000;
        System.out.println("name:"+name);
        System.out.println("age"+age);
        System.out.println("salary"+salary);



    }

}
```

```
<terminated> task9 [Java Application] C:\Users\STUDENT\.p2\pool\plug
name:kumaran
age20
salary20000
```

Task10

```java
package demo;

public class task10 {

    public static void main(String[] args) {
        int a=20;
        int b=30;
        System.out.println("before swapping a&b"+a+"
        int temp =a;
        a=b;
        b=temp;

        System.out.println("after swapping b:"+b);
        System.out.println("after swapping a:"+a);


    }

}
```

```
<terminated> task10 [Java Application] C:\Users\STUDENT\.p2\pool\plugins\org.eclipse.
before swapping a&b20 30
after swapping b:20
after swapping a:30
```

Hackerank

Change Theme Language Java 7

```java
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        Scanner scan = new Scanner(System.in);
        int a=scan.nextInt();
        int b=scan.nextInt();
        int c=scan.nextInt();
        System.out.println(a+"\n"+b+"\n"+c);
    }
}
```

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases

Sample Test case 0

Input (stdin)

```
42
100
125
```

Your Output (stdout)

```
42
100
125
```

Expected Output

```
42
100
```

Change Theme Language Java 7

```java
public class Solution {

    public static void main(String[] args) {
        System.out.println("Hello, World.");
        System.out.println("Hello, Java.");
    }
}
```

Upload Code as File Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Your Output (stdout)

```
Hello, World.
Hello, Java.
```

Expected Output Download

```
Hello, World.
Hello, Java.
```