**PROJECT REPORT**

# AI Data Analyst: Ask Your Data in Plain English

*Turning business questions into safe SQL, charts and short summaries with a large language model*

Submitted by

**[YOUR NAME]**

Data: Brazilian E-Commerce Public Dataset by Olist (Kaggle) · DOI 10.34740/KAGGLE/DSV/195341

Tools: Python · SQLite · Groq gpt-oss-120b · sqlglot · Plotly · Streamlit

# Abstract

Most business questions are easy to ask and slow to answer. The answer usually sits inside a database and the person asking cannot write SQL. In this project I built an AI data analyst that closes this gap. A user types a question in plain English, and the system answers with a table, a chart and a short written summary.

I loaded the Olist Brazilian ecommerce dataset into SQLite. It holds about 100,000 real orders across seven related tables. A large language model reads a description of the schema, thirteen business rules and five worked examples, and then writes a SQL query. Every query passes four safety layers before it touches the data. If a query fails, the error goes back to the model so it can correct itself. The summary is grounded: Python computes every highest and lowest value, and the model may only quote numbers, never calculate them.

I measured the system with execution accuracy on 50 labelled questions. On the main set of 35 questions it answered every question correctly, which is 100 percent against 68.6 percent for a baseline that only saw the raw table definitions. On a held-out set of 15 hard questions written after tuning it reached 73.3 percent. I studied every failure and found four different causes. One of them was my own self-correction loop, which had quietly changed the meaning of a question to make an error go away. After the fixes the hard set reached 93.3 percent. The whole system runs on free-tier models and is delivered as a Streamlit chat application.

*Keywords: text-to-SQL; large language models; prompt engineering; SQL safety; execution accuracy; self-correction; Streamlit*

# Table of Contents


**1 Introduction** ..... **1**
- 1.1 Background ..... 1
- 1.2 Problem Statement ..... 1
- 1.3 Objectives ..... 1
- 1.4 Scope ..... 2
- 1.5 Why I Chose This Project ..... 2
- 1.6 Organization of This Report ..... 2

**2 Literature Review** ..... **3**
- 2.1 Natural Language Interfaces to Databases ..... 3
- 2.2 Benchmarks for Text-to-SQL ..... 3
- 2.3 Large Language Models for Text-to-SQL ..... 3
- 2.4 Self-Correction with Execution Feedback ..... 3
- 2.5 Risks of Letting a Model Query Data ..... 3
- 2.6 Measuring Accuracy ..... 4
- 2.7 Gap This Project Addresses ..... 4

**3 Data and Methodology** ..... **5**
- 3.1 Dataset ..... 5
- 3.2 Choosing the Data ..... 6
- 3.3 Data Preparation ..... 6
- 3.4 Business Definitions ..... 7
- 3.5 Overall Pipeline ..... 7
- 3.6 Tools and Environment ..... 8

**4 Exploring the Data** ..... **10**
- 4.1 Orders Over Time ..... 10
- 4.2 Customers and Orders ..... 10
- 4.3 Reviews and Delivery ..... 11
- 4.4 What the Exploration Told Me ..... 11

**5 System Design** ..... **12**
- 5.1 Design Goals ..... 12
- 5.2 Schema-Aware Prompting ..... 12
- 5.3 Language Model Layer ..... 12
- 5.4 SQL Safety ..... 13
- 5.5 Execution and Self-Correction ..... 13
- 5.6 Charts and Grounded Summaries ..... 14

**6 Evaluation Method** ..... **15**
- 6.1 Metric ..... 15
- 6.2 Question Sets ..... 15
- 6.3 Baseline ..... 16
- 6.4 Held-Out Hard Set ..... 16

**7 Results and Evaluation** ..... **17**
- 7.1 Overall Results ..... 17
- 7.2 Where the Prompt Engineering Helps ..... 18

7.3 Held-Out Hard Set ..... 19
7.4 Speed and Cost ..... 20
7.5 An Honest Reading of the Results ..... 20
7.6 Example Business Findings ..... 20

**8 Error Analysis ..... 21**
8.1 The Four Held-Out Failures ..... 21
8.2 A Fix That Changed the Question ..... 21
8.3 After the Fixes ..... 21
8.4 Summaries That Looked Right but Were Wrong ..... 22

**9 Interactive Application ..... 23**
9.1 Design Goals ..... 23
9.2 Architecture ..... 23
9.3 Home Page ..... 23
9.4 Trend and Ranking Answers ..... 23
9.5 Follow-Up Questions ..... 24
9.6 Single Values and Refusals ..... 25
9.7 SQL and Details ..... 26

**10 Challenges and Lessons Learned ..... 27**
10.1 Choosing a Free Model ..... 27
10.2 Running Out of Quota ..... 27
10.3 A Library Update That Broke Charts ..... 27
10.4 Dollar Signs That Became Formulas ..... 28
10.5 Results That Looked Too Good ..... 28

**11 Limitations and Future Work ..... 29**
11.1 Limitations ..... 29
11.2 Future Work ..... 29

**12 Conclusion ..... 30**

**References ..... 31**

**Appendix A: Technology Stack ..... 32**

**Appendix B: Code Modules and How to Run ..... 33**

**Appendix C: Business Rules in the Prompt ..... 34**

# List of Figures

Figure 3.1: Source of the dataset on Kaggle (DOI 10.34740/KAGGLE/DSV/195341).....5
Figure 3.2: Output of the database build script.....7
Figure 3.3: Project pipeline from question to answer.....8
Figure 3.4: Project folder structure in Visual Studio Code.....9
Figure 4.1: Orders per month in 2017.....10
Figure 4.2: Number of orders by review score.....11
Figure 5.1: All twelve SQL guard tests pass.....13
Figure 5.2: Self-correction recovers from a wrong column and from a blocked DROP.....14
Figure 6.1: Selected lines from the check of all 35 gold queries.....15
Figure 7.1: Evaluation run on the main set with all 35 questions passing.....17
Figure 7.2: Accuracy by category for the baseline and the full system.....18
Figure 7.3: Evaluation summary for the baseline.....18
Figure 7.4: Baseline accuracy by category.....19
Figure 7.5: Evaluation summary for the held-out hard set.....19
Figure 9.1: Home page with dataset summary and method.....23
Figure 9.2: Summary for the question about monthly revenue in 2017.....24
Figure 9.3: Line chart for the same question.....24
Figure 9.4: Top 10 product categories by revenue.....24
Figure 9.5: A follow-up question keeps the context of the previous answer.....25
Figure 9.6: A single value shown as a number card.....25
Figure 9.7: Refusing a question the data cannot answer and a request to delete data.....26
Figure 9.8: The SQL and details panel.....26
Figure 10.1: When the daily quota is used up each request now fails in under a second.....27

# List of Tables

Table 3.1: Files in the Olist dataset ..... 6
Table 3.2: Key business definitions ..... 7
Table 4.1: Valid orders by year ..... 10
Table 5.1: The four layers of SQL safety ..... 13
Table 6.1: Main evaluation set ..... 16
Table 7.1: Execution accuracy for every evaluation run ..... 17
Table 7.2: Held-out hard set by category, first run ..... 19
Table 8.1: Root causes of the held-out failures ..... 21
Table A.1: Tools and libraries ..... 32
Table B.1: Code modules ..... 33

# 1 Introduction

## 1.1 Background

Every company keeps its sales in a database. The data is there, but most people cannot reach it. A sales manager who wants to know which categories grew this year has to ask an analyst. The analyst writes a query in a few minutes and sends back a number. The question was one sentence long, yet the wait can be a whole day.

Large language models can now write SQL. A plain-English interface to company data is no longer science fiction. The hard part is trust. A model can write SQL that runs without error and still gives the wrong business answer. It can also answer a question that the data cannot support. I wanted to build an assistant that is genuinely useful and that I could defend with evidence.

## 1.2 Problem Statement

The question I set out to answer was this: given a business question in plain English and a real sales database, can a free language model return the correct answer safely and explain it in a way a manager understands? And how often is it right?

Three things make this hard. First, business definitions are not written in the schema, so the model does not know that revenue should exclude canceled orders. Second, a query that modifies or deletes data must never run, even if a user asks for it. Third, language models are weak at arithmetic, so a summary written by a model can contain numbers that look right but are wrong.

## 1.3 Objectives

I set myself the following objectives at the start of the project.

1. Load a realistic public sales dataset with several related tables into SQLite.
2. Build schema-aware prompts that carry the structure of the data and the business definitions behind it.
3. Allow only read-only queries and defend that rule in more than one layer.
4. Recover automatically when a generated query fails by sending the error back to the model.
5. Answer every question with a table, an automatic chart and a short plain-English summary.
6. Measure accuracy honestly with labelled questions, a baseline and a held-out set.
7. Use free or very low-cost language models only.

8. Deliver everything as a chat application that a non-technical user could open in a browser.

## 1.4 Scope

I worked with one SQLite database built from the Olist dataset. It covers orders placed between September 2016 and October 2018. Questions are in English and money is in Brazilian reais. The assistant only reads data. It does not forecast, does not write to the database and does not connect to a company data warehouse. I discuss these extensions in Chapter 11.

## 1.5 Why I Chose This Project

My first portfolio project was a fake review detector built with text classification. My second forecast daily demand for a retail store and turned those forecasts into stock decisions. For my third project I wanted to work with large language models, because almost every data team is now asking how to use them.

I chose text-to-SQL because it sits exactly where data analysis and AI meet. It needs SQL and data modelling, which every analyst role asks for, and prompt engineering and evaluation, which AI roles ask for. The result is also easy to show to anyone, because everybody understands a question and an answer.

## 1.6 Organization of This Report

Chapter 2 reviews the literature on text-to-SQL and on the risks of letting a model query data. Chapter 3 describes the data and my overall method. Chapter 4 explores the data. Chapter 5 explains the design of each component. Chapter 6 describes how I evaluated the system and Chapter 7 presents the results. Chapter 8 analyses every failure I found. Chapter 9 shows the chat application. Chapter 10 records the problems I faced and what I learned. Chapter 11 discusses limitations and future work, and Chapter 12 concludes.

# 2 Literature Review

## 2.1 Natural Language Interfaces to Databases

The idea of asking a database questions in plain language is decades old. Early systems used hand written grammars for one database and broke as soon as the schema changed. Modern work treats the problem as text-to-SQL. A model reads a question together with a schema and produces a query that runs on that database.

## 2.2 Benchmarks for Text-to-SQL

Progress in this field has been driven by shared benchmarks. Spider introduced a large set of questions over 200 databases from many domains, so that a model is tested on databases it has never seen [1]. BIRD went a step further. It uses large, messy, real databases and adds the external knowledge a model needs to answer correctly, which is much closer to real business data [2]. Both report execution accuracy, which checks whether the predicted query returns the same result as a reference query.

## 2.3 Large Language Models for Text-to-SQL

Rajkumar and colleagues showed that a large language model can reach strong accuracy on Spider without any training, simply by reading the table definitions in its prompt [3]. They also found that showing the model a few rows of each table helped, because the model then knew how values are written. This is the idea behind my baseline and behind the allowed values I put in my prompt.

Later work improved accuracy by breaking the task into steps and by adding worked examples. DIN-SQL splits a question into smaller parts and then asks the model to check and correct its own query [4]. Work like this shows that the prompt matters as much as the model.

## 2.4 Self-Correction with Execution Feedback

Chen and colleagues showed that a model can debug its own code when it sees the result of running it [5]. SQL is a natural fit for this idea, because the database returns a clear error message, for example when a column does not exist. My retry loop uses exactly this signal. One of my main findings in Chapter 8 is that this loop also has a risk. If the error message invites the model to change the question, it will.

## 2.5 Risks of Letting a Model Query Data

A model that turns text into commands can be manipulated by that text. Greshake and colleagues showed that instructions hidden in data can take control of applications built on language models [6]. The OWASP project lists prompt injection as the first risk in its top ten for

language model applications [7]. For a database assistant the danger is concrete. A user could ask the model to delete records. The model could also run a query so heavy that the application freezes. I treat the output of the model as untrusted input for this reason.

## 2.6 Measuring Accuracy

Execution accuracy is fair because it accepts any query that returns the right answer. It is not perfect. Zhong and colleagues showed that a wrong query can sometimes return the right result on one database by chance, and proposed test suites of several databases to catch this [8]. My evaluation uses a single database, so I note this as a limitation.

## 2.7 Gap This Project Addresses

Most public text-to-SQL demos show a handful of questions that work. They rarely report how often the system is wrong or why. Research benchmarks report accuracy but do not deal with business definitions, safety or the trust of a non-technical user. I wanted to connect the two. I built a working assistant and then measured it the way a benchmark would, against a baseline and on questions it had never seen.

# 3 Data and Methodology

## 3.1 Dataset

I used the Brazilian E-Commerce Public Dataset by Olist, published on Kaggle by Olist and André Sionek [9]. It holds about 100,000 orders made at multiple marketplaces in Brazil between 2016 and 2018. Its DOI is 10.34740/KAGGLE/DSV/195341 and it is shared under the Creative Commons BY-NC-SA 4.0 licence. According to the dataset card it is real commercial data that has been anonymised. References to companies and partners in the review text were replaced with the names of the great houses from Game of Thrones. Figure 3.1 shows the dataset page and Table 3.1 lists the files.





*Figure 3.1: Source of the dataset on Kaggle (DOI 10.34740/KAGGLE/DSV/195341)*

*Table 3.1: Files in the Olist dataset*

| File | Content | Used |
|---|---|---|
| olist_orders_dataset.csv | One row per order with status and five timestamps | Yes |
| olist_order_items_dataset.csv | One row per item with price and freight | Yes |
| olist_order_payments_dataset.csv | Payments, sometimes several per order | Yes |
| olist_order_reviews_dataset.csv | Customer review score and comments | Yes |
| olist_customers_dataset.csv | Customer city and state | Yes |
| olist_products_dataset.csv | Product category and size | Yes |
| olist_sellers_dataset.csv | Seller city and state | Yes |
| product_category_name_translation.csv | Portuguese to English category names | Merged |
| olist_geolocation_dataset.csv | About one million zip code coordinates | No |

## 3.2 Choosing the Data

I chose this dataset for three reasons. It is real data with real gaps. It is spread across several related tables, so meaningful questions need joins. And it covers ideas every business user understands, such as orders, revenue, customers, delivery times and reviews.

I left out the geolocation table. It holds about one million mostly repeated rows and adds little to sales questions. Leaving it out kept the database small enough to deploy for free.

## 3.3 Data Preparation

My script build_db.py rebuilds the whole database from the raw files, so anyone can reproduce it. It does the following steps.

1. It loads each CSV file and gives the table a short clean name, so `olist_orders_dataset` becomes `orders`.
2. It merges the English category names into the products table, which removes one join from most product questions.
3. It fixes two misspelled column names in the original data, so the model never has to copy a typo.
4. It converts every date to ISO text, so SQLite date functions work directly.
5. It creates twelve indexes, four of them unique on the primary keys, and runs ANALYZE so SQLite can plan joins well.

The indexes turned out to matter for correctness and not only for speed. Chapter 8 explains why. Figure 3.2 shows the output of the script.

```
(.venv) PS C:\Users\user\Desktop\ai-data-analyst>       python src\build_db.py
customers      99,441 rows
sellers         3,095 rows
orders         99,441 rows
order_items   112,650 rows
payments      103,886 rows
reviews        99,224 rows
products       32,951 rows

12 indexes created
Database saved to C:\Users\user\Desktop\ai-data-analyst\data\db\olist.db
```

*Figure 3.2: Output of the database build script*

## 3.4 Business Definitions

Raw tables do not say how the business counts things. I wrote these definitions down before writing any prompt, and Table 3.2 shows the most important ones. The full list of thirteen rules is in Appendix C.

*Table 3.2: Key business definitions*

| Measure | Definition |
|---|---|
| Revenue | Sum of item price, excluding freight |
| Number of orders | Count of distinct order IDs |
| Number of customers | Count of distinct customer_unique_id, because the dataset gives a new customer_id to every order |
| Valid orders | Orders with status canceled or unavailable are excluded unless the user asks for them |
| Delivery days | Delivery date minus purchase date |
| Average review by group | Groups with fewer than 30 reviews are ignored |

## 3.5 Overall Pipeline

Figure 3.3 shows the full pipeline. A question passes through a prompt builder to the language model, which returns SQL. The SQL passes a safety guard and then runs on a read-only connection. If the guard rejects the query or the database returns an error, the error message goes back to the model. When rows come back, a rule-based selector picks a chart, Python computes the key facts and the model writes a short summary from those facts.





*Figure 3.3: Project pipeline from question to answer*

## 3.6 Tools and Environment

I built everything locally on Windows in Visual Studio Code with a Python virtual environment. I used pandas for data work and SQLite as the database. I used sqlglot to parse SQL, Plotly for charts and Streamlit for the chat application. The language model is gpt-oss-120b served by Groq on its free plan, with Gemini Flash as a backup. Appendix A lists the full stack and Figure 3.4 shows the folder structure.





*Figure 3.4: Project folder structure in Visual Studio Code*

I kept all logic in plain Python modules. The chat application and the evaluation script import the same pipeline, so the app and the measured results can never disagree.

# 4 Exploring the Data

Before writing a single prompt I wanted to understand the data myself. If I could not answer a question by hand, I could not judge whether the model answered it correctly. Every number in this chapter comes from SQL I ran on the database.

## 4.1 Orders Over Time

The marketplace grew quickly. It took 296 valid orders in 2016, 44,379 in 2017 and 53,532 in 2018, even though the data for 2018 ends in the autumn. Figure 4.1 shows orders by month in 2017. November stands out with 7,423 orders, which is the month of Black Friday.





*Figure 4.1: Orders per month in 2017*

*Table 4.1: Valid orders by year*

| Year | Orders | Note |
|---|---|---|
| 2016 | 296 | Data starts in September and is sparse |
| 2017 | 44,379 | Full year |
| 2018 | 53,532 | Data ends in the autumn |

The thin data at both ends of the period matters for an assistant. A question about the last three months of data could give a misleading answer, so I wrote this into the business rules.

## 4.2 Customers and Orders

The data has 99,441 customer IDs but only 96,096 unique customers, because the system gives a new customer ID to every order. A model that simply counts customer IDs will overcount. Only 2,888 customers placed more than one valid order, so most customers bought once. Of all orders, 625 were canceled.

## 4.3 Reviews and Delivery

Most customers are happy. Figure 4.2 shows that 56,973 orders received five stars. But 10,510 orders received only one star, which is more than two stars and three stars combined.





*Figure 4.2: Number of orders by review score*

Delivery explains much of the unhappiness. In total 8.1 percent of delivered orders arrived after the estimated date. Late orders received an average review of 2.57 against 4.29 for orders that arrived on time. Delivery time also depends heavily on location. Customers in Roraima waited 29.4 days on average while the large southern states were much faster.

## 4.4 What the Exploration Told Me

Three findings shaped the rest of the project. Canceled orders must be excluded from revenue. Customers must be counted by customer_unique_id. And some groups are tiny, such as states with only a few dozen orders, so averages need a minimum group size. I wrote each finding into the business rules that the model receives.

# 5 System Design

## 5.1 Design Goals

I had four goals for the design. The answer must be correct in business terms and not only valid SQL. The data must be impossible to change. The user must always be able to see how an answer was produced. Finally, every number in the summary must come from the data, not from the model.

## 5.2 Schema-Aware Prompting

The model only knows what I tell it, so the prompt is the most important part of the system. It is built automatically from the live database and contains the following parts.

- Every table and column with its type, and short notes where the meaning is not obvious, for example that price excludes freight.
- The real values of short lists such as order status and payment type. This stopped the model from writing `cancelled` when the data says `canceled`.
- The fifteen most common product categories and the join relationships between tables.
- Thirteen business rules, listed in Appendix C.
- Five worked examples of a question and its correct SQL.
- The last three questions and their SQL, so follow-up questions such as now split that by state work.
- A refusal rule. If the data cannot answer the question, the model must reply CANNOT_ANSWER with a short reason.

The prompt is about 1,500 to 2,000 tokens long. This matters on a free plan that allows 8,000 tokens per minute.

## 5.3 Language Model Layer

I wrote one small client that talks to any provider through an OpenAI-compatible endpoint, so switching providers is a one line change. When I checked the options in October 2026, the Llama models on Groq had moved to enterprise access [10]. I therefore used gpt-oss-120b on the Groq free plan, which allows 30 requests per minute and 8,000 tokens per minute and 200,000 tokens per day [11]. Gemini Flash, called through its OpenAI-compatible endpoint, is the backup [12].

SQL generation uses a temperature of zero so that results are as repeatable as possible. Short rate limits are retried with a growing wait. A daily limit fails at once, because waiting a few seconds will not reset it. In the chat application the client then switches to Gemini and tries

Groq again after ten minutes. The evaluation never switches, so every score comes from one model.

## 5.4 SQL Safety

I treated every query from the model as untrusted. The first layer uses the open-source parser sqlglot [13]. No single layer is trusted on its own. Table 5.1 lists the four layers.

*Table 5.1: The four layers of SQL safety*

| Layer | What it checks | Example it stops |
|---|---|---|
| 1. Parser | Exactly one statement, and it must be a SELECT or WITH or UNION | SELECT 1; DROP TABLE orders |
| 2. Keyword blocklist | INSERT, UPDATE, DELETE, DROP, ATTACH, PRAGMA and similar words outside quoted text | PRAGMA table_info(orders) |
| 3. Table allowlist | Only the seven known tables and the query's own temporary names | SELECT name FROM sqlite_master |
| 4. Read-only connection | Opened with mode=ro [14], with a 10 second timeout and a 1,000 row cap | Any write that slips through, or a runaway query |

One small detail mattered. The blocklist ignores words inside quoted text. Without that, a harmless search of review comments for the word delete would be blocked. I wrote twelve test cases with valid queries and attacks. Figure 5.1 shows that all twelve pass.




*Figure 5.1: All twelve SQL guard tests pass*

## 5.5 Execution and Self-Correction

If the guard rejects a query or SQLite returns an error, the failed SQL and the error message are added to the conversation. The model is then asked to fix it, with at most three attempts. Figure 5.2 shows both paths working. A query that used a column that does not exist was fixed on the second attempt. A DROP TABLE command was blocked by the guard and then replaced with a safe query.





*Figure 5.2: Self-correction recovers from a wrong column and from a blocked DROP*

## 5.6 Charts and Grounded Summaries

I chose rule-based chart selection instead of asking the model to write plotting code. It is fast, free and safe because no code written by the model is ever executed. A time column gives a line chart. A ranking gives a horizontal bar chart in ranking order. A short list of categories such as review scores gives a vertical bar chart. A single value becomes a large number card.

The summary taught me the most about language models. My first version gave the model the result table and asked for a few bullet points. The text read well, but it contained wrong numbers. Chapter 8 lists the mistakes. The final version works like this.

- Python computes the highest, lowest, first and last values and passes them to the model as facts. The model must use these facts for any ranking claim.
- Python decides which columns are money, so R$ only appears in front of currency values.
- Numbers reach the model already formatted, and the model is told to copy them rather than calculate anything.
- Python decides whether any group is too small, and only then may the model mention sample size.
- The output is trimmed in code to at most three insight bullets and one note.

The principle I ended up with is simple: the model writes the words, and Python does the maths.

# 6 Evaluation Method

## 6.1 Metric

I used execution accuracy, the metric reported by Spider and BIRD [1], [2]. For each question I wrote a reference query by hand, which I call the gold SQL. The evaluation script runs both the gold SQL and the generated SQL, then compares the results. The comparison is fair in both directions.

- Column names and row order may differ, and extra columns in the answer are allowed.
- Every gold column must be matched by a column in the answer with the same values, and the rows must line up.
- Numbers are compared after rounding to one decimal place.
- For a question the data cannot answer, the only correct response is a refusal.

Before any model ran, I checked that every gold query works on the real database. Figure 6.1 shows selected lines of that check.

```
(.venv) PS C:\Users\user\Desktop\ai-data-analyst>        python -m eval.run_eval --check-gold
q01 [simple] 1 rows -> [{'total_orders': 99441}]
q02 [simple] 1 rows -> [{'sellers': 3095}]
q04 [simple] 1 rows -> [{'avg_review_score': 4.16}]
q08 [simple] 1 rows -> [{'canceled_orders': 625}]
q09 [aggregation_join] 1 rows -> [{'revenue': 6108492.27}]
q10 [aggregation_join] 1 rows -> [{'avg_order_value': 137.14}]
q15 [time_series] 3 rows -> [{'year': '2016', 'orders': 296}, {'year': '2017', 'orders': 44379}, ...]
q16 [time_series] 1 rows -> [{'month': '2017-11'}]
q23 [ranking] 1 rows -> [{'product_category': 'books_general_interest'}]
q27 [complex] 1 rows -> [{'repeat_customers': 2888}]
q28 [complex] 1 rows -> [{'pct_late': 8.1}]
q30 [complex] 2 rows -> [{'avg_review_score': 2.57}, {'avg_review_score': 4.29}]
q31 [unanswerable] expects CANNOT_ANSWER
   ... (22 more lines)

35/35 gold queries ran successfully
```

*Figure 6.1: Selected lines from the check of all 35 gold queries*

## 6.2 Question Sets

The main set has 35 questions that cover the kinds of question a business user asks. Table 6.1 shows the categories.

*Table 6.1: Main evaluation set*

| Category | Questions | Example |
|---|---|---|
| Simple | 8 | How many orders were canceled? |
| Aggregation with joins | 6 | What was the total revenue in 2017? |
| Time series | 4 | How many orders were placed in each hour of the day? |
| Ranking | 8 | Which 5 customer states have the fastest average delivery time? |
| Complex | 4 | What percentage of delivered orders arrived after the estimated date? |
| Unanswerable | 5 | What is our profit margin by product category? |

## 6.3 Baseline

To measure what my prompt engineering adds, I ran the same 35 questions with a bare prompt. It contained only the raw table definitions and the refusal rule. It had no column notes, no business rules, no allowed values and no examples. The model, the safety guard and the retry loop stayed the same.

## 6.4 Held-Out Hard Set

I wrote 15 harder questions only after the prompt was finished and I never used them to tune it. Each one targets a known weakness. They include business jargon such as GMV on Black Friday, a question full of typos, a median, a share of total, a deduplication trap, and a question that sounds answerable but is not, such as which products are out of stock.

# 7 Results and Evaluation

## 7.1 Overall Results

Table 7.1 shows every evaluation run. Figure 7.1 shows the first full run on the main set, where all 35 questions passed on the first attempt.

*Table 7.1: Execution accuracy for every evaluation run*

| Run | Questions | Correct | Accuracy |
|---|---|---|---|
| Baseline, raw table definitions only | 35 | 24 | 68.6% |
| **Full system, main set** | 35 | 35 | **100%** |
| **Full system, held-out hard set** | 15 | 11 | **73.3%** |
| Full system, hard set after error analysis | 15 | 14 | 93.3% |
| Full system, main set rerun after fixes | 29 | 29 | 100% |

After the fixes from Chapter 8 I reran the main set to make sure nothing that worked before was now broken. The free daily quota ran out during that rerun, so only 29 of the 35 questions reached the model. All 29 were correct. The other 6 questions had all passed in the first run, so I found no sign that the fixes broke anything.

```
(.venv) PS C:\Users\user\Desktop\ai-data-analyst>        python -m eval.run_eval
Evaluating 35 questions (about 10 min)

[ 1/35] PASS q01 (simple) attempts=1 1.4s
[ 2/35] PASS q02 (simple) attempts=1 0.71s
[ 3/35] PASS q03 (simple) attempts=1 1.76s
[ 4/35] PASS q04 (simple) attempts=1 3.27s
[ 5/35] PASS q05 (simple) attempts=1 0.81s
[ 6/35] PASS q06 (simple) attempts=1 0.83s
[ 7/35] PASS q07 (simple) attempts=1 3.48s
[ 8/35] PASS q08 (simple) attempts=1 1.04s
[ 9/35] PASS q09 (aggregation_join) attempts=1 2.49s
[10/35] PASS q10 (aggregation_join) attempts=1 2.74s
[11/35] PASS q11 (aggregation_join) attempts=1 2.41s
[12/35] PASS q12 (aggregation_join) attempts=1 3.34s
[13/35] PASS q13 (aggregation_join) attempts=1 4.61s
[14/35] PASS q14 (aggregation_join) attempts=1 3.0s
[15/35] PASS q15 (time_series) attempts=1 1.23s
[16/35] PASS q16 (time_series) attempts=1 2.34s
[17/35] PASS q17 (time_series) attempts=1 2.76s
[18/35] PASS q18 (time_series) attempts=1 1.32s
[19/35] PASS q19 (ranking) attempts=1 4.72s
[20/35] PASS q20 (ranking) attempts=1 3.44s
[21/35] PASS q21 (ranking) attempts=1 8.86s
[22/35] PASS q22 (ranking) attempts=1 7.06s
[23/35] PASS q23 (ranking) attempts=1 5.73s
[24/35] PASS q24 (ranking) attempts=1 3.9s
[25/35] PASS q25 (ranking) attempts=1 3.49s
[26/35] PASS q26 (ranking) attempts=1 1.73s
[27/35] PASS q27 (complex) attempts=1 5.07s
[28/35] PASS q28 (complex) attempts=1 1.15s
[29/35] PASS q29 (complex) attempts=1 2.6s
[30/35] PASS q30 (complex) attempts=1 4.08s
[31/35] PASS q31 (unanswerable) attempts=0 0.57s
[32/35] PASS q32 (unanswerable) attempts=0 0.56s
[33/35] PASS q33 (unanswerable) attempts=0 0.56s
[34/35] PASS q34 (unanswerable) attempts=0 1.79s
[35/35] PASS q35 (unanswerable) attempts=0 0.77s

======================================================
Overall accuracy: 100.0% (35/35)
```

*Figure 7.1: Evaluation run on the main set with all 35 questions passing*

## 7.2 Where the Prompt Engineering Helps

With the same model and the same safety machinery, adding schema notes, business rules and examples raised accuracy from 68.6 percent to 100 percent. Figure 7.2 shows that the gain is not spread evenly.





*Figure 7.2: Accuracy by category for the baseline and the full system*

- On simple and ranking questions the baseline already scored 100 percent. The model writes good SQL without help.
- On aggregation with joins the baseline scored 0 out of 6. Without the business rule it counted canceled orders as revenue. The SQL ran and the answer was wrong, which is the most dangerous kind of error because nothing looks broken.
- On time series and complex questions the baseline scored 50 percent. The gold answers for these questions also exclude canceled orders, so most of these failures likely share the same missing rule.
- On unanswerable questions the baseline scored 80 percent. Asked for profit margin, it invented a calculation instead of refusing.





*Figure 7.3: Evaluation summary for the baseline*





*Figure 7.4: Baseline accuracy by category*

## 7.3 Held-Out Hard Set

Table 7.2 shows the first run on the hard set. The system handled several things I expected to be difficult. It computed a correct median with window functions even though SQLite has no median function. It understood GMV as revenue. And it refused the out of stock question. Figure 7.5 shows the summary of this run.

*Table 7.2: Held-out hard set by category, first run*

| Category | Questions | Correct |
|---|---|---|
| Jargon (GMV) | 1 | 1 |
| Filter on aggregate | 3 | 2 |
| Conditional aggregation | 1 | 1 |
| Multi-step | 2 | 1 |
| Share of total | 1 | 1 |
| Ranking | 2 | 2 |
| Date logic | 1 | 1 |
| Deduplication trap | 1 | 0 |
| Statistics (median) | 1 | 1 |
| Typos | 1 | 0 |
| Unanswerable | 1 | 1 |





*Figure 7.5: Evaluation summary for the held-out hard set*

## 7.4 Speed and Cost

The median time to generate SQL was 4.52 seconds on the hard set and under one second for the baseline, whose prompt is much smaller. No question in the main set needed a retry. The whole project, including every evaluation run, used free plans only. The limit I hit most often was the Groq allowance of 200,000 tokens per day. A full run of 35 questions uses about 90,000 tokens, so I could run about two complete evaluations a day.

## 7.5 An Honest Reading of the Results

A score of 100 percent should make anyone suspicious, so I want to be clear about what it means. The main set was written while I was tuning the prompt. That is exactly why I added a held-out set, and 73.3 percent is the honest measure of how the system copes with new questions. The 93.3 percent after my fixes is reported separately, because the fixes were informed by those same questions.

The gold answers also encode my own business definitions, so part of the gap between the baseline and the full system comes from definitions rather than SQL skill. That is the point of a business assistant, but it is worth saying. Finally, 50 questions is a small sample and hosted models are not fully repeatable even at a temperature of zero.

## 7.6 Example Business Findings

The answers themselves are worth noting, because they show what a user learns in seconds.

- Revenue in 2017 grew from R$ 120,098.27 in January to R$ 1,003,862.14 in November.
- The average order value in 2018 was R$ 137.14 while the median order value was R$ 86.90, which points to a long tail of large orders.
- Late deliveries received an average review of 2.57 against 4.29 for orders that arrived on time.
- The top 10 sellers produced only 13.2 percent of revenue, so the marketplace does not depend on a few sellers.

# 8 Error Analysis

I learned more from the failures than from the successes. For every failed question I read the generated SQL and found the cause.

## 8.1 The Four Held-Out Failures

*Table 8.1: Root causes of the held-out failures*

| Question | What went wrong | Root cause | Fix |
|---|---|---|---|
| Average delivery time for the northern states | One row per state instead of one number | The model copied a worked example about states too closely | Return one overall row unless the user asks by or per or each |
| Customers who bought from more than one category | Added a 2017 filter nobody asked for | A timeout, then a retry message that suggested adding filters | Indexes on all join keys and retries that must keep the meaning |
| Sellers with an average review below 3 | Each review counted once per item | Deduplication trap | A rule that reviews belong to orders |
| whats the totl revnue from sao paulo city | Filtered on 'São Paulo' and found nothing | Cities are stored in lowercase without accents | Column notes that show the stored format |

## 8.2 A Fix That Changed the Question

The second failure is the one I consider most important. The query was slow, so the first attempt hit the ten-second timeout. My timeout message told the model to simplify the query or add filters. The model did exactly that. It added a filter for the year 2017, the query ran, and the system returned a confident answer to a different question. Nothing on the screen would have shown that anything was wrong.

A self-correction loop can make a system less trustworthy if it is allowed to change the question to make an error go away. I fixed this in two ways. Indexes on every join key mean the query now finishes well inside the limit. The retry and timeout messages now tell the model to keep exactly the same meaning and never to add filters the user did not ask for. I also changed the evaluation report to record the error of every attempt, so a problem like this is visible in future.

## 8.3 After the Fixes

After the four fixes the hard set reached 14 of 15. The failure in that run was on a question that had passed in the first run. This shows the run-to-run variation of a hosted model, and it means one run of 15 questions cannot separate a real improvement of one question from noise. I report it rather than hide it.

## 8.4 Summaries That Looked Right but Were Wrong

Before the formal evaluation I tested the summary step by hand and checked every claim against the data. The model presented each of these mistakes with full confidence.

1. **Small samples ranked first.** The best rated category was a category with only 14 reviews. I added a rule that averages need at least 30 records.
2. **Wrong percentages.** The model said about 56 percent of orders received five stars. The real figure is 58.3 percent.
3. **Currency on counts.** After I said that money is in reais, it wrote R$ 14,984 customers.
4. **Rounded totals.** Revenue in 2018 is R$ 7,341,182.41 but the summary said R$ 7,341,180, because the table it received showed the number in scientific notation.
5. **Wrong ranking.** It said the fewest orders received one star. The fewest actually received two stars, 3,061 against 10,510.

Every one of these was fixed by moving the work out of the model and into code, as Chapter 5 described.

# 9 Interactive Application

## 9.1 Design Goals

The application is for a manager and not for an engineer. I wanted the answer to come first, the chart second, and the technical detail last, hidden until someone asks for it. I also wanted the method and the evaluation results visible, so a user knows how far to trust the answer.

## 9.2 Architecture

The application is a Streamlit chat app [15]. It imports the same pipeline that the evaluation uses. The language model client is created once and shared. Each answer keeps its question and SQL, so the last three can be sent as history for follow-up questions. To protect the free quota on a public demo, each session is limited to 25 questions.

## 9.3 Home Page

Figure 9.1 shows the home page. Four cards summarise the dataset. The sidebar explains the method, shows the evaluation results and offers six example questions.





*Figure 9.1: Home page with dataset summary and method*

## 9.4 Trend and Ranking Answers

A trend question gives a line chart. The summary quotes the lowest and highest months from the facts that Python computed, and notes that canceled orders were excluded. A ranking question gives a horizontal bar chart in ranking order.





*Figure 9.2: Summary for the question about monthly revenue in 2017*




*Figure 9.3: Line chart for the same question*





*Figure 9.4: Top 10 product categories by revenue*

## 9.5 Follow-Up Questions

Follow-up questions use the conversation history. In Figure 9.5 the user first asked for the slowest states and then narrowed the answer to states with more than 1,000 orders.




*Figure 9.5: A follow-up question keeps the context of the previous answer*

## 9.6 Single Values and Refusals

A single value appears as a large number card. A question the data cannot answer, or a request to change the data, receives a clear explanation instead of a number.





*Figure 9.6: A single value shown as a number card*





*Figure 9.7: Refusing a question the data cannot answer and a request to delete data*

## 9.7 SQL and Details

Every answer has a panel that shows the formatted SQL, the model used, the response time and the number of attempts. A curious user can check exactly how the answer was produced.





*Figure 9.8: The SQL and details panel*

# 10 Challenges and Lessons Learned

Not everything went smoothly, and the problems taught me as much as the results did.

## 10.1 Choosing a Free Model

I planned to use a Llama model on Groq. When I checked the current model list, it had moved to enterprise access. I switched to gpt-oss-120b, which is free and fast. I learned to check a provider's current documentation before designing around it, because free offers change often.

## 10.2 Running Out of Quota

During a long evaluation the daily token limit ran out. My first client spent 75 seconds retrying each question before giving up. A daily limit will not reset in seconds, so I made it fail at once. I also added a fallback to Gemini in the app and made the evaluation ignore questions that never reached the model. Figure 10.1 shows the new behaviour.





*Figure 10.1: When the daily quota is used up each request now fails in under a second*

## 10.3 A Library Update That Broke Charts

Monthly data suddenly appeared as bars instead of a line. My time detection checked for the old pandas text type, and pandas 3 stores text in a new string type. I made the check work with both versions. I learned to test code against the library version I actually have and not the one I remember.

## 10.4 Dollar Signs That Became Formulas

Streamlit reads text between two dollar signs as a maths formula. A summary with two values in reais therefore showed part of a sentence as a formula. I now escape every dollar sign before display. It was a small bug but it would have looked broken in front of a recruiter.

## 10.5 Results That Looked Too Good

My first full evaluation scored 100 percent. It would have been easy to report that number and move on. Instead I asked whether the questions were too easy, because I had written them while tuning. The held-out set gave 73.3 percent and showed four real weaknesses. This was the most valuable lesson of the project for me.

# 11 Limitations and Future Work

## 11.1 Limitations

- Summaries are still written by a model. Numbers and rankings are grounded in code, but softer statements such as slower states tend to have fewer orders are not checked.
- Follow-up questions inherit earlier limits. When a user narrowed a top 10 list to large states, the model kept the limit of ten.
- The evaluation set is small. Fifty questions show the big effects clearly but not differences of one or two questions.
- Execution accuracy on one database can accept a wrong query that happens to return the right result [8].
- Business rules live in the prompt. This works for one database but would not scale to hundreds of tables.
- A public demo shares 200,000 Groq tokens per day, which is about 60 questions with summaries before it falls back to Gemini.

## 11.2 Future Work

- Collect real questions from the deployed demo and grow the evaluation set from them.
- Move the business rules into a semantic layer such as dbt metrics, so dashboards and the assistant share one definition.
- Retrieve only the relevant tables and examples for each question so the approach scales to larger schemas.
- Ask a clarifying question when a question is ambiguous instead of guessing.
- Add a cache for repeated questions to save quota and answer instantly.
- Check pattern statements in summaries with simple statistics before showing them.

# 12 Conclusion

I set out to build an assistant that answers business questions in plain English and that I could trust enough to put in front of other people. I believe the project achieved that.

The system turns a question into a safe, read-only SQL query, recovers from its own mistakes and explains the result with a chart and a summary whose numbers come from code. On the main set it answered all 35 questions correctly against 68.6 percent for a raw schema baseline. On 15 hard questions it had never seen it reached 73.3 percent, and every failure taught me something specific.

The most important lessons are simple. Valid SQL is not the same as a correct answer. Business definitions matter more than clever prompting. And an automatic fix that quietly changes the question is worse than an honest error. I now feel confident taking a language model from a promising demo to a system that can be measured and trusted.

# References


[1] T. Yu et al., "Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-SQL task," in Proc. 2018 Conf. Empirical Methods in Natural Language Processing (EMNLP), Brussels, Belgium, 2018, pp. 3911 to 3921.

[2] J. Li et al., "Can LLM already serve as a database interface? A big bench for large-scale database grounded text-to-SQLs," in Advances in Neural Information Processing Systems 36 (NeurIPS), 2023. [Online]. Available: https://arxiv.org/abs/2305.03111

[3] N. Rajkumar, R. Li, and D. Bahdanau, "Evaluating the text-to-SQL capabilities of large language models," arXiv preprint arXiv:2204.00498, 2022.

[4] M. Pourreza and D. Rafiei, "DIN-SQL: Decomposed in-context learning of text-to-SQL with self-correction," in Advances in Neural Information Processing Systems 36 (NeurIPS), 2023.

[5] X. Chen, M. Lin, N. Schärli, and D. Zhou, "Teaching large language models to self-debug," in Proc. Int. Conf. Learning Representations (ICLR), 2024.

[6] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in Proc. 16th ACM Workshop on Artificial Intelligence and Security (AISec), 2023.

[7] OWASP Foundation, "OWASP Top 10 for Large Language Model Applications." [Online]. Available: https://owasp.org/www-project-top-10-for-large-language-model-applications/

[8] R. Zhong, T. Yu, and D. Klein, "Semantic evaluation for text-to-SQL with distilled test suites," in Proc. 2020 Conf. Empirical Methods in Natural Language Processing (EMNLP), 2020.

[9] Olist and A. Sionek, "Brazilian E-Commerce Public Dataset by Olist," Kaggle, 2018. doi: 10.34740/KAGGLE/DSV/195341. [Online]. Available: https://www.kaggle.com/dsv/195341

[10] Groq, "Supported models," GroqCloud documentation. Accessed: Oct. 11, 2026. [Online]. Available: https://console.groq.com/docs/models

[11] Groq, "Rate limits," GroqCloud documentation. Accessed: Oct. 11, 2026. [Online]. Available: https://console.groq.com/docs/rate-limits

[12] Google, "OpenAI compatibility," Gemini API documentation. Accessed: Oct. 11, 2026. [Online]. Available: https://ai.google.dev/gemini-api/docs/openai

[13] T. Mao, "sqlglot: Python SQL parser and transpiler." [Online]. Available: https://github.com/tobymao/sqlglot

[14] SQLite, "Uniform resource identifiers." [Online]. Available: https://www.sqlite.org/uri.html

[15] Streamlit Inc., "Streamlit documentation." [Online]. Available: https://docs.streamlit.io

# Appendix A: Technology Stack

*Table A.1: Tools and libraries*

| Area | Tool |
|---|---|
| Language | Python 3.13 in a virtual environment |
| Editor | Visual Studio Code |
| Database | SQLite with twelve indexes |
| Data handling | pandas and PyYAML |
| SQL parsing | sqlglot |
| Language models | gpt-oss-120b on Groq, with Gemini Flash as backup, through the OpenAI Python SDK |
| Charts | Plotly for the app and Matplotlib for the report |
| Application | Streamlit |
| Operating system | Windows |

# Appendix B: Code Modules and How to Run

*Table B.1: Code modules*

| File | Role |
|---|---|
| src/build_db.py | Build the SQLite database from the CSV files with indexes |
| src/schema.py | Schema description, allowed values and business rules for the prompt |
| src/prompts.py | System prompt, worked examples, baseline prompt and retry prompt |
| src/llm.py | Groq and Gemini client with backoff and fallback |
| src/sql_guard.py | Four-layer SQL safety check and its tests |
| src/pipeline.py | Question to validated and executed SQL with self-correction |
| src/insights.py | Chart selection, number cards and grounded summaries |
| eval/run_eval.py | Execution accuracy harness and reports |
| eval/questions.yaml | 35 labelled main questions |
| eval/questions_hard.yaml | 15 held-out hard questions |
| app/streamlit_app.py | The chat application |

To reproduce the project, I place the Olist CSV files in the data/raw folder and install the packages in requirements.txt. I copy .env.example to .env and add a free Groq API key. I then run python src/build_db.py to build the database and python -m src.sql_guard to test the safety layer. The evaluation runs with python -m eval.run_eval and the application starts with streamlit run app/streamlit_app.py. Building the database takes under a minute. A full evaluation takes about ten minutes because it waits between questions to stay inside the free limits.

# Appendix C: Business Rules in the Prompt

1. Revenue is the sum of order item price. Freight is added only when the user asks for totals with shipping.
2. Number of orders is a count of distinct order IDs.
3. Number of customers is a count of distinct customer_unique_id.
4. Units sold is the number of rows in order items.
5. Average order value is revenue divided by the number of distinct orders.
6. Orders with status canceled or unavailable are excluded unless the user says otherwise.
7. Data covers September 2016 to October 2018; 2016 and late 2018 are sparse.
8. Months and years come from the purchase timestamp.
9. Delivery days are the delivery date minus the purchase date.
10. Payment values must not be summed after joining to order items, because the join repeats rows.
11. Reviews belong to orders, so each review is counted once per seller or category.
12. City names are stored in lowercase without accents.
13. When ranking averages by group, groups with fewer than 30 records are ignored.