Q#4 Pseudocode

```
Function getValidDays()
    Repeat
        input days
        if days < 1 or days > 7 then
            display "invalid days"
        end if
    until days >= 1 and day <= 7
    return days
End Function
Function calculate daily sales (day number)
    input orders
        total = 0
        highest = 0
    For i = 1 To orders
        repeat
            input amount
        if amount <= 0 then
            display "Amount must be +ve"
        end if
    until amount > 0
    total = total + amount
    if i = 1 or amount > highest then
        highest = amount
    end if
```

```
End for
    avg = total / sales
display total
display avg to 2 decimal places
display highest
    return total
End Function
    Function findhighestsalesday (dailysales, no: of days)
    bestday = 0
    highestsales = dailysales [0]
for i = 1 to numbes of Days - 1
    if dailysales [i] > highest sales then
    highestsales = dailysales [0]
    bestday = i
End if
End for
    return bestday + 1
end function
Function displayBarchart (dailysales, no: of days)
    for i = 0 To no: of days - 1
    stars = integer (dailysales [i] / 100)
    display "day", i+1
for j = 1 to stars
display "*"
```

```
End for
    Display New Line
end for
end function
    Begin
        days = get valid days ()
        declare daily sales [7]
        festival total = 0
for i = 0 to days - 1
daily sales [i] = cal daily sales (i+1)
festival total = festival total + dailysales [i]
end for
    highest day = find highest sales day (daily sales,
                                          days)
Display festival total
"       highest day
"       daily sales [highestday - 1]
Call display bar chart (daily Sales, days)
end
```