


# Syntax Analysis

## Part I

### Chapter 4

# Position of a Parser in the Compiler Model



# The Parser

- A parser implements a C-F grammar
- The role of the parser is twofold:
  1. To check syntax (= string recognizer)
    - And to report syntax errors accurately
  2. To invoke semantic actions
    - For static semantics checking, e.g. type checking of expressions, functions, etc.
    - For syntax-directed translation of the source code to an intermediate representation

# Syntax-Directed Translation

- One of the major roles of the parser is to produce an intermediate representation (IR) of the source program using syntax-directed translation methods
- Possible IR output:
  - Abstract syntax trees (ASTs)
  - Control-flow graphs (CFGs) with triples, three-address code, or register transfer list notation
  - WHIRL (SGI Pro64 compiler) has 5 IR levels!

# Error Handling

- A good compiler should assist in identifying and locating errors
  - *Lexical errors*: important, compiler can easily recover and continue
  - *Syntax errors*: most important for compiler, can almost always recover
  - *Static semantic errors*: important, can sometimes recover
  - *Dynamic semantic errors*: hard or impossible to detect at compile time, runtime checks are required
  - *Logical errors*: hard or impossible to detect

# Viable-Prefix Property

- The *viable-prefix property* of LL/LR parsers allows early detection of syntax errors
  - Goal: detection of an error *as soon as possible* without further consuming unnecessary input
  - How: detect an error as soon as the prefix of the input does not match a prefix of any string in the language

Prefix { ...  
 Error is detected here  
**for ( ; )**  
 ...

Prefix { ...  
 Error is detected here  
**DO 10 I = 1 ; 0**  
 ...

# Error Recovery Strategies

- *Panic mode*
  - Discard input until a token in a set of designated synchronizing tokens is found
- *Phrase-level recovery*
  - Perform local correction on the input to repair the error
- *Error productions*
  - Augment grammar with productions for erroneous constructs
- *Global correction*
  - Choose a minimal sequence of changes to obtain a global least-cost correction

# Grammars (Recap)

- Context-free grammar is a 4-tuple  $G = (N, T, P, S)$  where
  - $T$  is a finite set of tokens (*terminal* symbols)
  - $N$  is a finite set of *nonterminals*
  - $P$  is a finite set of *productions* of the form
$$\alpha \rightarrow \beta$$
where  $\alpha \in (N \cup T)^* N (N \cup T)^*$  and  $\beta \in (N \cup T)^*$
  - $S \in N$  is a designated *start symbol*



# Notational Conventions Used

- Terminals  
 $a, b, c, \dots \in T$   
specific terminals: **0**, **1**, **id**, **+**
- Nonterminals  
 $A, B, C, \dots \in N$   
specific nonterminals: *expr*, *term*, *stmt*
- Grammar symbols  
 $X, Y, Z \in (N \cup T)$
- Strings of terminals  
 $u, v, w, x, y, z \in T^*$
- Strings of grammar symbols  
 $\alpha, \beta, \gamma \in (N \cup T)^*$

# Derivations (Recap)

- The *one-step derivation* is defined by  

$$\alpha A \beta \Rightarrow \alpha \gamma \beta$$
 where  $A \rightarrow \gamma$  is a production in the grammar
- In addition, we define
  - $\Rightarrow$  is *leftmost*  $\Rightarrow_{lm}$  if  $\alpha$  does not contain a nonterminal
  - $\Rightarrow$  is *rightmost*  $\Rightarrow_{rm}$  if  $\beta$  does not contain a nonterminal
  - Transitive closure  $\Rightarrow^*$  (zero or more steps)
  - Positive closure  $\Rightarrow^+$  (one or more steps)
- The *language generated by  $G$*  is defined by  

$$L(G) = \{w \in T^* \mid S \Rightarrow^+ w\}$$

# Derivation (Example)

Grammar  $G = (\{E\}, \{+, *, (, ), -, \mathbf{id}\}, P, E)$  with productions  $P =$

$$E \rightarrow E + E$$

$$E \rightarrow E * E$$

$$E \rightarrow ( E )$$

$$E \rightarrow - E$$

$$E \rightarrow \mathbf{id}$$

Example derivations:

$$E \Rightarrow - E \Rightarrow - \mathbf{id}$$

$$E \Rightarrow_{rm} E + E \Rightarrow_{rm} E + \mathbf{id} \Rightarrow_{rm} \mathbf{id} + \mathbf{id}$$

$$E \Rightarrow^* E$$

$$E \Rightarrow^* \mathbf{id} + \mathbf{id}$$

$$E \Rightarrow^+ \mathbf{id} * \mathbf{id} + \mathbf{id}$$

# Chomsky Hierarchy: Language Classification

- A grammar  $G$  is said to be
  - *Regular* if it is *right linear* where each production is of the form
 
$$A \rightarrow w B \quad \text{or} \quad A \rightarrow w$$
 or *left linear* where each production is of the form
 
$$A \rightarrow B w \quad \text{or} \quad A \rightarrow w$$
  - *Context free* if each production is of the form
 
$$A \rightarrow \alpha$$
 where  $A \in N$  and  $\alpha \in (N \cup T)^*$
  - *Context sensitive* if each production is of the form
 
$$\alpha A \beta \rightarrow \alpha \gamma \beta$$
 where  $A \in N$ ,  $\alpha, \gamma, \beta \in (N \cup T)^*$ ,  $|\gamma| > 0$
  - *Unrestricted*

# Chomsky Hierarchy

$L(\text{regular}) \subset L(\text{context free}) \subset L(\text{context sensitive}) \subset L(\text{unrestricted})$

Where  $L(T) = \{ L(G) \mid G \text{ is of type } T \}$

That is: the set of all languages  
generated by grammars  $G$  of type  $T$

Examples:

Every *finite language* is regular! (construct a FSA for strings in  $L(G)$ )

$L_1 = \{ \mathbf{a}^n \mathbf{b}^n \mid n \geq 1 \}$  is context free

$L_2 = \{ \mathbf{a}^n \mathbf{b}^n \mathbf{c}^n \mid n \geq 1 \}$  is context sensitive

# Parsing

- *Universal* (any C-F grammar)
  - Cocke-Younger-Kasimi
  - Earley
- *Top-down* (C-F grammar with restrictions)
  - Recursive descent (predictive parsing)
  - LL (Left-to-right, Leftmost derivation) methods
- *Bottom-up* (C-F grammar with restrictions)
  - Operator precedence parsing
  - LR (Left-to-right, Rightmost derivation) methods
    - SLR, canonical LR, LALR

# Top-Down Parsing

- LL methods (Left-to-right, Leftmost derivation) and recursive-descent parsing

Grammar:

$$E \rightarrow T + T$$

$$T \rightarrow ( E )$$


$$T \rightarrow - E$$

$$T \rightarrow \mathbf{id}$$

Leftmost derivation:

$$E \Rightarrow_{lm} T + T$$

$$\Rightarrow_{lm} \mathbf{id} + T$$

$$\Rightarrow_{lm} \mathbf{id} + \mathbf{id}$$


# Left Recursion (Recap)

- Productions of the form

$$A \rightarrow A \alpha$$

$$| \beta$$

$$| \gamma$$

are left recursive

- When one of the productions in a grammar is left recursive then a predictive parser loops forever on certain inputs



# General Left Recursion Elimination Method

Arrange the nonterminals in some order  $A_1, A_2, \dots, A_n$

**for**  $i = 1, \dots, n$  **do**

**for**  $j = 1, \dots, i-1$  **do**

        replace each

$$A_i \rightarrow A_j \gamma$$

    with

$$A_i \rightarrow \delta_1 \gamma \mid \delta_2 \gamma \mid \dots \mid \delta_k \gamma$$

    where

$$A_j \rightarrow \delta_1 \mid \delta_2 \mid \dots \mid \delta_k$$

**enddo**

    eliminate the *immediate left recursion* in  $A_i$

**enddo**

# Immediate Left-Recursion Elimination Method

Rewrite every left-recursive production

$$\begin{aligned}
 A &\rightarrow A \alpha \\
 &\mid \beta \\
 &\mid \gamma \\
 &\mid A \delta
 \end{aligned}$$

into a right-recursive production:

$$\begin{aligned}
 A &\rightarrow \beta A_R \\
 &\mid \gamma A_R \\
 A_R &\rightarrow \alpha A_R \\
 &\mid \delta A_R \\
 &\mid \varepsilon
 \end{aligned}$$

# Example Left Recursion Elim.

$$\left. \begin{array}{l} A \rightarrow B C \mid \mathbf{a} \\ B \rightarrow C A \mid A \mathbf{b} \\ C \rightarrow A B \mid C C \mid \mathbf{a} \end{array} \right\} \text{Choose arrangement: } A, B, C$$

$i = 1$ : nothing to do

$$\begin{aligned} i = 2, j = 1: \quad & B \rightarrow C A \mid \underline{A} \mathbf{b} \\ \Rightarrow \quad & B \rightarrow C A \mid \underline{B C} \mathbf{b} \mid \underline{a} \mathbf{b} \\ \Rightarrow_{(\text{imm})} \quad & B \rightarrow C A B_R \mid \mathbf{a} \mathbf{b} B_R \\ & B_R \rightarrow C \mathbf{b} B_R \mid \varepsilon \end{aligned}$$

$$\begin{aligned} i = 3, j = 1: \quad & C \rightarrow \underline{A} B \mid C C \mid \mathbf{a} \\ \Rightarrow \quad & C \rightarrow \underline{B C} B \mid \underline{a} B \mid C C \mid \mathbf{a} \end{aligned}$$

$$\begin{aligned} i = 3, j = 2: \quad & C \rightarrow \underline{B} C B \mid \mathbf{a} B \mid C C \mid \mathbf{a} \\ \Rightarrow \quad & C \rightarrow \underline{C A B_R} C B \mid \underline{\mathbf{a} \mathbf{b} B_R} C B \mid \mathbf{a} B \mid C C \mid \mathbf{a} \\ \Rightarrow_{(\text{imm})} \quad & C \rightarrow \mathbf{a} \mathbf{b} B_R C B C_R \mid \mathbf{a} B C_R \mid \mathbf{a} C_R \\ & C_R \rightarrow A B_R C B C_R \mid C C_R \mid \varepsilon \end{aligned}$$

# Left Factoring

- When a nonterminal has two or more productions whose right-hand sides start with the same grammar symbols, the grammar is not LL(1) and cannot be used for predictive parsing

- Replace productions

$$A \rightarrow \alpha \beta_1 \mid \alpha \beta_2 \mid \dots \mid \alpha \beta_n \mid \gamma$$

with

$$A \rightarrow \alpha A_R \mid \gamma$$

$$A_R \rightarrow \beta_1 \mid \beta_2 \mid \dots \mid \beta_n$$

# Predictive Parsing

- Eliminate left recursion from grammar
- Left factor the grammar
- Compute FIRST and FOLLOW
- Two variants:
  - Recursive (recursive calls)
  - Non-recursive (table-driven)

# FIRST (Revisited)

- $\text{FIRST}(\alpha) = \{ \text{the set of terminals that begin all strings derived from } \alpha \}$

$\text{FIRST}(a) = \{a\}$  if  $a \in T$

$\text{FIRST}(\epsilon) = \{\epsilon\}$

$\text{FIRST}(A) = \cup_{A \rightarrow \alpha} \text{FIRST}(\alpha)$  for  $A \rightarrow \alpha \in P$

$\text{FIRST}(X_1X_2\dots X_k) =$

**if** for all  $j = 1, \dots, i-1 : \epsilon \in \text{FIRST}(X_j)$  **then**  
 add non- $\epsilon$  in  $\text{FIRST}(X_i)$  to  $\text{FIRST}(X_1X_2\dots X_k)$   
**if** for all  $j = 1, \dots, k : \epsilon \in \text{FIRST}(X_j)$  **then**  
 add  $\epsilon$  to  $\text{FIRST}(X_1X_2\dots X_k)$

# FOLLOW

- $\text{FOLLOW}(A) = \{ \text{the set of terminals that can immediately follow nonterminal } A \}$

$\text{FOLLOW}(A) =$

**for** all  $(B \rightarrow \alpha A \beta) \in P$  **do**

add  $\text{FIRST}(\beta) \setminus \{\epsilon\}$  to  $\text{FOLLOW}(A)$

**for** all  $(B \rightarrow \alpha A \beta) \in P$  and  $\epsilon \in \text{FIRST}(\beta)$  **do**

add  $\text{FOLLOW}(B)$  to  $\text{FOLLOW}(A)$

**for** all  $(B \rightarrow \alpha A) \in P$  **do**

add  $\text{FOLLOW}(B)$  to  $\text{FOLLOW}(A)$

**if**  $A$  is the start symbol  $S$  **then**

add  $\$$  to  $\text{FOLLOW}(A)$

# LL(1) Grammar

- A grammar  $G$  is LL(1) if it is not left recursive and for each collection of productions

$$A \rightarrow \alpha_1 \mid \alpha_2 \mid \dots \mid \alpha_n$$

for nonterminal  $A$  the following holds:

1.  $\text{FIRST}(\alpha_i) \cap \text{FIRST}(\alpha_j) = \emptyset$  for all  $i \neq j$
2. if  $\alpha_i \Rightarrow^* \varepsilon$  then
  - 2.a.  $\alpha_j \not\Rightarrow^* \varepsilon$  for all  $i \neq j$
  - 2.b.  $\text{FIRST}(\alpha_j) \cap \text{FOLLOW}(A) = \emptyset$   
for all  $i \neq j$



# Non-LL(1) Examples

<i>Grammar</i>	<i>Not LL(1) because:</i>
$S \rightarrow S \mathbf{a} \mid \mathbf{a}$	Left recursive
$S \rightarrow \mathbf{a} S \mid \mathbf{a}$	$\text{FIRST}(\mathbf{a} S) \cap \text{FIRST}(\mathbf{a}) \neq \emptyset$
$S \rightarrow \mathbf{a} R \mid \epsilon$ $R \rightarrow S \mid \epsilon$	For $R$ : $S \Rightarrow^* \epsilon$ and $\epsilon \Rightarrow^* \epsilon$
$S \rightarrow \mathbf{a} R \mathbf{a}$ $R \rightarrow S \mid \epsilon$	For $R$ : $\text{FIRST}(S) \cap \text{FOLLOW}(R) \neq \emptyset$

# Recursive Descent Parsing (Recap)

- Grammar must be LL(1)
- Every nonterminal has one (recursive) procedure responsible for parsing the nonterminal's syntactic category of input tokens
- When a nonterminal has multiple productions, each production is implemented in a branch of a selection statement based on input look-ahead information

# Using FIRST and FOLLOW to Write a Recursive Descent Parser

$expr \rightarrow term\ rest$ $rest \rightarrow +\ term\ rest$ $  -\ term\ rest$ $  \epsilon$ $term \rightarrow id$		<pre> <b>procedure</b> <i>rest</i>(); <b>begin</b>   <b>if</b> <i>lookahead</i> in <u>FIRST(+ <i>term rest</i>)</u> <b>then</b>     <i>match</i>('+'); <i>term</i>(); <i>rest</i>()   <b>else if</b> <i>lookahead</i> in <u>FIRST(- <i>term rest</i>)</u> <b>then</b>     <i>match</i>(''); <i>term</i>(); <i>rest</i>()   <b>else if</b> <i>lookahead</i> in <u>FOLLOW(<i>rest</i>)</u> <b>then</b>     <b>return</b>   <b>else</b> <i>error</i>() <b>end</b>;         </pre>
---	--	--


$FIRST(+\ term\ rest) = \{ + \}$

$FIRST(-\ term\ rest) = \{ - \}$

$FOLLOW(rest) = \{ \$ \}$

# Non-Recursive Predictive Parsing: Table-Driven Parsing

- Given an LL(1) grammar  $G = (N, T, P, S)$  construct a table  $M[A, a]$  for  $A \in N, a \in T$  and use a *driver program* with a *stack*



# Constructing an LL(1) Predictive Parsing Table

```
for each production  $A \rightarrow \alpha$  do  
    for each  $a \in \text{FIRST}(\alpha)$  do  
        add  $A \rightarrow \alpha$  to  $M[A,a]$   
    enddo  
    if  $\epsilon \in \text{FIRST}(\alpha)$  then  
        for each  $b \in \text{FOLLOW}(A)$  do  
            add  $A \rightarrow \alpha$  to  $M[A,b]$   
        enddo  
    endif  
enddo  
Mark each undefined entry in  $M$  error
```

# Example Table


$$E \rightarrow T E_R$$

$$E_R \rightarrow + T E_R \mid \varepsilon$$

$$T \rightarrow F T_R$$

$$T_R \rightarrow * F T_R \mid \varepsilon$$

$$F \rightarrow ( E ) \mid \mathbf{id}$$



$A \rightarrow \alpha$	FIRST( $\alpha$ )	FOLLOW( $A$ )
$E \rightarrow T E_R$	( <b>id</b>	<b>\$</b> )
$E_R \rightarrow + T E_R$	<b>+</b>	<b>\$</b> )
$E_R \rightarrow \varepsilon$	$\varepsilon$	<b>\$</b> )
$T \rightarrow F T_R$	( <b>id</b>	<b>+</b> <b>\$</b> )
$T_R \rightarrow * F T_R$	<b>*</b>	<b>+</b> <b>\$</b> )
$T_R \rightarrow \varepsilon$	$\varepsilon$	<b>+</b> <b>\$</b> )
$F \rightarrow ( E )$	(	<b>*</b> <b>+</b> <b>\$</b> )
$F \rightarrow \mathbf{id}$	<b>id</b>	<b>*</b> <b>+</b> <b>\$</b> )

	<b>id</b>	<b>+</b>	<b>*</b>	(	)	<b>\$</b>
$E$	$E \rightarrow T E_R$			$E \rightarrow T E_R$		
$E_R$		$E_R \rightarrow + T E_R$			$E_R \rightarrow \varepsilon$	$E_R \rightarrow \varepsilon$
$T$	$T \rightarrow F T_R$			$T \rightarrow F T_R$		
$T_R$		$T_R \rightarrow \varepsilon$	$T_R \rightarrow * F T_R$		$T_R \rightarrow \varepsilon$	$T_R \rightarrow \varepsilon$
$F$	$F \rightarrow \mathbf{id}$			$F \rightarrow ( E )$		



# LL(1) Grammars are Unambiguous

Ambiguous grammar

$$S \rightarrow \mathbf{i} E \mathbf{t} S S_R \mid \mathbf{a}$$

$$S_R \rightarrow \mathbf{e} S \mid \epsilon$$

$$E \rightarrow \mathbf{b}$$



$A \rightarrow \alpha$	FIRST( $\alpha$ )	FOLLOW( $A$ )
$S \rightarrow \mathbf{i} E \mathbf{t} S S_R$	<b>i</b>	<b>e \$</b>
$S \rightarrow \mathbf{a}$	<b>a</b>	<b>e \$</b>
$S_R \rightarrow \mathbf{e} S$	<b>e</b>	<b>e \$</b>
$S_R \rightarrow \epsilon$	$\epsilon$	<b>e \$</b>
$E \rightarrow \mathbf{b}$	<b>b</b>	<b>t</b>

Error: duplicate table entry

	<b>a</b>	<b>b</b>	<b>e</b>	<b>i</b>	<b>t</b>	<b>\$</b>
$S$	$S \rightarrow \mathbf{a}$			$S \rightarrow \mathbf{i} E \mathbf{t} S S_R$		
$S_R$			$S_R \rightarrow \epsilon$ $S_R \rightarrow \mathbf{e} S$			$S_R \rightarrow \epsilon$
$E$		$E \rightarrow \mathbf{b}$				

# Predictive Parsing Program (Driver)

```
push($)  
push(S)  
a := lookahead  
repeat  
     $X := \text{pop}()$   
    if  $X$  is a terminal or  $X = \$$  then  
        match(X) // moves to next token and a := lookahead  
    else if  $M[X, a] = X \rightarrow Y_1 Y_2 \dots Y_k$  then  
        push( $Y_k, Y_{k-1}, \dots, Y_2, Y_1$ ) // such that  $Y_1$  is on top  
        ... invoke actions and/or produce IR output ...  
    else    error()  
    endif  
until  $X = \$$ 
```



# Example Table-Driven Parsing

Stack	Input	Production applied
$\$E$	$\underline{\text{id}}+\text{id}*\text{id}\$$	$E \rightarrow T E_R$
$\$E_R \underline{T}$	$\underline{\text{id}}+\text{id}*\text{id}\$$	$T \rightarrow F T_R$
$\$E_R T_R \underline{F}$	$\underline{\text{id}}+\text{id}*\text{id}\$$	$F \rightarrow \text{id}$
$\$E_R T_R \underline{\text{id}}$	$\underline{\text{id}}+\text{id}*\text{id}\$$	
$\$E_R \underline{T}_R$	$\underline{+}\text{id}*\text{id}\$$	$T_R \rightarrow \epsilon$
$\$E_R$	$\underline{+}\text{id}*\text{id}\$$	$E_R \rightarrow + T E_R$
$\$E_R T \underline{+}$	$\underline{+}\text{id}*\text{id}\$$	
$\$E_R \underline{T}$	$\underline{\text{id}}*\text{id}\$$	$T \rightarrow F T_R$
$\$E_R T_R \underline{F}$	$\underline{\text{id}}*\text{id}\$$	$F \rightarrow \text{id}$
$\$E_R T_R \underline{\text{id}}$	$\underline{*}\text{id}\$$	
$\$E_R \underline{T}_R$	$\underline{*}\text{id}\$$	$T_R \rightarrow * F T_R$
$\$E_R T_R F \underline{*}$	$\underline{\text{id}}\$$	
$\$E_R T_R \underline{F}$	$\underline{\text{id}}\$$	$F \rightarrow \text{id}$
$\$E_R T_R \underline{\text{id}}$	$\underline{\$}$	
$\$E_R \underline{T}_R$	$\underline{\$}$	$T_R \rightarrow \epsilon$
$\$E_R$	$\underline{\$}$	$E_R \rightarrow \epsilon$

# Panic Mode Recovery

Add synchronizing actions to  
undefined entries based on FOLLOW

Pro: Can be automated

Cons: Error messages are needed

$\text{FOLLOW}(E) = \{ ) \$ \}$

$\text{FOLLOW}(E_R) = \{ ) \$ \}$

$\text{FOLLOW}(T) = \{ + ) \$ \}$

$\text{FOLLOW}(T_R) = \{ + ) \$ \}$

$\text{FOLLOW}(F) = \{ + * ) \$ \}$

	id	+	*	(	)	\$
$E$	$E \rightarrow T E_R$			$E \rightarrow T E_R$	<i>synch</i>	<i>synch</i>
$E_R$		$E_R \rightarrow + T E_R$			$E_R \rightarrow \epsilon$	$E_R \rightarrow \epsilon$
$T$	$T \rightarrow F T_R$	<i>synch</i>		$T \rightarrow F T_R$	<i>synch</i>	<i>synch</i>
$T_R$		$T_R \rightarrow \epsilon$	$T_R \rightarrow * F T_R$		$T_R \rightarrow \epsilon$	$T_R \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$	<i>synch</i>	<i>synch</i>	$F \rightarrow ( E )$	<i>synch</i>	<i>synch</i>

***synch***: the driver pops current nonterminal  $A$  and skips input till  
synch token or skips input until one of  $\text{FIRST}(A)$  is found

# Phrase-Level Recovery

Change input stream by inserting missing tokens

For example: **id id** is changed into **id \* id**

Pro: Can be automated

Cons: Recovery not always intuitive

Can then continue here

	<b>id</b>	<b>+</b>	<b>*</b>	<b>(</b>	<b>)</b>	<b>\$</b>
$E$	$E \rightarrow T E_R$			$E \rightarrow T E_R$	<i>synch</i>	<i>synch</i>
$E_R$		$E_R \rightarrow + T E_R$			$E_R \rightarrow \epsilon$	$E_R \rightarrow \epsilon$
$T$ .	$T \rightarrow F T_R$	<i>synch</i>		$T \rightarrow F T_R$	<i>synch</i>	<i>synch</i>
$T_R$	<i>insert *</i>	$T_R \rightarrow \epsilon$	$T_R \rightarrow * F T_R$		$T_R \rightarrow \epsilon$	$T_R \rightarrow \epsilon$
$F$	$F \rightarrow \text{id}$	<i>synch</i>	<i>synch</i>	$F \rightarrow ( E )$	<i>synch</i>	<i>synch</i>

*insert \**: driver inserts missing \* and retries the production

# Error Productions

$$E \rightarrow T E_R$$

$$E_R \rightarrow + T E_R \mid \varepsilon$$

$$T \rightarrow F T_R$$

$$T_R \rightarrow * F T_R \mid \varepsilon$$

$$F \rightarrow ( E ) \mid \mathbf{id}$$

Add “*error production*”:

$$T_R \rightarrow F T_R$$

to ignore missing \*, e.g.: **id id**

Pro: Powerful recovery method

Cons: Cannot be automated

	id	+	*	(	)	\$
$E$	$E \rightarrow T E_R$			$E \rightarrow T E_R$	<i>synch</i>	<i>synch</i>
$E_R$		$E_R \rightarrow + T E_R$			$E_R \rightarrow \varepsilon$	$E_R \rightarrow \varepsilon$
$T$	$T \rightarrow F T_R$	<i>synch</i>		$T \rightarrow F T_R$	<i>synch</i>	<i>synch</i>
$T_R$	$T_R \rightarrow F T_R$	$T_R \rightarrow \varepsilon$	$T_R \rightarrow * F T_R$		$T_R \rightarrow \varepsilon$	$T_R \rightarrow \varepsilon$
$F$	$F \rightarrow \mathbf{id}$	<i>synch</i>	<i>synch</i>	$F \rightarrow ( E )$	<i>synch</i>	<i>synch</i>