



ALL HTML TAGS WITH DESCRIPTION

PART-1

swipe



Subrat Shukla





<!--> : This tag is used to apply comment in an HTML document.

<!DOCTYPE> : This tag is used to specify the version of HTML

A

<a> : It is termed as anchor tag and it creates a hyperlink or link.

<abbr> : It defines an abbreviation for a phrase or longer word.

<acronym> : It defines acronym for a word. (Not supported in HTML5)

<address> : It defines the author's contact information of the HTML article

<applet> : It defines an embedded Java applet. (Not supported in HTML5)

<area> : It defines the area of an image map.

<article> : HTML Tags List It defines the self-contained content.

<aside> : HTML Tags List It defines content aside from main content. Mainly represented as sidebar.

<audio> : HTML Tags List It is used to embed sound content in HTML document.

B

**** : It is used to make a text bold.

<base> : This tag defines the base URL for all relative URL within the document.

<basefont> : This tag is used to set default font, size and color for all elements of document. (Not supported in HTML5)

<bdi> : HTML Tags List This tag is used to provide isolation for that part of text which may be formatted in different directions from its surrounding text.

<bdo> : It is used to override the current text direction.

<big> : This tag is used to make font size one level larger than its surrounding content. (Not supported in HTML5)

<blockquote> : It is used to define a content which is taken from another source.

<body> : It is used to define the body section of an HTML document.

**
** : It is used to apply single line break.

<button> : It is used to represent a clickable button

C

<canvas> : HTML Tags List It is used to provide a graphics space within a web document.

<caption> : It is used to define a caption for a table.

<center> : It is used to align the content in center. (Not supported in HTML5)

<cite> : It is used to define the title of the work, book, website, etc.

<code> : It is used to display a part of programming code in an HTML document.

<col> : It defines a column within a table which represent common properties of columns and used with the **<colgroup>** element.

<colgroup> : It is used to define group of columns in a table.

D

<data> : HTML Tags List It is used to link the content with the machine-readable translation.

<datalist> : HTML Tags List It is used to provide a predefined list for input option.



E

**** : It is used to emphasis the content applied within this element.

<embed> : HTML Tags List It is used as embedded container for external file/application/media, etc.

F

<fieldset> : It is used to group related elements/labels within a web form.

<figcaption> : HTML Tags List It is used to add a caption or explanation for the element.

<figure> : HTML Tags List It is used to define the self-contained content, and s mostly refer as single unit.

**** : It defines the font, size, color, and face for the content. (Not supported in HTML5)

<footer> : HTML Tags List It defines the footer section of a webpage.

<form> : It is used to define an HTML form.

<frame> : It defines a particular area of webpage which can contain another HTML file. (Not supported in HTML5)

<frameset> : It defines group of Frames. (Not supported in HTML5)

H

<h1> to <h6> : It defines headings for an HTML document from level 1 to level 6.

<head> : It defines the head section of an HTML document.

<header> : HTML Tags List It defines the header of a section or webpage.

<hr> : It is used to apply thematic break between paragraph-level elements.

<html> : It represents root of an HTML document.

I

<i> : It is used to represent a text in some different voice.

<iframe> : It defines an inline frame which can embed other content.

**** : It is used to insert an image within an HTML document.

<input> : It defines an input field within an HTML form.

<ins> : It represent text that has been inserted within an HTML document.

<isindex> : It is used to display search string for current document. (Not supported in HTML5)

K

<kbd> : It is used to define keyboard input.

L

<label> : It defines a text label for the input field of form.

<legend> It defines a caption for content of **<fieldset>**

**** : It is used to represent items in list.

<link> : It represents a relationship between current document and an external resource.

M

<main> : HTML Tags List It represents the main content of an HTML document.

<map> : It defines an image map with active areas.

<mark> : HTML Tags List It represents a highlighted text.

<marquee> : It is used to insert the scrolling text or an image either horizontally or vertically. (Not supported in HTML5)



M

<menu> : It is used for creating a menu list of commands.

<meta> : It defines metadata of an HTML document.

<meter> : HTML Tags List It defines scalar measurement with known range or fractional value.

N

<nav> : HTML Tags List It represents section of page to represent navigation links.

<noframes> : It provides alternate content to represent in browser which does not support the **<frame>** elements. (Not supported in HTML5)

<noscript> : It provides an alternative content if a script type is not supported in browser.

O

<object> : It is used to embed an object in HTML file.

**** : It defines an ordered list of items.

<optgroup> : It is used to group the options of a drop-down list.

Loved it ??
Then follow and connect
with me
@subratshukla for more
such useful contents

