

SCRIPT-CONTROLLED ACL – RECORD ACCESS JOURNEY MAP

Restrict Record Access Based on Field Value | ServiceNow ACL Lab

STAGE	KEY STEP	EXPERIENCE / ACTION	INTERACTIONS & TOUCHPOINTS
ENTICE	Prepare Users & Roles	Admin logs in and creates the EEE test user. Creates custom roles bb1, bb2, bb3 and bb4 and assigns the required roles.	ServiceNow instance User Administration → Users / Roles Admin
ENGAGE	Create Institution Details Table	Create u_institution_details table. Add Student Roll Number, Student Name, Faculty Name, Branch, Email, Phone Number and Description fields.	Application Navigator System Definition → Tables Table records
APPLY	Create Records & READ ACL	Create records with ECE, EEE and CSE branch values. Create READ ACL for the table; require bb1 and add Data condition: Branch is EEE . Script allows admin and bb1 users; denies others.	System Security → Access Control (ACL) Security_admin role ACL form
EXTEND	CREATE / WRITE / DELETE ACLs	CREATE: bb2 role. WRITE: bb3 role. DELETE: bb4 role. No additional data condition is required for these ACLs.	ACL records Roles bb2, bb3, bb4 Institution Details
VERIFY	Impersonate & Verify Access	Impersonate EEE user and open the Student Records list. Verify role-based access, then impersonate Admin and verify full access.	u_institution_details.list Impersonation List / Form
GOAL / MOTIVATION Help authorized users access the records they are permitted to use, while preventing unauthorized record access.		POSITIVE MOMENTS Admin retains full access. Users with the required roles can perform the permitted ACL operations.	NEGATIVE MOMENTS Users without the required role are denied access. Incorrect role/ACL configuration can prevent the expected operation.
			AREAS OF OPPORTUNITY Use clear role assignments and verify each READ, CREATE, WRITE and DELETE ACL independently.

OUTCOME: Script-controlled READ, WRITE, CREATE and DELETE ACLs enforce record-level security by evaluating user roles and record access rules.