PIZZA SALES

ANALYSIS

Retrieve the total number of orders placed.

```
-- Retrieve the total number of orders placed.

select count(order_id)  as total_orders from orders;
```

Result Grid

	total_orders
▶	21350

Calculate the total revenue generated from pizza sales.

```
-- Calculate the total revenue generated from pizza sales.
select
round(sum(order_details.quantity * pizzas.price),2) as total_Sales
from order_details join pizzas
on pizzas.pizza_id= order_details.pizza_id
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

	total_Sales
▶	817860.05

Identify the highest-priced pizza.

```
-- Identify the highest-priced pizza

select pizza_types.name, pizzas.price
from pizza_types join  pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
order by pizzas.price desc limit 1;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

name	price
The Greek Pizza	35.95

Identify the most common pizza size ordered.

```sql
-- Identify the most common pizza size ordered.

select  pizzas.size, count(order_details.order_details_id) as order_count
from pizzas join order_details
on pizzas.pizza_id = order_details.pizza_id
group by pizzas .size order by order_count desc;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

size	order_count
L	18526
M	15385
S	14137
XL	544
XXL	28

List the top 5 most ordered pizza types along with their quantities.

```
-- List the top 5 most ordered pizza types along with their quantities.

select pizza_types.name,
sum(order_details.quantity) as quantity
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id= pizzas.pizza_id
 group by pizza_types.name order by quantity desc limit 5;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

name	quantity
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

Join the necessary tables to find the total quantity of each pizza category ordered.

```sql
-- Join the necessary tables to find the total quantity of each pizza category ordered.

select pizza_types.category,
sum(order_details.quantity)as quantity
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.Pizza_id = pizzas.pizza_id
group by pizza_types.category order by quantity desc;
```

Determine the distribution of orders by hour of the day.

```
-- Determine the distribution of orders by hour of the day.
select hour(order_time),count(order_id)from orders
group by hour(order_time);
```

Join relevant tables to find the category-wise distribution of pizzas.

```sql
-- Join relevant tables to find the category-wise distribution of pizzas
select category, count(name) from pizza_types
group by category;
```

Group the orders by date and calculate the average number of pizzas ordered per day.

```sql
-- Group the orders by date and calculate the average number of pizzas ordered per day

select avg(quantity)from
(select orders.order_date,sum(order_details.quantity) as quantity
from orders join order_details
on orders.order_id = order_details.order_id
 group by orders.order_date) as order_quantity;
```

Determine the top 3 most ordered pizza types based on revenue.

```
-- Determine the top 3 most ordered pizza types based on revenue

select pizza_types.name,
sum(order_details.quantity* pizzas.price )as revenue
from pizza_types join pizzas
on pizzas.pizza_type_id = pizza_types.pizza_type_id
join order_details
on order_details.Pizza_id = pizzas.pizza_id
group by  pizza_types.name order by revenue desc limit 3;
```

Calculate the percentage contribution of each pizza type to total revenue.

```
-- Calculate the percentage contribution of each pizza type to total revenue.

select pizza_types.category,
round(sum(order_details.quantity * pizzas.price) /(select round(sum(order_details.quantity * pizzas.price),2)as
from order_details join pizzas on pizzas.pizza_id = order_details.pizza_id ))* 100,2) as revenue
from  pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details_pizza_id = pizzas.pizza_id
group by pizza_types.category order by revenue desc ;
```

Analyze the cumulative revenue generated over time.

```sql
-- Analyze the cumulative revenue generated over time.

select order_date,
sum(revenue) over(order by order_date) as cum_revenue
from
(select orders.order_date,
sum(order_details.quantity * pizzas.price) as revenue
from order_details join pizzas
on order_details.Pizza_id = pizzas.pizza_id
join orders
on orders.order_id = order_details.order_id
group by orders.order_date)as rsales;
```

Determine the top 3 most ordered pizza types based on revenue for each pizza category.

```sql
-- Determine the top 3 most ordered pizza types based on revenue for each pizza category.

select name, revenue from
(select category ,name,revenue,
rank() over(partition by category order by revenue desc) as rn
from
(select pizza_types.category,pizza_types.name,
sum((order_details.quantity) * pizzas.price) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category,pizza_types.name)  as a) as b
where rn>=3;
```

Thank You