

## CP-VAC-D50L2-V2

5 MP Full HD IR Dome Camera - 20 Mtr.



## **Main Features**

- 5MP HQIS Pro Image Sensor
- 20fps@5MP
- DWDR, Day/Night (ICR), AWB, AGC, BLC
- Plug-n-Play HD/SD Camera
- 3.6mm (6mm optional)
- Equipped with fine IR LEDs for clearer night vision
- IR Range of 20 Mtr.
- Compatible with HDCVI, HDTVI, AHD and CVBS Formats



















## CP-VAC-D50L2-V2

5 MP Full HD IR Dome Camera - 20 Mtr.

**Specification** 

5 MP HQIS Pro Image Sensor

1lux (IR LED ON), 3lux (IR LED OFF)

1/50s(1/60s)-1/100,000s (Auto/Fixed)

**Feature** 

**Image Sensor** 

Minimum Illumination

**Shutter Speed** 

White Balance

Gain Control (AGC)

Lens

3.6mm (6mm optional)

5.0MP@20fps/12.5fps, 4.0MP@15fps/25fps/30fps Frame Rate

Auto

Auto

Auto

≥35dB

**Back Light Compensation** 

S/N Ratio

Video Output

1.0Vp-p Composite Output (75 $\Omega$  / BNC), HD-AHD(5MP)\ HD-TVI(5MP)\ HD-CVI(5MP)\ CVBS

Resolution 5.0MP **ICR** Support GLOBE/BLC ΑE

IR IR Range of 20 Mtr.

No. of IR LEDs 12pcs

**Operating Temperature** -20°C~ 50°C

Humidity 10% ~ 90% , ≤95% RH no dew

Power Source DC12V(+/-15%)

**Power Consumption** 1.2W(4W after IR LED Powered on)

Dimension 108mm x 108mm x 73.5mm

Weight 0.2Kg.

