



APC Easy UPS On-Line, 3kVA, Rackmount 2U, 230V, 3x India + 1x Hard wire 3-wire(1P+N+E) outlets, Intelligent Card Slot, No battery, W/O rail kit

SRV3KUXI-IN

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main	
Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2400 W
rated power in VA	3000 VA
output connection type	3 India 3-pin 6A
Output connector type	Hard wire 3-wire (1P + N + E) 1
Number of rack unit	2U
Provided equipment	1 USB cable 1 RS-232 configuration cable 1 rack mounting brackets 1 stabilization/wall mounting feet 1 battery cable user manual
Range of product	Easy UPS On-Line

Batteries & Runtime

Efficiency	View Efficiency Graph ☐
Battery type	External battery system
Battery voltage	72 V
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery charger power	700 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

_	
Colour	Black (RAL 7010)
Height	8.6 cm
Width	43.8 cm
Depth	46.2 cm
Net weight	10.1 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
USB compatible	Yes
Mounting position	Horizontal

Input

Input voltage limits	110280 V half load 160280 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Input protection type	Circuit breaker
Network frequency	4070 Hz auto sensing

Output

Maximum configurable power in VA	3000 VA	
Maximum configurable power in W	2400 W	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	
Harmonic distortion	3 %	
UPS type	Double conversion online	
Wave type	Sine wave	
Efficiency	90 % (full load)	
Additional information	Configurable for 220 : 230 or 240 nominal output voltage	
Bypass type	Internal bypass (automatic and manual)	
Crest factor	3:1	

Conformance

Product certifications BIS

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m

Ambient air temperature for storage	-2060 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	015000 m
Acoustic level	50 dBA
Heat dissipation	910 Btu/h
IP degree of protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm	
Emergency power off	Yes	
control panel	Multifunction LCD status and control console	

Surge Protection and Filtering

Surge energy rate 600 c

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	70 cm
Package 1 Length	54.5 cm
Package 1 Weight	13.7 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

0	Environmental	factorist
4	Environmental	TOOLDITIL

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product datasheet

SRV3KUXI-IN

Image of product / Alternate images

Alternative





SRV3KUXI-IN

