The Al-powered Avigilon Ava 360 Camera for Alta Aware provides 360° visibility, making it ideal for locations that require coverage in all directions. With a 12MP image sensor, IR illumination and HDR, the 360 Camera provides crisp, clear visibility even in challenging lighting conditions. On-camera storage and processing and cloud management minimize physical infrastructure, enabling plug and play configuration for fast deployments. Intelligent video and audio analytics help detect threats in real-time, and provide valuable insights to improve operations.



360° fisheye panoramic with IR



Built-in Al video and audio analytics and on-device storage



Versatile, robust and sleek, fit for both the harshest outdoor and discreet indoor setups



Factory-installed certificates backed by a trusted platform module (TPM)



12MP image sensor



NDAA-Compliant: designed and developed in Norway and the UK, manufactured in Taiwan



FEATURES

IMAGE SENSOR

12MP

IMAGE SENSOR SIZE FORMAT

1/2.3"

LENS

Aperture: *f* / 2.0

Fixed focus

Focus distance: 0.5m - ∞

IR NIGHT VISION

Automatic night mode

IR-cut filter

IR range: 20m

850 nm IR LED

MINIMUM ILLUMINATION IN COLOR MODE

0.4lux

FIELD OF VIEW

>180°

MAXIMUM RESOLUTION & FRAME RATE

3000x3000@30fps

DYNAMIC RANGE

Multi-exposure line-based HDR

VIDEO COMPRESSION

H.264

Motion JPEG

AUDIO

Microphone array (4x microphones)

Al audio event classification

Audio source localization

SECURITY

Factory-installed certificates

No default passwords

Mandatory access authentication

HTTPS/TLS encryption

ONVIF

NETWORK PROTOCOLOS

IPv4, HTTPS, TLS, DNS, mDNS, DNS-SD, NTP, RTSP, RTP, RTCP, ICMP, DHCP, ARP

Streaming: RTP/UDP, RTP/RTSP/HTTPS/TCP

POWER SOURCE

PoE+ (802.3at Type 2)

For installation only: USB-C (1.5A mode)

POWER CONSUMPTION

Typical: 5W

Max without heater: 13W

Max with heater: 23W

STORAGE

MicroSD

SDXC UHS-I

CONNECTION

802.3ab 10/100/1000 Gigabit Ethernet

USB-C for preview and setup

INSTALLATION AID

Automatic wall and ceiling detection

Flexible bracket, mounts to standard back boxes. Refer to technical drawing.

IMPACT RESISTANCE

IK10 (IEC/EN 62262)

INGRESS PROTECTION

IP66 (IEC/EN 60529)

TEMPERATURE

Operating: -40°C to +50°C

Storage: -40°C to +60°C

PHYSICAL CHARACTERISTICS

Dimensions: 152x152x77mm

Weight: 1.1 kg

Body: Aluminum

EMC

EN 55032

EN 61000-3-2/-3

EN 55024

EN 55035

EN61000-6-2/-4

FCC Part 15B

ICES-003 Issue 6

SAFETY

IEC60950-1

IEC62368-1

IEC60950-22

UL/CSA60950-1

UL/CSA 62368-1

UL E164374 NOM-019

INUIVI-U13

IEC62471(IR LED)


WARRANTY

10-year warranty with Alta Aware license or 3-year warranty without

TECHNICAL DRAWINGS

Camera


Side view



Scale 1:2

Mounting Bracket

Top view



	DESIGNATION	DIMENSION (MM)	DIMENSION (INCH)	
A	Octagon	62.9 x 62.9 (88.9 diagonal)	2.47 x 2.47 (3.50 diagonal)	
В	4" Square Box	85.5 x 85.5 (120.9 diagonal)	3.36 x 3.36 (4.76 diagonal)	
C	Single Gang	84.1	3.31	
D	Double Gang	84.1 x 46	3.31 x 1.81	
E	EU Ceiling Box	70	2.76	
F	EU Outlet Box	60	2.36	

ORDERING INFORMATION

AVIGILON AVA 360

PRODUCT ID	RESOLUTION	DEPLOYMENT	COLOR
360-W-30	30 days	Alta Aware Cloud	White
360-B-30	30 days	Alta Aware Cloud	Black
360-W-60	60 days	Alta Aware Cloud	White
360-B-60	60 days	Alta Aware Cloud	Black
360-W	No	Alta Aware on-prem	White
360-B	No	Alta Aware on-prem	Black

ACCESSORIES

PRODUCT ID	PRODUCT NAME	COLOR
ACC-PEN-CAP-W	Avigilon Ava Pendant Mounting Cap	White
ACC-PEN-CAP-B	Avigilon Ava Pendant Mounting Cap	Black
ACC-MNT-ARM-W	Avigilon Ava Wall Mount Arm	White
ACC-MNT-ARM-B	Avigilon Ava Wall Mount Arm	Black
ACO-PEN-HEA	Avigilon Ava Pendant Head	White
ACQ-PEN-PIP	Avigilon Ava Pendant Pipe 40cm	White
ACC-POL-BRA-W	Avigilon Ava Pole Bracket	White
ACC-POL-BRA-B	Avigilon Ava Pole Bracket	Black
ACC-CRN-BRA-W	Avigilon Ava Corner Bracket	White
ACC-CRN-BRA-B	Avigilon Ava Corner Bracket	Black
ACC-CON-A34-W	Avigilon Ava Conduit Adapter 3/4"	White
ACC-CON-A34-B	Avigilon Ava Conduit Adapter 3/4"	Black

To learn more, visit: www.avigilon.com



