



Back-UPS

APC Back-UPS, 600VA, Tower, 230V, 3 India 3-pin 6A Outlets, AVR, W/O Auto Shutdown Software

BX600I-IN

Overview

Lead time	Usually in Stock
Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	360 W
rated power in VA	600 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	India 3-pin 6A 6 A
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery

Batteries & Runtime

Range of product

Run Time	View Runtime Graph ☐	
Efficiency	View Efficiency Graph ☐	
Number of battery filled slots	0	
Number of battery free slots	0	
Battery recharge time	6 h	
Number of battery replacement quantity	1	
Battery voltage	12 V	
Battery charger power	14 W rated 20 W rated	
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v	
Extended runtime	0	
Replacement battery	APCRBCV210 ☐	

General

Provided equipment 1.2 m

Max runtime	0 min
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	222 mm
Width	346 mm
Depth	142 mm
Net weight	4.5 kg
Mounting mode	Not rack-mountable
Two post mountable	0

Input

Network frequency	4070 Hz auto-sensing	
Plug standard	India 3-pin 6A	
Input voltage limits	140300 V	

Output

Maximum configurable power in W	360 W
Output frequency	Sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	360 W
Maximum configurable power in VA	600 VA
Transfer time	10 ms typical : 12 ms maximum

Conformance

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	03000 m
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	015000 m
Acoustic level	45 dBA

Communications & Management

LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators

Surge Protection and Filtering

Surge energy rate 255 J

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.85 cm
Package 1 Width	9.8 cm
Package 1 Length	31.0 cm
Package 1 Weight	4.2 kg
SCC14	10731304743504

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Removable battery	User replaceable
Take-back	No

BX600I-IN

Technical Illustration

Dimensions



BX600I-IN

Image of product / Alternate images

Alternative







