

Symmetra PX Battery Frame for 400V PX 96/160kW & 208V PX 100kW for 9 Battery Modules & Startup

SYCFXR9-S

Overview

Lead time Usually Ships within 8 Weeks

Main

Battery type	VRLA
Provided equipment	Installation guide User manual

Batteries & Runtime

Number of battery blocks per string	4
Number of battery free slots	9
Number of battery filled slots	0
Device mounting	19 inch battery tray
Additional information	Request SYBT9-B4 for replacement battery

Physical

Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net weight	345 kg
USB compatible	No

Conformance

Standards	EN/IEC 62040-2 EN/IEC 62040-3 EN/IEC 62040-1-1	
Product certifications	CE	

Environmental

Ambient air temperature for operation	040 °C
Operating altitude	03333 ft
Relative humidity	095 %
Ambient air temperature for storage	-1540 °C
Storage altitude	0.000000000015240.000000000 m

Storage Relative Humidity 0...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	215 cm
Package 1 Width	121 cm
Package 1 Length	84.8 cm
Package 1 Weight	379 kg

Contractual warranty

Warranty 1 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint		
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1	

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Removable battery	User replaceable
Take-back	Yes