

CP- UVC-VC4K08ZL5-VD

4K WDR HDCVI IR Vandal Dome Camera - 50Mtr.





Main Features

- 1/2" 8Megapixel progressive scan CMOS
- Max. 15fps@3840×2160
- 3.7-11mm motorized lens
- Up to 500m transmission with RG59 coaxial cable
- WDR(120dB), Day/Night (ICR), 2D/3D-DNR, AWB, AGC, BLC, HLC
- 3x optical motorized zoom lens
- IR Range of 50 Mtrs.
- IP67, IK10



















CP- UVC-VC4K08ZL5-VD

4K WDR HDCVI IR Vandal Dome Camera - 50Mtr.

0.01Lux/F1.5(Color), 30IRE,0lux/F1.5(B/W)

Specification

1/1s~1/100,00s

Auto / Manual

Auto

3840(H)×2160(V), 8MP

3.7-11mm motorized Lens

1/2" CMOS



Feature

Image Sensor

Effective Pixels

Minimum Illumination

Shutter Speed

White Balance

Gain Control (AGC)

Lens

S/N Ratio More than 65dB

Back Light Compensation BLC / HLC / WDR(120dB)

Angle of View H: 112°~46°

Video Streaming PAL:3840×2160@12.5fps,2560x1440@25fps; NTSC:3840×2160@15fps,2560x1440@30fps

Video Output 1-channel HDCVI 4K video output & 1-channel CVBS video output

Resolution 8MP (3840×2160)
ICR Auto (ICR) / Manual

Audio Input 1 channel
Alarm IN 2 channel
Alarm Out 1 channel

IR IR Range of 50 Mtr.
OSD Multi-language

Operating Temperature $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}/\text{Less than } 95\%\text{RH}$ Power Source $12\text{V DC} \pm 25\%/24\text{V AC} \pm 25\%$

Power Consumption Max 12.4W Weatherproof Standard IP67 & IK10

Dimension Φ159.1mm×117.9mm (Φ6.26"×4.64")

Weight 0.90kg

