



APC Easy UPS On-Line, 3kVA/ 2400W, Rackmount 2U, 230V, 4x India + 1x Hard wire 3wire(1P+N+E) outlets, Intelligent Card Slot, LCD, W/O rail kit

SRV3KL-IN

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main	
Main Input Voltage	230 V AC
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2400 W
rated power in VA	3000 VA
Input Connection Type	IEC 60320 C20
output connection type	4 India 3-pin 6A
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	2U
Cable length	1.5 m
Number of cables	1
Provided equipment	1 IEC 60320 C19 to India 3-pin 16A power cable 1 USB cable 1 RS-232 configuration cable 1 rack mounting brackets 1 stabilization/wall mounting feet user manual
Range of product	Easy UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery type	Lead-acid battery
Battery voltage	72 V
Extended runtime	0

Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	4 h
Battery charger power	60 W rated
Replacement battery	APCRBCV202 ☐

General

Max runtime	3 min
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

•	
Colour	Black (RAL 7010)
Height	8.8 cm
Width	43.8 cm
Depth	63.2 cm
Net weight	28 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	No
Mounting position	Horizontal

Input

Switching current capacity	20 A
Input voltage limits	110280 V half load 160280 V full load
Input protection type	Circuit breaker
Network frequency	4070 Hz auto sensing

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	90 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3:1

Conformance

Product certifications	BIS
Froduct certifications	DI 2

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m
Ambient air temperature for storage	-2060 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	015000 m
Acoustic level	50 dBA
Heat dissipation	910 Btu/h
IP degree of protection	IP20

Communications & Management

Alarm	Audible and visible alarms : prioritized by severity
control panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge energy rate 600 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.8 cm
Package 1 Width	79.4 cm
Package 1 Length	57 cm
Package 1 Weight	32 kg

Contractual warranty

Warranty	2 years repair or replace	
----------	---------------------------	--



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	No	

Product datasheet

SRV3KL-IN

Image of product / Alternate images

Alternative

SRV3KL-IN





SRV3KL-IN

