



Network

Positioning

## TNU-6321

2MP Positioning Camera



### Key Features

- Max. 2megapixel (1920 x 1080) resolution
- 4.44 ~ 142.6mm (32x) varifocal lens
- Max. 60fps@2MP (H.265/H.264), Max. 30fps@2MP (MJPEG)
- H.265, H.264, MJPEG codec support
- Day & Night (ICR), WDR (120dB), Defog
- Tampering, Virtual line, Enter / Exit, (Dis)Appear, Audio detection
- Face detection, Motion detection
- microSD / SDHC / SDXC slot

### Compatible Devices



SPI-50



SBU-500WM

## TNU-6321

### 2MP Positioning Camera



### Specifications

#### Video

Imaging Device	1/2.8" CMOS
Resolution	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264: Max. 60fps/50fps(60Hz/50Hz) MJPEG: Max. 30fps
Min. Illumination	Color: 0.05Lux(F1.6, 1/30sec) B/W: 0.005 Lux(F1.6, 1/30sec)
Video Out	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P), for installation

#### Lens

Focal Length (Zoom Ratio)	4.44~142.6mm(32x) zoom
Optical Zoom	x32
Max. Aperture Ratio	F1.6(Wide)~F4.4(Tele)
Angular Field of View	H: 61.8-(Wide)~2.19-(Tele) / V: 36.2-(Wide)~1.24-(Tele)
Min. Object Distance	1.5m(4.92ft)
Focus Control	Auto, One shot AF
Lens Type	DC auto iris

#### Pan / Tilt / Rotate

Pan Range	360- Endless
Pan Speed	0.036°~120°/sec
Tilt Range	-90°~40°
Tilt Speed	0.012°~ 40°/sec
Sequence	Preset(255ea), Swing, Group(6ea), Tour(1ea), Auto Run, Schedule
Preset Accuracy	±0.3°

#### Operational

Camera Title	Displayed up to 85 characters
Direction Indicator	Support
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SSDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR V
Digital Image Stabilization	Support
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Gain Control	Low, Middle, High
White Balance	ATW, AWC, Manual, Indoor, Outdoor

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com).

Hanwha Vision is formerly known as Hanwha Techwin.

Electronic Shutter Speed	Minimum, Maximum, Anti flicker (1~1/12,000sec)
Analytics	Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection
Alarm I/O	Input 1ea / Output 1ea
Alarm Triggers	Analytics, Network disconnect, Alarm input
Alarm Events	File upload via FTP and E-Mail Notification via E-Mail SD/SDHC/SDXC or NAS recording at event triggers Alarm output Handover
Audio In	Selectable(Mic in/Line in), Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
Audio Out	Line out, Max.output level: 1Vrms
IR Illuminator (Optional)	Support (Auto/Manual)
Water Removal	Support (with Wiper)
<b>Network</b>	
Ethernet	RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression	G.711 u-law, G.726 G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
Smart Codec	Manual(5ea area), WiseStream II
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users), Multicast Multiple streaming(Up to 10 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTP
Security	HTTPS(SSL) login authentication Digest login authentication IP address filtering User access log 802.1X authentication(EAP-TLS, EAP-LEAP)
Application Programming Interface	ONVIF Profile S/G/T SUNAPI(HTTP API) Wisenet open platform
<b>General</b>	
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Edge Storage	Micro SD/SDHC/SDXC 1slot 256GB
Memory	1024MB RAM, 256MB Flash
<b>Environmental &amp; Electrical</b>	
Operating Temperature / Humidity	-40°C~+55°C(-40°F~+131°F) / Less than 90% RH
Storage Temperature / Humidity	-40°C~+60°C(-40°F~+140°F) / Less than 90% RH
Certification	IP66, Safety(UL, KC-SDOC), EMC(FCC, CE, VCCI, RCM, KC), IK10(Except wiper & window)
Input Voltage	24VAC
Power Consumption	Max 100W(Heater On), typical 25W(Heater Off)
<b>Mechanical</b>	
Color / Material	White / Aluminum
RAL Code	RAL9003
Product Dimensions / Weight	219(W) × 528.2(H) × 460(D)mm (8.62x20.79x18.11"), 14Kg (30.86 lb)

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com).

Hanwha Vision is formerly known as Hanwha Techwin.

Compatible Models

Wall Mount	SBU-500WM
------------	-----------

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide: 64.2m(210.50ft) / Tele: 2,009.0m(6,591.31ft)
Observe (63PPM/ 19PPF)	Wide: 25.7m(84.20ft) / Tele: 803.6m(2,636.53ft)
Recognize (125PPM/ 38PPF)	Wide: 12.8m(42.10ft) / Tele: 401.8m(1,318.26t)
Identify (250PPM/ 76PPF)	Wide: 6.4m(21.05ft) / Tele: 200.9m(659.13ft)

TNU-6321

2MP Positioning Camera



CAD

Unit:mm [inch]

