



APC Smart-UPS RC 1000VA, 230V, 4x India 3-pin 6A outlets, harsh environment

SRC1KI-IN

Overview

Lead time Usually in Stock

Main

IVIAIII		
Main Input Voltage	230 V	
Product or component type	Uninterruptible power supply (UPS)	
Main Output Voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated power in W	800 W	
rated power in VA	1000 VA	
Input Connection Type	India 3-pin 6A	
output connection type	4 India 3-pin 6A	
Cable length	1.5 m	
Number of cables	1	
Provided equipment	Smart UPS signalling RS-232 cable User manual Warranty card	
Range of product	Smart-UPS On-Line	

Batteries & Runtime

Run Time	View Runtime Graph ☐	
Battery type	Lead-acid battery	
Extended runtime	0	
Number of battery filled slots	0	
Number of battery free slots	0	
Battery recharge time	6 h	
Battery charger power	54 W rated	

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
UPS type	Double conversion online

Physical

Colour	Black
Height	22 cm
Width	14.5 cm
Depth	40 cm
Net weight	13.5 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Switching current capacity	10 A
Plug standard	India 3-pin 6A
Input voltage limits	110280 V half load
Network frequency	4070 Hz

Output

Bypass type	Built-in bypass
Crest factor	3:1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
Wave type	Sine wave
Efficiency	90 % (full load) 88 % (half load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Environmental

Operating altitude	03000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-2060 °C
Storage altitude	0.0000000004572.0000000000 m
Relative humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators	
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34 cm
Package 1 Width	47.8 cm
Package 1 Length	23.5 cm
Package 1 Weight	14.5 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

$\ensuremath{ \ensuremath{ \mathcal{O}}}$ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
REACh Regulation	REACh Declaration
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes

Product datasheet

SRC1KI-IN

Image of product / Alternate images

Alternative





SRC1KI-IN

