# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





# APC Easy UPS, 650VA, Floor Mount, 230V, 4x IEC C13 outlets, AVR

BV650-IN

Usually Ships within 4 Weeks

Lead-acid battery

User manual

Back-UPS

1 x detachable IEC power cord

### Overview

Lead time

Main		
Main Input Voltage	230 V	
Main Output Voltage	230 V	
Other Output Voltage	230 V	
Rated power in W	360 W	
rated power in VA	650 VA	
Product or component type	Uninterruptible power supply (UPS)	
Input Connection Type	IEC 60320 C14	
output connection type	4 IEC 60320 C13	
Cable length	1.2 m	
Number of cables	1	

### **Batteries & Runtime**

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Battery voltage	12 V
Battery capacity	7 Ah
Extended runtime	0

### **General**

Battery type

**Provided equipment** 

Range of product

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

# **Physical**

Black	
14.2 cm	
10.1 cm	
27.9 cm	
4.4 kg	
No preference	
Not rack-mountable	
0	
No	

# Input

Network frequency	4070 Hz +/- 5 Hz auto-sensing	
Input voltage limits	140300 V	

# Output

Maximum configurable power in W	360 W	
Output frequency	50/60 Hz +/- 1 Hz unsynchronised	
UPS type	Line interactive	
Wave type	Stepped approximation to a sinewave	
Graph display	1	
Maximum configurable power in VA	650 VA	
Transfer time	4 ms typical : 8 ms maximum	

### **Environmental**

Ambient air temperature for operation	040 °C	
Relative humidity	095 % non-condensing	
Operating altitude	03000 m	
Ambient air temperature for storage	-2050 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	015000 m	
Acoustic level	40 dBA	
IP degree of protection	IP20	

# **Surge Protection and Filtering**

Surge energy rate	160 J

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22 cm
Package 1 Width	32.4 cm

Package 1 Length	14 cm
Package 1 Weight	5 kg
SCC14	10731304345876

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### ∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
<sup>⋄</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes

# BV650-

Image of product / Alternate images

**Alternative** 



