



Network

PTZ

XNP-6371RH

2M H.265 37x IR PTZ Camera



Key Features

- Max. 2megapixel (1920 x 1080) resolution
- 6~ 222mm (Optical 37x) lens
- 0.01Lux@F1.5 (Color), 0Lux (B/W, IR LED on)
- Max. IR viewable length : 350m (1,148ft)
- Day & Night (ICR), WDR (150dB)
- DIS & Shock detection with built-in gyro sensor
- Intelligent Video / Audio Analytics, Defog
- H.265, H.264, MJPEG codec support
- Multiple streaming, WiseStream II support
- SD / SDHC / SDXC memory 1 slot (Up to 256 GB)
- IP66, IK10

XNP-6371RH

2M H.265 37x IR PTZ Camera



Specifications

| | |
|-----------------------------|---|
| Video | |
| Imaging Device | 1/2" 2MP CMOS |
| Resolution | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| Max. Framerate | H.265/H.264: Max. 60fps/50fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz) |
| Min. Illumination | Color: 0.01Lux(F1.5, 1/30sec) BW: 0Lux(IR LED On) |
| Video Out | CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation |
| Lens | |
| Focal Length (Zoom Ratio) | 6~222mm(37x) zoom |
| Optical Zoom | 37x |
| Max. Aperture Ratio | F1.5(Wide)~F4.6(Tele) |
| Angular Field of View | H: 59.3°(Wide)~1.90°(Tele) / V: 35.8°(Wide)~1.1°(Tele) |
| Min. Object Distance | Wide: 1.5m(4.92ft) / Tele: 2.0m(6.56ft) |
| Focus Control | AF / One-Shot AF / Manual |
| Lens Type | DC auto iris |
| Pan / Tilt / Rotate | |
| Pan Range | 360° Endless |
| Pan Speed | Preset: 400°/sec, Manual: 0.024°/sec~250°/sec |
| Tilt Range | 190°(-5°~185°) |
| Tilt Speed | Preset: 300°/sec, Manual: 0.024°/sec ~ 250°/sec |
| Sequence | Preset(300ea), Swing, Group(6ea), Trace, Tour, Auto Run, Schedule |
| Preset Accuracy | ±0.2° |
| Operational | |
| Camera Title | Displayed up to 85 characters |
| Direction Indicator | Support |
| Day & Night | Auto(ICR) |
| Backlight Compensation | BLC, HLC, WDR, SSDR |
| Wide Dynamic Range | 150dB |
| Digital Noise Reduction | SSNR V |
| Digital Image Stabilization | Support(built-in gyro sensor) |
| Defog | Support |
| Motion Detection | 8ea, 8point polygonal zones |
| Privacy Masking | 32ea, rectangular Support - Color: Grey/Green/Red/Blue/Black/White - Mosaic |

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com.

Hanwha Vision is formerly known as Hanwha Techwin.

| | |
|--------------------------|---|
| Gain Control | Low / Middle / High |
| White Balance | ATW / AWC / Manual / Indoor / Outdoor |
| Electronic Shutter Speed | Minimum / Maximum / Anti flicker (2~1/12,000sec) |
| Video Rotation | Flip, Mirror |
| Analytics | Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification, Shock detection |
| Serial Interface | RS-485(Samsung-T, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell) |
| Alarm I/O | Input 4ea / Output 2ea |
| Alarm Triggers | Analytics, Network disconnect, Alarm input |
| Alarm Events | File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at event triggers Alarm output PTZ Preset |
| Audio In | Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm |
| Audio Out | Line out, Max.output level: 1Vrms |
| Light Type | IR LED (850nm) |
| IR Viewable Length | 350m(1,148.29ft) |
| Auto Tracking | Support |

| | |
|-----------------------------------|---|
| Network | |
| Ethernet | RJ-45(10/100BASE-T), SFP(Optional) |
| Video Compression | H.265/H.264: Main/Baseline/High, MJPEG |
| Audio Compression | G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz |
| Smart Codec | Manual(5ea area), WiseStream II |
| Bitrate Control | H.264/H.265: CBR or VBR MJPEG: VBR |
| Streaming | Unicast(20 users) / Multicast (128 user) Multiple streaming(Up to 10 profiles) |
| Protocol | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP, NTCIP 1205 |
| Security | HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) Device Certificate(Hanwha Private Root CA) |
| Application Programming Interface | ONVIF Profile S/G SUNAPI(HTTP API) Wisenet open platform |

| | |
|------------------|---|
| General | |
| Webpage Language | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek |
| Edge Storage | SD/SDHC/SDXC 1slot 256GB |
| Memory | 1024MB RAM, 256MB Flash |

| | |
|----------------------------------|---|
| Environmental & Electrical | |
| Operating Temperature / Humidity | -50°C ~ +55°C (-58°F ~ +131°F) |
| Storage Temperature / Humidity | -50°C ~ +60°C (-58°F~+140°F) / Less than 90% RH |
| Certification | IP66, IK10 |

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com.

Hanwha Vision is formerly known as Hanwha Techwin.

| | |
|-------------------|----------------|
| Input Voltage | 24VAC |
| Power Consumption | 24VAC: Max 90W |

Mechanical

| | |
|-----------------------------|--|
| Color / Material | Body: Ivory / Aluminum+Plastic, Head: Black / Aluminum+Plastic |
| Product Dimensions / Weight | ø236.9x407.7mm(9.33x16.05"), 7.1Kg(15.65 lb) |
| Ceiling Mount (Assy) | SBP-300CM |
| Wall Mount | SBP-300WM1, SBP-300WM |
| Pole Mount | SBP-300PM1 |
| Parapet Mount | SBP-300LM |
| Corner Mount | SBP-300KM1 |
| Other Compatible Models | SBP-303HF |

DORI (EN62676-4 standard)

| | |
|---------------------------|--|
| Detect (25PPM/ 8PPF) | Wide: 67.5m(221.3ft) / Tele: 2315.7m(7597.6ft) |
| Observe (63PPM/ 19PPF) | Wide: 27m(88.5ft) / Tele: 926.3m(3039ft) |
| Recognize (125PPM/ 38PPF) | Wide: 13.5m(44.3ft) / Tele: 463.1m(1519.5ft) |
| Identify (250PPM/ 76PPF) | Wide: 6.7m(22.1ft) / Tele: 231.6m(759.8ft) |

XNP-6371RH

2M H.265 37x IR PTZ Camera



CAD

Unit:mm [inch]

