



APC Smart-UPS On-Line, 15kVA/ 15kW, Rack/Tower, 230V/400V, Hard wire 3-wire(1P+N+E)/5wire(3P+N+E), Network Card, No battery, W/O rail kit

SURT15KUXIG-INX

Overview

Lead time Usually in Stock

Main	
Main Input Voltage	230 V 1 phase 415 V 3 phases
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220240 V
Main Output Voltage	230 V 1 phase 415 V 3 phases
Other Output Voltage	230 V
Rated power in W	15000 W
rated power in VA	15000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1 Hard wire 3-wire (1P + N + E) 1 IEC Jumpers 3-wire (1P + N + E) 1
Number of rack unit	3U
Provided equipment	1 x installation guide 1 x safety guide 1 x Smart UPS signalling RS-232 cable
Range of product	Smart-UPS On-Line

Batteries & Runtime

Efficiency	View Efficiency Graph ☐
Battery type	External battery system
Battery voltage	+/- 192 V
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	0
Battery charger power	6074 W rated

General

Redundant	No
UPS type	Double conversion online

Physical

Colour Black Height 13.1 cm Width 44.0 cm Depth 75.7 cm Net weight 26.5 kg Mounting location Front Mounting preference Lower Mounting mode Rack-mounted Two post mountable 0 USB compatible No	•	
Width 44.0 cm Depth 75.7 cm Net weight 26.5 kg Mounting location Front Mounting preference Lower Mounting mode Rack-mounted Two post mountable 0	Polour B	Black
Depth 75.7 cm Net weight 26.5 kg Mounting location Front Mounting preference Lower Mounting mode Rack-mounted Two post mountable 0	leight 1	3.1 cm
Net weight 26.5 kg Mounting location Front Mounting preference Lower Mounting mode Rack-mounted Two post mountable 0	Vidth 4	14.0 cm
Mounting location Front Mounting preference Lower Mounting mode Rack-mounted Two post mountable 0	Pepth 7	75.7 cm
Mounting preference Lower Mounting mode Rack-mounted Two post mountable 0	let weight 2	26.5 kg
Mounting mode Rack-mounted Two post mountable 0	founting location F	Front
Two post mountable 0	Nounting preference	ower
	Nounting mode	Rack-mounted
USB compatible No	wo post mountable 0	
	JSB compatible N	No

Input

Maximum input current	66 A
Input harmonic distortion	Less than 5 % for full load
Load power factor	From 0.9 leading to 1 lagging
Switching current capacity	100 A
Input voltage limits	160285 V
Input current	66 A
Number of input connectors	1 hard wire 3-wire (H N + E)
Network frequency	4070 Hz auto sensing

Output

Bypass type	Built-in static bypass
Crest factor	3:1
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	15000 VA
Maximum configurable power in W	15000 W
Output overload operation	60 seconds at 125% and 30 seconds at 150%
Wave type	Sine wave
Efficiency	93 % (in battery operation)
Output frequency	50/60 Hz +/- 0.1 Hz sync to mains
Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage

Conformance

Product certifications CB

Environmental

Acoustic level	58 dBA
Heat dissipation	3821 Btu/h
Operating altitude	03000 m

Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1560 °C
Storage altitude	015000 m
IP degree of protection	IP20
Relative humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

Communications & Management

Emergency power off	Yes
Free slots	0
Preinstalled device	Network management card
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Noise suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping
	response time: meets III 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	240 mm
Package 1 Width	590 mm
Package 1 Length	790 mm
Package 1 Weight	35 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental Disclosure

Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No

SURT15KUXIG-INX

Image of product / Alternate images

Alternative





SURT15KUXIG-INX





SURT15KUXIG-INX



