



# APC Smart-UPS RC 1000VA, 230V, no battery, 4x India 3-pin 6A outlets

SRC1KUXI

#### Overview

Lead time Usually in Stock

#### Main

wain	
Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	800 W
rated power in VA	1000 VA
Input Connection Type	India 3-pin 6A
output connection type	4 India 3-pin 6A
Cable length	1.5 m
Number of cables	1
Provided equipment	Smart UPS signalling RS-232 cable User manual Warranty card
Range of product	Smart-UPS On-Line

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐	
Battery type	External battery system	
Extended runtime	0	
Number of battery filled slots	0	
Number of battery free slots	0	

## **General**

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
UPS type	Double conversion online

# **Physical**

Colour	Black
Height	22 cm
Width	14.5 cm
Depth	40 cm
Net weight	5.7 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Switching current capacity	10 A
Plug standard	India 3-pin 6A
Input voltage limits	110280 V half load
Network frequency	4070 Hz

## Output

Crest factor	3:1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
Wave type	Sine wave
Efficiency	90 % (full load) 88 % (half load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

#### Conformance

Product certifications BIS

## **Environmental**

Operating altitude	03000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-2060 °C
Storage altitude	0.00000000004572.0000000000 m
Relative humidity	095 %
Storage Relative Humidity	095 %

## **Communications & Management**

Alarm Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## **Packing Units**

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	34 cm
Package 1 Width	47.8 cm
Package 1 Length	23.5 cm
Package 1 Weight	6.3 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

## ∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
REACh Regulation	REACh Declaration
Optimized Energy Efficiency	Energy efficient product

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes

## **Product datasheet**

## **SRC1KUXI**

Image of product / Alternate images

**Alternative** 





