Assignment –6

Using Special Operators in Conditions.

Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.

```
mysql> select * from orders
    -> where Odate ='1990-03-10' or Odate = '1990-04-10';
+------+---------+------------+------+------+
| Onum | Amt     | Odate      | Cnum | Snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-03-10 | 2008 | 1007 |
| 3003 |  767.19 | 1990-03-10 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-03-10 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-03-10 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-03-10 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-04-10 | 2002 | 1003 |
| 3007 |   75.75 | 1990-04-10 | 2004 | 1002 |
+------+---------+------------+------+------+
```

Query 2:-

```
mysql> select * from orders
    -> where odate between '1990-03-10' and '1990-04-10';
+------+---------+------------+------+------+
| Onum | Amt     | Odate      | Cnum | Snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-03-10 | 2008 | 1007 |
| 3003 |  767.19 | 1990-03-10 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-03-10 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-03-10 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-03-10 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-04-10 | 2002 | 1003 |
| 3007 |   75.75 | 1990-04-10 | 2004 | 1002 |
+------+---------+------------+------+------+
```

2)Write a query that selects all of the customers serviced by Peel or Motika.(Hint: the snum field relates the two tables to one another).

```
mysql> select * from customers
    -> where snum ='1001' or snum ='1004';
+------+---------+--------+--------+------+
| Cnum | Cname   | City   | Rating | Snum |
+------+---------+--------+--------+------+
| 2001 | Hoffman | London |    100 | 1001 |
| 2006 | Clemens | London |    100 | 1001 |
| 2007 | Pereira | Rome   |    100 | 1004 |
+------+---------+--------+--------+------+
3 rows in set (0.01 sec)
```

Write a query that will produce all the customers whose names begin with a letter from ‘A’ to ‘G’.

```
mysql> select * from customers
    ->  where cname like 'A%'
    ->  or cname like 'B%'
    -> or cname like 'C%'
    -> or cname like 'D%'
    -> or cname like 'E%'
    -> or cname like 'F%'
    -> or cname like 'G%';
+------+----------+----------+--------+------+
| Cnum | Cname    | City     | Rating | Snum |
+------+----------+----------+--------+------+
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2006 | Clemens  | London   |    100 | 1001 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
4 rows in set (0.01 sec)
```

4) Write a query that selects all customers whose names begin with the letter 'C'.

```
mysql>  select * from customers
    ->  where cname like 'C%';
+------+----------+----------+--------+------+
| Cnum | Cname    | City     | Rating | Snum |
+------+----------+----------+--------+------+
| 2006 | Clemens  | London   |    100 | 1001 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
2 rows in set (0.00 sec)
```

5)Write a query that selects all orders except those with zeroes or NULLs in the amt field.

```
mysql> select * from orders
    -> where Amt != 0 or Amt != null;
+------+---------+------------+------+------+
| Onum | Amt     | Odate      | Cnum | Snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-03-10 | 2008 | 1007 |
| 3003 |  767.19 | 1990-03-10 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-03-10 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-03-10 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-03-10 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-04-10 | 2002 | 1003 |
| 3007 |   75.75 | 1990-04-10 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-05-10 | 2006 | 1001 |
| 3010 | 1309.95 | 1990-06-10 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-06-10 | 2006 | 1001 |
+------+---------+------------+------+------+
10 rows in set (0.00 sec)
```