Assignment – 11

Subqueries.

Write a query that uses a subquery to obtain all orders for the customer named Cisneros. Assume you do not know his customer number (cnum).

```
mysql>  select * from orders
    -> where cnum = (
    -> select cnum from customers
    -> where cname = 'Cisneros');
+------+---------+------------+------+------+
| Onum | Amt     | Odate      | Cnum | Snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-03-10 | 2008 | 1007 |
| 3006 | 1098.16 | 1990-03-10 | 2008 | 1007 |
+------+---------+------------+------+------+
2 rows in set (0.07 sec)
```

Write a query that produces the names and ratings of all customers who have above-average orders.

```
mysql>  select cname, rating from customers
    ->  where cnum in(
    ->  select cnum from orders
    -> where amt >(select avg(amt)from orders));
+---------+--------+
| cname   | rating |
+---------+--------+
| Liu     |    200 |
| Clemens |    100 |
+---------+--------+
2 rows in set (0.00 sec)
```

Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the amount of the largest order in the table.

```
mysql> select snum,sum(amt) as total_sales
    -> from orders group by snum
    -> having sum(amt)>
    -> (select max(amt) from orders);
+------+-------------+
| snum | total_sales |
+------+-------------+
| 1001 |    15382.07 |
+------+-------------+
1 row in set (0.05 sec)
```