Assignment –5 **Relational and Logical Operators.**

1) Write a query that will give you all orders for more than Rs. 1,000.

```
mysql> select * from ORDERS
    -> where Amt >1000;
+------+---------+------------+------+------+
| Onum | Amt     | Odate      | Cnum | Snum |
+------+---------+------------+------+------+
| 3002 | 1900.10 | 1990-03-10 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-03-10 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-03-10 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-04-10 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-05-10 | 2006 | 1001 |
| 3010 | 1309.95 | 1990-06-10 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-06-10 | 2006 | 1001 |
+------+---------+------------+------+------+
```

2) Write a query that will give you the names and cities of all salespeople in London with a commission above .10.

Ans:

```
mysql> select  * from SALESPEOPLE
    -> where City = 'London' and Comm > 0.10;
+------+--------+--------+------+
| Snum | Sname  | City   | Comm |
+------+--------+--------+------+
| 1001 | Peel   | London | 0.12 |
| 1003 | Motika | London | 0.11 |
+------+--------+--------+------+
2 rows in set (0.00 sec)
```

3)Write a query on the Customers table whose output will exclude all customers with a rating <= 100, unless they are located in Rome.

Ans:

```
mysql> select * from  CUSTOMERS
    -> where Rating <= 100 or City = 'Rome';
+------+----------+--------+--------+------+
| Cnum | Cname    | City   | Rating | Snum |
+------+----------+--------+--------+------+
| 2001 | Hoffman  | London |    100 | 1001 |
| 2002 | Giovanni | Rome   |    200 | 1003 |
| 2006 | Clemens  | London |    100 | 1001 |
| 2007 | Pereira  | Rome   |    100 | 1004 |
+------+----------+--------+--------+------+
```

4) What will be the output from the following query?

Select * from Orders

where (amt < 1000 OR

NOT (odate = ‘1990-10-03’ AND cnum > 2003));

```
mysql> select * from orders
    -> where(amt<1000 or not (odate ='1990-03-10' and cnum>2003));
+------+---------+------------+------+------+
| Onum | Amt     | Odate      | Cnum | Snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-03-10 | 2008 | 1007 |
| 3003 |  767.19 | 1990-03-10 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-03-10 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-04-10 | 2002 | 1003 |
| 3007 |   75.75 | 1990-04-10 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-05-10 | 2006 | 1001 |
| 3010 | 1309.95 | 1990-06-10 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-06-10 | 2006 | 1001 |
+------+---------+------------+------+------+
```

5) What will be the output of the following query?

Select * from Orders where NOT ((odate = ‘1990-10-03’ OR snum >1006) AND amt >= 1500);

```
mysql> select * from ORDERS
    -> where not ((Odate = '1990-10-03' or Snum >1006) and Amt >= 1500);
+------+---------+------------+------+------+
| Onum | Amt     | Odate      | Cnum | Snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-03-10 | 2008 | 1007 |
| 3003 |  767.19 | 1990-03-10 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-03-10 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-03-10 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-03-10 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-04-10 | 2002 | 1003 |
| 3007 |   75.75 | 1990-04-10 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-05-10 | 2006 | 1001 |
| 3010 | 1309.95 | 1990-06-10 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-06-10 | 2006 | 1001 |
+------+---------+------------+------+------+
```

6)What is a simpler way to write this query?

Select snum, sname, city, comm From Salespeople where (comm > .12 OR comm <.14);