Assignment – 15

Using Subqueries with DML Commands.

Assume there is a table called Multicust, with all of the same column definitions as Salespeople. Write a command that inserts all salespeople with more than one customer into this table.

```
mysql> create table multicust
    -> select * from salespeople
    ->  where snum in (
    ->  select snum from customers
    ->  group by snum
    ->  having count(*) > 1
    -> );
Query OK, 2 rows affected, 1 warning (0
Records: 2  Duplicates: 0  Warnings: 1

mysql> select * from multicust;
+------+--------+----------+------+
| Snum | Sname  | City     | Comm |
+------+--------+----------+------+
| 1001 | Peel   | London   | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
+------+--------+----------+------+
```

Write a command that deletes all customers with no current orders.

Query:

Output:

Write a command that increases by twenty percent the commissions of all salespeople with total orders above Rs. 3,000.

```
mysql> update salespeople
    -> set comm = comm+0.2
    -> where snum in
    -> (select snum from orders
    -> where amt>3000);
Query OK, 1 row affected (0.10 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> select * from salespeople;
+------+---------+----------+------+
| Snum | Sname   | City     | Comm |
+------+---------+----------+------+
| 1001 | Peel    | London   | 0.12 |
| 1002 | Serres  | San Jose | 0.33 |
| 1003 | Motika  | London   | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1004 | Axelrod | New York | 0.10 |
| 1100 | Blanco  | San Jose | NULL |
+------+---------+----------+------+
6 rows in set (0.00 sec)
```