Assignment – 19

Views.

1) Create a view that shows all of the customers who have the highest ratings.

```
mysql> create view high_rate
    -> as
    -> select * from customers
    -> where rating = (select max(rating) from customers);
Query OK, 0 rows affected (0.07 sec)

mysql> select * from kharghar.high_rate;
+------+----------+----------+--------+------+
| Cnum | Cname    | City     | Rating | Snum |
+------+----------+----------+--------+------+
| 2002 | Giovanni | Rome     |    300 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
3 rows in set (0.05 sec)
```

2) Create a view that shows the number of salespeople in each city.

```
sql> create view city_count
  -> as
  -> select count(sname), city from salespeople
  -> group by city;
ery OK, 0 rows affected (0.06 sec)

sql> select * from khargar.city_count;
+--------------+-----------+
| count(sname) | city      |
+--------------+-----------+
|            2 | London    |
|            2 | San Jose  |
|            1 | Barcelona |
|            1 | New York  |
+--------------+-----------+
```

3) Create a view that shows the average and total orders for each salesperson after his or her name. Assume all names are unique.

```
mysql> create view avg_count
    -> as
    -> select sname, avg(amt), count(onum) from salespeople,
    -> orders
    ->  where orders.snum = salespeople.snum
    -> group by sname;
Query OK, 0 rows affected (0.05 sec)

mysql> select * from khargar.avg_count;
+---------+-------------+-------------+
| sname   | avg(amt)    | count(onum) |
+---------+-------------+-------------+
| Rifkin  |  558.425017 |           2 |
| Motika  | 1900.099976 |           1 |
| Peel    |  767.190002 |           1 |
| Serres  | 2182.050049 |           3 |
| Axelrod | 1713.229980 |           1 |
+---------+-------------+-------------+
```

4) Create a view that shows each salesperson with multiple customers.

```
mysql> create view multicustomer
    -> as
    -> select sname, cname from salespeople, customers
    -> where customers.snum = salespeople.snum;
Query OK, 0 rows affected (0.05 sec)

mysql> select * from multicustomer;
+---------+----------+
| sname   | cname    |
+---------+----------+
| Peel    | Hoffman  |
| Serres  | Grass    |
| Serres  | Liu      |
| Serres  | Giovanni |
| Rifkin  | Cisneros |
| Axelrod | Pereira  |
+---------+----------+
```