- A. client.c and server.c source code submitted in the zip file
- B. The server sends the hello message to the client

```
2019A7PS0134G_L5 — server — 80x24

[(base) kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 % ./server SERVER IS RUNNING, WAITING FOR CLIENT TO CONNECT
Server : Hello, what is your name?

[Client : ■

2019A7PS0134G_L5 — client — 80x24

[(base) kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 % ./client Server : Hello, what is your name?

Client : ■
```

C. CASE 1: Sends name with small case

```
| Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * ./server | SERVER IS RUNNING, WAITING FOR CLIENT TO CONNECT | Server : Hello, what is your name? | Client : kunal | Server : 500 ERROR | Client : .

Server : Thank You, kunal | Server : Thank You, kunal | Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * ./client | Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * ./client | Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * | Client : .

Server : Thank You, kunal | Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * | Client : .

Server : Thank You, kunal | Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * | Client : .

Server : Thank You, kunal | Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * | Client : .

Server : Thank You, kunal | Clase| kunalkariwala@kunals-MacBook-Air 2019A7PS0134G_L5 * | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .

Server : Thank You, kunal | Client : .


Server : Thank You, kunal | Client : .

Server : Thank You, kunal |
```

## CASE 2: Sends name with the first letter capital

```
| Collect | Server |
```

D. CASE 1: Client receives a 500 ERROR and terminates by sending a "."



## CASE 2: Client receives a 200 OK and is allowed to send messages

```
| Client : YO! Thanks for accepting | 2019A7PS0134G_L5 - server - 80x24 | 2019A7PS0134G_L5 - client -
```

E. Client is allowed to send continuous lines of messages to the server

```
| Client : I can type anything as long as it is within the max length client : dang this works | Client : thank you | Client : thank yo
```

## F. Server sends Thank you message

