

# Computer Networks Lab 6

More on Client-Server Communication




Arun Ganti

2019A7PS0021G

NOTE: While testing the code, if after running the server once, and you get “Cannot bind -1” error while running again, then wait for some time.

If you run **netstat --tcp --numeric | grep 4444** you will see that the socket on the port 4444 is in TIME\_WAIT state. Meaning that connection is closed, so it will be terminated in the timeout specified by the OS. After the timeout expires, the program executes without the error.

# Directory structure



# The server and client are asking for input

```
PROBLEMS OUTPUT TERMINAL DEBUG CONSOLE
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ ./server
> Enter port number : █

samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ ./client
> Enter port number : █
```

# The client is asking for file name.

```
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ ./server
> Enter port number : 4444
> Server bound to IP : 127.0.0.1 and PORT : 4444
> New connection

> Client's requested file: █

samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ ./client
> Enter port number : 4444
> Enter server address : 127.0.0.1
> Connected to server IP = 127.0.0.1 and PORT = 4444

> Enter file name: █
```

# The server sent 10 bytes of data from the file requested and the client created the file.

```
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ ./server
> Enter port number : 4444
> Server bound to IP : 127.0.0.1 and PORT : 4444
> New connection

> Client's requested file: Networkingtrends.txt
> Data sent to the client : Enabling m

> Closing connection...

> Closing server...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ █

samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ ./client
> Enter port number : 4444
> Enter server address : 127.0.0.1
> Connected to server IP = 127.0.0.1 and PORT = 4444

> Enter file name: Networkingtrends.txt
> Server response: Enabling m

> Creating file : Networkingtrends.txt

> Closing client...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ █
```

# More examples

```
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ ./server
> Enter port number : 4444
> Server bound to IP : 127.0.0.1 and PORT : 4444
> New connection

> Client's requested file: Networkingtrends.txt
> Data sent to the client : Enabling m

> Closing connection...

> Closing server...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ ./server
> Enter port number : 4444
> Server bound to IP : 127.0.0.1 and PORT : 4444
> New connection

> Client's requested file: b.txt
> Data sent to the client : hello

> Closing connection...

> Closing server...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ ./server
```

```
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ ./client
> Enter port number : 4444
> Enter server address : 127.0.0.1
> Connected to server IP = 127.0.0.1 and PORT = 4444

> Enter file name: Networkingtrends.txt
> Server response: Enabling m

> Creating file : Networkingtrends.txt

> Closing client...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ ./client
> Enter port number : 4444
> Enter server address : 127.0.0.1
> Connected to server IP = 127.0.0.1 and PORT = 4444

> Enter file name: b.txt
> Server response: hello

> Creating file : b.txt

> Closing client...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ ./client
```

```
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$ ./server
> Enter port number : 4444
> Server bound to IP : 127.0.0.1 and PORT : 4444
> New connection

> Client's requested file: random.txt
> Data sent to the client :

> Closing connection...

> Closing server...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/server$
```


```
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$ ./client
> Enter port number : 4444
> Enter server address : 127.0.0.1
> Connected to server IP = 127.0.0.1 and PORT = 4444

> Enter file name: random.txt
> Server response:

> Creating file : random.txt


> Closing client...
samaritan@pop-os:~/Desktop/3-2/cn/labs/lab6/client$
```

Results : Networkingtrends.txt in client directory (10 bytes)




A screenshot of a text editor window. The title bar shows the filename 'Networkingtrends.txt' and the path '~/Desktop/3-2/cn/labs/lab6/client'. The window contains a single line of text: '1|Enabling m'.

Results : b.txt in client directory (5 bytes)



A screenshot of a text editor window. The title bar shows the filename 'b.txt' and the path '~/Desktop/3-2/cn/labs/lab6/client'. The window contains a single line of text: '1|hello'.

Results : random.txt in client directory (empty file / 0 bytes)



A screenshot of a text editor window. The title bar shows the filename 'random.txt' and the path '~/Desktop/3-2/cn/labs/lab6/client'. The window is empty, with only a cursor visible at the start of the first line.