

Run the first 4 cells to import data and create training and testing set

```
In [3]: import numpy as np
import h5py
import tensorflow as tf
import matplotlib.pyplot as plt
from keras.models import Sequential
from keras.layers import SimpleRNN, LSTM, Dense, Activation
from keras.utils import to_categorical
#from sklearn.preprocessing import OneHotEncoder
from sklearn.preprocessing import StandardScaler
from UtilNNDL import *
```

```
In [16]: """
#file_path = '/home/carla/Downloads/project_datasets/project_datasets/'
file_path = '/home/kunal/Desktop/FinalProject/datasets/A01T_slice.mat'

A01T = h5py.File(file_path, 'r')
data = np.copy(A01T['image'])
data = np.transpose(data, (0, 2, 1))
data = data[:, :, :22]
labels = np.copy(A01T['type'])
labels = labels[0, 0:data.shape[0]:1]
labels = np.asarray(labels, dtype=np.int32)

a = data[:56]
b = data[57:]
data = np.vstack((a, b))
a = labels[:56]
b = labels[57:]
labels = np.hstack((a, b))
#enc = OneHotEncoder()
#enc_labels = enc.fit_transform(labels.reshape(-1, 1)).toarray()
enc_labels = to_categorical(labels-769, num_classes=4)
print(enc_labels)

#scaler = StandardScaler()
#data = scaler.fit_transform(data, enc_labels)
"""
```

```
[[ 0.  0.  0.  1.]
 [ 0.  0.  1.  0.]
 [ 0.  1.  0.  0.]
 ...,
 [ 1.  0.  0.  0.]
 [ 0.  1.  0.  0.]
 [ 1.  0.  0.  0.]]
```

```
In [17]: """
bs, t, f = data.shape
np.random.seed(42)
shuffle = np.random.choice(bs,bs,replace=False)

train_samples = 237
train_data = data[shuffle[:train_samples],:,:]
train_labels = enc_labels[shuffle[:train_samples]]
test_data = data[shuffle[train_samples:],:,:]
test_labels = enc_labels[shuffle[train_samples:]]

train_data = np.transpose(train_data,(0,2,1))
test_data = np.transpose(test_data,(0,2,1))

train_data,train_labels = create_window_data(train_data,train_labels)
test_data,test_labels = create_window_data(test_data,test_labels)

train_data = np.transpose(train_data,(0,2,1))
test_data = np.transpose(test_data,(0,2,1))

bs, t, f = train_data.shape
"""
```

```
In [4]: A01T = h5py.File('/home/carla/Downloads/project_datasets/project_datasets/A01T_slice.mat', 'r')
data = np.copy(A01T['image'])
labels = np.copy(A01T['type'])
labels = labels[0,0:data.shape[0]:1]
labels = np.asarray(labels, dtype=np.int32)
```

```
a = data[:56]
b = data[57:]
data = np.vstack((a,b))
a = labels[:56]
b = labels[57:]
labels = np.hstack((a,b))
#enc = OneHotEncoder()
#enc_labels = enc.fit_transform(labels.reshape(-1,1)).toarray()
enc_labels = to_categorical(labels-769, num_classes=4)
print(enc_labels)
```

```
-----
IOError                                Traceback (most recent call last)
<ipython-input-4-2bdf612bd310> in <module>()
----> 1 A01T = h5py.File('/home/carla/Downloads/project_datasets/project_datasets/A01T_slice.mat', 'r')
```

```
      2 data = np.copy(A01T['image'])
      3 labels = np.copy(A01T['type'])
      4 labels = labels[0,0:data.shape[0]:1]
      5 labels = np.asarray(labels, dtype=np.int32)
```

```
/home/kunal/Desktop/FinalProject/venv/local/lib/python2.7/site-packages/h5py/_hl/files.pyc in __init__(self, name, mode, driver, libver, userblock_size, swmr, **kwargs)
```

```
    267         with phil:
    268             fapl = make_fapl(driver, libver, **kwargs)
--> 269             fid = make_fid(name, mode, userblock_size, fapl, swmr=swmr)
    270
    271         if swmr_support:
```

```
/home/kunal/Desktop/FinalProject/venv/local/lib/python2.7/site-packages/h5py/_hl/files.pyc in make_fid(name, mode, userblock_size, fapl, fcpl, swmr)
```

```
    97         if swmr and swmr_support:
    98             flags |= h5f.ACC_SWMR_READ
--> 99         fid = h5f.open(name, flags, fapl=fapl)
    100     elif mode == 'r+':
    101         fid = h5f.open(name, h5f.ACC_RDWR, fapl=fapl)
```

```
h5py/_objects.pyx in h5py._objects.with_phil.wrapper()
```

```
h5py/_objects.pyx in h5py._objects.with_phil.wrapper()
```

```
h5py/h5f.pyx in h5py.h5f.open()
```

```
IOError: Unable to open file (unable to open file: name = '/home/carla/Downloads/project_datasets/project_datasets/A01T_slice.mat', errno = 2, error message = 'No such file or directory', flags = 0, o_flags = 0)
```

```
In [7]: #file_path = '/home/carla/Downloads/project_datasets/project_datasets/'
file_path = '/home/kunal/Desktop/FinalProject/datasets/'
train_data, test_data, train_labels, test_labels = prepare_data(file_path,
                                                                    num_test_sam
                                                                    ples = 50,
                                                                    verbose= Fa
                                                                    lse,
                                                                    return_all=
                                                                    True,
                                                                    num_files =
                                                                    1)
print train_data.shape
print train_labels.shape
print test_data.shape
print test_labels.shape

(237, 22, 1000)
(237, 4)
(50, 22, 1000)
(50, 4)
```

```
In [8]: #assist numerical stability
train_data = train_data*(1e6)
test_data = test_data*(1e6)
```

```
In [9]: train_data = train_data.swapaxes(1,2)
test_data = test_data.swapaxes(1,2)
print train_data.shape
print test_data.shape
for i,a in enumerate(train_data):
    train_data[i] = bandpass_cnt(a, 4, 38, 250, filt_order=3)
for i,a in enumerate(test_data):
    test_data[i] = bandpass_cnt(a, 4, 38, 250, filt_order=3)
print train_data.shape
print test_data.shape

(237, 1000, 22)
(50, 1000, 22)
(237, 1000, 22)
(50, 1000, 22)
```

```
In [10]: for i,a in enumerate(train_data):
    train_data[i] = exponential_running_standardize(a, factor_new=0.001, ini
    t_block_size=1000, eps=1e-4)
for i,a in enumerate(test_data):
    test_data[i] = exponential_running_standardize(a, factor_new=0.001, ini
    t_block_size=1000, eps=1e-4)
train_data = train_data.swapaxes(1,2)
test_data = test_data.swapaxes(1,2)
print train_data.shape
print test_data.shape

(237, 22, 1000)
(50, 22, 1000)
```

```
In [12]: train_data_sliced, train_labels_sliced = create_window_data(train_data, tra
in_labels, windows=10)
test_data_sliced, test_labels_sliced = create_window_data(test_data, test_l
abels, windows=10)
print train_data_sliced.shape
print train_labels_sliced.shape
print test_data_sliced.shape
print test_labels_sliced.shape

(2370, 22, 512)
(2370, 4)
(500, 22, 512)
(500, 4)
```

Everything from this point down is Testing

```
In [18]: model = Sequential([
    LSTM(100, input_shape=(t,f)),
    Dense(32),
    Activation('relu'),
    #Dense(64),
    #Activation('relu'),
    Dense(32),
    Activation('relu'),
    Dense(4),
    Activation('softmax'),
])

model.compile(optimizer = 'adam',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

hist = model.fit(train_data,train_labels,epochs=15,validation_split=0.25,batch_size=32,verbose=0)
test_score = model.evaluate(test_data, test_labels, batch_size=32)

print(test_score)

plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy', 'Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss', 'Val Loss'],title='Losses')
```

```

-----
KeyboardInterrupt                                Traceback (most recent call last)
<ipython-input-18-4798cfald3bb> in <module>()
      15         metrics=['accuracy'])
      16
--> 17 hist = model.fit(train_data,train_labels,epochs=15,validation_split
=0.25,batch_size=32,verbose=0)
      18 test_score = model.evaluate(test_data, test_labels, batch_size=32)
      19

/home/carla/Documents/tensorflow/local/lib/python2.7/site-packages/keras/mo
dels.py in fit(self, x, y, batch_size, epochs, verbose, callbacks, validat
ion_split, validation_data, shuffle, class_weight, sample_weight, initial_e
poch, steps_per_epoch, validation_steps, **kwargs)
      961         initial_epoch=initial_epoch,
      962         steps_per_epoch=steps_per_epoch,
--> 963         validation_steps=validation_steps)
      964
      965     def evaluate(self, x=None, y=None,

/home/carla/Documents/tensorflow/local/lib/python2.7/site-packages/keras/en
gine/training.py in fit(self, x, y, batch_size, epochs, verbose, callbacks
, validation_split, validation_data, shuffle, class_weight, sample_weight,
initial_epoch, steps_per_epoch, validation_steps, **kwargs)
     1710         initial_epoch=initial_epoch,
     1711         steps_per_epoch=steps_per_epoch,
-> 1712         validation_steps=validation_steps)
     1713
     1714     def evaluate(self, x=None, y=None,

/home/carla/Documents/tensorflow/local/lib/python2.7/site-packages/keras/en
gine/training.py in _fit_loop(self, f, ins, out_labels, batch_size, epochs
, verbose, callbacks, val_f, val_ins, shuffle, callback_metrics, initial_ep
och, steps_per_epoch, validation_steps)
     1233         ins_batch[i] = ins_batch[i].toarray()
     1234
-> 1235         outs = f(ins_batch)
     1236         if not isinstance(outs, list):
     1237             outs = [outs]

/home/carla/Documents/tensorflow/local/lib/python2.7/site-packages/keras/ba
ckend/tensorflow_backend.py in __call__(self, inputs)
     2473         session = get_session()
     2474         updated = session.run(fetches=fetches, feed_dict=feed_dict,
-> 2475                             **self.session_kwargs)
     2476         return updated[:len(self.outputs)]
     2477

/home/carla/Documents/tensorflow/local/lib/python2.7/site-packages/tensorfl
ow/python/client/session.py in run(self, fetches, feed_dict, options, run_
metadata)
     893     try:
     894         result = self._run(None, fetches, feed_dict, options_ptr,
--> 895                             run_metadata_ptr)
     896     if run_metadata:
     897         proto_data = tf_session.TF_GetBuffer(run_metadata_ptr)

/home/carla/Documents/tensorflow/local/lib/python2.7/site-packages/tensorfl
ow/python/client/session.py in _run(self, handle, fetches, feed_dict, opti
ons, run_metadata)
     1126     if final_fetches or final_targets or (handle and feed_dict_tens
or):
     1127         results = self._do_run(handle, final_targets, final_fetches,

```

Modified VGGnet for this type of data

Modified VGG net to handle our input i.e. replace 2D with 1D, etc.(need to check dimensions and might need to transpose input to original shape)

Original VGGnet implementation can be found at the address below


```

In [39]: ### VGGnet
# https://keras.io/getting-started/sequential-model-guide/#examples

import numpy as np
import keras
from keras.models import Sequential
from keras.layers import Dense, Dropout, Flatten
from keras.layers import Conv1D, MaxPooling1D, BatchNormalization
from keras.optimizers import SGD

norm_train = np.transpose((-np.mean(train_data,axis=2)+np.transpose(train_data,(2,0,1)))/np.std(train_data,axis=2),(1,2,0))
norm_test = np.transpose((-np.mean(test_data,axis=2)+np.transpose(test_data,(2,0,1)))/np.std(test_data,axis=2),(1,2,0))

model = Sequential()
#model.add(LSTM(100, input_shape=(t,f)))
model.add(Conv1D(32, 4, activation='relu',input_shape=(t,f))) #
Originally 32 each
model.add(BatchNormalization())
model.add(Conv1D(32, 4, activation='relu'))
model.add(MaxPooling1D())
model.add(Dropout(0.25))

model.add(Conv1D(64, 4, activation='relu'))
#Originally 64 each
model.add(BatchNormalization())
model.add(Conv1D(64, 4, activation='relu'))
model.add(MaxPooling1D())
model.add(Dropout(0.25))

model.add(Flatten())
model.add(Dense(256, activation='relu'))
model.add(Dropout(0.5))
model.add(Dense(4, activation='softmax'))

#sgd = SGD(lr=0.01, decay=1e-6, momentum=0.9, nesterov=True)
#model.compile(loss='categorical_crossentropy', optimizer=sgd, metrics=['accuracy'])

model.compile(optimizer = 'sgd',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

hist = model.fit(train_data_sliced,train_labels,epochs=25,validation_split=0.25,batch_size=64,verbose=0)
test_score = model.evaluate(test_data_sliced, test_labels, batch_size=64)

print(test_score)
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy','Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss','Val Loss'],title='Losses')

```

500/500 [=====] - 0s 135us/step
[1.083584098815918, 0.48400000095367429]



Simple RNN model

```

In [42]: model = Sequential([
    SimpleRNN(64, input_shape=(t,f)),
    Dense(32),
    BatchNormalization(),
    Activation('relu'),
    Dense(4),
    Activation('softmax'),
    ])



model.compile(optimizer = 'sgd',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

hist = model.fit(train_data,train_labels,epochs=30,validation_split=0.25,batch_size=64,verbose=0)
test_score = model.evaluate(test_data, test_labels, batch_size=32)

print(test_score)
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy',
'Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss',
'Val Loss'],title='Losses')

500/500 [=====] - 1s 1ms/step
[1.438882619857788, 0.25000000005960465]

```



CHRONONET PAPER

C-RNN implementation (Figure 1b)

```
In [21]: import numpy as np
import keras
from keras.models import Sequential
from keras.layers import Dense, Dropout, Flatten
from keras.layers import Conv1D, MaxPooling1D, BatchNormalization, GRU
from keras.optimizers import SGD

model = Sequential()

model.add(Conv1D(32, 4, strides=2, activation='relu', input_shape=(t, f)))
model.add(Conv1D(32, 4, strides=2, activation='relu'))
model.add(Conv1D(32, 4, strides=2, activation='relu'))

#model.add(Flatten())

model.add(GRU(32, activation='tanh', return_sequences=True))
model.add(GRU(32, activation='tanh', return_sequences=True))
model.add(GRU(32, activation='tanh', return_sequences=True))
model.add(GRU(32, activation='tanh'))

model.add(Dense(4, activation='softmax'))


#sgd = SGD(lr=0.01, decay=1e-6, momentum=0.9, nesterov=True)
#model.compile(loss='categorical_crossentropy', optimizer=sgd)

#model.add()

model.compile(optimizer = 'adam',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

hist = model.fit(norm_train, train_labels, epochs=15, validation_split=0.25, batch_size=32, verbose=1)
test_score = model.evaluate(norm_test, test_labels, batch_size=32)
print(test_score)
plot_hist([hist.history['acc'], hist.history['val_acc']], ['Training Accuracy', 'Val Accuracy'], title='Accuracies')
plot_hist([hist.history['loss'], hist.history['val_loss']], ['Training Loss', 'Val Loss'], title='Losses')
```

```
Train on 1777 samples, validate on 593 samples
Epoch 1/15
1777/1777 [=====] - 16s 9ms/step - loss: 1.3795 -
acc: 0.2988 - val_loss: 1.3649 - val_acc: 0.2546
Epoch 2/15
1777/1777 [=====] - 15s 8ms/step - loss: 1.2895 -
acc: 0.3832 - val_loss: 1.3480 - val_acc: 0.3221
Epoch 3/15
1777/1777 [=====] - 16s 9ms/step - loss: 1.1189 -
acc: 0.4778 - val_loss: 1.2941 - val_acc: 0.3322
Epoch 4/15
1777/1777 [=====] - 15s 8ms/step - loss: 0.9349 -
acc: 0.5582 - val_loss: 1.2390 - val_acc: 0.4165
Epoch 5/15
1777/1777 [=====] - 16s 9ms/step - loss: 0.8677 -
acc: 0.5869 - val_loss: 1.0405 - val_acc: 0.4924
Epoch 6/15
1777/1777 [=====] - 15s 8ms/step - loss: 0.8094 -
acc: 0.6314 - val_loss: 1.2984 - val_acc: 0.4418
Epoch 7/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.7327 -
acc: 0.6517 - val_loss: 1.1225 - val_acc: 0.4975
Epoch 8/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.7196 -
acc: 0.6725 - val_loss: 1.1790 - val_acc: 0.4739
Epoch 9/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.6863 -
acc: 0.6944 - val_loss: 1.3383 - val_acc: 0.4266
Epoch 10/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.6068 -
acc: 0.7406 - val_loss: 1.4264 - val_acc: 0.4418
Epoch 11/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.5337 -
acc: 0.7743 - val_loss: 1.3017 - val_acc: 0.4755
Epoch 12/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.4895 -
acc: 0.7850 - val_loss: 1.3851 - val_acc: 0.4941
Epoch 13/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.4411 -
acc: 0.8104 - val_loss: 1.3025 - val_acc: 0.5126
Epoch 14/15
1777/1777 [=====] - 14s 8ms/step - loss: 0.3963 -
acc: 0.8396 - val_loss: 2.0994 - val_acc: 0.3879
Epoch 15/15
1777/1777 [=====] - 15s 8ms/step - loss: 0.4772 -
acc: 0.7918 - val_loss: 1.5593 - val_acc: 0.4570
500/500 [=====] - 1s 2ms/step
[1.2193489513397218, 0.55599999952316281]
```



Implementation of Figure 1b but adding regularization structures like that found in VGGnet

```

In [74]: import numpy as np
import keras
from keras.models import Sequential
from keras.layers import Dense, Dropout, Flatten
from keras.layers import Conv1D, MaxPooling1D, BatchNormalization, GRU
from keras.optimizers import SGD

#norm_train = np.transpose((-np.mean(train_data,axis=2)+np.transpose(train_
data,(2,0,1)))/np.std(train_data,axis=2),(1,2,0))
model = Sequential()

model.add(Conv1D(32, 4, strides=2,activation='relu',input_shape=(t,f)))
model.add(BatchNormalization()) #From VGGnet
model.add(Conv1D(32, 4, strides=2,activation='relu'))
model.add(BatchNormalization()) #From VGGnet
model.add(Conv1D(32, 4, strides=2,activation='relu'))
model.add(MaxPooling1D()) #From VGGnet
model.add(Dropout(0.25)) #From VGGnet
#model.add(Flatten())

model.add(GRU(32,activation='tanh',return_sequences=True))
model.add(GRU(32,activation='tanh',return_sequences=True))
model.add(GRU(32,activation='tanh',return_sequences=True)) #removed becaus
e of overfitting problem to small sample size
model.add(GRU(32,activation='tanh'))

#model.add(Dense(256, activation='relu')) #From VGGnet, b
ut makes model suck
#model.add(Dropout(0.5)) #From VGGnet, b
ut makes model suck
model.add(Dense(4, activation='softmax'))

# From VGGnet, works well for some reason
#sgd = SGD(lr=0.01, decay=1e-6, momentum=0.9, nesterov=True)
#model.compile(loss='categorical_crossentropy', optimizer=sgd,metrics=['acc
uracy'])


model.compile(optimizer = 'adam',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

#hist.history is a dictionary with all accs and losses
hist = model.fit(train_data,train_labels,epochs=15,validation_split=0.25,ba
tch_size=32,verbose=0)
test_score = model.evaluate(test_data, test_labels, batch_size=32)
print(test_score)

plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy
','Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss',
'Val Loss'],title='Losses')

```


500/500 [=====] - 1s 1ms/step
[1.1770159482955933, 0.63999999904632565]



Replaced GRU with LSTM

```

In [72]: import numpy as np
import keras
from keras.models import Sequential
from keras.layers import Dense, Dropout, Flatten
from keras.layers import Conv1D, MaxPooling1D, BatchNormalization, GRU, LSTM
from keras.optimizers import SGD

#norm_train = np.transpose((-np.mean(train_data,axis=2)+np.transpose(train_
data,(2,0,1)))/np.std(train_data,axis=2),(1,2,0))
model = Sequential()

model.add(Conv1D(32, 4, strides=2,activation='relu',input_shape=(t,f)))
model.add(BatchNormalization()) #From VGGnet
model.add(Conv1D(32, 4, strides=2,activation='relu'))
model.add(BatchNormalization()) #From VGGnet
model.add(Conv1D(32, 4, strides=2,activation='relu'))
model.add(MaxPooling1D()) #From VGGnet
model.add(Dropout(0.25)) #From VGGnet
#model.add(Flatten())

model.add(LSTM(32,activation='tanh',return_sequences=True))
model.add(LSTM(32,activation='tanh',return_sequences=True))
#model.add(LSTM(32,activation='tanh',return_sequences=True))
model.add(LSTM(32,activation='tanh'))

#model.add(Dense(256, activation='relu')) #From VGGnet, b
#ut makes model suck
#model.add(Dropout(0.5)) #From VGGnet, b
#ut makes model suck
model.add(Dense(4, activation='softmax'))

# From VGGnet, works well for some reason
#sgd = SGD(lr=0.01, decay=1e-6, momentum=0.9, nesterov=True)
#model.compile(loss='categorical_crossentropy', optimizer=sgd,metrics=['acc
uracy'])


model.compile(optimizer = 'adam',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

#hist.history is a dictionary with all accs and losses
hist = model.fit(train_data,train_labels,epochs=15,validation_split=0.25,ba
tch_size=32,verbose=0)
test_score = model.evaluate(test_data, test_labels, batch_size=32)

print "Test Results are ", test_score
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy
','Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss',
'Val Loss'],title='Losses')

```

500/500 [=====] - 1s 1ms/step
Test Results are [0.99758425903320314, 0.63000000095367437]



IC-RNN

```

In [22]: from keras.layers import Input,Dense,concatenate,Flatten,GRU,Conv1D
from keras.models import Model

inputs= Input(shape=(t,f))

# First Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(inputs)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(inputs)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(inputs)
x = concatenate([tower1,tower2,tower3],axis=2)

# Second Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
x = concatenate([tower1,tower2,tower3],axis=2)

# Third Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
x = concatenate([tower1,tower2,tower3],axis=2)

x = GRU(32,activation='tanh',return_sequences=True)(x)
#x = GRU(32,activation='tanh',return_sequences=True)(x)
#x = GRU(32,activation='tanh',return_sequences=True)(x)
x = GRU(32,activation='tanh')(x)

predictions = Dense(4,activation='softmax')(x)

model = Model(inputs=inputs, outputs=predictions)


model.compile(optimizer = 'rmsprop',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

#hist.history is a dictionary with all accs and losses
hist = model.fit(norm_train,train_labels,epochs=30,validation_split=0.25,batch_size=64,verbose=0)
test_score = model.evaluate(norm_test, test_labels, batch_size=64)

print "Test Results are ", test_score
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy', 'Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss', 'Val Loss'],title='Losses')

```

500/500 [=====] - 1s 3ms/step
Test Results are [1.7054030046463013, 0.43000000286102297]



IC-RNN Testing

```

In [100]: from keras.layers import Input,Dense,concatenate,Flatten,GRU,Conv1D,Bidirectional
          from keras.models import Model

          inputs= Input(shape=(t,f))

          # First Inception
          tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(inputs)
          #tower1 = BatchNormalization()(tower1)
          tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(inputs)
          tower2 = BatchNormalization()(tower2)
          tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(inputs)
          tower3 = BatchNormalization()(tower3)
          #tower4 = MaxPooling1D()(inputs)
          x = concatenate([tower1,tower2,tower3],axis=2)
          x = Dropout(0.5)(x)

          # Second Inception
          tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
          #tower1 = BatchNormalization()(tower1)
          tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
          tower2 = BatchNormalization()(tower2)
          tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
          tower3 = BatchNormalization()(tower3)
          #tower4 = MaxPooling1D()(x)
          x = concatenate([tower1,tower2,tower3],axis=2)
          x = Dropout(0.5)(x)

          # Third Inception
          tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
          #tower1 = BatchNormalization()(tower1)
          tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
          tower2 = BatchNormalization()(tower2)
          tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
          tower3 = BatchNormalization()(tower3)
          #tower4 = MaxPooling1D()(x)
          x = concatenate([tower1,tower2,tower3],axis=2)
          x = Dropout(0.5)(x)

          x = (GRU(32,activation='tanh',return_sequences=True))(x)
          x = (GRU(32,activation='tanh',return_sequences=True))(x)
          #x = (GRU(32,activation='tanh',return_sequences=True))(x)
          x = (GRU(32,activation='tanh'))(x)

          predictions = Dense(4,activation='softmax')(x)

          model = Model(inputs=inputs, outputs=predictions)

          model.compile(optimizer = 'rmsprop',
                        loss = 'categorical_crossentropy',
                        metrics=['accuracy'])

          #hist.history is a dictionary with all accs and losses
          hist = model.fit(train_data,train_labels,epochs=20,validation_split=0.25,batch_size=32,verbose=0)
          test_score = model.evaluate(test_data, test_labels, batch_size=32)

```

500/500 [=====] - 1s 1ms/step
Test Results are [1.0994007132053376, 0.4920000009536743]



C-DRNN

```
In [8]: from keras.layers import Input,Dense,concatenate,Flatten,GRU,Conv1D
        from keras.models import Model

        inputs= Input(shape=(t,f))

        x = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(inputs)
        x = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
        x = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)

        res1 = GRU(32,activation='tanh',return_sequences=True)(x)
        res2 = GRU(32,activation='tanh',return_sequences=True)(res1)

        res1_2 = concatenate([res1,res2],axis=2)

        res3 = GRU(32,activation='tanh',return_sequences=True)(res1_2)

        x = concatenate([res1,res2,res3])

        x = GRU(32,activation='tanh')(x)
        predictions = Dense(4,activation='softmax')(x)

        model = Model(inputs=inputs, outputs=predictions)

        model.compile(optimizer = 'rmsprop',
                      loss = 'categorical_crossentropy',
                      metrics=['accuracy'])



        #hist.history is a dictionary with all accs and losses
        hist = model.fit(train_data,train_labels,epochs=15,validation_split=0.25,batch_size=32,verbose=0)
        test_score = model.evaluate(test_data, test_labels, batch_size=32)

50/50 [=====] - 0s 4ms/step
```



```
In [9]: print "Test Results are ", test_score
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy',
'Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss',
'Val Loss'],title='Losses')
```

Test Results are [1.8914880275726318, 0.30000000238418578]



C-DRNN Testing

```
In [11]: from keras.layers import Input,Dense,concatenate,Flatten,GRU,Conv1D,BatchNormali-
zation,Dropout
from keras.models import Model

inputs= Input(shape=(t,f))

x = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(inputs)
x = BatchNormalization()(x)
x = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
x = BatchNormalization()(x)
#x = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
x = Dropout(0.5)(x)

res1 = GRU(32,activation='tanh',return_sequences=True)(x)
res2 = GRU(32,activation='tanh',return_sequences=True)(res1)

res1_2 = concatenate([res1,res2],axis=2)

res3 = GRU(32,activation='tanh',return_sequences=True)(res2)

x = concatenate([res1,res2,res3])

x = GRU(32,activation='tanh')(x)
predictions = Dense(4,activation='softmax')(x)



model = Model(inputs=inputs, outputs=predictions)

model.compile(optimizer = 'adam',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

#hist.history is a dictionary with all accs and losses
hist = model.fit(train_data,train_labels,epochs=5,validation_split=0.25,batch_size=32,verbose=0)
test_score = model.evaluate(test_data, test_labels, batch_size=32)

print "Test Results are ", test_score
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy',
'Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss',
'Val Loss'],title='Losses')
```

500/500 [=====] - 2s 4ms/step
Test Results are [1.1681010141372681, 0.43600000047683718]



ChronoNet

```

In [49]: from keras.layers import Input,Dense,concatenate,Flatten,GRU,Conv1D
from keras.models import Model

inputs= Input(shape=(t,f))

# First Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(inputs
)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(inputs
)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(inputs
)
x = concatenate([tower1,tower2,tower3],axis=2)

# Second Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
x = concatenate([tower1,tower2,tower3],axis=2)

# Third Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
x = concatenate([tower1,tower2,tower3],axis=2)

res1 = GRU(32,activation='tanh',return_sequences=True)(x)
res2 = GRU(32,activation='tanh',return_sequences=True)(res1)

res1_2 = concatenate([res1,res2],axis=2)

res3 = GRU(32,activation='tanh',return_sequences=True)(res2)

x = concatenate([res1,res2,res3])

x = GRU(32,activation='tanh')(x)
predictions = Dense(4,activation='softmax')(x)

model = Model(inputs=inputs, outputs=predictions)

model.compile(optimizer = 'rmsprop',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])


#hist.history is a dictionary with all accs and losses
hist = model.fit(train_data,train_labels,epochs=30,validation_split=0.25,batch_size=32,verbose=0)
test_score = model.evaluate(test_data, test_labels, batch_size=32)

50/50 [=====] - 0s 7ms/step

```

```
In [50]: print "Testing Accuracy is", test_score
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy',
'Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss',
'Val Loss'],title='Losses')
```

Testing Accuracy is [1.6881582021713257, 0.2600000047683716]



ChronoNet Model Testing

```
In [13]: from keras.layers import Input,Dense,concatenate,Flatten,GRU,Conv1D
from keras.models import Model

inputs= Input(shape=(t,f))

# First Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(inputs)
tower1 = BatchNormalization()(tower1)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(inputs)
tower2 = BatchNormalization()(tower2)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(inputs)
tower3 = BatchNormalization()(tower3)
x = concatenate([tower1,tower2,tower3],axis=2)

# Second Inception
#tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
#tower1 = BatchNormalization()(tower1)
#tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
#tower2 = BatchNormalization()(tower2)
#tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
#tower3 = BatchNormalization()(tower3)
#x = concatenate([tower1,tower2,tower3],axis=2)

# Third Inception
tower1 = Conv1D(32, 2, strides=2,activation='relu',padding="causal")(x)
tower1 = BatchNormalization()(tower1)
tower2 = Conv1D(32, 4, strides=2,activation='relu',padding="causal")(x)
tower2 = BatchNormalization()(tower2)
tower3 = Conv1D(32, 8, strides=2,activation='relu',padding="causal")(x)
tower3 = BatchNormalization()(tower3)
x = concatenate([tower1,tower2,tower3],axis=2)

res1 = GRU(32,activation='tanh',return_sequences=True)(x)
res2 = GRU(32,activation='tanh',return_sequences=True)(res1)

res1_2 = concatenate([res1,res2],axis=2)

res3 = GRU(32,activation='tanh',return_sequences=True)(res2)

x = concatenate([res1,res2,res3])

x = GRU(32,activation='tanh')(x)
predictions = Dense(4,activation='softmax')(x)

model = Model(inputs=inputs, outputs=predictions)

model.compile(optimizer = 'adam',
              loss = 'categorical_crossentropy',
              metrics=['accuracy'])

#hist.history is a dictionary with all accs and losses
hist = model.fit(train_data,train_labels,epochs=10,validation_split=0.25,batch_size=128,verbose=0)
test_score = model.evaluate(test_data, test_labels, batch_size=128)

print "Testing Accuracy is", test_score
plot_hist([hist.history['acc'],hist.history['val_acc']],['Training Accuracy', 'Val Accuracy'],title='Accuracies')
plot_hist([hist.history['loss'],hist.history['val_loss']],['Training Loss', 'Val Loss'],title='Losses')
```

500/500 [=====] - 2s 5ms/step
Testing Accuracy is [1.3958248071670531, 0.47799999785423281]

