

Runners

```
=> CommandLineRunner(I)[1.0V]
=> ApplicationRunner(I)[1.3V]
```

The difference b/w the above 2 runners is they vary in the way the arguments are collected.

ApplicationArguments

=====

1. Option Arguments(inputs)
 --key = val
2. Non Option Arguments(commands)
 start
 close
 data
 execute
 dump
 stop

Difference b/w CLR and APR?

Ans. Working process same, only difference is in inputs.

CLR reads inputs from main() and stores as ArrayFormat(String[])

ALR reads inputs from main() and converts into Option(--key=value) and Non-Option(only value) args and given to AR.

Note: ApplicationRunner can be used to override the value which are coming from application.properties file aslo.

CommandLineRunner

=====

@FunctionalInterface

```
public interface CommandLineRunner {
    void run(String... args) throws Exception;
}
```

+++++

SourceCode1::

@Configuration

```
public class AppConfig {
```

```
    @Bean
```

```
    public CommandLineRunner runA() {
```

```
        // syntax:: new CommandLineRunner(){....}
```

```
        return new CommandLineRunner() {
```

```
            @Override
```

```
            public void run(String... args) throws Exception {
```

```
                System.out.println("HELLO :: " + Arrays.asList(args));
```

```
            }
```

```
        };
```

```
    }
```

```
}
```

SourceCode::2

@Configuration

```
public class AppConfig {
```

```
    @Bean
```

```
    public CommandLineRunner runA() {
```

```
        // Syntax:: Interface obj =(params)->{MethodBody;}
```

```

        return (args) -> {
            System.out.println("FROM RUNNER :: " + Arrays.asList(args));
        };
    }
}

```

SourceCode:: 3

```

@Configuration
public class AppConfig {
    @Bean
    public CommandLineRunner runA() {
        //Syntax=> ClassName :: methodName
        return SampleTest::test;
    }
}
public class SampleTest {
    public static void test(String... args) {
        System.out.println("FROM METHOD REF:: " + Arrays.asList(args));
    }
}

```

refer:: [SpringBoot-Runner-02](#), [SpringBoot-Runner-03](#)

Adding Custom banner to SpringBoot application

```

=====
public ConfigurableApplicationContext run(String... args) {

    long startTime = System.nanoTime();
    DefaultBootstrapContext bootstrapContext = createBootstrapContext();
    ConfigurableApplicationContext context = null;
    configureHeadlessProperty();

    SpringApplicationRunListeners listeners = getRunListeners(args);
    listeners.starting(bootstrapContext, this.mainApplicationClass);

    try {
        ApplicationArguments applicationArguments = new
DefaultApplicationArguments(args);
        ConfigurableEnvironment environment =
prepareEnvironment(listeners, bootstrapContext, applicationArguments);
        configureIgnoreBeanInfo(environment);

        //Banner is getting generated
        Banner printedBanner = printBanner(environment);

        context = createApplicationContext();
        context.setApplicationStartup(this.applicationStartup);
        prepareContext(bootstrapContext, context, environment, listeners,
applicationArguments, printedBanner);
        refreshContext(context);
        afterRefresh(context, applicationArguments);
        Duration timeTakenToStartup = Duration.ofNanos(System.nanoTime()
- startTime);
        if (this.logStartupInfo) {
            new
StartupInfoLogger(this.mainApplicationClass).logStarted(getApplicationLog(),
timeTakenToStartup);
        }
    }
}

```

```

        listeners.started(context, timeTakenToStartup);
        callRunners(context, applicationArguments);
    }
    catch (Throwable ex) {
        handleRunFailure(context, ex, listeners);
        throw new IllegalStateException(ex);
    }
    try {
        Duration timeTakenToReady = Duration.ofNanos(System.nanoTime() -
startTime);
        listeners.ready(context, timeTakenToReady);
    }
    catch (Throwable ex) {
        handleRunFailure(context, ex, null);
        throw new IllegalStateException(ex);
    }
    return context;
}

```

Creating our OwnBanner in Programmatic Approach

=====

```

@FunctionalInterface
public interface Banner {

    /**
     * Print the banner to the specified print stream.
     * @param environment the spring environment
     * @param sourceClass the source class for the application
     * @param out the output print stream
     */
    void printBanner(Environment environment, Class<?> sourceClass, PrintStream
out);
}

```

Making the Banner to display while booting the Application

=====

```

enum Mode {

    /**
     * Disable printing of the banner.
     */
    OFF,

    /**
     * Print the banner to System.out.
     */
    CONSOLE,

    /**
     * Print the banner to the log file.
     */
    LOG

}

```

Step1::
src/main/java

```
|=> in.neuron.banner
                        |=> banner.txt
```

banner.txt
=====

[illegible]

```
Step2::
application.properties
=====
spring.main.banner-mode=console
spring.banner.location=classpath:in/ineuron/banner/banner.txt
```

```
Step3::
@SpringBootApplication
public class SpringBootBannerAppApplication {

    @SuppressWarnings("static-access")
    public static void main(String[] args) {
        SpringApplication application = new SpringApplication();
        ConfigurableApplicationContext ctx =
application.run(SpringBootBannerAppApplication.class, args);
        ctx.close();
    }
}
```

Step4:: Run the application and check the banner in console.

Working with SpringBoot-Mail

1. Add the following dependancies

```
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-mail</artifactId>
</dependency>
```

2. Required Bean `JavaMailSender` will be autoconfigured

3. Create a Service class

```
public interface IPurchaseOrder {
    public String purchase(String[] items,double [] prices,String[] toEmails)
    throws Exception;
}
```

```
@Service("service")
public class PurchaseOrderImpl implements IPurchaseOrder {

    @Autowired
    private JavaMailSender sender;
```

```

        @Value("${spring.mail.username}")
        private String fromEmail;

        @Override
        public String purchase(String[] items, double[] prices, String[] toEmails)
        throws Exception {

            double amt = 0.0;
            for (double price : prices) {
                amt = amt + price;
            }

            String msg = Arrays.toString(items) + "with price :: " +
            Arrays.toString(prices)
                + " are purchase with billamount :: " + amt;

            String status = sendMail(msg, toEmails);

            return msg + "---> " + status;
        }

        private String sendMail(String msg, String[] toEmails) throws Exception {
            System.out.println("Sender implementation class is :: " +
            sender.getClass().getName());

            MimeMessage message = sender.createMimeMessage();
            MimeMessageHelper helper = new MimeMessageHelper(message, true);

            helper.setFrom(fromEmail);
            helper.setCc(toEmails);
            helper.setSubject("Open it to know it");
            helper.setSentDate(new Date());
            helper.setText(msg);
            helper.addAttachment("ineuron.jpg", new
            ClassPathResource("ineuron.jpg"));
            sender.send(message);

            return "mail-sent";
        }
    }

```

4. Set up application.properties

```

#Properties to tell the mail protocol vendor
spring.mail.host=smtp.gmail.com
spring.mail.port=587

```

#Actual username,password of sender

```

spring.mail.username=setusername
spring.mail.password=setpassword

```

#Property to trigger smtp

```

spring.mail.properties.mail.smtp.auth=false
spring.mail.properties.mail.smtp.starttls.enable=true
spring.mail.properties.mail.smtp.starttls.required = true

```

5. Build main app and run the application

```

@SpringBootApplication
public class SpringBootMailAppApplication {

    public static void main(String[] args) {
        ApplicationContext context =
SpringApplication.run(SpringBootMailAppApplication.class, args);

        IPurchaseOrder order = context.getBean(IPurchaseOrder.class);

        try {
            String msg = order.purchase(new String[] { "Fossil-Chronography",
"USPOLO-Tshirt", "LouisPhilippe-Shoes" },
                new double[] { 12000.0, 5000.0, 6000.0 }, new
String[] { "attrayaghoshdas@gmail.com",
                "nithinvanga01@gmail.com",
"nilesh7345kaka@gmail.com" });

            System.out.println(msg);

        } catch (Exception e) {
            e.printStackTrace();
        }

        ((ConfigurableApplicationContext) context).close();
    }
}

```

Note: Before running app

- a. login to sender email account(like gmail login),go to account letter/image
- b. go to manage settings -> security -> change less secure apps access to ON

Evening :: All the remaining topics of DataJpA(H2,postgresql,workign with mulitple database,Association)