

The Operator's Manual

*How to run, configure and operate the BSS — by role and by task. The companion volume, *The Honest Machine* (a build memoir · verify everything — how one person and an AI built a complete telecom suite and proved every piece of it), tells how it was built and why; this book tells you which button, which endpoint, which environment variable. Everything here is proven by the suite named beside it.*

Contents

1. Getting started
2. Surfaces & sign-ins
3. The product owner
4. The CSR
5. Billing & money operations
6. Partner channels
7. The host administrator
8. AI configuration
9. The seam catalog
10. Environment reference
11. Extension API reference
12. The mock integrations
13. Production operations
14. Privacy & GDPR operations
15. The agent channel (agentic commerce)
16. The digital workforce
17. The wrapped legacy estate (overlay)
18. Generative discoverability (GEO)
19. The capability map
20. Loyalty — reward & retain
21. Revenue export — the subledger
22. Credit notes
23. Process flows & the incident agent
24. The standards sweep
25. The product configurator
26. Service qualification & the coverage map
27. AI management — the control plane's face
28. Risk management — the door check
29. Partnership types & geographic sites
30. The proof run & fleet-age runbooks
31. The shop that knows you
32. The CTK campaign — twenty-five kits, the closed list

1 • Getting started

```
docker compose up -d          # ~90 containers; first build takes a while
open http://localhost:8080/shop/ # the storefront (guest browsing works)
```

The gateway is :8080 ; Keycloak is :8085 (admin/admin). Two seed operators run side by side: **genalpha** (EN/EUR, realm `bss`) and **nova** (NO/NOK, realm `nova`) — plus any operator you

mint (§7). Demo card 4242 4242 4242 4242 pays; anything ending 0002 declines. Promo code WELCOME10 . Serviceable fiber postcodes start 111 / 222 / 333 .

The one discipline: every feature in this manual has an end-to-end Playwright suite in `ops/e2e/` . When in doubt about how something behaves, the suite is the specification: `node ops/e2e/<name>_test.js` runs it against the live stack.

2 • Surfaces & sign-ins

URL	WHO	DEMO SIGN-IN
<code>/shop/</code>	Customers (self-register or guest)	<code>kai@bss.local</code> / <code>kai</code>
<code>/app/</code>	Customers on mobile (Expo web)	<code>emil@acme.example</code> / <code>emil</code>
<code>/biz/</code>	B2B org admins + invited members	<code>bianca@acme.example</code> / <code>bianca</code>
<code>/csr/</code>	Agents (role-scoped powers)	<code>agent-anna</code> / <code>agent ; junior: jo@bss.local</code> / <code>jo</code>
<code>/console/</code>	Back office (role-scoped tabs)	<code>demo</code> / <code>demo ; product-only: pat@bss.local</code> / <code>pat</code>
<code>/dealer-app/</code>	Retail-partner clerks & telesales agents	any account whose org holds a dealer agreement
<code>shop.nova.localhost:8080/shop/</code>	Nova's white-label storefront	<code>nils@nova.local</code> / <code>nils</code>
<code>biz.nova.localhost:8080/biz/</code>	Nova's B2B console (Norwegian)	<code>birgit@fjellheim.no</code> / <code>birgit</code>

White-labeling is hostname-driven: `shop.<tenant>.localhost` serves that operator's brand, locale and currency from the live registry (§7).

3 • The product owner

Catalog (console → Product Offerings / Specifications / Prices)

Offerings are TMF620 data: hard and soft bundles (`bundledProductOfferingOption` cardinality, pick-N-of-M choice groups), characteristic-conditioned prices ("+2.00/mo when colour = Titanium"), commitment terms, categories that drive placement *and* fulfilment (Top-ups and Insurance are billing-only; Partner services mint entitlement codes; everything else draws an MSISDN + SIM). Artwork rides the offering's attachments — internal store or the tenant's own PIM; the internal store's bytes live in-row by default or in S3-protocol / Azure Blob object storage (deployment config, §9 — suite #54 proves all three).

Rules & pricing as data (console → Rules)

Order rules and dynamic pricing are JSON-logic rows with a dry-run panel. A price change is a rule, not a release. See `docs/product-rules.md` for the authoring guide.

Product Copilot (console → Copilot)

Chat a product into the catalog: the model proposes specs/prices/offerings as TMF620 payloads, the console shows a human card, and a deterministic executor applies it with *your* token on confirmation. The model never writes. The copilot also authors **pricing rules** ("10% off the phone with this plan") and — suite #61 — **personalization experience rules** ("device browsers see this banner and this pin"): both become policy rows you can disable in Rules. **Voice input:** the  button uses the browser's speech recognizer (Chrome/Edge; hidden where unsupported) — the transcript lands in the input and the human still presses Send; the mic never auto-sends. Server-side STT (bring-your-own Whisper) is a named seam for later.

Product Advisor (console → Product advisor) — suite #52

Findings with receipts: top-up attach counted from inventory ("2 of 2 customers on this plan also bought top-ups"), market price gaps from the tenant's market feed (10% materiality threshold — small gaps are deliberately silent), an LLM narrative that never invents a number. **Adopt as draft...** births an `In study` offering; nothing reaches the shop until you promote it.

Campaigns & growth (console → Campaigns / Journeys / Audiences)

Segments form from consented shop behavior; campaigns prove lift against real holdouts; journeys read the customer before speaking; A/B arms split deterministically; guardrails (frequency caps, quiet hours) are settings. Every message lands on the TMF683 timeline.

4 • The CSR

Search the 360 (multi-word, name-ranked, with a trigram typo net — "Solvieg" finds Solveig when strict matching finds nothing), then act — every action logs itself on the customer's timeline:

THE CUSTOMER ASKS	THE BUTTON / ACT
"What's my PUK?" / "reset my PIN"	Reveal PUK · Reset PIN (owner notified — a silent credential change reads as fraud)
"I lost my SIM"	Replace SIM (old card quarantined first)
"new number, please"	Change number (old number quarantined with its story)
"pause my subscription"	Pause / Resume (charging pauses at the OCS; auto-resumes on the promised date)
"I can't pay all of it"	Installments (parts sum exactly; miss one → reminder → grace → dunning)
"this charge is wrong"	Dispute (collection pauses; resolution credits or upholds, in writing)
"send me my invoice"	PDF (the exact document) · Email bill (to the address on file, never one dictated on the phone)
"my internet is slow"	Diagnose (triage across usage/assurance/network facts)
"give my number to my colleague"	Transfer (three-way authorization; B2B handover keeps the company paying)

Self-care mirrors most of these in the shop and app — customers act on their OWN line (ownership-checked; a foreign line answers 404, never 403).

The knowledge base at the desk

Articles are audience-shelved (customer / CSR / sales / product owner) and the CSR's ask-with-sources grounds its answers in them. Search is full-text, ranked, and stems in **the tenant's own language** — the locale that picks the storefront's currency also picks the stemmer, so on nova "regning" finds "regningene" (suite #55). Typos in customer search are caught by a trigram net that only speaks when strict matching finds nothing — strict results are byte-identical to before. Beneath the keyword search sits the **semantic net** (pgvector): "why is my internet so slow" finds the fair-use article that contains neither word, and nonsense finds nothing — the cosine ceiling keeps the net honest. Embeddings are a seam: `bss.knowledge.embeddings = stub` (deterministic, keyless) or `openai-compatible` (any real model).

5 • Billing & money operations

The billing run

`POST /tmf-api/customerBillManagement/v4/billingRun` (staff). Segment-based and per-account: mid-month starts, mid-cycle plan changes and ceases each bill exactly their own days, labelled ("from the 16th, 15 days"). Payday alignment per customer (`POST /individual/{id}/billingCycle` , day 1–28). The invariant the suites enforce from every direction: **no day is ever billed twice**.

The bill as a document — suite #46

`GET /customerBill/{id}/document.pdf` (owner-scoped); `POST /customerBill/{id}/resend` emails it to the address on file. Delivery preference per customer: `paper | einvoice | digital` (`POST /individual/{id}/billDelivery`) — the customer picks the channel; the tenant keeps the plumbing.

E-invoice formats are rows (console → Bill formats)

CODE	STANDARD	SYNTAX
<code>ehf</code>	EHF Billing 3.0 (Norway; carries the KID)	UBL 2.1
<code>peppol</code>	Peppol BIS Billing 3.0	UBL 2.1
<code>cii</code>	EN 16931	UN/CEFACT CII
<code>aunz</code>	A-NZ Peppol BIS 3.0	UBL 2.1
<code>edifact</code>	UN/EDIFACT INVOIC D96A	segments
<code>facturx</code>	Factur-X / ZUGFeRD	PDF + embedded CII

Adding a country is an INSERT (the suite added XRechnung through the form). The tenant's `BILL_DISTRIBUTION_FORMAT` picks a row by code; the renderer follows the row.

Delivery, status, and the money coming home — suites #46/#47

Deliveries (console tab): the outbox-backed ledger — every bill's trip, attempts, the buyer's Peppol Invoice Response (accepted / rejected with their words / paid), one-click Retry on failures. **Remittance**: the bank posts camt.054, Nets OCR or BAI2 to `POST /bank/v1/remittance` (per-tenant `BANK_TOKEN`); a matched KID settles the bill through the

card path's own guarantee; everything unclear parks on **Unapplied cash** (console tab) with its reason. Money is fail-closed: never guessed, never dropped.

Dunning (console → Dunning)

The collections worklist: overdue installments, broken plans, what is still owed.

6 • Partner channels — suites #48/#51

Being a dealer is a row. Sign a chain: `POST /dealer/v1/agreement` (staff) with the org, commission per activation, and — for a chain with its own POS — the `OAuth2 clientId` that speaks for them. Clerks are org membership; foreign dealers see 404-shaped nothing.

Retail (the CSP + external-retail model — think Elkjøp/Power)

Counter sale: sell against the customer's email; the order carries the dealer stamp. **Starter kits:** mint batches (code + SIM + attribution in the box); the customer self-activates (`POST /dealer/v1/starterKit/activate`) and the line rides the SIM from the box. **POS API:** same endpoints, machine credential, per-partner rate limits at the edge (429 + Retry-After); the chain's own phone rides the sale as `device` context — never a billable item. **Commission:** pending → earned after the angreter window → clawed back with the reason if the customer leaves inside it.

Telesales (outbound, shaped by the law)

Dial list: `GET /dealer/v1/telesales/dialList?segment=` — consented at the source (insight segments), every number DNC-washed, reserved citizens excluded *and counted*. **The call makes an OFFER** (`POST /dealer/v1/telesales/offer`): washed fail-closed (reserved refuses, unreachable register refuses, unconfigured tenant refuses); no order exists yet. **The customer confirms in writing** (`POST /telesales/v1/confirm` , signed in, code from their inbox — or, for a cold prospect, after registering with the offered email); only then the order, the activation and the commission are born. Silence expires on a clock. Every dialer call logs to TMF683.

7 • The host administrator

The tenant fleet is a file

`infra/tenants/tenants.yml` is the shared registry (mounted into all 31 services); every service live-refreshes it. NEW operators join the running fleet within one refresh interval; changes to a serving operator's seams/brand/hosts apply live; identity fields (`id` , `issuer` , key endpoints) require a restart — by design.

Minting an operator — suites #49/#50

```
# the script (~2 minutes to a billed customer):
ops/onboard-tenant.sh fjord "Fjord Mobil" da DKK "#1B6CA8"

# or the form: console → Operators → five fields → Save
#   (host-tenant admins only; realm clone + registry block + seeded catalog;
#   shop.<id>.localhost wears the brand the moment the gateway refreshes)
# live rebrand of a form-born operator:
PATCH /onboarding/v1/operator/{id} {"name","color","locale","currency"}
```

Seed operators (genalpha, nova) are protected from the form — their config is env.

Staff & roles (console → Staff)

Grant/revoke whole areas per operator over the tenant's own IdP (TMF672) — no Keycloak console needed for daily administration.

8 • AI configuration & governance — suites #53/#59

The individualized shop (suite #60)

`GET /ai/v1/forYou` — the signed-in customer's own rail (self-scoped: party = token subject, no parameter to probe). TMF680 candidates + consented interests + churn-risk loyalty flag; ONE governed FAST caption per 5-minute cache window ("Picked for you after your look at devices"). No personalization consent → zero interests, generic caption. The storefront renders it as the "Recommended for you" shelf, and the mobile app's For-you card rides the same endpoint (same cache — the second channel is free).

The control plane (suite #59)

Every LLM turn is **metered** (token counts + cost land on the AI Audit ledger — the console's AI Audit tab shows tokens, cost and outcome per turn) and **governed** per tenant: `GET /ai/v1/governance` shows spend this window, the ceiling, remaining headroom and the **agent-action trail** (which AI wrote which resource — e.g. the advisor's

`catalog.createDraftOffering`). `POST /ai/v1/governance/budget {"budgetMicros": 5000000, "windowHours": 720, "enabled": true}` sets the ceiling and the **kill-switch**; crossing the ceiling refuses fail-closed (429, audited as `refused-budget`), `enabled=false` refuses instantly (403). No budget row = unlimited-and-enabled — governance is opt-in per tenant. Cost is estimated (`chars/4 tokens × per-model rate, bss.ai.prices.<model>` in micros per 1K, default `bss.ai.default-price-per-1k-micros`); exact provider usage is a wired-later seam.

Per tenant, all data: `ai-provider` (`stub` — keyless CI default — `openai-compatible` , `anthropic`), `ai-base-url` , `ai-api-key` , `ai-model` . **Tiered routing**: the task class lives at the call site — FAST (copywriting, summaries, narratives) vs SMART (product proposals, next-best-offer; the default when unclassified). Every value resolves tier-first:

```
AI_MODEL_FAST=swift-mini           # cheap model for volume work
AI_MODEL_SMART=frontier-x           # careful model for judgment
AI_PROVIDER_SMART=anthropic         # tiers go down to the PROVIDER:
AI_BASE_URL_SMART=https://api...    # a local endpoint for volume,
AI_API_KEY_SMART=...                # a frontier API for judgment — at once
```

9 • The seam catalog

Every external system is a per-tenant seam: configure it and the feature lights up; leave it blank and the feature degrades honestly (fail-open for enrichment, fail-closed for money, identity and consent).

SEAM	TENANT FIELDS (ENV)	BEHAVIOR WHEN BLANK
Email provider (ESP)	DELIVERY_PROVIDER, ESP_URL, ESP_API_KEY, ESP_FROM	in-app inbox only
Bill distribution partner	BILL_DISTRIBUTION_{PROVIDER,URL,TOKEN,FORMAT,CHANNEL}	bills stay in-app/PDF
Bank (remittance)	BANK_TOKEN	webhook refuses (money: fail-closed)
Do-not-call register	DNC_URL, DNC_TOKEN	outbound telesales refuses (opt-IN by configuring)
Market-intelligence feed	MARKET_FEED_URL, MARKET_FEED_TOKEN	advisor's market findings absent; own-data findings stand
LLM	AI_* (§8)	keyless stub answers
PIM (product imagery)	PIM_BASE_URL	internal TMF667 store
Content store (deployment-level)	CONTENT_STORE = in-row s3 azure-blob (+ S3_* / AZURE_*)	bytes in the document row (dev-simple)
Embeddings (deployment-level)	bss.knowledge.embeddings = stub openai-compatible (+ embeddings-url/key/model)	deterministic keyless stub — the semantic net still works, with curated synonyms instead of a model
Web analytics (GA4)	ANALYTICS_*	internal insight only

Social platform	SOCIAL_API_URL, SOCIAL_ACCESS_TOKEN	no audience push / lead import
-----------------	-------------------------------------	--------------------------------

Per-tenant variants ride suffixes: `_NOVA`, `_FJORD`, ... matching the placeholders in `tenants.yml`.

10 • Environment reference (dev clocks)

VARIABLE	MEANING	DEV / PROD DEFAULT
BSS_BILLING_DUNNING_TICK_MS / _GRACE_MS	collections sweep / grace	5s & 20s / 60s & 7d
BSS_BILLING_DISTRIBUTION_TICK_MS / _RETRY_SECONDS	delivery relay / backoff base	3s & 4s / 30s & 60s
BSS_SOM_COMMISSION_WINDOW_MS / _TICK_MS	angrerett window / harden tick	15s & 5s / 14d & 1h
BSS_SOM_TELESALES_EXPIRY_MS / _TICK_MS	offer expiry / sweep	15s & 5s / 48h & 1h
BSS_TENANTS_REFRESH_MS	live registry refresh	15s
BSS_GATEWAY_PARTNER_RATE_CAPACITY / _WINDOW_MS	per-partner rate limit (dealer surface)	10 per 2s / 60 per 60s
GLOBAL_RATE_CAPACITY / GLOBAL_RATE_WINDOW_MS	the wide ring — a ceiling on EVERY path, per subject/client/IP	1200 per 60s

11 • Extension API reference (beyond the TMF standard surfaces)

ENDPOINT	WHO	DOES
GET /customerBill/{id}/document.pdf	owner/staff	the bill as a PDF
POST /customerBill/{id}/resend	owner/staff	email the invoice to the address on file
POST /customerBill/{id}/dispute · /installmentPlan	owner/agent	contest / split a bill
GET/PATCH/POST /billFormatProfile[/code]]	read: billing · write: billing:admin	e-invoice profiles as rows
GET /billDistribution · POST /billDistribution/{id}/retry	billing:admin	the delivery ledger
POST /bank/v1/remittance	the bank (X-Bank-Token)	camt.054 / OCR / BAI2 in
POST /distribution/v1/response	the partner (X-Distribution-Token)	Peppol Invoice Response onto the ledger
GET /remittance/unapplied	billing:admin	unapplied cash worklist
POST /individual/{id}/billingCycle · /billDelivery	self/staff	payday alignment · delivery preference
/dealer/v1/* (agreement, kits, sell, commission, orders/{id}, telesales/*)	staff / dealer / partner POS	the whole dealer & telesales channel
POST /telesales/v1/confirm	the customer, signed in	the written yes that births the order
GET /advisor/v1/findings · POST /advisor/v1/adopt	catalog:write	product advisor · adopt-as-draft
GET/POST /onboarding/v1/operator · PATCH .../{id}	host roles:admin	mint / live-mutate an operator
GET /app/tenant-config.json	public, by Host	the white-label manifest

12 • The mock integrations (dev stand-ins)

CONTAINER	PORT	STANDS IN FOR	CHAOS / INSPECTION
mock-esp	8121	SendGrid-shaped email provider	GET /mails , webhook receipts
mock-social	8122	Meta-shaped audiences/leads	—
mock-distribution	8124	Peppol access point / print house (validates EHF/EDIFACT/Factur-X!)	GET /invoices , POST /outage , POST /invoices/{billNo}/respond
mock-dnc	8125	reservation register	numbers ending 9999 are reserved; POST /outage
mock-market	8126	tariff-comparison feed	GET /offers
minio	9000	S3-protocol object store (AWS/R2/on-prem)	—
azurite	10000	Azure Blob Storage (Microsoft's emulator)	—
mock-llm	8127	OpenAI- and Anthropic-dialect LLM	names the model in answers; GET /requests

13 • Production operations — suites #56/#57

Ticks that never double-fire

Every mutating scheduled job — dunning, bill delivery, campaign journeys, churn sweeps, porting cutover, commission hardening, order resume, telesales expiry, cart abandonment — claims a row-lease (`tick_lock` table in the service's own database) before it runs. Scale any service to N replicas and each tick still fires once; a crashed holder's lease expires on its own. Inspect a service's leases with `psql -d billing -c "SELECT * FROM tick_lock"`. Suite #56 proves it by running TWO billing replicas and counting exactly one delivered bill at the receiving partner.

The billing run — partitioned, resumable, and on a ledger

Each account's bill commits in its *own* transaction; a failed account is recorded and skipped, never the run. A crashed run RESUMES on the next trigger — every bill already cut is its own checkpoint — and every run is a row: `GET /tmf-api/customerBillManagement/v4/billingRun`

lists recent runs (status running/completed/superseded, accounts, bills, failures, last error). One run speaks at a time: a trigger during a live run answers `{"busy": true}` (the lease heartbeats per account, so a crashed run frees it within ~2 minutes), and the database enforces one bill per account per period with a unique index — constraint, not convention. Suite #57 kills billing mid-run and proves exactly-one-bill-per-customer after the resume.

`BSS_BILLING_RUN_ACCOUNT_DELAY_MS` (default 0) is the dev pacing knob the suite uses to hold a run open.

Load numbers and the smoke SLO

`node ops/load/loadtest.js --seconds 15 --workers 10` — plain-Node closed-loop driver, three scenarios (anonymous catalog, storefront page, authenticated bill reads), reporting req/s and p50/p95/p99. LIFT THE WIDE RING FIRST (`GLOBAL_RATE_CAPACITY=1000000` `docker compose up -d gateway`) or the Po ceiling will throttle the harness — that is it working. Baselines and their caveats: [docs/perf-baselines.md](https://docs.gene.com/perf-baselines.md).

Alerts

`infra/prometheus/alert-rules.yml` : ServiceDown (2 min unscraped), OutboxPublishFailures (events queuing, not lost), GatewayServerErrors (5xx > 5%). The whole fleet is scraped (32 targets). View at `:9090/alerts` ; a deployment routes them to a pager via Alertmanager.

Backup and the restore drill

`ops/backup.sh` dumps every database and role to `backups/` (git-ignored, newest 14 kept). `ops/restore-drill.sh` restores the newest dump into a throwaway container, verifies databases and rows, optionally proves a sentinel (`--expect <db> "<sql>"`), and removes the container. Run the drill on a schedule — an untested backup is a hope, not a backup.

Rate limits, two rings — buckets in Redis

The dealer surface keeps strict per-partner buckets; every other path passes a generous fleet-wide ceiling (per subject for people, per client for machines, per IP for anonymous), answering `429 + Retry-After` when tripped. Dials in \$10. The buckets live in Redis (`BSS_GATEWAY_REDIS_URL` ; blank = in-memory): replicas share ONE exact ceiling, a restarted gateway still refuses inside the same window, and an unreachable Redis fails open — fairness, never authorization.

The live k8s soak (on demand) — local, AWS, and Azure

The Helm chart has run on three live clusters: local k3s, AWS EKS, and Azure AKS — each with billing at 2 replicas holding ONE set of tick leases, requests served through the in-cluster

gateway. The cloud runs are one command each: `ops/k8s-soak/eks-run.sh up|smoke|down` and `ops/k8s-soak/aks-run.sh up|smoke|down` (compose must stop first — one laptop, two worlds). Both wrap Terraform + registry push + managed-Postgres + Helm + smoke + teardown. The cloud-by-cloud differences (all absorbed by seams — the app never changed) are tabulated in [architecture.md §5](#); the receipts and the live-run truths each cloud taught are in [k8s-soak-plan.md](#). Smoke: `ops/k8s-soak/smoke.js` against port-forwarded gateway/keycloak.

Managed-Postgres note: point `config.dbHost` at the managed server and set `local.postgres.enabled=false`. Some tiers cap connections low (Azure B1ms ≈ 50) — the chart now holds only one idle connection per pool; raise the server's `max_connections` for headroom. Managed Postgres may also gate extensions (Azure needs `pg_trgm/vector` allow-listed) and demand TLS (add `sslmode=require` to the datasource URL, or relax on the server for a soak).

The secret gate

`ops/install-hooks.sh` wires `ops/scan-secrets.sh` as a pre-commit hook: any staged diff carrying a real-secret shape (Anthropic/OpenAI/AWS/GitHub/Slack keys, private-key blocks) refuses to commit. Injectable values are listed in `.env.example`; what a real deployment must add beyond this stack — external secrets, TLS in transit, managed HA Postgres/Kafka — is the runbook, [docs/hardening.md](#).

14 • Privacy & GDPR operations — suite #58

The data passport (right of access)

`GET /privacy/v1/export` — a customer exports THEMSELVES with their own sign-in (no role needed; the fan-out rides their token to every service). The DPO — any user with `roles:admin` — adds `?partyId=` to export another person. The JSON names its categories and also the legal-hold categories it cannot delete.

Erasure (right to be forgotten)

`POST /privacy/v1/erase {"partyId": "..."} (DPO only)`. Refuses 409 while the person holds ACTIVE services — terminate first. Deletes interactions, messages, marketing, carts, tickets, appointments, behavioural data; anonymizes the profile in place; disables and scrubs the login at the IdP. Bills/payments/orders/usage/agreements are retained with their legal basis named in the report. A partial fan-out answers `"status": "partial – re-run required"` — re-run until `completed`. `GET /privacy/v1/erasure` lists the audit trail.

Retention clocks

`BSS_RETENTION_INTERACTIONS_SECONDS` (party-interaction) and `BSS_RETENTION_TICKETS_SECONDS` (trouble-ticket, settled tickets only) — 0 = keep forever (default). Production sets day-scale values (e.g. 63072000 = 2 years); `BSS_RETENTION_SWEEP_MS` paces the sweep. TickGuard-guarded: replicas never double-sweep.

PCI & lawful intercept, honestly

Card data never enters the BSS — the vault stores `pspToken/brand/lastFour/expiry` (SAQ-A-shaped; a QSA attests the rest). Lawful intercept: the BSS half is warrant-gated subscriber disclosure — shaped, not built; see [docs/privacy.md](https://docs.genalpha-bss.com/privacy.md).

15 • The agent channel (agentic commerce) — suite #64

Being shopped by AI agents is opt-in. Every operator carries `agent-commerce: off | discovery | full` in the tenant registry — `off` (dark to agents, 404), `discovery` (the product feed answers; agent checkout refused with 403 — findable, checkout stays human), `full` (delegated checkout too). Newborn operators are born `off`. Flip it on the operator form (console → Operators → Agent commerce) or by env (`AGENT_COMMERCE` , `AGENT_COMMERCE_<ID>`); the gateway enforces it live — no restart.

The surface (ACP, spec 2026-04-17)

Feed: `GET /acp/product_feed` — public projection of the active TMF620 catalog (unconditioned prices only, one-time preferred; unpriced offerings are skipped). **Checkout:** `POST /acp/checkout_sessions` with `{items:[{id,quantity}]}`, then `GET/POST /acp/checkout_sessions/{id}`, `POST .../{id}/complete` (needs `Authorization` + `Idempotency-Key` + `payment_data.token`), `POST .../{id}/cancel`. A session rides a real TMF663 cart; complete charges the payment token and places a TMF622 order marked `category=agenticCommerce` with the buyer as relatedParty. A replayed `Idempotency-Key` returns the *same* order; a fresh key on a completed session is 409.

Delegated checkout (the trust model)

Agents never hold a machine identity. The shopper's token is exchanged (OAuth token exchange, Keycloak ≥26.2) through the confidential `bss-agent` client — `fullScopeAllowed` `off`, scope-mapped to exactly `catalog:read` `ordering:read/write` `payment:read/write` — so the agent's credential can order and pay and nothing else. The shopper's client must carry an audience

mapper naming `bss-agent` : the realm grants the delegation path explicitly, or the exchange is refused. Suite #64 decodes both tokens to prove the downscoping.

MCP tools (Claude-class agents)

`integrations/mcp-server` wears the same surface as five retail tools: `search_offerings` , `get_offering` (with "also bought"), `start_checkout` , `update_checkout` , `complete_checkout` . Shopper env: `BSS_SHOPPER_USERNAME/PASSWORD` ; exchange client: `BSS_AGENT_CLIENT_ID/SECRET` .

Honest scope: the merchant surface is implemented and proven. Appearing *inside* ChatGPT/Perplexity additionally requires the operator's business onboarding with those platforms (feed registration, PSP delegated-payment agreement) — an operator act, not a code gap. The endpoints they register are the ones suite #64 exercises.

16 · The digital workforce — suite #65

The badge is the opt-in. An AI worker is hired like staff: mint a login, grant the `digital-worker` bundle (console → Staff, or `integrations/hermes-worker/hire-worker.sh`). The grant sheds the walk-in customer defaults — a worker is staff. Revoke the badge to fire; the tenant's AI kill-switch stops the whole workforce mid-shift.

The job

`GET /ai/v1/workforce/tasks` — the open queue, derived LIVE from real backlogs (unassigned TMF621 tickets, unapplied cash). `POST .../tasks/{id}/claim` (15-min lease, `BSS_WORKFORCE_LEASE_SECONDS`), `.../complete` (VERIFIED: a ticket task completes only when the ticket is actually resolved), `.../escalate` (a reason required — escalations are counted, not punished). `GET .../ledger` is the shift record, including the worker's self-reported model usage (labeled: its own word — the worker brings its own LLM).

Approvals (the T3 gate)

Refunds, cease, erasure: the worker FILES (`POST .../approvals` — method + `/tmf-api/` path + body + reason); nothing executes. A human approves on the Workforce tab and the stored action runs under *the approver's own token*; refusing keeps its receipt too. Filing is `workforce:use` ; deciding is `ai:use` — a worker can never approve its own ask.

The scoreboard — and the controls

Console → **Workforce**: completed / escalated / deflection, average handle time, **reopen rate** (completed tickets re-checked live — the honesty metric), the crew by name and observed type, approvals queue, shift ledger, self-reported cost (labeled), and human-minutes saved — an estimate that SAYS so, computed from operator-set baselines (`BSS_WORKFORCE_BASELINE_MINUTES_TICKET/-CASH`). The tab also holds the operator's two levers: **Crew ceiling** (governance `maxWorkers` ; a new worker past it is refused at claim time — surge staffing never outgrows it) and **Hire a worker** (pick a job — care / back-office / generalist — the badge is minted and the credentials shown ONCE with the matching job card to run; activating is the runtime's act, firing is the Staff-tab revoke).

Surge staffing

The staffing signal — `staffing` in the KPIs, Prometheus gauges (`bss_workforce_backlog_depth / _active_workers / _surge` , per tenant) and `WorkforceSurgeEvent` on the boundary — tells an autoscaler when the crew is behind. Scale with KEDA (`integrations/hermes-worker/k8s-surge-example.yaml`) or the dev watcher (`surge.sh`); the ceiling caps whatever the scaler does. The BSS signals and refuses; it never spawns worker processes itself.

The Hermes package (day 1)

`integrations/hermes-worker/` : `hire-worker.sh` (the badge, shown once), `config.snippet.yaml` (Hermes `~/hermes/config.yaml` MCP block with the tool whitelist), and `SKILL.md` job cards (care-triage every 15 min, cash-matching daily). Runtime-neutral by construction — any MCP-speaking agent hires into the same job, badge and audit.

17 • The wrapped legacy estate (overlay) — suite #67

A legacy BSS is just another seam. Three per-tenant registry fields — `legacy-catalog-base-url` , `legacy-fulfilment-base-url` , `legacy-ticket-base-url` (empty = native mode) — wrap an existing estate: its catalog federates read-through into the native list and the ACP feed (legacy-prefixed, cached, fail-soft); orders carrying `legacy-` items hand off to the legacy work-order queue; the digital workforce works the legacy incident backlog age-stamped, with completion VERIFIED against the legacy system's own state. Never two writers: legacy masters its data, genalpha masters engagement. Also: the workforce package's closed loop — dashboard Hire starts a running worker container via the controller (`--profile workforce`); the worker's LLM is live registry config (`worker-ai-*`) rolled onto by the controller.

18 · Generative discoverability (GEO) — suite #68

AI crawlers read HTML only — and the operator holds the switch. Per-tenant ai-visibility: open | search-only | dark executes at robots.txt: open welcomes all crawlers (+ llms.txt, honestly labeled speculative); search-only keeps classic search and disallows AI answer/training bots (GPTBot, ClaudeBot, PerplexityBot, Google-Extended, CCBot...); dark disallows everyone. Newborn operators default search-only .

The gateway DUAL-SERVES /shop/offering/{id} by User-Agent: crawlers get bot-readable HTML with schema.org Product/Offer JSON-LD rendered live from TMF620 (no authoring, no syncing — suite #68 proves bot price == catalog price); humans get the SPA unchanged.

/robots.txt , /sitemap.xml , /llms.txt generate per tenant from the same source. Follow-ups, named: insight ai-answer referrer tagging; knowledge-base FAQ pages as a public help center.

19 · The capability map

What's here, what isn't — TM Forum business capabilities (verb-first, implementation-free) mapped to tech capabilities (ODA functional blocks / TMF Open APIs) and the component carrying each, across eTOM-style domains. Every  cites its proof suite; every  carries its caveat (mock-default PSP, OCS facade, NRDB shaped-not-connected); the  column names what a deployment brings from elsewhere (production OCS, tax engine, ERP/GL, roaming settlement, fraud/RA, FSM, real OSS) — each behind an existing seam or the overlay pattern (suite #67). The full map: [docs/capability-map.md](#) · executive view (filterable, GENERATED from the md so the faces cannot drift): [capability-map.html](#).

20 · Loyalty — reward & retain — suite #69

The program is data; membership is a choice. Component #34 (loyalty , TMF658, :8114) is a points LEDGER wired between engines that already exist. The program — earn rate, gigabyte price, voucher percent, tier thresholds, expiry clock (0 = never) — is marketer-editable data (campaign:write). Customers OPT IN on the storefront My page or the app's My-points card; nobody is enrolled by default. Every point movement is an append-only journal row carrying its cause: bill:<id> , redeem:... , expiry:<date> , adjust:<reason> (goodwill credits REQUIRE a reason).

Earn — a settled bill earns at the program's rate, idempotent per bill (the journal's unique cause index), members only. **Burn** — three ways, each landing on an existing engine and verified there,

never on loyalty's own word: points → gigabytes on THIS month's meter via the usage allowance-boost mechanic; points → a single-use discount voucher minted as a REAL TMF671 promotion (unique code, valid at the same `checkPromotion` door as any campaign code, second redemption 409s); tiers → PRICING, because `loyaltyTier` rides the billing pricing context and one console-authored rule ("Loyalty tier benefit" preset) prices gold differently — the pricing engine needed zero new code. **Govern** — points are a liability: the TickGuard-guarded expiry sweep journals every expired point (FIFO arithmetic), and `GET .../liability` returns the outstanding-points number a finance team books.

Retention wiring — `LoyaltyTierChangedEvent` rides the outbox onto `bss.loyalty.events`, which the campaign engine hears like any business event: the console's campaign form now opens with RECIPES ("Churn save: a loyalty offer to at-risk customers" on the churn scorer's alert; "Loyalty: congratulate a tier change") that prefill trigger + message and stay fully editable. Suite #69 proves all nine legs end to end, including a real tier flip landing a real TMF681 message, and paula's points card composed onto her app Home.

21 • Revenue export — the subledger — suite #70

The BSS is the subledger; the ERP is the ledger. Component #35 (`revenue`, house API `/revenue/v1`, :8107 — no TM Forum Open API covers the GL, deliberately) turns billing and payment events into balanced double-entry journal postings: invoice issued → AR debit / revenue credits per rate line (discounts as contra-revenue); cash books ONCE, at payment capture, whichever door the money came through (card, CSR, bank giro via remittance); refunds book the reverse. Balance is a save-time INVARIANT and every posting is idempotent per source ref — at-least-once delivery can never double-book.

The chart is data — `GET/POST /revenue/v1/accountMapping` (billing:admin): finance's own codes and names per posting key; booked lines keep the snapshot they were born with, so a remap never rewrites history. **The export** — `GET /revenue/v1/journalExport?date=` (CSV, one row per line) is the file a period-close import ingests; `journalEntry` serves the same data as JSON; the console's read-only **Journal** tab shows entries with their lines. **The tie-out** — `GET /revenue/v1/reconciliation?date=` : per-account totals, billed vs cash, every entry balance-checked live, and the loyalty points liability as a labeled CONTROL number (no currency valuation is invented — pricing a point is P2 config). `POST /revenue/v1/backfill` onboards pre-arc bills idempotently. P2 dials, all data: a VAT percent on the `tax` key splits postings into net revenue + tax payable (gross-minus-nets — rounding can never unbalance); a per-point value on `loyalty:liability` turns the points control number into a daily booked accrual; `POST /periodClose` makes the export FINAL (postings into a closed period 409); dispute credits on unpaid bills book contra-revenue automatically; `?format=sap|netsuite` emits ERP-shaped

layouts. Rev-rec (ASC 606/IFRS 15) stays in the ERP's engine; this feed is its clean input. See [docs/revenue-export-plan.md](#).

22 • Credit notes — suite #71

The wrong invoice is never edited — a numbered credit note reverses it. `POST /customerBill/{id}/creditNote {amount?, reason}` (billing:admin — agents open disputes, admins decide money; the 403 wall is suite-proven): mints `CN-NNNNNN` from billing's gapless per-tenant `document_sequence` (row-locked — the bookkeeping rules demand an unbroken series), references the original bill number, and **REQUIRES** a reason. Unpaid bill → the due comes down (a negative `creditNote` line says why; zero settles). Settled bill → the money moves **BACK** through the PSP (`settlement refunded`, `refundRef` kept). Dispute resolutions with `outcome=credit` now mint their own credit note (`disputeId` carried). Customers read their own notes (`GET /creditNote`, PDF at `/creditNote/{id}/document.pdf`) — the storefront shows a `kreditnota` chip per bill; the CSR 360 has the issue button. The revenue subledger books **REDUCED** notes as contra-revenue under the document's number and books nothing extra for **REFUNDED** ones (the refund event owns that). P2 shipped: `GET /creditNote/{id}/document.xml` is the UBL `CreditNote-2` (type 381, EHF/Peppol shape, `BillingReference` to the invoice) and partner-wired tenants ship it on the **SAME** distribution ledger as bills; `lines:[{id, amount?}]` credits named rate lines (each reversal names what it reverses, capped per line); the back-office console's Disputes tab is the decide worklist.

23 • Process flows & the incident agent — suite #72

Choreography runs the flows; TMF701 explains them. Component #36 (`process`, :8116, `/tmf-api/processFlowManagement/v4`): design intent as editable `processFlowSpecification`s (each task's owed event + time allowance), run-time `processFlow`s **PROJECTED** from ordering/SOM events with the per-flow cross-system timeline persisted, and **STUCK AS A STATE** — the TickGuard sweep fails a task past its allowance, out loud on `bss.process.events`. Operators recover via `PATCH .../taskFlow/{id}`; customers see their own flows (self-service order tracking); console: Process flows tab.

The agent whose memory compounds (in `intelligence`, IG1547-aligned): a failed task triggers context assembly (spec + failed step + timeline) and a **GOVERNED** diagnosis — same kill-switch/budget/meter/audit doors as every AI call; its **ONLY** write is a ticket note (LO). Every investigation is an episodic trace with a **MANDATORY** human verdict (`POST /ai/v1/incident/{id}/verdict`). Three useful verdicts on one signature draft a runbook (governed, provenance to source traces) that stays `proposed` until approved (console: Runbooks

tab); the next occurrence auto-diagnoses FROM MEMORY — no model call, audit as witness — and GET /ai/v1/incident/stats carries the learning curve as data. Revocation sends diagnosis back to the LLM path: the brake is first-class. L2 auto-remediation stays out of scope until per-taskFlow idempotency is earned. See [docs/process-memory-plan.md](#).

24 · The standards sweep — suites #73–76

Fulfilment (TMF700+697, component #37, :8117) — physical orders mint shippingOrder s (warehouse PATCHes states, tracking ref), install bookings mint workOrder s; DELIVERED + visit COMPLETED completes the product order machine-driven. Customers track their own deliveries; state changes are staff-only. **SLA (TMF623)** — an sla block on the agreement characteristic (circuit, thresholdMinutes, creditAmount, capPerMonth); late-resolved problems mint violations on assurance's capped ledger (/tmf-api/slaManagement/v4/sla|slaViolation) and billing compensates with the PRE-AGREED credit note, in-process, no one deciding at breach time. **Event hub (TMF688, component #38, :8123)** — POST /hub callback + filter (billing:admin), delivery ledger with backoff retries and dead-letter. **Thin faces:** TMF724 incidents over the agent's memory (verdicts are the state machine), TMF653 serviceTests with history over diagnose, TMF639 pools + issued-number ledger with the honest generator note. See [docs/standards-completion-plan.md](#).

25 · The product configurator (TMF760) — suites #77/#78

Two anonymous task resources on product-catalog at /tmf-api/productConfigurationManagement/v5 (TMF760 has no v4), stateless — the POST computes from the catalog's own rows and answers. **Query:** POST /queryProductConfiguration with {productConfiguration:{productOffering:{id}}} returns the configuration space — fixed members, choice groups (minSelections / maxSelections /default), each option's pickers and prices with appliesWhen conditions visible. **Check:** POST /checkProductConfiguration with selectedOption:[{id}] + configurationCharacteristic:[{name,value}] validates BOTH pick bounds, characteristic values scoped to the PICKED options, and policy block rules (under bss-catalog , the catalog's machine identity; fail-open) — rejections use ordering's exact wording. An approved answer carries configurationPrice (monthly + one-time + lines; conditioned lines only on exact match; the deal engine's indicative total rides along) and an ORDER-READY productConfiguration echo with each pick on the option whose spec owns it. **Agent channel:** MCP tools get_configuration_options and configure_product (an approved answer includes a ready checkoutItem); ACP checkout items accept configuration — the cart prices from the check, refuses invalid picks before a session opens, and complete

builds nested order items with `product.productCharacteristic`, so billing rates the configuration like any other channel's order. See <docs/tmf760-configurator-plan.md>.

26 · Service qualification & the coverage map (TMF645) — suites #79/#80

TMF679 answers the commercial question (may this offering be sold here); TMF645 answers the technical one, on the same `qualification` service at `/tmf-api/serviceQualificationManagement/v4`. The substance is the **coverage map** — operator-editable rows `{technology, postcodePrefix, maxDownMbps, maxUpMbps}`; an EMPTY prefix matches everywhere (the mobile fallback), longest matching prefix wins per technology; seeded by `ops/seed/seed_coverage_map.py`, CRUD gated by `qualification:write`. **Query:** `POST /queryServiceQualification` with `{searchCriteria:{place:{postCode}}}` — every technology deliverable there, with bandwidth characteristics. **Check:** `POST /checkServiceQualification` — verdict per requested service (name the technology via `serviceSpecification.name` or a characteristic; optional `minDownstreamMbps`), and NEVER a bare no: a refusal carries `eligibilityUnavailabilityReason` AND `alternateServiceProposal` with the best technology the address can have. Checks persist and read back anonymously by unguessable id; the LIST (customer addresses) is back-office. **Channels:** ordering qualifies every placed item at create (same TMF679 check the storefront runs; fail-open; refusals speak the qualification's words), and the cart's address block names what the network delivers ("Fiber up to 1000 Mbit/s at your address"). See <docs/tmf645-service-qualification-plan.md>.

27 · AI management — the control plane's face (TMF915) — suite #81

The governed-AI machinery, standards-addressable on intelligence at `/tmf-api/aiManagement/v4`. **GET /aiModel** (ai:use): the models the audit ledger PROVES have served — distinct provider/model/tier pairs with the scenarios each served, plus the trained churn classifier carrying its `trainingRecord` (`sampleCount`, `positives`, `trainedAt`). **GET /aiModelContract/{id}** (ai:use): one contract per governed scenario — `state` (`active` | `suspended` | `haltedByKillSwitch`), `servedBy` model refs, `monitoring` (`calls`, `tokens`, `costMicros`, `avgLatencyMs`, and per-outcome counts including `refused-budget` / `refused-disabled` / `refused-contract`), and the `guardrail` block (`tenant kill-switch`, `budget`, `window`). **PATCH /aiModelContract/{id}** (ai:admin — the seam, now open): `{state: suspended|active, note}` — the per-scenario brake, checked in the governor's gate order right

after the tenant kill-switch; a suspended contract's calls 403 and land on the ledger as `refused-contract`. Budget-setting (`POST /ai/v1/governance/budget`) now also requires `ai:admin`. Ops note: `accessTokenLifespan` is 1800s in BOTH realm files — a Keycloak container recreate re-imports realms from files, so live-only settings (and dynamically-onboarded realms like `aurora`) do not survive one. See [docs/tmf915-ai-management-plan.md](https://docs.tmf915-ai-management-plan.md).

28 · Risk management — the door check (TMF696) — suite #82

The acquisition-side twin of churn, on intelligence at `/tmf-api/riskManagement/v4` behind `risk:assess` (demo staff + the bss-ordering machine; customers 403 even on their own scores — a risk score is a credit check). **POST /partyRiskAssessment** `{relatedParty:[{id}]}` and **POST /productOrderRiskAssessment** (adds `totalQuantity`, `lineCount`, `verifiedIdentity` — supplied by the caller whose session knows it; a verified session scores 20 lower). The score is TRANSPARENT: named signals (`unpaidBills`, `creditNotes`, `orderVelocity`, `newAccount`, `bulkOrder`, `verifiedSession`) each with points + raw evidence in the body — recomputable by hand. Deliberately NOT scored: failed payments (refusals never persist) and lifetime verification (session claim only). Assessments persist and read back by id.

Enforcement is data: ordering fetches a fresh assessment (machine identity, fail-open) into the policy context as `riskScore` / `riskLevel`; the operator's `JsonLogic` rule sets the threshold — deny returns 422 `POLICY_DENIED`. Billing's `GET /creditNote` grew a `relatedPartyId` filter for the engine. See [docs/tmf696-risk-plan.md](https://docs.tmf696-risk-plan.md).

29 · Partnership types & geographic sites (TMF668 + TMF674) — suites #83/#84

TMF668 on the agreement service at `/tmf-api/partnershipTypeManagement/v4/partnershipType` (reads `agreement:read`, writes `agreement:write`): a partnership `KIND` is `{name, description, status, roleType:[{name, description}]}` — a kind without roles is refused. An agreement with `agreementType: "partnership"` whose `characteristic.partnershipTypeId` names a kind is **VALIDATED** at create: every `engagedParty.role` must be one the kind permits (refusals name the permitted list; unknown/retired kinds refuse outright). Untyped agreements are untouched. **TMF674** on geographic-address at `/tmf-api/geographicSiteManagement/v4/geographicSite` (reads `address:read`, writes `address:write`): a site is `{name, status: planned|active|retired, relatedParty, place:{id}}` where `place.id` **MUST** reference a stored **TMF673** `geographicAddress` (validated at create, embedded on every read); filter with `?`

relatedPartyId= ; PATCH moves the lifecycle; a site's address is reusable on orders — entered once. See [docs/tmf668-674-thin-tail-plan.md](https://docs.tmf668-674-thin-tail-plan.md).

30 · The proof run & fleet-age runbooks — suite #85 and the receipt

The proof run: `ops/run-all-suites.sh` runs all suites serially with a readiness gate (IdP + gateway must answer before each suite), inter-suite pacing (a young fleet out-runs its own per-subject rate limiter), the surge controller parked except for the suite that tests it, onboarding suites first (a recreated Keycloak forgets dynamic realms), rate-limit suites last, and one automatic retry pass with attempts recorded. The receipt renders to `docs/proof-run.html` via `docs/build-proof-run-html.py`. **The pruning runbook:** `ops/prune-dev-fleet.sh` retires active subscriptions owned by anyone who is not a named demo persona (nothing deleted — products stop billing), then seed one usage record per persona (meters derive from monthly usage). **Fleet-age laws** (from docs/proof-run-findings.md): machine list-clients page to exhaustion or filter server-side (an unfiltered list ages out of any fixed page — `GET /revenue/v1/journalEntry?sourceRef=` exists because of this); batch endpoints get batch timeouts; suites probing aged personas should mint purpose-made customers; ad-hoc suite runs park `bss-worker-controller` first. Billing runs on a worker pool (`bss.billing.run-concurrency`, default 8; crash-resume proven by suite #57 against the pool) — suite #85 asserts the aged-fleet run completes inside suite patience.

31 · The shop that knows you (personalization) — suite #86

Usage-aware upsell: the signed-in `GET /ai/v1/forYou` payload carries an `upsell` block when any meter is $\geq 80\%$ used — `{bucketName, usedPct, currentAllowance, suggestedOffering, suggestedAllowance}`, the suggestion being the NEXT rung of the allowance ladder (the usage service's `usageAllowance` rows per offering, smallest larger allowance for the same usage type; rows without an offering name get a descriptive label). No meter, a comfortable meter, or no fuller rung → no block. The Shop page renders it as `data-testid=upsell-card` above the recommended rail. **Returning-visitor rules:** the personalization rule context now carries `visits` (distinct event-days per visitor) — author `{">=": [{"var": "visits"}, 2]}` rules in Rules or via the copilot. **Full-profile grid:** the Shop grid ranks singles by the visitor's whole consented `interests[]` array in browse-weight order; a rule's `heroCategory` still floats to the top. Pricing on the grid is deliberately NOT a personalization lever. Hygiene note: killed suite runs orphan their finally-cleanup policy rules —

if default experiences misbehave, list `domain=personalization` rules for leftovers. See [docs/personalization-shop-plan.md](https://docs/ctk-conformance.md).

32 · The CTK campaign — twenty-five kits, the closed list

Scorecard: docs/ctk-conformance.md — twenty-five official CTKs at zero failures; TMF676/681 stay intentional partials. **The list is CLOSED:** the `tmforum-rand` org publishes no kit for the remaining faces (688/696/760/915/700/697/701/724/623) — there is nothing left to run.

Runners: modern kits (`config.json` + `index.js`) via `ops/ctk/runctk.py` ; R18-era kits (raw collection + environment) via `ops/ctk/runctk-r18.py` — both structure URLs for modern newman, bake the bearer, run with `--timeout-script 120000` . Gotchas that will bite again: pass the kit dir by **absolute path** (relative once made newman fail silently and the summary read a STALE `result.json`); some kits write `pmtest.json` BEFORE their own payload injection (`runctk.py` injects config payloads itself now); secondary host-vars (`{{Service_Ordering}}`)/tmf-api/...) hang newman on literal-var DNS — `runctk-r18.py` resolves them to the gateway origin.

One-time kit prep (documented in ops/ctk/README.md): TMF674's example payload must reference a STORED TMF673 address; TMF638 assumes a sandbox — seed two uniquely-named probe services, the newer in state `designed` . **Contract changes the campaign shipped, fleet-wide:** `agreement type` (= `agreementType`) and `ticket ticketType` are now MANDATORY (storefront files `support` , self-heal files `incident`); a roleless partnership kind stores but permits NOTHING at signature; `serviceTest` requires `testSpecification` (the built-in virtual spec is `diagnose`); `agreement` + `ticket` lists page NEWEST-FIRST. New faces: read-only TMF633 `serviceSpecification` on SOM (so inventory spec refs dereference), northbound `POST /serviceOrder` (external orders recorded `acknowledged`), `POST /serviceProblem` (declared problems), and v3 task dialects for TMF645/679 that delegate to the v4 coverage/serviceable-area engines. **Gateway:** SCG 4.2+ only adds `X-Forwarded-*` for `trusted-proxies` (now set to the private ranges); services build absolute Location headers from those — keep that setting when changing gateway config. **Workforce suites:** `workforce_runtime / agentic_workforce` need `bss-worker-controller` UP (start for them, stop after, then `docker rm -f wf-*`).

genalpha-bss · eighty-six suites, twenty-five CTKs at zero failures · the build story is *The Honest Machine* (docs/book) · the TMF vocabulary is docs/book/tmf-reference.md