

# **Hands-on Large Scale Optimization in Python**

**From Beginning to Giving Up**

Kunlei Lian

2023-02-18

# Table of contents

<b>Preface</b>	<b>3</b>
<b>1 Environment Setup</b>	<b>4</b>
1.1 Install Homebrew . . . . .	4
1.2 Install Anaconda . . . . .	4
1.3 Create a Conda Environment . . . . .	5
1.4 Install Google OR-Tools . . . . .	6
<b>2 Introduction</b>	<b>8</b>
<b>3 Environment Setup</b>	<b>9</b>
3.1 Install Homebrew . . . . .	9
3.2 Install Anaconda . . . . .	9
3.3 Create a Conda Environment . . . . .	10
3.4 Install Google OR-Tools . . . . .	11
<b>I Benders Decomposition</b>	<b>13</b>
<b>4 Benders Decomposition</b>	<b>14</b>
4.1 The Decomposition Logic . . . . .	14
4.2 Solving Linear Programs . . . . .	17
4.2.1 Solving the problem as a whole . . . . .	17
4.2.2 The original problem and its optimal solution . . . . .	24
4.2.3 Benders decomposition . . . . .	26
4.2.4 Solving the problem step by step . . . . .	26
4.2.5 Putting it together . . . . .	32
4.2.6 A generic solver . . . . .	39
4.2.7 Implementation with callbacks . . . . .	71
4.2.8 Implementation with SCIP . . . . .	71
Testing . . . . .	73

# Preface

# 1 Environment Setup

In this chapter, we explain the steps needed to set up Python and Google OR-Tools. All the steps below are based on MacBook Air with M1 chip and macOS Ventura 13.1.

## 1.1 Install Homebrew

The first tool we need is Homebrew, ‘the Missing Package Manager for macOS (or Linux)’, and it can be accessed at <https://brew.sh/>. To install Homebrew, just copy the command below and run it in the Terminal.

```
/bin/bash -c "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"
```

We can then use the `brew --version` command to check the installed version. On my system, it shows the info below.

```
~/ brew --version
Homebrew 3.6.20
Homebrew/homebrew-core (git revision 5f1582e4d55; last commit 2023-02-05)
Homebrew/homebrew-cask (git revision fa3b8a669d; last commit 2023-02-05)
```

## 1.2 Install Anaconda

Since there are several Python versions available for our use and we may end up having multiple Python versions installed on our machine, it is important to use a consistent environment to work on our project in. Anaconda is a package and environment manager for Python and it provides easy-to-use tools to facilitate our data science needs. To install Anaconda, run the below command in the Terminal.

```
~/ brew install anaconda
```

After the installation is done, we can use `conda --version` to verify whether it is available on our machine or not.

```
~/ conda --version
conda 23.1.0
```

## 1.3 Create a Conda Environment

Now we will create a Conda environment named 'ortools'. Execute the below command in the Terminal, which effectively creates the required environment with Python version 3.10.

```
~/ conda create -n ortools python=3.10
Retrieving notices: ...working... done
Collecting package metadata (current_repodata.json): done
Solving environment: done
```

```
## Package Plan ##
```

```
environment location: /opt/homebrew/anaconda3/envs/test
```

```
added / updated specs:
- python=3.10
```

The following packages will be downloaded:

package	build		
----- -----			
setuptools-67.4.0	pyhd8ed1ab_0	567 KB	conda-forge
----- -----			
	Total:	567 KB	

The following NEW packages will be INSTALLED:

bzip2	conda-forge/osx-arm64::bzip2-1.0.8-h3422bc3_4
ca-certificates	conda-forge/osx-arm64::ca-certificates-2022.12.7-h4653dfc_0
libffi	conda-forge/osx-arm64::libffi-3.4.2-h3422bc3_5
libsqlite	conda-forge/osx-arm64::libsqlite-3.40.0-h76d750c_0
libzlib	conda-forge/osx-arm64::libzlib-1.2.13-h03a7124_4
ncurses	conda-forge/osx-arm64::ncurses-6.3-h07bb92c_1
openssl	conda-forge/osx-arm64::openssl-3.0.8-h03a7124_0
pip	conda-forge/noarch::pip-23.0.1-pyhd8ed1ab_0
python	conda-forge/osx-arm64::python-3.10.9-h3ba56d0_0_cpython

```

readline          conda-forge/osx-arm64::readline-8.1.2-h46ed386_0
setuptools        conda-forge/noarch::setuptools-67.4.0-pyhd8ed1ab_0
tk                conda-forge/osx-arm64::tk-8.6.12-he1e0b03_0
tzdata            conda-forge/noarch::tzdata-2022g-h191b570_0
wheel             conda-forge/noarch::wheel-0.38.4-pyhd8ed1ab_0
xz                conda-forge/osx-arm64::xz-5.2.6-h57fd34a_0

```

Proceed ([y]/n)?

Type 'y' to proceed and Conda will create the environment for us. We can use `conda env list` to show all the created environments on our machine:

```

~/ conda env list
# conda environments:
#
base                /opt/homebrew/anaconda3
ortools             /opt/homebrew/anaconda3/envs/ortools

```

Note that we need to manually activate an environment in order to use it: `conda activate ortools`. On my machine, the activated environment `ortools` will appear in the beginning of my prompt.

```

~/ conda activate ortools
(ortools) ~/

```

## 1.4 Install Google OR-Tools

As of this writing, the latest version of Google OR-Tools is 9.5.2237, and we can install it in our newly created environment using the command `pip install ortools==9.5.2237`. We can use `conda list` to verify whether it is available in our environment.

```

(ortools) ~/ conda list
# packages in environment at /opt/homebrew/anaconda3/envs/ortools:
#
# Name                Version                Build    Channel
abs1-py               1.4.0                  pypi_0   pypi
bzip2                 1.0.8                  h3422bc3_4  conda-forge
ca-certificates       2022.12.7              h4653dfc_0  conda-forge
libffi                3.4.2                  h3422bc3_5  conda-forge

```

libsqlite	3.40.0	h76d750c_0	conda-forge
libzlib	1.2.13	h03a7124_4	conda-forge
ncurses	6.3	h07bb92c_1	conda-forge
numpy	1.24.2	pypi_0	pypi
openssl	3.0.8	h03a7124_0	conda-forge
ortools	9.5.2237	pypi_0	pypi
pip	23.0.1	pyhd8ed1ab_0	conda-forge
protobuf	4.22.0	pypi_0	pypi
python	3.10.9	h3ba56d0_0_cpython	conda-forge
readline	8.1.2	h46ed386_0	conda-forge
setuptools	67.4.0	pyhd8ed1ab_0	conda-forge
tk	8.6.12	he1e0b03_0	conda-forge
tzdata	2022g	h191b570_0	conda-forge
wheel	0.38.4	pyhd8ed1ab_0	conda-forge
xz	5.2.6	h57fd34a_0	conda-forge

Now we have Python and Google OR-Tools ready, we can start our next journey.

## 2 Introduction

This is a book created from markdown and executable code.

See Knuth (1984) for additional discussion of literate programming.



## 3 Environment Setup

In this chapter, we explain the steps needed to set up Python and Google OR-Tools. All the steps below are based on MacBook Air with M1 chip and macOS Ventura 13.1.

### 3.1 Install Homebrew

The first tool we need is Homebrew, ‘the Missing Package Manager for macOS (or Linux)’, and it can be accessed at <https://brew.sh/>. To install Homebrew, just copy the command below and run it in the Terminal.

```
/bin/bash -c "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"
```

We can then use the `brew --version` command to check the installed version. On my system, it shows the info below.

```
~/ brew --version
Homebrew 3.6.20
Homebrew/homebrew-core (git revision 5f1582e4d55; last commit 2023-02-05)
Homebrew/homebrew-cask (git revision fa3b8a669d; last commit 2023-02-05)
```

### 3.2 Install Anaconda

Since there are several Python versions available for our use and we may end up having multiple Python versions installed on our machine, it is important to use a consistent environment to work on our project in. Anaconda is a package and environment manager for Python and it provides easy-to-use tools to facilitate our data science needs. To install Anaconda, run the below command in the Terminal.

```
~/ brew install anaconda
```

After the installation is done, we can use `conda --version` to verify whether it is available on our machine or not.

```
~/ conda --version
conda 23.1.0
```

### 3.3 Create a Conda Environment

Now we will create a Conda environment named 'ortools'. Execute the below command in the Terminal, which effectively creates the required environment with Python version 3.10.

```
~/ conda create -n ortools python=3.10
Retrieving notices: ...working... done
Collecting package metadata (current_repodata.json): done
Solving environment: done
```

```
## Package Plan ##
```

```
environment location: /opt/homebrew/anaconda3/envs/test
```

```
added / updated specs:
- python=3.10
```

The following packages will be downloaded:

package	build		
----- -----			
setuptools-67.4.0	pyhd8ed1ab_0	567 KB	conda-forge
----- -----			
Total:		567 KB	

The following NEW packages will be INSTALLED:

bzip2	conda-forge/osx-arm64::bzip2-1.0.8-h3422bc3_4
ca-certificates	conda-forge/osx-arm64::ca-certificates-2022.12.7-h4653dfc_0
libffi	conda-forge/osx-arm64::libffi-3.4.2-h3422bc3_5
libsqlite	conda-forge/osx-arm64::libsqlite-3.40.0-h76d750c_0
libzlib	conda-forge/osx-arm64::libzlib-1.2.13-h03a7124_4
ncurses	conda-forge/osx-arm64::ncurses-6.3-h07bb92c_1
openssl	conda-forge/osx-arm64::openssl-3.0.8-h03a7124_0
pip	conda-forge/noarch::pip-23.0.1-pyhd8ed1ab_0
python	conda-forge/osx-arm64::python-3.10.9-h3ba56d0_0_cpython

```

readline          conda-forge/osx-arm64::readline-8.1.2-h46ed386_0
setuptools        conda-forge/noarch::setuptools-67.4.0-pyhd8ed1ab_0
tk                conda-forge/osx-arm64::tk-8.6.12-he1e0b03_0
tzdata            conda-forge/noarch::tzdata-2022g-h191b570_0
wheel             conda-forge/noarch::wheel-0.38.4-pyhd8ed1ab_0
xz                conda-forge/osx-arm64::xz-5.2.6-h57fd34a_0

```

Proceed ([y]/n)?

Type 'y' to proceed and Conda will create the environment for us. We can use `conda env list` to show all the created environments on our machine:

```

~/ conda env list
# conda environments:
#
base                /opt/homebrew/anaconda3
ortools             /opt/homebrew/anaconda3/envs/ortools

```

Note that we need to manually activate an environment in order to use it: `conda activate ortools`. On my machine, the activated environment `ortools` will appear in the beginning of my prompt.

```

~/ conda activate ortools
(ortools) ~/

```

### 3.4 Install Google OR-Tools

As of this writing, the latest version of Google OR-Tools is 9.5.2237, and we can install it in our newly created environment using the command `pip install ortools==9.5.2237`. We can use `conda list` to verify whether it is available in our environment.

```

(ortools) ~/ conda list
# packages in environment at /opt/homebrew/anaconda3/envs/ortools:
#
# Name                Version                Build    Channel
abs1-py               1.4.0                  pypi_0   pypi
bzip2                 1.0.8                  h3422bc3_4  conda-forge
ca-certificates       2022.12.7              h4653dfc_0  conda-forge
libffi                 3.4.2                  h3422bc3_5  conda-forge

```

libsqlite	3.40.0	h76d750c_0	conda-forge
libzlib	1.2.13	h03a7124_4	conda-forge
ncurses	6.3	h07bb92c_1	conda-forge
numpy	1.24.2	pypi_0	pypi
openssl	3.0.8	h03a7124_0	conda-forge
ortools	9.5.2237	pypi_0	pypi
pip	23.0.1	pyhd8ed1ab_0	conda-forge
protobuf	4.22.0	pypi_0	pypi
python	3.10.9	h3ba56d0_0_cpython	conda-forge
readline	8.1.2	h46ed386_0	conda-forge
setuptools	67.4.0	pyhd8ed1ab_0	conda-forge
tk	8.6.12	he1e0b03_0	conda-forge
tzdata	2022g	h191b570_0	conda-forge
wheel	0.38.4	pyhd8ed1ab_0	conda-forge
xz	5.2.6	h57fd34a_0	conda-forge

Now we have Python and Google OR-Tools ready, we can start our next journey.

**Part I**

**Benders Decomposition**

## 4 Benders Decomposition

In this chapter, we will explain the theories behind Benders decomposition and demonstrate its usage on a trial linear programming problem. Keep in mind that Benders decomposition is not limited to solving linear programming problems. In fact, it is one of the most powerful techniques to solve some large-scale mixed-integer linear programming problems.

In the following sections, we will go through the critical steps during the decomposition process when applying the algorithm on optimization problems represented in standard forms. This is important as it helps build up the intuition of when we should consider applying Benders decomposition to a problem at hand. Often times, recognizing the applicability of Benders decomposition is the most important and challenging step when solving an optimization problem. Once we know that the problem structure is suitable to solve via Benders decomposition, it is straightforward to follow the decomposition steps and put it into work.

Generally speaking, Benders decomposition is a good solution candidate when the resulting problem is much easier to solve if some of the variables in the original problem are fixed. We will illustrate this point using an example in the following sections. In the optimization world, the first candidate that should come to mind when we say a problem is easy to solve is a linear programming formulation, which is indeed the case in Benders decomposition applications.

### 4.1 The Decomposition Logic

To explain the reasoning of Benders decomposition, let us look at the standard form of linear programming problems that involve two vector variables,  $\mathbf{x}$  and  $\mathbf{y}$ . Let  $p$  and  $q$  indicate the dimensions of  $\mathbf{x}$  and  $\mathbf{y}$ , respectively. Below is the original problem  $\mathbf{P}$  we intend to solve.

$$(\mathbf{P}) \quad \min. \quad \mathbf{c}^T \mathbf{x} + \mathbf{f}^T \mathbf{y} \quad (4.1)$$

$$\text{s.t.} \quad \mathbf{Ax} + \mathbf{By} = \mathbf{b} \quad (4.2)$$

$$\mathbf{x} \geq 0, \mathbf{y} \geq 0 \quad (4.3)$$

In this formulation,  $\mathbf{c}$  and  $\mathbf{f}$  in the objective function represent the cost coefficients associated with decision variables  $\mathbf{x}$  and  $\mathbf{y}$ , respectively. Both of them are column vectors of corresponding dimensions. In the constraints, matrix  $\mathbf{A}$  is of dimension  $m \times p$ , and matrix  $\mathbf{B}$  is of dimension  $m \times q$ .  $\mathbf{b}$  is a column vector of dimension  $m$ .

Suppose the variable  $\mathbf{y}$  is a complicating variable in the sense that the resulting problem is substantially easier to solve if the value of  $\mathbf{y}$  is fixed. In this case, we could rewrite problem  $\mathbf{P}$  as the following form:

$$\min. \quad \mathbf{f}^T \mathbf{y} + g(\mathbf{y}) \quad (4.4)$$

$$\text{s.t.} \quad \mathbf{y} \geq 0 \quad (4.5)$$

where  $g(\mathbf{y})$  is a function of  $\mathbf{y}$  and is defined as the subproblem  $\mathbf{SP}$  of the form below:

$$(\mathbf{SP}) \quad \min. \quad \mathbf{c}^T \mathbf{x} \quad (4.6)$$

$$\text{s.t.} \quad \mathbf{Ax} = \mathbf{b} - \mathbf{By} \quad (4.7)$$

$$\mathbf{x} \geq 0 \quad (4.8)$$

Note that the  $\mathbf{y}$  in constraint (4.7) takes on some known values when the problem is solved and the only decision variable in the above formulation is  $\mathbf{x}$ . The dual problem of  $\mathbf{SP}$ ,  $\mathbf{DSP}$ , is given below.

$$(\mathbf{DSP}) \quad \max. \quad (\mathbf{b} - \mathbf{By})^T \mathbf{u} \quad (4.9)$$

$$\text{s.t.} \quad \mathbf{A}^T \mathbf{u} \leq \mathbf{c} \quad (4.10)$$

$$\mathbf{u} \text{ unrestricted} \quad (4.11)$$

A key characteristic of the above  $\mathbf{DSP}$  is that its solution space does not depend on the value of  $\mathbf{y}$ , which only affects the objective function. According to the Minkowski's representation theorem, any  $\bar{\mathbf{u}}$  satisfying the constraints (4.10) can be expressed as

$$\bar{\mathbf{u}} = \sum_{j \in \mathbf{J}} \lambda_j \mathbf{u}_j^{point} + \sum_{k \in \mathbf{K}} \mu_k \mathbf{u}_k^{ray} \quad (4.12)$$

where  $\mathbf{u}_j^{point}$  and  $\mathbf{u}_k^{ray}$  represent an extreme point and extreme ray, respectively. In addition,  $\lambda_j \geq 0$  for all  $j \in \mathbf{J}$  and  $\sum_{j \in \mathbf{J}} \lambda_j = 1$ , and  $\mu_k \geq 0$  for all  $k \in \mathbf{K}$ . It follows that the  $\mathbf{DSP}$  is equivalent to

$$\max. \quad (\mathbf{b} - \mathbf{B}\mathbf{y})^T \left( \sum_{j \in \mathbf{J}} \lambda_j \mathbf{u}_j^{point} + \sum_{k \in \mathbf{K}} \mu_k \mathbf{u}_k^{ray} \right) \quad (4.13)$$

$$\text{s.t.} \quad \sum_{j \in \mathbf{J}} \lambda_j = 1 \quad (4.14)$$

$$\lambda_j \geq 0, \quad \forall j \in \mathbf{J} \quad (4.15)$$

$$\mu_k \geq 0, \quad \forall k \in \mathbf{K} \quad (4.16)$$

We can therefore conclude that

- The **DSP** becomes unbounded if any  $\mathbf{u}_k^{ray}$  exists such that  $(\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_k^{ray} > 0$ . Note that an unbounded **DSP** implies an infeasible **SP** and to prevent this from happening, we have to ensure that  $(\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_k^{ray} \leq 0$  for all  $k \in \mathbf{K}$ .
- If an optimal solution to **DSP** exists, it must occur at one of the extreme points. Let  $g$  denote the optimal objective value, it follows that  $(\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_j^{point} \leq g$  for all  $j \in \mathbf{J}$ .

Based on this idea, the **DSP** can be reformulated as follows:

$$\min. \quad g \quad (4.17)$$

$$\text{s.t.} \quad (\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_k^{ray} \leq 0, \quad \forall k \in \mathbf{K} \quad (4.18)$$

$$(\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_j^{point} \leq g, \quad \forall j \in \mathbf{J} \quad (4.19)$$

$$j \in \mathbf{J}, k \in \mathbf{K} \quad (4.20)$$

Constraints (4.18) are called **Benders feasibility cuts**, while constraints (4.19) are called **Benders optimality cuts**. Now we are ready to define the Benders Master Problem (**BMP**) as follows:

$$(\mathbf{BMP}) \quad \min. \quad \mathbf{f}^T \mathbf{y} + g \quad (4.21)$$

$$\text{s.t.} \quad (\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_k^{ray} \leq 0, \quad \forall k \in \mathbf{K} \quad (4.22)$$

$$(\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_j^{point} \leq g, \quad \forall j \in \mathbf{J} \quad (4.23)$$

$$j \in \mathbf{J}, k \in \mathbf{K}, \mathbf{y} \geq 0 \quad (4.24)$$

Typically  $J$  and  $K$  are too large to enumerate upfront and we have to work with subsets of them, denoted by  $J_s$  and  $K_s$ , respectively. Hence we have the following Restricted Benders Master Problem (**RBMP**):



$$\text{(RBMP)} \quad \min. \quad \mathbf{f}^T \mathbf{y} + g \quad (4.25)$$

$$\text{s.t.} \quad (\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_k^{ray} \leq 0, \quad \forall j \in \mathbf{J}_s \quad (4.26)$$

$$(\mathbf{b} - \mathbf{B}\mathbf{y})^T \mathbf{u}_j^{point} \leq g, \quad \forall k \in \mathbf{K}_s \quad (4.27)$$

$$j \in \mathbf{J}, k \in \mathbf{K}, \mathbf{y} \geq 0 \quad (4.28)$$




Figure 4.1: Benders decomposition workflow

## 4.2 Solving Linear Programs

In this section, we will first present a small linear programming problem and solve it directly using the Gurobi API in Python - *gurobipy*. Then we will demonstrate the Benders decomposition approach on this artificial problem. Lastly, we will provide an implementation to solve this problem in *gurobipy*.

### 4.2.1 Solving the problem as a whole

```

import gurobipy as gp
from gurobipy import GRB
import numpy as np
import scipy.sparse as sp

class LpSolverGurobi:

    def __init__(self, obj_coeff, constr_mat, rhs):
        self._env = gp.Env('GurobiEnv')
        self._model = gp.Model(env=self._env, name='GurobiLpSolver')

```

```

# prepare data
self._obj_coeff = obj_coeff
print(self._obj_coeff)
self._constr_mat = constr_mat
print(self._constr_mat)
self._rhs = rhs
self._num_vars = len(self._obj_coeff)
self._num_constrs = len(self._rhs)

# create decision variables
self._vars = self._model.addMVar(self._num_vars, vtype=GRB.CONTINUOUS, lb=0)

# create constraints
self._constrs = self._model.addConstr(self._constr_mat@self._vars == self._rhs)

# create objective
self._model.setObjective(self._obj_coeff @ self._vars, GRB.MINIMIZE)

def optimize(self):
    self._model.update()
    print(self._model.display())
    self._model.optimize()

def clean_up(self):
    self._model.dispose()
    self._env.dispose()

import pycipopt as scip
from pycipopt import SCIP_PARAMSETTING

class LpSolverSCIP:

    def __init__(self, obj_coeff, constr_mat, rhs):
        self._model = scip.Model('LpModel')

        # create variables
        self._vars = {
            i: self._model.addVar(lb=0, vtype='C', name=f'var_{i}')
            for i in range(len(obj_coeff))
        }

```

```

        # create constraints
        for c in range(len(rhs)):
            expr = [
                constr_mat[c][j] * self._vars.get(j)
                for j in range(len(obj_coeff))
            ]
            self._model.addCons(scip.quicksum(expr) == rhs[c])

        # create objective
        obj_expr = [
            obj_coeff[i] * self._vars.get(i)
            for i in range(len(obj_coeff))
        ]
        self._model.setObjective(scip.quicksum(obj_expr), "minimize")

    def optimize(self):
        self._model.optimize()
        pass

import gurobipy as gp
from gurobipy import GRB
import numpy as np

np.random.seed(142)
c = np.random.randint(2, 6, size=20)
f = np.random.randint(1, 15, size=10)
A = np.random.randint(2, 6, size=(20, 20))
B = np.random.randint(2, 26, size=(20, 10))
b = np.random.randint(20, 50, size=20)

obj_coeff = np.concatenate((c, f))
constr_mat = np.concatenate((A, B), axis=1)
rhs = b

lpsolver_gurobi = LpSolverGurobi(obj_coeff=obj_coeff, constr_mat=constr_mat, rhs=rhs)
lpsolver_gurobi.optimize()

```

Set parameter Username

Set parameter LogFile to value "GurobiEnv"

```
[ 3  3  5  5  2  4  3  2  3  3  4  2  5  5  2  5  4  4  5  5  3  6  8 12
 3  5  4  4  9  3]
```

```

[[ 2  4  3  5  5  2  5  4  5  3  3  4  2  2  2  2  3  2  3  3 11 11 25 20
   9  5  7  8  9  2]
 [ 5  2  2  4  3  5  4  2  3  5  4  3  2  5  2  3  5  4  5  4 23 19 23 19
 12 12 13 15 19 19]
 [ 2  3  2  2  5  5  4  5  5  2  5  2  5  4  5  4  3  5  3  3 11 10  8 20
 17  9 25 25 10 12]
 [ 3  5  4  3  4  2  4  2  4  2  4  2  3  3  2  5  3  2  4  2 16 23 18 20
 20 25 14 10  2  6]
 [ 5  4  3  4  3  4  5  4  4  2  5  4  2  3  2  2  5  2  4  3  3  8 10  4
 22 25 11 15 15  9]
 [ 5  5  5  3  2  5  2  2  3  4  2  5  4  4  2  5  4  5  5  4 21 14 22 19
 15 19 16  8 22 23]
 [ 4  2  2  5  2  5  5  4  2  3  2  3  2  5  4  3  3  4  5  3 18  8 11  2
 19 23 23  8 18 25]
 [ 3  2  4  5  3  2  3  5  3  4  5  2  5  4  2  4  2  4  3  5 20 19 13 24
 19  7  4 15 24  3]
 [ 4  4  2  3  2  2  5  5  2  3  5  5  4  5  3  4  2  2  4  2 19  6 20 16
  5 14 20 18 19  6]
 [ 4  2  3  4  4  4  2  5  2  5  5  2  3  4  4  5  4  4  2  3 25 11 17 14
 15 12  6 23 24  6]
 [ 3  5  2  5  3  2  3  3  5  5  3  2  5  3  4  3  5  5  4  4  3 23  9 16
 22  3 14 16 12 16]
 [ 2  3  4  3  5  5  3  5  4  4  2  5  4  3  5  2  3  4  5  4 13 11  7  2
 15 24 13 16  4  6]
 [ 4  4  2  2  4  4  3  2  2  2  5  5  2  5  3  3  5  2  4  3  9 13 10 16
 25 16 24 21  6 16]
 [ 3  5  5  4  3  2  3  5  2  3  5  3  5  3  3  3  5  5  5  5  3 20  5 18
  8 19 25  2 17  7]
 [ 3  2  5  2  2  3  3  3  4  3  5  5  4  4  4  3  3  4  4  4  9 15  6 23
 14 21 21 22 18 22]
 [ 3  2  2  3  4  3  2  4  5  3  2  2  2  3  5  3  2  2  4  4 19 17 17 17
  4 22 12 18  4 18]
 [ 4  2  2  5  2  3  5  4  2  3  2  5  5  5  5  4  4  4  2  5  2 13 23  8
 22 17 10 24 20 23]
 [ 2  4  2  3  2  2  2  4  4  5  2  4  4  4  2  4  3  4  5  3 10  6 20 21
 16 15 13  3 24 16]
 [ 2  5  4  3  3  3  4  2  5  4  2  4  5  2  2  2  3  5  4  5 12 18 21  8
 19  8 11 20 21 21]
 [ 4  2  2  2  2  2  4  3  4  3  2  2  4  2  4  3  5  2  4  3 11  4  2  9
 13 20 23 16 16 14]]

```

Minimize

3.0 C0 + 3.0 C1 + 5.0 C2 + 5.0 C3 + 2.0 C4 + 4.0 C5 + 3.0 C6 + 2.0 C7 + 3.0 C8  
+ 3.0 C9 + 4.0 C10 + 2.0 C11 + 5.0 C12 + 5.0 C13 + 2.0 C14 + 5.0 C15 + 4.0 C16 + 4.0 C17

+ 5.0 C18 + 5.0 C19 + 3.0 C20 + 6.0 C21 + 8.0 C22 + 12.0 C23 + 3.0 C24 + 5.0 C25  
+ 4.0 C26 + 4.0 C27 + 9.0 C28 + 3.0 C29

Subject To

R0: 2.0 C0 + 4.0 C1 + 3.0 C2 + 5.0 C3 + 5.0 C4 + 2.0 C5 + 5.0 C6 + 4.0 C7 + 5.0 C8 +  
3.0 C9 + 3.0 C10 + 4.0 C11 + 2.0 C12 + 2.0 C13 + 2.0 C14 + 2.0 C15 + 3.0 C16 + 2.0 C17 +  
3.0 C18 + 3.0 C19 + 11.0 C20 + 11.0 C21 + 25.0 C22 + 20.0 C23 + 9.0 C24 + 5.0 C25 + 7.0  
C26 + 8.0 C27 + 9.0 C28 + 2.0 C29 = 21

R1: 5.0 C0 + 2.0 C1 + 2.0 C2 + 4.0 C3 + 3.0 C4 + 5.0 C5 + 4.0 C6 + 2.0 C7 + 3.0 C8 +  
5.0 C9 + 4.0 C10 + 3.0 C11 + 2.0 C12 + 5.0 C13 + 2.0 C14 + 3.0 C15 + 5.0 C16 + 4.0 C17 +  
5.0 C18 + 4.0 C19 + 23.0 C20 + 19.0 C21 + 23.0 C22 + 19.0 C23 + 12.0 C24 + 12.0 C25 +  
13.0 C26 + 15.0 C27 + 19.0 C28 + 19.0 C29 = 26

R2: 2.0 C0 + 3.0 C1 + 2.0 C2 + 2.0 C3 + 5.0 C4 + 5.0 C5 + 4.0 C6 + 5.0 C7 + 5.0 C8 +  
2.0 C9 + 5.0 C10 + 2.0 C11 + 5.0 C12 + 4.0 C13 + 5.0 C14 + 4.0 C15 + 3.0 C16 + 5.0 C17 +  
3.0 C18 + 3.0 C19 + 11.0 C20 + 10.0 C21 + 8.0 C22 + 20.0 C23 + 17.0 C24 + 9.0 C25 + 25.0  
C26 + 25.0 C27 + 10.0 C28 + 12.0 C29 = 38

R3: 3.0 C0 + 5.0 C1 + 4.0 C2 + 3.0 C3 + 4.0 C4 + 2.0 C5 + 4.0 C6 + 2.0 C7 + 4.0 C8 +  
2.0 C9 + 4.0 C10 + 2.0 C11 + 3.0 C12 + 3.0 C13 + 2.0 C14 + 5.0 C15 + 3.0 C16 + 2.0 C17 +  
4.0 C18 + 2.0 C19 + 16.0 C20 + 23.0 C21 + 18.0 C22 + 20.0 C23 + 20.0 C24 + 25.0 C25 +  
14.0 C26 + 10.0 C27 + 2.0 C28 + 6.0 C29 = 42

R4: 5.0 C0 + 4.0 C1 + 3.0 C2 + 4.0 C3 + 3.0 C4 + 4.0 C5 + 5.0 C6 + 4.0 C7 + 4.0 C8 +  
2.0 C9 + 5.0 C10 + 4.0 C11 + 2.0 C12 + 3.0 C13 + 2.0 C14 + 2.0 C15 + 5.0 C16 + 2.0 C17 +  
4.0 C18 + 3.0 C19 + 3.0 C20 + 8.0 C21 + 10.0 C22 + 4.0 C23 + 22.0 C24 + 25.0 C25 + 11.0  
C26 + 15.0 C27 + 15.0 C28 + 9.0 C29 = 35

R5: 5.0 C0 + 5.0 C1 + 5.0 C2 + 3.0 C3 + 2.0 C4 + 5.0 C5 + 2.0 C6 + 2.0 C7 + 3.0 C8 +  
4.0 C9 + 2.0 C10 + 5.0 C11 + 4.0 C12 + 4.0 C13 + 2.0 C14 + 5.0 C15 + 4.0 C16 + 5.0 C17 +  
5.0 C18 + 4.0 C19 + 21.0 C20 + 14.0 C21 + 22.0 C22 + 19.0 C23 + 15.0 C24 + 19.0 C25 +  
16.0 C26 + 8.0 C27 + 22.0 C28 + 23.0 C29 = 37

R6: 4.0 C0 + 2.0 C1 + 2.0 C2 + 5.0 C3 + 2.0 C4 + 5.0 C5 + 5.0 C6 + 4.0 C7 + 2.0 C8 +  
3.0 C9 + 2.0 C10 + 3.0 C11 + 2.0 C12 + 5.0 C13 + 4.0 C14 + 3.0 C15 + 3.0 C16 + 4.0 C17 +  
5.0 C18 + 3.0 C19 + 18.0 C20 + 8.0 C21 + 11.0 C22 + 2.0 C23 + 19.0 C24 + 23.0 C25 + 23.0  
C26 + 8.0 C27 + 18.0 C28 + 25.0 C29 = 28

R7: 3.0 C0 + 2.0 C1 + 4.0 C2 + 5.0 C3 + 3.0 C4 + 2.0 C5 + 3.0 C6 + 5.0 C7 + 3.0 C8 +  
4.0 C9 + 5.0 C10 + 2.0 C11 + 5.0 C12 + 4.0 C13 + 2.0 C14 + 4.0 C15 + 2.0 C16 + 4.0 C17 +  
3.0 C18 + 5.0 C19 + 20.0 C20 + 19.0 C21 + 13.0 C22 + 24.0 C23 + 19.0 C24 + 7.0 C25 + 4.0  
C26 + 15.0 C27 + 24.0 C28 + 3.0 C29 = 22

R8: 4.0 C0 + 4.0 C1 + 2.0 C2 + 3.0 C3 + 2.0 C4 + 2.0 C5 + 5.0 C6 + 5.0 C7 + 2.0 C8 +  
3.0 C9 + 5.0 C10 + 5.0 C11 + 4.0 C12 + 5.0 C13 + 3.0 C14 + 4.0 C15 + 2.0 C16 + 2.0 C17 +  
4.0 C18 + 2.0 C19 + 19.0 C20 + 6.0 C21 + 20.0 C22 + 16.0 C23 + 5.0 C24 + 14.0 C25 + 20.0  
C26 + 18.0 C27 + 19.0 C28 + 6.0 C29 = 39

R9: 4.0 C0 + 2.0 C1 + 3.0 C2 + 4.0 C3 + 4.0 C4 + 4.0 C5 + 2.0 C6 + 5.0 C7 + 2.0 C8 +  
5.0 C9 + 5.0 C10 + 2.0 C11 + 3.0 C12 + 4.0 C13 + 4.0 C14 + 5.0 C15 + 4.0 C16 + 4.0 C17 +  
2.0 C18 + 3.0 C19 + 25.0 C20 + 11.0 C21 + 17.0 C22 + 14.0 C23 + 15.0 C24 + 12.0 C25 +  
6.0 C26 + 23.0 C27 + 24.0 C28 + 6.0 C29 = 33

R10: 3.0 C0 + 5.0 C1 + 2.0 C2 + 5.0 C3 + 3.0 C4 + 2.0 C5 + 3.0 C6 + 3.0 C7 + 5.0 C8 +  
5.0 C9 + 3.0 C10 + 2.0 C11 + 5.0 C12 + 3.0 C13 + 4.0 C14 + 3.0 C15 + 5.0 C16 + 5.0 C17 +  
4.0 C18 + 4.0 C19 + 3.0 C20 + 23.0 C21 + 9.0 C22 + 16.0 C23 + 22.0 C24 + 3.0 C25 + 14.0  
C26 + 16.0 C27 + 12.0 C28 + 16.0 C29 = 28  
R11: 2.0 C0 + 3.0 C1 + 4.0 C2 + 3.0 C3 + 5.0 C4 + 5.0 C5 + 3.0 C6 + 5.0 C7 + 4.0 C8 +  
4.0 C9 + 2.0 C10 + 5.0 C11 + 4.0 C12 + 3.0 C13 + 5.0 C14 + 2.0 C15 + 3.0 C16 + 4.0 C17 +  
5.0 C18 + 4.0 C19 + 13.0 C20 + 11.0 C21 + 7.0 C22 + 2.0 C23 + 15.0 C24 + 24.0 C25 + 13.0  
C26 + 16.0 C27 + 4.0 C28 + 6.0 C29 = 38  
R12: 4.0 C0 + 4.0 C1 + 2.0 C2 + 2.0 C3 + 4.0 C4 + 4.0 C5 + 3.0 C6 + 2.0 C7 + 2.0 C8 +  
2.0 C9 + 5.0 C10 + 5.0 C11 + 2.0 C12 + 5.0 C13 + 3.0 C14 + 3.0 C15 + 5.0 C16 + 2.0 C17 +  
4.0 C18 + 3.0 C19 + 9.0 C20 + 13.0 C21 + 10.0 C22 + 16.0 C23 + 25.0 C24 + 16.0 C25 +  
24.0 C26 + 21.0 C27 + 6.0 C28 + 16.0 C29 = 47  
R13: 3.0 C0 + 5.0 C1 + 5.0 C2 + 4.0 C3 + 3.0 C4 + 2.0 C5 + 3.0 C6 + 5.0 C7 + 2.0 C8 +  
3.0 C9 + 5.0 C10 + 3.0 C11 + 5.0 C12 + 3.0 C13 + 3.0 C14 + 3.0 C15 + 5.0 C16 + 5.0 C17 +  
5.0 C18 + 5.0 C19 + 3.0 C20 + 20.0 C21 + 5.0 C22 + 18.0 C23 + 8.0 C24 + 19.0 C25 + 25.0  
C26 + 2.0 C27 + 17.0 C28 + 7.0 C29 = 28  
R14: 3.0 C0 + 2.0 C1 + 5.0 C2 + 2.0 C3 + 2.0 C4 + 3.0 C5 + 3.0 C6 + 3.0 C7 + 4.0 C8 +  
3.0 C9 + 5.0 C10 + 5.0 C11 + 4.0 C12 + 4.0 C13 + 4.0 C14 + 3.0 C15 + 3.0 C16 + 4.0 C17 +  
4.0 C18 + 4.0 C19 + 9.0 C20 + 15.0 C21 + 6.0 C22 + 23.0 C23 + 14.0 C24 + 21.0 C25 + 21.0  
C26 + 22.0 C27 + 18.0 C28 + 22.0 C29 = 45  
R15: 3.0 C0 + 2.0 C1 + 2.0 C2 + 3.0 C3 + 4.0 C4 + 3.0 C5 + 2.0 C6 + 4.0 C7 + 5.0 C8 +  
3.0 C9 + 2.0 C10 + 2.0 C11 + 2.0 C12 + 3.0 C13 + 5.0 C14 + 3.0 C15 + 2.0 C16 + 2.0 C17 +  
4.0 C18 + 4.0 C19 + 19.0 C20 + 17.0 C21 + 17.0 C22 + 17.0 C23 + 4.0 C24 + 22.0 C25 +  
12.0 C26 + 18.0 C27 + 4.0 C28 + 18.0 C29 = 34  
R16: 4.0 C0 + 2.0 C1 + 2.0 C2 + 5.0 C3 + 2.0 C4 + 3.0 C5 + 5.0 C6 + 4.0 C7 + 2.0 C8 +  
3.0 C9 + 2.0 C10 + 5.0 C11 + 5.0 C12 + 5.0 C13 + 5.0 C14 + 4.0 C15 + 4.0 C16 + 4.0 C17 +  
2.0 C18 + 5.0 C19 + 2.0 C20 + 13.0 C21 + 23.0 C22 + 8.0 C23 + 22.0 C24 + 17.0 C25 + 10.0  
C26 + 24.0 C27 + 20.0 C28 + 23.0 C29 = 46  
R17: 2.0 C0 + 4.0 C1 + 2.0 C2 + 3.0 C3 + 2.0 C4 + 2.0 C5 + 2.0 C6 + 4.0 C7 + 4.0 C8 +  
5.0 C9 + 2.0 C10 + 4.0 C11 + 4.0 C12 + 4.0 C13 + 2.0 C14 + 4.0 C15 + 3.0 C16 + 4.0 C17 +  
5.0 C18 + 3.0 C19 + 10.0 C20 + 6.0 C21 + 20.0 C22 + 21.0 C23 + 16.0 C24 + 15.0 C25 +  
13.0 C26 + 3.0 C27 + 24.0 C28 + 16.0 C29 = 35  
R18: 2.0 C0 + 5.0 C1 + 4.0 C2 + 3.0 C3 + 3.0 C4 + 3.0 C5 + 4.0 C6 + 2.0 C7 + 5.0 C8 +  
4.0 C9 + 2.0 C10 + 4.0 C11 + 5.0 C12 + 2.0 C13 + 2.0 C14 + 2.0 C15 + 3.0 C16 + 5.0 C17 +  
4.0 C18 + 5.0 C19 + 12.0 C20 + 18.0 C21 + 21.0 C22 + 8.0 C23 + 19.0 C24 + 8.0 C25 + 11.0  
C26 + 20.0 C27 + 21.0 C28 + 21.0 C29 = 46  
R19: 4.0 C0 + 2.0 C1 + 2.0 C2 + 2.0 C3 + 2.0 C4 + 2.0 C5 + 4.0 C6 + 3.0 C7 + 4.0 C8 +  
3.0 C9 + 2.0 C10 + 2.0 C11 + 4.0 C12 + 2.0 C13 + 4.0 C14 + 3.0 C15 + 5.0 C16 + 2.0 C17 +  
4.0 C18 + 3.0 C19 + 11.0 C20 + 4.0 C21 + 2.0 C22 + 9.0 C23 + 13.0 C24 + 20.0 C25 + 23.0  
C26 + 16.0 C27 + 16.0 C28 + 14.0 C29 = 32

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 20 rows, 30 columns and 600 nonzeros

Model fingerprint: 0x05cb70d4

Coefficient statistics:

Matrix range [2e+00, 2e+01]

Objective range [2e+00, 1e+01]

Bounds range [0e+00, 0e+00]

RHS range [2e+01, 5e+01]

Presolve time: 0.00s

Presolved: 20 rows, 30 columns, 600 nonzeros

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	3.3913043e+00	5.119565e+01	0.000000e+00	0s

Solved in 13 iterations and 0.01 seconds (0.00 work units)

Infeasible model

```
lpsolver_scip = LpSolverSCIP(obj_coeff=obj_coeff, constr_mat=constr_mat, rhs=rhs)
lpsolver_scip.optimize()
```

presolving:

(round 1, fast) 0 del vars, 0 del conss, 0 add conss, 74 chg bounds, 0 chg sides, 0 chg

(0.0s) running MILP presolver

(0.0s) MILP presolver found nothing

(0.0s) sparsify finished: 158/600 (26.3%) nonzeros canceled - in total 158 canceled nonzeros

(round 2, exhaustive) 0 del vars, 0 del conss, 0 add conss, 74 chg bounds, 0 chg sides, 570 c

(0.0s) sparsify aborted: 8/442 (1.8%) nonzeros canceled - in total 166 canceled nonzeros,

(round 3, exhaustive) 0 del vars, 0 del conss, 0 add conss, 74 chg bounds, 0 chg sides, 632 c

(round 4, fast) 0 del vars, 0 del conss, 0 add conss, 77 chg bounds, 0 chg sides, 632 c

(0.0s) symmetry computation started: requiring (bin +, int +, cont +), (fixed: bin -, int

(0.0s) no symmetry present (symcode time: 0.00)

presolving (5 rounds: 5 fast, 3 medium, 3 exhaustive):

0 deleted vars, 0 deleted constraints, 0 added constraints, 77 tightened bounds, 0 added ho

0 implications, 0 cliques

presolved problem has 30 variables (0 bin, 0 int, 0 impl, 30 cont) and 20 constraints

20 constraints of type <linear>

Presolving Time: 0.00

time	node	left	LP iter	LP it/n	mem/heur	mdpt	vars	cons	rows	cuts	sepa	confs	str
------	------	------	---------	---------	----------	------	------	------	------	------	------	-------	-----

0.0s	1	0	13	-	1509k	0	30	20	20	0	0	0	0
0.0s	1	0	13	-	1509k	0	30	20	20	0	0	0	0

```

SCIP Status      : problem is solved [infeasible]
Solving Time (sec) : 0.00
Solving Nodes    : 1
Primal Bound     : +1.0000000000000000e+20 (0 solutions)
Dual Bound      : +1.0000000000000000e+20
Gap              : 0.00 %

```

#### 4.2.2 The original problem and its optimal solution

The linear program we examine here is devoid of any practical meaning and is solely used to demonstrate the solution process of Benders decomposition. The problem is stated below, in which  $\mathbf{x} = (x_1, x_2, x_3)$  and  $\mathbf{y} = (y_1, y_2)$  are the decision variables. We assume that  $\mathbf{y}$  is the complicating variable.

$$\begin{aligned}
\min. \quad & 8x_1 + 12x_2 + 10x_3 + 15y_1 + 18y_2 \\
\text{s.t.} \quad & 2x_1 + 3x_2 + 2x_3 + 4y_1 + 5y_2 = 300 \\
& 4x_1 + 2x_2 + 3x_3 + 2y_1 + 3y_2 = 220 \\
& x_i \geq 0, \quad \forall i = 1, \dots, 3 \\
& y_i \geq 0, \quad \forall j = 1, 2
\end{aligned}$$

In this example,  $\mathbf{c}^T = (8, 12, 10)$ ,  $\mathbf{f}^T = (15, 18)$  and  $\mathbf{b}^T = (300, 220)$ . In addition,

$$\mathbf{A} = \begin{bmatrix} 2 & 3 & 2 \\ 4 & 2 & 3 \end{bmatrix} \quad \mathbf{B} = \begin{bmatrix} 4 & 5 \\ 2 & 3 \end{bmatrix}$$

We first use Gurobi to identify its optimal solution.

```

import gurobipy as gp
from gurobipy import GRB

# Create a new model
env = gp.Env(empty=True)
env.setParam('OutputFlag', 0)
env.start()
model = gp.Model(env=env, name="original_problem")

# Decision variables

```



```

x1 = model.addVar(vtype=GRB.CONTINUOUS, name='x1')
x2 = model.addVar(vtype=GRB.CONTINUOUS, name='x2')
x3 = model.addVar(vtype=GRB.CONTINUOUS, name='x3')
y1 = model.addVar(vtype=GRB.CONTINUOUS, name='y1')
y2 = model.addVar(vtype=GRB.CONTINUOUS, name='y2')

# Objective function
model.setObjective(8*x1 + 12*x2 + 10*x3 + 15*y1 + 18*y2,
                  GRB.MINIMIZE)

# Constraints
model.addConstr(2*x1 + 3*x2 + 2*x3 + 4*y1 + 5*y2 == 300)
model.addConstr(4*x1 + 2*x2 + 3*x3 + 2*y1 + 3*y2 == 220)

# Optimize the model
model.optimize()

# Print the results
if model.status == GRB.OPTIMAL:
    print("Optimal solution found!")
    print(f'x1 = {x1.X:.2f}')
    print(f'x2 = {x2.X:.2f}')
    print(f'x3 = {x3.X:.2f}')
    print(f'y1 = {y1.X:.2f}')
    print(f'y2 = {y2.X:.2f}')
    print(f"Total cost: {model.objVal:.2f}")
else:
    print("No solution found.")

# Close the Gurobi environment
model.dispose()
env.dispose()

```

The optimal solution and objective value are as follows.

```

```{python}
Optimal solution found!
x1 = 14.29
x2 = 0.00
x3 = 0.00
y1 = 0.00

```

```

y2 = 54.29
Total cost: 1091.43
...

```

### 4.2.3 Benders decomposition

We first state the subproblem as follows:

$$\begin{aligned}
 (\text{SP}) \quad & \min. \quad 8x_1 + 12x_2 + 10x_3 \\
 & \text{s.t.} \quad 2x_1 + 3x_2 + 2x_3 = 300 - 4y_1 - 5y_2 \\
 & \quad \quad 4x_1 + 2x_2 + 3x_3 = 220 - 2y_1 - 3y_2 \\
 & \quad \quad x_i \geq 0, \quad \forall i = 1, \dots, 3
 \end{aligned}$$

We define two dual variables  $u_1$  and  $u_2$  to associate with the two constraints in the subproblem. The dual subproblem could then be stated as follows:

$$\begin{aligned}
 (\text{DSP}) \quad & \max. \quad (300 - 4y_1 - 5y_2)u_1 + (220 - 2y_1 - 3y_2)u_2 \\
 & \text{s.t.} \quad 2u_1 + 4u_2 \leq 8 \\
 & \quad \quad 3u_1 + 2u_2 \leq 12 \\
 & \quad \quad 2u_1 + 3u_2 \leq 10 \\
 & \quad \quad u_1, u_2 \text{ unrestricted}
 \end{aligned}$$

The *RBMP* can be stated as:

$$\begin{aligned}
 (\text{RBMP}) \quad & \min. \quad 15y_1 + 18y_2 + g \\
 & \text{s.t.} \quad y_1, y_2 \geq 0 \\
 & \quad \quad g \leq 0
 \end{aligned}$$

### 4.2.4 Solving the problem step by step

In this section, we will solve the linear program step by step using Gurobi. To this end, we first import the necessary libraries and create an environment `env`.

```

# output: false
import numpy as np
import gurobipy as gp
from gurobipy import GRB

env = gp.Env('benders')
env.setParam('OutputFlag', 0)

```

Next, we initialize several algorithm parameters, specifically, we use `lb` and `ub` to represent the lower and upper bounds of the solution. The `eps` is defined as a small number to decide whether the searching process should stop.

The remaining codes aim to create the restricted master Benders problem indicated by `rbmp`. Note that it only has the  $y$  and  $g$  variables and the objective function, there is no constraint added to the model yet.

```

# parameters
lb = -GRB.INFINITY
ub = GRB.INFINITY
eps = 1.0e-5

# create restricted Benders master problem
rbmp = gp.Model(env=env, name='RBMP')

# create decision variables
y1 = rbmp.addVar(vtype=GRB.CONTINUOUS, lb=0, name='y1')
y2 = rbmp.addVar(vtype=GRB.CONTINUOUS, lb=0, name='y2')
g = rbmp.addVar(vtype=GRB.CONTINUOUS, lb=0, name='g')

# create objective
rbmp.setObjective(15*y1 + 18*y2 + g, GRB.MINIMIZE)

```

We then define the model in Gurobi to solve the dual subproblem, represented by `dsp`. It consists of two decision variables `u1` and `u2`. The constraints are created in lines 12 - 14.

```

# create dual subproblem
dsp = gp.Model(env=env, name='DSP')

# create decision variables
u1 = dsp.addVar(vtype=GRB.CONTINUOUS, name='u1')
u2 = dsp.addVar(vtype=GRB.CONTINUOUS, name='u2')

```

```

# create objective function
dsp.setObjective(300*u1 + 220*u2)

# create constraints
dsp.addConstr(2*u1 + 4*u2 <= 8, name='c1')
dsp.addConstr(3*u1 + 2*u2 <= 12, name='c2')
dsp.addConstr(2*u1 + 3*u2 <= 10, name='c3')

dsp.update()

```

In the very first iteration, we solve the **RBMP**, as shown in the following code snippet.

```

rbmp.optimize()

if rbmp.status == GRB.OPTIMAL:
    print(f'optimal solution found!')

    y1_opt = y1.X
    y2_opt = y2.X
    g_opt = g.X
    lb = np.max([lb, rbmp.objVal])

    print(f'optimal obj: {rbmp.objVal:.2f}')
    print(f'y1 = {y1_opt:.2f}')
    print(f'y2 = {y2_opt:.2f}')
    print(f'g = {g_opt:.2f}')
    print(f'lb={lb}, ub={ub}')
elif rbmp.status == GRB.INFEASIBLE:
    print(f'original problem is infeasible!')

```

Now we have obtained an optimal solution  $(\bar{y}_1, \bar{y}_2, \bar{g}) = (0, 0, 0)$ , which also provides a new lower bound to our problem. We now feed the values of  $\bar{y}_1$  and  $\bar{y}_2$  into the Benders subproblem (**SP**):

```

dsp.setObjective((300-4*y1_opt-5*y2_opt)*u1 +
                (220-2*y1_opt-3*y2_opt)*u2,
                GRB.MAXIMIZE)

dsp.update()
dsp.optimize()

if dsp.status == GRB.OPTIMAL:

```

```

u1_opt = u1.X
u2_opt = u2.X

print(f'optimal obj = {dsp.objVal:.2f}')
print(f'u1 = {u1_opt:.2f}')
print(f'u2 = {u2_opt:.2f}')
ub = np.min([ub, 15*y1_opt + 18*y2_opt + dsp.objVal])
print(f'lb={lb}, ub={ub}')
elif dsp.Status == GRB.UNBOUNDED:
    # add feasibility cut
    pass
else:
    pass

```

We see that the dual subproblem has an optimal solution. Note that in line 15, the upper bound of the problem is updated.

Since the optimal objective value of the subproblem turns out to be 1200 and is greater than  $\bar{g} = 0$ , which implies that an optimality cut is needed to make sure that the variable  $g$  in the restricted Benders master problem reflects this newly obtained information from the subproblem.

```

rbmp.addConstr((300-4*y2-5*y2)*u1_opt
               + (220-2*y1-3*y2)*u2_opt <= g,
               name='c3')
rbmp.update()
rbmp.optimize()

if rbmp.status == GRB.OPTIMAL:
    print(f'optimal solution found!')

    y1_opt = y1.X
    y2_opt = y2.X
    g_opt = g.X
    lb = np.max([lb, rbmp.objVal])

    print(f'optimal obj: {rbmp.objVal:.2f}')
    print(f'y1 = {y1_opt:.2f}')
    print(f'y2 = {y2_opt:.2f}')
    print(f'g = {g_opt:.2f}')
    print(f'lb={lb}, ub={ub}')
elif rbmp.status == GRB.INFEASIBLE:

```

```
print(f'original problem is infeasible!')
```

Now we solve the subproblem again with the newly obtained solution  $(\bar{y}_1, \bar{y}_2, \bar{g}) = (0, 33.33, 0)$ .

```
dsp.setObjective((300 - 4*y1_opt - 5*y2_opt) * u1
                + (220 - 2*y1_opt - 3*y2_opt) * u2,
                GRB.MAXIMIZE)

dsp.update()
dsp.optimize()

if dsp.status == GRB.OPTIMAL:
    u1_opt = u1.X
    u2_opt = u2.X

    print(f'optimal obj = {dsp.objVal:.2f}')
    print(f'u1 = {u1_opt:.2f}')
    print(f'u2 = {u2_opt:.2f}')
    ub = np.min([ub, 15*y1_opt + 18*y2_opt + dsp.objVal])
    print(f'lb={lb}, ub={ub}')
elif dsp.status == GRB.UNBOUNDED:
    print(f'dual subproblem is unbounded!')
```

Since the optimal objective value of the subproblem, 533.33, is still bigger than  $\bar{g} = 0$ , an optimality cut is needed. In the below code snippet, we add the new cut and solve the restricted Benders master problem again.

```
rbmp.addConstr((300 - 4*y1 - 5*y2) * u1_opt + (220 - 2*y1 - 3*y2) * u2_opt <= g, name='c3')
rbmp.update()
rbmp.optimize()

if rbmp.status == GRB.OPTIMAL:
    print(f'optimal solution found!')

    y1_opt = y1.X
    y2_opt = y2.X
    g_opt = g.X
    lb = np.max([lb, rbmp.objVal])

    print(f'optimal obj: {rbmp.objVal:.2f}')
    print(f'y1 = {y1_opt:.2f}')
```

```

    print(f'y2 = {y2_opt:.2f}')
    print(f'g = {g_opt:.2f}')
    print(f'lb={lb}, ub={ub}')
elif rbmp.status == GRB.INFEASIBLE:
    print(f'original problem is infeasible!')

```

Note that a new lower bound is obtained after solving the master problem. Since there is still a large gap between the lower bound and upper bound, we continue solving the subproblem.

```

dsp.setObjective((300 - 4*y1_opt - 5*y2_opt) * u1 + (220 - 2*y1_opt - 3*y2_opt) * u2, GRB.
dsp.update()
dsp.optimize()

if dsp.status == GRB.OPTIMAL:
    u1_opt = u1.X
    u2_opt = u2.X

    print(f'optimal obj = {dsp.objVal:.2f}')
    print(f'u1 = {u1_opt:.2f}')
    print(f'u2 = {u2_opt:.2f}')
    ub = np.min([ub, 15*y1_opt + 18*y2_opt + dsp.objVal])
    print(f'lb={lb}, ub={ub}')
elif dsp.status == GRB.UNBOUNDED:
    print(f'dual subproblem is unbounded!')

```

Now the upper bound is reduced to 1133.33, but the subproblem optimal solution is still bigger than the value of  $\bar{g} = 0$ .

```

rbmp.addConstr((300 - 4*y1 - 5*y2) * u1_opt + (220 - 2*y1 - 3*y2) * u2_opt <= g, name='c3')
rbmp.update()
rbmp.optimize()

if rbmp.status == GRB.OPTIMAL:
    print(f'optimal solution found!')

    y1_opt = y1.X
    y2_opt = y2.X
    g_opt = g.X
    lb = np.max([lb, rbmp.objVal])

    print(f'optimal obj: {rbmp.objVal:.2f}')

```

```

        print(f'y1 = {y1_opt:.2f}')
        print(f'y2 = {y2_opt:.2f}')
        print(f'g = {g_opt:.2f}')
        print(f'lb={lb}, ub={ub}')
    elif rbmp.status == GRB.INFEASIBLE:
        print(f'original problem is infeasible!')

    dsp.setObjective((300 - 4*y1_opt - 5*y2_opt) * u1 + (220 - 2*y1_opt - 3*y2_opt) * u2, GRB.
    dsp.update()
    dsp.optimize()

    if dsp.status == GRB.OPTIMAL:
        u1_opt = u1.X
        u2_opt = u2.X

        print(f'optimal obj = {dsp.objVal:.2f}')
        print(f'u1 = {u1_opt:.2f}')
        print(f'u2 = {u2_opt:.2f}')
        ub = np.min([ub, 15*y1_opt + 18*y2_opt + dsp.objVal])
        print(f'lb={lb}, ub={ub}')
    elif dsp.status == GRB.UNBOUNDED:
        print(f'dual subproblem is unbounded!')

```

Now the gap between the lower bound and upper bound is reduced to 0, the problem completes.

#### 4.2.5 Putting it together

Certainly we don't want to manually control the interaction between the master problem and subproblem to find the optimal solution. Therefore, in this section, we will put every together to come up with a control flow to help us identify the optimal solution automatically.

```

import gurobipy as gp
from gurobipy import GRB
import numpy as np
from enum import Enum

class OptStatus(Enum):
    OPTIMAL = 0
    UNBOUNDED = 1

```



```
INFEASIBLE = 2
```

```
ERROR = 3
```

```
class MasterSolver:
```

```
    def __init__(self, env):
```

```
        self._model = gp.Model(env=env, name='RBMP')
```

```
        # create decision variables
```

```
        self._y1 = self._model.addVar(vtype=GRB.CONTINUOUS, lb=0, name='y1')
```

```
        self._y2 = self._model.addVar(vtype=GRB.CONTINUOUS, lb=0, name='y2')
```

```
        self._g = self._model.addVar(vtype=GRB.CONTINUOUS, lb=0, name='g')
```

```
        # create objective
```

```
        self._model.setObjective(15*self._y1 + 18*self._y2 + self._g, GRB.MINIMIZE)
```

```
        self._opt_obj = None
```

```
        self._opt_y1 = None
```

```
        self._opt_y2 = None
```

```
        self._opt_g = None
```

```
    def solve(self) -> OptStatus:
```

```
        print('-' * 50)
```

```
        print(f'Start solving master problem.')
```

```
        self._model.optimize()
```

```
        opt_status = None
```

```
        if self._model.status == GRB.OPTIMAL:
```

```
            opt_status = OptStatus.OPTIMAL
```

```
            self._opt_obj = self._model.objVal
```

```
            self._opt_y1 = self._y1.X
```

```
            self._opt_y2 = self._y2.X
```

```
            self._opt_g = self._g.X
```

```
            print(f'\tmaster problem is optimal.')
```

```
            print(f'\topt_obj={self._opt_obj:.2f}')
```

```
            print(f'\topt_y1={self._opt_y1:.2f}, opt_y2={self._opt_y2:.2f}, opt_g={self._opt_g:.2f}')
```

```
        elif self._model.status == GRB.INFEASIBLE:
```

```
            print(f'\tmaster problem is infeasible.')
```

```
            opt_status = OptStatus.INFEASIBLE
```

```
        else:
```

```
            print(f'\tmaster problem encountered error.')
```

```

        opt_status = OptStatus.ERROR

    print(f'Finish solving master problem.')
    print('-' * 50)
    return opt_status

def add_feasibility_cut(self, opt_u1, opt_u2) -> None:
    self._model.addConstr((300 - 4*self._y1 - 5*self._y2) * opt_u1 +
                          (220 - 2*self._y1 - 3*self._y2) * opt_u2 <= 0)
    print(f'Benders feasibility cut added!')

def add_optimality_cut(self, opt_u1, opt_u2) -> None:
    self._model.addConstr((300 - 4*self._y1 - 5*self._y2) * opt_u1 +
                          (220 - 2*self._y1 - 3*self._y2) * opt_u2 <= self._g)
    print(f'Benders optimality cut added!')

def clean_up(self):
    self._model.dispose()

@property
def opt_obj(self):
    return self._opt_obj

@property
def opt_y1(self):
    return self._opt_y1

@property
def opt_y2(self):
    return self._opt_y2

@property
def opt_g(self):
    return self._g

class DualSubprobSolver:

    def __init__(self, env):
        self._model = gp.Model(env=env, name='DSP')

        # create decision variables

```

```

self._u1 = self._model.addVar(vtype=GRB.CONTINUOUS, name='u1')
self._u2 = self._model.addVar(vtype=GRB.CONTINUOUS, name='u2')

# create constraints
self._model.addConstr(2*self._u1 + 4*self._u2 <= 8, name='c1')
self._model.addConstr(3*self._u1 + 2*self._u2 <= 12, name='c2')
self._model.addConstr(2*self._u1 + 3*self._u2 <= 10, name='c3')

self._model.setObjective(1, GRB.MAXIMIZE)
self._model.update()

self._opt_obj = None
self._opt_u1 = None
self._opt_u2 = None

def solve(self):
    print('-' * 50)
    print(f'Start solving dual subproblem.')
    self._model.optimize()

    status = None
    if self._model.status == GRB.OPTIMAL:
        self._opt_obj = self._model.objVal
        self._opt_u1 = self._u1.X
        self._opt_u2 = self._u2.X
        status = OptStatus.OPTIMAL
        print(f'\tdual subproblem is optimal.')
        print(f'\topt_obj={self._opt_obj:.2f}')
        print(f'\topt_y1={self._opt_u1:.2f}, opt_y2={self._opt_u2:.2f}')
    elif self._model.status == GRB.UNBOUNDED:
        status = OptStatus.UNBOUNDED
    else:
        status = OptStatus.ERROR

    print(f'Finish solving dual subproblem.')
    print('-' * 50)
    return status

def update_objective(self, opt_y1, opt_y2):
    self._model.setObjective((300-4*opt_y1-5*opt_y2)*self._u1 + (220-2*opt_y1-3*opt_y2)
    print(f'dual subproblem objective updated!')

```

```

def clean_up(self):
    self._model.dispose()

@property
def opt_obj(self):
    return self._opt_obj

@property
def opt_u1(self):
    return self._opt_u1

@property
def opt_u2(self):
    return self._opt_u2

class BendersDecomposition:

    def __init__(self, master_solver, dual_subprob_solver):
        self._master_solver = master_solver
        self._dual_subprob_solver = dual_subprob_solver

    def optimize(self) -> OptStatus:
        eps = 1.0e-5
        lb = -np.inf
        ub = np.inf

        while True:
            # solve master problem
            master_status = self._master_solver.solve()
            if master_status == OptStatus.INFEASIBLE:
                return OptStatus.INFEASIBLE

            # update lower bound
            lb = np.max([lb, self._master_solver.opt_obj])
            print(f'Bounds: lb={lb:.2f}, ub={ub:.2f}')

            opt_y1 = self._master_solver.opt_y1
            opt_y2 = self._master_solver.opt_y2

```

```

# solve subproblem
self._dual_subprob_solver.update_objective(opt_y1, opt_y2)
dsp_status = self._dual_subprob_solver.solve()

if dsp_status == OptStatus.OPTIMAL:
    # update upper bound
    opt_obj = self._dual_subprob_solver.opt_obj
    ub = np.min([ub, 15*opt_y1 + 18*opt_y2 + opt_obj])
    print(f'Bounds: lb={lb:.2f}, ub={ub:.2f}')

    if ub - lb <= eps:
        break

    opt_u1 = self._dual_subprob_solver.opt_u1
    opt_u2 = self._dual_subprob_solver.opt_u2
    self._master_solver.add_optimality_cut(opt_u1, opt_u2)
elif dsp_status == OptStatus.UNBOUNDED:
    opt_u1 = self._dual_subprob_solver.opt_u1
    opt_u2 = self._dual_subprob_solver.opt_u2
    self._master_solver.add_feasibility_cut(opt_u1, opt_u2)

env = gp.Env('benders')
env.setParam("OutputFlag",0)
master_solver = MasterSolver(env)
dual_subprob_solver = DualSubprobSolver(env)

benders_decomposition = BendersDecomposition(master_solver, dual_subprob_solver)
benders_decomposition.optimize()

```

```

Set parameter Username
Set parameter LogFile to value "benders"

```

```

-----
Start solving master problem.
    master problem is optimal.
    opt_obj=0.00
    opt_y1=0.00, opt_y2=0.00, opt_g=0.00
Finish solving master problem.

```

```

-----
Bounds: lb=0.00, ub=inf
dual subproblem objective updated!

```

```

-----
Start solving dual subproblem.
    dual subproblem is optimal.
    opt_obj=1200.00
    opt_y1=4.00, opt_y2=0.00
Finish solving dual subproblem.
-----

Bounds: lb=0.00, ub=1200.00
Benders optimality cut added!
-----

Start solving master problem.
    master problem is optimal.
    opt_obj=1080.00
    opt_y1=0.00, opt_y2=60.00, opt_g=0.00
Finish solving master problem.
-----

Bounds: lb=1080.00, ub=1200.00
dual subproblem objective updated!
-----

Start solving dual subproblem.
    dual subproblem is optimal.
    opt_obj=80.00
    opt_y1=0.00, opt_y2=2.00
Finish solving dual subproblem.
-----

Bounds: lb=1080.00, ub=1160.00
Benders optimality cut added!
-----

Start solving master problem.
    master problem is optimal.
    opt_obj=1091.43
    opt_y1=0.00, opt_y2=54.29, opt_g=114.29
Finish solving master problem.
-----

Bounds: lb=1091.43, ub=1160.00
dual subproblem objective updated!
-----

Start solving dual subproblem.
    dual subproblem is optimal.
    opt_obj=114.29
    opt_y1=0.00, opt_y2=2.00
Finish solving dual subproblem.
-----

```

Bounds: lb=1091.43, ub=1091.43

## 4.2.6 A generic solver

In this section, we will create a more generic Benders decomposition based solver for linear programming problems.

```
class GenericLpMasterSolver:

    def __init__(self, f: np.array, B: np.array, b: np.array):
        # save data
        self._f = f
        self._B = B
        self._b = b

        # env and model
        self._env = gp.Env('MasterEnv')
        # self._env.setParam("OutputFlag",0)
        self._model = gp.Model(env=self._env, name='MasterSolver')

        # create variables
        self._num_y_vars = len(f)
        self._y = self._model.addVars(self._num_y_vars, lb=0, vtype=GRB.CONTINUOUS, name='y')
        self._g = self._model.addVar(vtype=GRB.CONTINUOUS, lb=0, name='g')

        # create objective
        self._model.setObjective(gp.quicksum(self._f[i] * self._y.get(i)
  for i in range(self._num_y_vars)) + self._g,
                                GRB.MINIMIZE)

        self._model.update()

        self._opt_obj = None
        self._opt_obj_y = None
        self._opt_y = None
        self._opt_g = None

    def solve(self) -> OptStatus:
        print('-' * 50)
        print(f'Start solving master problem.')
        print(self._model.display())
        self._model.optimize()
```

```

opt_status = None
if self._model.status == GRB.OPTIMAL:
    opt_status = OptStatus.OPTIMAL
    self._opt_obj = self._model.objVal
    self._opt_y = {
        i: self._y.get(i).X
        for i in range(self._num_y_vars)
    }
    self._opt_g = self._g.X
    self._opt_obj_y = self._opt_obj - self._opt_g
    print(f'\tmaster problem is optimal.')
    print(f'\topt_obj={self._opt_obj:.2f}')
    print(f'\topt_g={self._opt_g:.2f}')
    # for i in range(self._num_y_vars):
    #     print(f'\topt_y[{i}]= {self._opt_y.get(i)}')
elif self._model.status == GRB.INFEASIBLE:
    print(f'\tmaster problem is infeasible.')
    opt_status = OptStatus.INFEASIBLE
else:
    print(f'\tmaster problem encountered error.')
    opt_status = OptStatus.ERROR

print(f'Finish solving master problem.')
print('-' * 50)
return opt_status

def add_feasibility_cut(self, opt_u: dict) -> None:
    constr_expr = [
        opt_u.get(u_idx) * (self._b[u_idx] - gp.quicksum(self._B[u_idx][j] * self._y.g
   for j in range(self._num_y_vars)))
        for u_idx in opt_u.keys()
    ]
    self._model.addConstr(gp.quicksum(constr_expr) <= 0)
    print(f'Benders feasibility cut added!')

def add_optimality_cut(self, opt_u: dict) -> None:
    constr_expr = [
        opt_u.get(u_idx) * (self._b[u_idx] - gp.quicksum(self._B[u_idx][j] * self._y.g
   for j in range(self._num_y_vars)))
        for u_idx in opt_u.keys()
    ]

```



```

        self._model.addConstr(gp.quicksum(constr_expr) <= self._g)
        self._model.update()
        print(self._model.display())
        print(f'Benders optimality cut added!')

    def clean_up(self):
        self._model.dispose()
        self._env.dispose()

    @property
    def f(self):
        return self._f

    @property
    def opt_obj(self):
        return self._opt_obj

    @property
    def opt_obj_y(self):
        return self._opt_obj_y

    @property
    def opt_y(self):
        return self._opt_y

    @property
    def opt_g(self):
        return self._g

```

```

class GenericLpSubprobSolver:

```

```

    def __init__(self, A: np.array, c: np.array, B: np.array, b: np.array):
        # save data
        self._A = A
        self._c = c
        self._b = b
        self._B = B

        # env and model
        self._env = gp.Env('SubprobEnv')
        self._env.setParam("OutputFlag",0)

```

```

self._model = gp.Model(env=self._env, name='SubprobSolver')

# create variables
self._num_vars = len(b)
self._u = self._model.addVars(self._num_vars, vtype=GRB.CONTINUOUS, name='u')

# create constraints
for c_idx in range(len(c)):
    self._model.addConstr(gp.quicksum(A[:,c_idx][i] * self._u.get(i)
                                     for i in range(len(b))) <= c[c_idx])

self._opt_obj = None
self._opt_u = None
self._extreme_ray = None

def solve(self):
    print('-' * 50)
    print(f'Start solving dual subproblem.')
    self._model.setParam(GRB.Param.DualReductions, 0)
    self._model.setParam(GRB.Param.InfUnbdInfo, 1)
    self._model.optimize()

    status = None
    if self._model.status == GRB.OPTIMAL:
        self._opt_obj = self._model.objVal
        self._opt_u = {
            i: self._u.get(i).X
            for i in range(self._num_vars)
        }
        status = OptStatus.OPTIMAL
        print(f'\tdual subproblem is optimal.')
        print(f'\topt_obj={self._opt_obj:.2f}')
        # for i in range(self._num_vars):
        #     print(f'\topt_u[{i}]= {self._opt_u.get(i)}')
    elif self._model.status == GRB.UNBOUNDED:
        status = OptStatus.UNBOUNDED
        self._extreme_ray = {
            i: self._u.get(i).UnbdRay
            for i in range(self._num_vars)
        }
        print(f'dual subproblem is unbounded')

```

```

        # for i in range(self._num_vars):
        #     print(f'\topt_u{i}={self._extreme_ray.get(i)}')
    else:
        status = OptStatus.ERROR

    print(f'Finish solving dual subproblem.')
    print('-' * 50)
    return status

def update_objective(self, opt_y: dict):
    obj_expr = [
        self._u.get(u_idx) * (self._b[u_idx] - sum(self._B[u_idx][j] * opt_y.get(j)
  for j in range(len(opt_y))))
        for u_idx in range(self._num_vars)
    ]
    self._model.setObjective(gp.quicksum(obj_expr), GRB.MAXIMIZE)
    print(f'dual subproblem objective updated!')

def clean_up(self):
    self._model.dispose()
    self._env.dispose()

@property
def opt_obj(self):
    return self._opt_obj

@property
def opt_u(self):
    return self._opt_u

@property
def extreme_ray(self):
    return self._extreme_ray

class GenericBendersSolver:

    def __init__(self, master_solver, dual_subprob_solver):
        self._master_solver = master_solver
        self._dual_subprob_solver = dual_subprob_solver

```

```

def optimize(self,) -> OptStatus:
    eps = 1.0e-5
    lb = -np.inf
    ub = np.inf

    while True:
        # solve master problem
        master_status = self._master_solver.solve()
        if master_status == OptStatus.INFEASIBLE:
            return OptStatus.INFEASIBLE

        # update lower bound
        lb = np.max([lb, self._master_solver.opt_obj])
        print(f'Bounds: lb={lb:.2f}, ub={ub:.2f}')

        opt_y = self._master_solver.opt_y

        # solve subproblem
        self._dual_subprob_solver.update_objective(opt_y)
        dsp_status = self._dual_subprob_solver.solve()

        if dsp_status == OptStatus.OPTIMAL:
            # update upper bound
            opt_obj = self._dual_subprob_solver.opt_obj
            opt_obj_y = self._master_solver.opt_obj_y
            ub = np.min([ub, opt_obj_y + opt_obj])
            print(f'Bounds: lb={lb:.2f}, ub={ub:.2f}')

            if ub - lb <= eps:
                break

            opt_u = self._dual_subprob_solver.opt_u
            self._master_solver.add_optimality_cut(opt_u)
        elif dsp_status == OptStatus.UNBOUNDED:
            extreme_ray = self._dual_subprob_solver.extreme_ray
            self._master_solver.add_feasibility_cut(extreme_ray)

import gurobipy as gp
from gurobipy import GRB
import numpy as np

```

```

c = np.array([8, 12, 10])
f = np.array([15, 18])
A = np.array([
    [2, 3, 2],
    [4, 2, 3]
])
B = np.array([
    [4, 5],
    [2, 3],
])
b = np.array([300, 220])

master_solver = GenericLpMasterSolver(f, B, b)
dual_subprob_solver = GenericLpSubprobSolver(A, c, B, b)

benders_solver = GenericBendersSolver(master_solver, dual_subprob_solver)
benders_solver.optimize()

```

```

Set parameter Username
Set parameter LogFile to value "MasterEnv"
Set parameter Username
Set parameter LogFile to value "SubprobEnv"
-----

```

Start solving master problem.

Minimize

15.0 y[0] + 18.0 y[1] + g

Subject To

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 0 rows, 3 columns and 0 nonzeros

Model fingerprint: 0xb00b2c2a

Coefficient statistics:

Matrix range [0e+00, 0e+00]

Objective range [1e+00, 2e+01]

Bounds range [0e+00, 0e+00]

RHS range [0e+00, 0e+00]

Presolve removed 0 rows and 3 columns

Presolve time: 0.00s

Presolve: All rows and columns removed

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	0.0000000e+00	0.0000000e+00	0.0000000e+00	0s

Solved in 0 iterations and 0.00 seconds (0.00 work units)

Optimal objective 0.000000000e+00

master problem is optimal.

opt\_obj=0.00

opt\_g=0.00

opt\_y0=0.0

opt\_y1=0.0

Finish solving master problem.

Bounds: lb=0.00, ub=inf

dual subproblem objective updated!

Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=1200.00

opt\_u0=4.0

opt\_u1=0.0

Finish solving dual subproblem.

Bounds: lb=0.00, ub=1200.00

Minimize

15.0 y[0] + 18.0 y[1] + g

Subject To

R0: -16.0 y[0] + -20.0 y[1] + -1.0 g <= -1200

None

Benders optimality cut added!

Start solving master problem.

Minimize

15.0 y[0] + 18.0 y[1] + g

Subject To

R0: -16.0 y[0] + -20.0 y[1] + -1.0 g <= -1200

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 1 rows, 3 columns and 3 nonzeros

Coefficient statistics:

Matrix range [1e+00, 2e+01]

Objective range [1e+00, 2e+01]

Bounds range [0e+00, 0e+00]

RHS range [1e+03, 1e+03]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	0.0000000e+00	1.500000e+02	0.000000e+00	0s
1	1.0800000e+03	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 1.080000000e+03

master problem is optimal.

opt\_obj=1080.00

opt\_g=0.00

opt\_y0=0.0

opt\_y1=60.0

Finish solving master problem.

-----  
Bounds: lb=1080.00, ub=1200.00

dual subproblem objective updated!

-----  
Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=80.00

opt\_u0=0.0

opt\_u1=2.0

Finish solving dual subproblem.

-----  
Bounds: lb=1080.00, ub=1160.00

Minimize

15.0 y[0] + 18.0 y[1] + g

Subject To

R0: -16.0 y[0] + -20.0 y[1] + -1.0 g <= -1200

R1: -4.0 y[0] + -6.0 y[1] + -1.0 g <= -440

None

Benders optimality cut added!

-----  
Start solving master problem.

Minimize

15.0 y[0] + 18.0 y[1] + g

Subject To

R0: -16.0 y[0] + -20.0 y[1] + -1.0 g <= -1200

R1: -4.0 y[0] + -6.0 y[1] + -1.0 g <= -440

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 2 rows, 3 columns and 6 nonzeros

Coefficient statistics:

Matrix range [1e+00, 2e+01]

Objective range [1e+00, 2e+01]

Bounds range [0e+00, 0e+00]

RHS range [4e+02, 1e+03]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	1.0800000e+03	4.000000e+01	0.000000e+00	0s
1	1.0914286e+03	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 1.091428571e+03

master problem is optimal.

opt\_obj=1091.43

opt\_g=114.29

opt\_y0=0.0

opt\_y1=54.285714285714285

Finish solving master problem.

-----  
Bounds: lb=1091.43, ub=1160.00

dual subproblem objective updated!

-----  
Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=114.29

opt\_u0=0.0

opt\_u1=2.0

Finish solving dual subproblem.

-----  
Bounds: lb=1091.43, ub=1091.43

```
import gurobipy as gp
from gurobipy import GRB
import numpy as np
```

```
c = np.array([1, 1, 1, 1, 1, 1])
```



```

f = np.array([1, 1, 1, 1])
A = np.array([
    [1, 1, 1, 1, 1, 1]
])
B = np.array([
    [1, 1, 1, 1]
])
b = np.array([1])

master_solver = GenericLpMasterSolver(f, B, b)
dual_subprob_solver = GenericLpSubprobSolver(A, c, B, b)

benders_solver = GenericBendersSolver(master_solver, dual_subprob_solver)
benders_solver.optimize()

```

```

Set parameter Username
Set parameter LogFile to value "MasterEnv"
Set parameter Username
Set parameter LogFile to value "SubprobEnv"
-----

```

Start solving master problem.

Minimize

$y[0] + y[1] + y[2] + y[3] + g$

Subject To

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 0 rows, 5 columns and 0 nonzeros

Model fingerprint: 0xbadf3d1d

Coefficient statistics:

Matrix range [0e+00, 0e+00]

Objective range [1e+00, 1e+00]

Bounds range [0e+00, 0e+00]

RHS range [0e+00, 0e+00]

Presolve removed 0 rows and 5 columns

Presolve time: 0.00s

Presolve: All rows and columns removed

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	0.0000000e+00	0.000000e+00	0.000000e+00	0s

```

Solved in 0 iterations and 0.00 seconds (0.00 work units)
Optimal objective  0.000000000e+00
  master problem is optimal.
  opt_obj=0.00
  opt_g=0.00
  opt_y0=0.0
  opt_y1=0.0
  opt_y2=0.0
  opt_y3=0.0
Finish solving master problem.
-----
Bounds: lb=0.00, ub=inf
dual subproblem objective updated!
-----
Start solving dual subproblem.
  dual subproblem is optimal.
  opt_obj=1.00
  opt_u0=1.0
Finish solving dual subproblem.
-----
Bounds: lb=0.00, ub=1.00
Minimize
  y[0] + y[1] + y[2] + y[3] + g
Subject To
  R0: -1.0 y[0] + -1.0 y[1] + -1.0 y[2] + -1.0 y[3] + -1.0 g <= -1
None
Benders optimality cut added!
-----
Start solving master problem.
Minimize
  y[0] + y[1] + y[2] + y[3] + g
Subject To
  R0: -1.0 y[0] + -1.0 y[1] + -1.0 y[2] + -1.0 y[3] + -1.0 g <= -1
None
Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1
Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 1 rows, 5 columns and 5 nonzeros
Coefficient statistics:
  Matrix range      [1e+00, 1e+00]

```

Objective range [1e+00, 1e+00]  
 Bounds range [0e+00, 0e+00]  
 RHS range [1e+00, 1e+00]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	0.0000000e+00	1.0000000e+00	0.0000000e+00	0s
1	1.0000000e+00	0.0000000e+00	0.0000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 1.000000000e+00

master problem is optimal.

opt\_obj=1.00

opt\_g=0.00

opt\_y0=1.0

opt\_y1=0.0

opt\_y2=0.0

opt\_y3=0.0

Finish solving master problem.

-----  
 Bounds: lb=1.00, ub=1.00

dual subproblem objective updated!

-----  
 Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=-0.00

opt\_u0=1.0

Finish solving dual subproblem.

-----  
 Bounds: lb=1.00, ub=1.00

```
import gurobipy as gp
from gurobipy import GRB
import numpy as np
import scipy.sparse as sp

class GurobiLpSolver:

    def __init__(self, c, f, A, B, b):
        self._env = gp.Env('GurobiEnv')
        self._model = gp.Model(env=self._env, name='GurobiLpSolver')

        # prepare data
        self._obj_coeff = np.concatenate((c, f))
```

```

        print(self._obj_coeff)
        self._constr_mat = np.concatenate((A, B), axis=1)
        print(self._constr_mat)
        self._rhs = b
        self._num_vars = len(self._obj_coeff)
        self._num_constrs = len(b)

        # create decision variables
        self._vars = self._model.addMVar(self._num_vars, vtype=GRB.CONTINUOUS, lb=0)

        # create constraints
        self._constrs = self._model.addConstr(self._constr_mat@self._vars == self._rhs)

        # create objective
        self._model.setObjective(self._obj_coeff @ self._vars, GRB.MINIMIZE)

    def optimize(self):
        self._model.update()
        print(self._model.display())
        self._model.optimize()
        pass

    def clean_up(self):
        pass

import gurobipy as gp
from gurobipy import GRB
import numpy as np

np.random.seed(142)
c = np.random.randint(2, 6, size=20)
f = np.random.randint(1, 15, size=10)
A = np.random.randint(2, 6, size=(20, 20))
B = np.random.randint(2, 26, size=(20, 10))
b = np.random.randint(20, 50, size=20)

model = GurobiLpSolver(c, f, A, B, b)
model.optimize()

```

Set parameter Username

Set parameter LogFile to value "GurobiEnv"

```
[ 3 3 5 5 2 4 3 2 3 3 4 2 5 5 2 5 4 4 5 5 3 6 8 12
 3 5 4 4 9 3]
[[ 2 4 3 5 5 2 5 4 5 3 3 4 2 2 2 2 3 2 3 3 11 11 25 20
 9 5 7 8 9 2]
[ 5 2 2 4 3 5 4 2 3 5 4 3 2 5 2 3 5 4 5 4 23 19 23 19
12 12 13 15 19 19]
[ 2 3 2 2 5 5 4 5 5 2 5 2 5 4 5 4 3 5 3 3 11 10 8 20
17 9 25 25 10 12]
[ 3 5 4 3 4 2 4 2 4 2 4 2 3 3 2 5 3 2 4 2 16 23 18 20
20 25 14 10 2 6]
[ 5 4 3 4 3 4 5 4 4 2 5 4 2 3 2 2 5 2 4 3 3 8 10 4
22 25 11 15 15 9]
[ 5 5 5 3 2 5 2 2 3 4 2 5 4 4 2 5 4 5 5 4 21 14 22 19
15 19 16 8 22 23]
[ 4 2 2 5 2 5 5 4 2 3 2 3 2 5 4 3 3 4 5 3 18 8 11 2
19 23 23 8 18 25]
[ 3 2 4 5 3 2 3 5 3 4 5 2 5 4 2 4 2 4 3 5 20 19 13 24
19 7 4 15 24 3]
[ 4 4 2 3 2 2 5 5 2 3 5 5 4 5 3 4 2 2 4 2 19 6 20 16
5 14 20 18 19 6]
[ 4 2 3 4 4 4 2 5 2 5 5 2 3 4 4 5 4 4 2 3 25 11 17 14
15 12 6 23 24 6]
[ 3 5 2 5 3 2 3 3 5 5 3 2 5 3 4 3 5 5 4 4 3 23 9 16
22 3 14 16 12 16]
[ 2 3 4 3 5 5 3 5 4 4 2 5 4 3 5 2 3 4 5 4 13 11 7 2
15 24 13 16 4 6]
[ 4 4 2 2 4 4 3 2 2 2 5 5 2 5 3 3 5 2 4 3 9 13 10 16
25 16 24 21 6 16]
[ 3 5 5 4 3 2 3 5 2 3 5 3 5 3 3 3 5 5 5 5 3 20 5 18
8 19 25 2 17 7]
[ 3 2 5 2 2 3 3 3 4 3 5 5 4 4 4 3 3 4 4 4 9 15 6 23
14 21 21 22 18 22]
[ 3 2 2 3 4 3 2 4 5 3 2 2 2 3 5 3 2 2 4 4 19 17 17 17
4 22 12 18 4 18]
[ 4 2 2 5 2 3 5 4 2 3 2 5 5 5 5 4 4 4 2 5 2 13 23 8
22 17 10 24 20 23]
[ 2 4 2 3 2 2 2 4 4 5 2 4 4 4 2 4 3 4 5 3 10 6 20 21
16 15 13 3 24 16]
[ 2 5 4 3 3 3 4 2 5 4 2 4 5 2 2 2 3 5 4 5 12 18 21 8
19 8 11 20 21 21]
[ 4 2 2 2 2 2 4 3 4 3 2 2 4 2 4 3 5 2 4 3 11 4 2 9
13 20 23 16 16 14]]
```

Minimize

$3.0 C_0 + 3.0 C_1 + 5.0 C_2 + 5.0 C_3 + 2.0 C_4 + 4.0 C_5 + 3.0 C_6 + 2.0 C_7 + 3.0 C_8$   
 $+ 3.0 C_9 + 4.0 C_{10} + 2.0 C_{11} + 5.0 C_{12} + 5.0 C_{13} + 2.0 C_{14} + 5.0 C_{15} + 4.0 C_{16} + 4.0 C_{17}$   
 $+ 5.0 C_{18} + 5.0 C_{19} + 3.0 C_{20} + 6.0 C_{21} + 8.0 C_{22} + 12.0 C_{23} + 3.0 C_{24} + 5.0 C_{25}$   
 $+ 4.0 C_{26} + 4.0 C_{27} + 9.0 C_{28} + 3.0 C_{29}$

Subject To

R0:  $2.0 C_0 + 4.0 C_1 + 3.0 C_2 + 5.0 C_3 + 5.0 C_4 + 2.0 C_5 + 5.0 C_6 + 4.0 C_7 + 5.0 C_8 +$   
 $3.0 C_9 + 3.0 C_{10} + 4.0 C_{11} + 2.0 C_{12} + 2.0 C_{13} + 2.0 C_{14} + 2.0 C_{15} + 3.0 C_{16} + 2.0 C_{17} +$   
 $3.0 C_{18} + 3.0 C_{19} + 11.0 C_{20} + 11.0 C_{21} + 25.0 C_{22} + 20.0 C_{23} + 9.0 C_{24} + 5.0 C_{25} + 7.0$   
 $C_{26} + 8.0 C_{27} + 9.0 C_{28} + 2.0 C_{29} = 21$

R1:  $5.0 C_0 + 2.0 C_1 + 2.0 C_2 + 4.0 C_3 + 3.0 C_4 + 5.0 C_5 + 4.0 C_6 + 2.0 C_7 + 3.0 C_8 +$   
 $5.0 C_9 + 4.0 C_{10} + 3.0 C_{11} + 2.0 C_{12} + 5.0 C_{13} + 2.0 C_{14} + 3.0 C_{15} + 5.0 C_{16} + 4.0 C_{17} +$   
 $5.0 C_{18} + 4.0 C_{19} + 23.0 C_{20} + 19.0 C_{21} + 23.0 C_{22} + 19.0 C_{23} + 12.0 C_{24} + 12.0 C_{25} +$   
 $13.0 C_{26} + 15.0 C_{27} + 19.0 C_{28} + 19.0 C_{29} = 26$

R2:  $2.0 C_0 + 3.0 C_1 + 2.0 C_2 + 2.0 C_3 + 5.0 C_4 + 5.0 C_5 + 4.0 C_6 + 5.0 C_7 + 5.0 C_8 +$   
 $2.0 C_9 + 5.0 C_{10} + 2.0 C_{11} + 5.0 C_{12} + 4.0 C_{13} + 5.0 C_{14} + 4.0 C_{15} + 3.0 C_{16} + 5.0 C_{17} +$   
 $3.0 C_{18} + 3.0 C_{19} + 11.0 C_{20} + 10.0 C_{21} + 8.0 C_{22} + 20.0 C_{23} + 17.0 C_{24} + 9.0 C_{25} + 25.0$   
 $C_{26} + 25.0 C_{27} + 10.0 C_{28} + 12.0 C_{29} = 38$

R3:  $3.0 C_0 + 5.0 C_1 + 4.0 C_2 + 3.0 C_3 + 4.0 C_4 + 2.0 C_5 + 4.0 C_6 + 2.0 C_7 + 4.0 C_8 +$   
 $2.0 C_9 + 4.0 C_{10} + 2.0 C_{11} + 3.0 C_{12} + 3.0 C_{13} + 2.0 C_{14} + 5.0 C_{15} + 3.0 C_{16} + 2.0 C_{17} +$   
 $4.0 C_{18} + 2.0 C_{19} + 16.0 C_{20} + 23.0 C_{21} + 18.0 C_{22} + 20.0 C_{23} + 20.0 C_{24} + 25.0 C_{25} +$   
 $14.0 C_{26} + 10.0 C_{27} + 2.0 C_{28} + 6.0 C_{29} = 42$

R4:  $5.0 C_0 + 4.0 C_1 + 3.0 C_2 + 4.0 C_3 + 3.0 C_4 + 4.0 C_5 + 5.0 C_6 + 4.0 C_7 + 4.0 C_8 +$   
 $2.0 C_9 + 5.0 C_{10} + 4.0 C_{11} + 2.0 C_{12} + 3.0 C_{13} + 2.0 C_{14} + 2.0 C_{15} + 5.0 C_{16} + 2.0 C_{17} +$   
 $4.0 C_{18} + 3.0 C_{19} + 3.0 C_{20} + 8.0 C_{21} + 10.0 C_{22} + 4.0 C_{23} + 22.0 C_{24} + 25.0 C_{25} + 11.0$   
 $C_{26} + 15.0 C_{27} + 15.0 C_{28} + 9.0 C_{29} = 35$

R5:  $5.0 C_0 + 5.0 C_1 + 5.0 C_2 + 3.0 C_3 + 2.0 C_4 + 5.0 C_5 + 2.0 C_6 + 2.0 C_7 + 3.0 C_8 +$   
 $4.0 C_9 + 2.0 C_{10} + 5.0 C_{11} + 4.0 C_{12} + 4.0 C_{13} + 2.0 C_{14} + 5.0 C_{15} + 4.0 C_{16} + 5.0 C_{17} +$   
 $5.0 C_{18} + 4.0 C_{19} + 21.0 C_{20} + 14.0 C_{21} + 22.0 C_{22} + 19.0 C_{23} + 15.0 C_{24} + 19.0 C_{25} +$   
 $16.0 C_{26} + 8.0 C_{27} + 22.0 C_{28} + 23.0 C_{29} = 37$

R6:  $4.0 C_0 + 2.0 C_1 + 2.0 C_2 + 5.0 C_3 + 2.0 C_4 + 5.0 C_5 + 5.0 C_6 + 4.0 C_7 + 2.0 C_8 +$   
 $3.0 C_9 + 2.0 C_{10} + 3.0 C_{11} + 2.0 C_{12} + 5.0 C_{13} + 4.0 C_{14} + 3.0 C_{15} + 3.0 C_{16} + 4.0 C_{17} +$   
 $5.0 C_{18} + 3.0 C_{19} + 18.0 C_{20} + 8.0 C_{21} + 11.0 C_{22} + 2.0 C_{23} + 19.0 C_{24} + 23.0 C_{25} + 23.0$   
 $C_{26} + 8.0 C_{27} + 18.0 C_{28} + 25.0 C_{29} = 28$

R7:  $3.0 C_0 + 2.0 C_1 + 4.0 C_2 + 5.0 C_3 + 3.0 C_4 + 2.0 C_5 + 3.0 C_6 + 5.0 C_7 + 3.0 C_8 +$   
 $4.0 C_9 + 5.0 C_{10} + 2.0 C_{11} + 5.0 C_{12} + 4.0 C_{13} + 2.0 C_{14} + 4.0 C_{15} + 2.0 C_{16} + 4.0 C_{17} +$   
 $3.0 C_{18} + 5.0 C_{19} + 20.0 C_{20} + 19.0 C_{21} + 13.0 C_{22} + 24.0 C_{23} + 19.0 C_{24} + 7.0 C_{25} + 4.0$   
 $C_{26} + 15.0 C_{27} + 24.0 C_{28} + 3.0 C_{29} = 22$

R8:  $4.0 C_0 + 4.0 C_1 + 2.0 C_2 + 3.0 C_3 + 2.0 C_4 + 2.0 C_5 + 5.0 C_6 + 5.0 C_7 + 2.0 C_8 +$   
 $3.0 C_9 + 5.0 C_{10} + 5.0 C_{11} + 4.0 C_{12} + 5.0 C_{13} + 3.0 C_{14} + 4.0 C_{15} + 2.0 C_{16} + 2.0 C_{17} +$   
 $4.0 C_{18} + 2.0 C_{19} + 19.0 C_{20} + 6.0 C_{21} + 20.0 C_{22} + 16.0 C_{23} + 5.0 C_{24} + 14.0 C_{25} + 20.0$   
 $C_{26} + 18.0 C_{27} + 19.0 C_{28} + 6.0 C_{29} = 39$

R9:  $4.0 C_0 + 2.0 C_1 + 3.0 C_2 + 4.0 C_3 + 4.0 C_4 + 4.0 C_5 + 2.0 C_6 + 5.0 C_7 + 2.0 C_8 +$

$5.0 C_9 + 5.0 C_{10} + 2.0 C_{11} + 3.0 C_{12} + 4.0 C_{13} + 4.0 C_{14} + 5.0 C_{15} + 4.0 C_{16} + 4.0 C_{17} + 2.0 C_{18} + 3.0 C_{19} + 25.0 C_{20} + 11.0 C_{21} + 17.0 C_{22} + 14.0 C_{23} + 15.0 C_{24} + 12.0 C_{25} + 6.0 C_{26} + 23.0 C_{27} + 24.0 C_{28} + 6.0 C_{29} = 33$

R10:  $3.0 C_0 + 5.0 C_1 + 2.0 C_2 + 5.0 C_3 + 3.0 C_4 + 2.0 C_5 + 3.0 C_6 + 3.0 C_7 + 5.0 C_8 + 5.0 C_9 + 3.0 C_{10} + 2.0 C_{11} + 5.0 C_{12} + 3.0 C_{13} + 4.0 C_{14} + 3.0 C_{15} + 5.0 C_{16} + 5.0 C_{17} + 4.0 C_{18} + 4.0 C_{19} + 3.0 C_{20} + 23.0 C_{21} + 9.0 C_{22} + 16.0 C_{23} + 22.0 C_{24} + 3.0 C_{25} + 14.0 C_{26} + 16.0 C_{27} + 12.0 C_{28} + 16.0 C_{29} = 28$

R11:  $2.0 C_0 + 3.0 C_1 + 4.0 C_2 + 3.0 C_3 + 5.0 C_4 + 5.0 C_5 + 3.0 C_6 + 5.0 C_7 + 4.0 C_8 + 4.0 C_9 + 2.0 C_{10} + 5.0 C_{11} + 4.0 C_{12} + 3.0 C_{13} + 5.0 C_{14} + 2.0 C_{15} + 3.0 C_{16} + 4.0 C_{17} + 5.0 C_{18} + 4.0 C_{19} + 13.0 C_{20} + 11.0 C_{21} + 7.0 C_{22} + 2.0 C_{23} + 15.0 C_{24} + 24.0 C_{25} + 13.0 C_{26} + 16.0 C_{27} + 4.0 C_{28} + 6.0 C_{29} = 38$

R12:  $4.0 C_0 + 4.0 C_1 + 2.0 C_2 + 2.0 C_3 + 4.0 C_4 + 4.0 C_5 + 3.0 C_6 + 2.0 C_7 + 2.0 C_8 + 2.0 C_9 + 5.0 C_{10} + 5.0 C_{11} + 2.0 C_{12} + 5.0 C_{13} + 3.0 C_{14} + 3.0 C_{15} + 5.0 C_{16} + 2.0 C_{17} + 4.0 C_{18} + 3.0 C_{19} + 9.0 C_{20} + 13.0 C_{21} + 10.0 C_{22} + 16.0 C_{23} + 25.0 C_{24} + 16.0 C_{25} + 24.0 C_{26} + 21.0 C_{27} + 6.0 C_{28} + 16.0 C_{29} = 47$

R13:  $3.0 C_0 + 5.0 C_1 + 5.0 C_2 + 4.0 C_3 + 3.0 C_4 + 2.0 C_5 + 3.0 C_6 + 5.0 C_7 + 2.0 C_8 + 3.0 C_9 + 5.0 C_{10} + 3.0 C_{11} + 5.0 C_{12} + 3.0 C_{13} + 3.0 C_{14} + 3.0 C_{15} + 5.0 C_{16} + 5.0 C_{17} + 5.0 C_{18} + 5.0 C_{19} + 3.0 C_{20} + 20.0 C_{21} + 5.0 C_{22} + 18.0 C_{23} + 8.0 C_{24} + 19.0 C_{25} + 25.0 C_{26} + 2.0 C_{27} + 17.0 C_{28} + 7.0 C_{29} = 28$

R14:  $3.0 C_0 + 2.0 C_1 + 5.0 C_2 + 2.0 C_3 + 2.0 C_4 + 3.0 C_5 + 3.0 C_6 + 3.0 C_7 + 4.0 C_8 + 3.0 C_9 + 5.0 C_{10} + 5.0 C_{11} + 4.0 C_{12} + 4.0 C_{13} + 4.0 C_{14} + 3.0 C_{15} + 3.0 C_{16} + 4.0 C_{17} + 4.0 C_{18} + 4.0 C_{19} + 9.0 C_{20} + 15.0 C_{21} + 6.0 C_{22} + 23.0 C_{23} + 14.0 C_{24} + 21.0 C_{25} + 21.0 C_{26} + 22.0 C_{27} + 18.0 C_{28} + 22.0 C_{29} = 45$

R15:  $3.0 C_0 + 2.0 C_1 + 2.0 C_2 + 3.0 C_3 + 4.0 C_4 + 3.0 C_5 + 2.0 C_6 + 4.0 C_7 + 5.0 C_8 + 3.0 C_9 + 2.0 C_{10} + 2.0 C_{11} + 2.0 C_{12} + 3.0 C_{13} + 5.0 C_{14} + 3.0 C_{15} + 2.0 C_{16} + 2.0 C_{17} + 4.0 C_{18} + 4.0 C_{19} + 19.0 C_{20} + 17.0 C_{21} + 17.0 C_{22} + 17.0 C_{23} + 4.0 C_{24} + 22.0 C_{25} + 12.0 C_{26} + 18.0 C_{27} + 4.0 C_{28} + 18.0 C_{29} = 34$

R16:  $4.0 C_0 + 2.0 C_1 + 2.0 C_2 + 5.0 C_3 + 2.0 C_4 + 3.0 C_5 + 5.0 C_6 + 4.0 C_7 + 2.0 C_8 + 3.0 C_9 + 2.0 C_{10} + 5.0 C_{11} + 5.0 C_{12} + 5.0 C_{13} + 5.0 C_{14} + 4.0 C_{15} + 4.0 C_{16} + 4.0 C_{17} + 2.0 C_{18} + 5.0 C_{19} + 2.0 C_{20} + 13.0 C_{21} + 23.0 C_{22} + 8.0 C_{23} + 22.0 C_{24} + 17.0 C_{25} + 10.0 C_{26} + 24.0 C_{27} + 20.0 C_{28} + 23.0 C_{29} = 46$

R17:  $2.0 C_0 + 4.0 C_1 + 2.0 C_2 + 3.0 C_3 + 2.0 C_4 + 2.0 C_5 + 2.0 C_6 + 4.0 C_7 + 4.0 C_8 + 5.0 C_9 + 2.0 C_{10} + 4.0 C_{11} + 4.0 C_{12} + 4.0 C_{13} + 2.0 C_{14} + 4.0 C_{15} + 3.0 C_{16} + 4.0 C_{17} + 5.0 C_{18} + 3.0 C_{19} + 10.0 C_{20} + 6.0 C_{21} + 20.0 C_{22} + 21.0 C_{23} + 16.0 C_{24} + 15.0 C_{25} + 13.0 C_{26} + 3.0 C_{27} + 24.0 C_{28} + 16.0 C_{29} = 35$

R18:  $2.0 C_0 + 5.0 C_1 + 4.0 C_2 + 3.0 C_3 + 3.0 C_4 + 3.0 C_5 + 4.0 C_6 + 2.0 C_7 + 5.0 C_8 + 4.0 C_9 + 2.0 C_{10} + 4.0 C_{11} + 5.0 C_{12} + 2.0 C_{13} + 2.0 C_{14} + 2.0 C_{15} + 3.0 C_{16} + 5.0 C_{17} + 4.0 C_{18} + 5.0 C_{19} + 12.0 C_{20} + 18.0 C_{21} + 21.0 C_{22} + 8.0 C_{23} + 19.0 C_{24} + 8.0 C_{25} + 11.0 C_{26} + 20.0 C_{27} + 21.0 C_{28} + 21.0 C_{29} = 46$

R19:  $4.0 C_0 + 2.0 C_1 + 2.0 C_2 + 2.0 C_3 + 2.0 C_4 + 2.0 C_5 + 4.0 C_6 + 3.0 C_7 + 4.0 C_8 + 3.0 C_9 + 2.0 C_{10} + 2.0 C_{11} + 4.0 C_{12} + 2.0 C_{13} + 4.0 C_{14} + 3.0 C_{15} + 5.0 C_{16} + 2.0 C_{17} + 4.0 C_{18} + 3.0 C_{19} + 11.0 C_{20} + 4.0 C_{21} + 2.0 C_{22} + 9.0 C_{23} + 13.0 C_{24} + 20.0 C_{25} + 23.0 C_{26} + 16.0 C_{27} + 16.0 C_{28} + 14.0 C_{29} = 32$

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 20 rows, 30 columns and 600 nonzeros

Model fingerprint: 0x05cb70d4

Coefficient statistics:

Matrix range [2e+00, 2e+01]

Objective range [2e+00, 1e+01]

Bounds range [0e+00, 0e+00]

RHS range [2e+01, 5e+01]

Presolve time: 0.00s

Presolved: 20 rows, 30 columns, 600 nonzeros

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	3.3913043e+00	5.119565e+01	0.000000e+00	0s

Solved in 13 iterations and 0.01 seconds (0.00 work units)

Infeasible model

```
import gurobipy as gp
from gurobipy import GRB
import numpy as np

np.random.seed(142)
c = np.random.randint(2, 6, size=20)
f = np.random.randint(1, 15, size=10)
A = np.random.randint(2, 6, size=(20, 20))
B = np.random.randint(2, 26, size=(20, 10))
b = np.random.randint(20, 50, size=20)

master_solver = GenericLpMasterSolver(f, B, b)
dual_subprob_solver = GenericLpSubprobSolver(A, c, B, b)

benders_solver = GenericBendersSolver(master_solver, dual_subprob_solver)
benders_solver.optimize()
```

Set parameter Username

Set parameter LogFile to value "MasterEnv"

Set parameter Username



Set parameter LogFile to value "SubprobEnv"

-----  
Start solving master problem.

Minimize

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]  
+ 9.0 y[8] + 3.0 y[9] + g

Subject To

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 0 rows, 11 columns and 0 nonzeros

Model fingerprint: 0xb01aa8a2

Coefficient statistics:

Matrix range [0e+00, 0e+00]

Objective range [1e+00, 1e+01]

Bounds range [0e+00, 0e+00]

RHS range [0e+00, 0e+00]

Presolve removed 0 rows and 11 columns

Presolve time: 0.00s

Presolve: All rows and columns removed

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	0.0000000e+00	0.000000e+00	0.000000e+00	0s

Solved in 0 iterations and 0.00 seconds (0.00 work units)

Optimal objective 0.000000000e+00

master problem is optimal.

opt\_obj=0.00

opt\_g=0.00

Finish solving master problem.

-----  
Bounds: lb=0.00, ub=inf

dual subproblem objective updated!

-----  
Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=28.16

Finish solving dual subproblem.

-----  
Bounds: lb=0.00, ub=28.16

Minimize

```

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
    <= -28.1562
None
Benders optimality cut added!
-----

Start solving master problem.
Minimize
3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
    <= -28.1562
None
Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1
Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 1 rows, 11 columns and 11 nonzeros
Coefficient statistics:
  Matrix range      [1e+00, 1e+01]
  Objective range   [1e+00, 1e+01]
  Bounds range      [0e+00, 0e+00]
  RHS range         [3e+01, 3e+01]
Iteration    Objective    Primal Inf.    Dual Inf.      Time
     0         0.0000000e+00    1.759766e+00    0.000000e+00     0s
     1         6.9664948e+00    0.000000e+00    0.000000e+00     0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)
Optimal objective 6.966494845e+00
  master problem is optimal.
  opt_obj=6.97
  opt_g=0.00
Finish solving master problem.
-----

Bounds: lb=6.97, ub=28.16
dual subproblem objective updated!
-----

```

```

Start solving dual subproblem.
    dual subproblem is optimal.
    opt_obj=11.82
Finish solving dual subproblem.

```

```

-----
Bounds: lb=6.97, ub=18.78

```

```

Minimize

```

```

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g

```

```

Subject To

```

```

R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
<= -28.1562

```

```

R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g
<= -16.4615

```

```

None

```

```

Benders optimality cut added!

```

```

-----
Start solving master problem.

```

```

Minimize

```

```

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g

```

```

Subject To

```

```

R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
<= -28.1562

```

```

R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g
<= -16.4615

```

```

None

```

```

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

```

```

CPU model: Apple M1

```

```

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

```

```

Optimize a model with 2 rows, 11 columns and 22 nonzeros

```

```

Coefficient statistics:

```

```

    Matrix range      [1e+00, 1e+01]
    Objective range   [1e+00, 1e+01]
    Bounds range      [0e+00, 0e+00]

```

RHS range		[2e+01, 3e+01]		
Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	6.9664948e+00	7.385755e-01	0.000000e+00	0s
1	7.9710765e+00	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 7.971076459e+00

master problem is optimal.

opt\_obj=7.97

opt\_g=0.00

Finish solving master problem.

Bounds: lb=7.97, ub=18.78

dual subproblem objective updated!

Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=14.74

Finish solving dual subproblem.

Bounds: lb=7.97, ub=18.78

Minimize

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]  
+ 9.0 y[8] + 3.0 y[9] + g

Subject To

R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +  
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g  
≤ -28.1562

R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +  
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]  
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g  
≤ -16.4615

R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +  
-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996  
y[9] + -1.0 g ≤ -25.5

None

Benders optimality cut added!

Start solving master problem.

Minimize

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]  
+ 9.0 y[8] + 3.0 y[9] + g

Subject To

R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +  
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g  
<= -28.1562

R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +  
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]  
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g  
<= -16.4615

R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +  
-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996  
y[9] + -1.0 g <= -25.5

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 3 rows, 11 columns and 33 nonzeros

Coefficient statistics:

Matrix range [1e+00, 1e+01]  
Objective range [1e+00, 1e+01]  
Bounds range [0e+00, 0e+00]  
RHS range [2e+01, 3e+01]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	7.9710765e+00	9.214938e-01	0.000000e+00	0s
1	8.3297685e+00	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 8.329768548e+00

master problem is optimal.

opt\_obj=8.33

opt\_g=0.00

Finish solving master problem.

-----  
Bounds: lb=8.33, ub=18.78

dual subproblem objective updated!

-----  
Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=5.92

Finish solving dual subproblem.

-----  
Bounds: lb=8.33, ub=14.25

Minimize

```

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
    <= -28.1562
R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g
    <= -16.4615
R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +
-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996
    y[9] + -1.0 g <= -25.5
R3: -3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5
    y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g <= -18.25
None
Benders optimality cut added!
-----

Start solving master problem.
Minimize
3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
    <= -28.1562
R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g
    <= -16.4615
R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +
-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996
    y[9] + -1.0 g <= -25.5
R3: -3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5
    y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g <= -18.25
None
Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1
Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 4 rows, 11 columns and 44 nonzeros
Coefficient statistics:

```

Matrix range [1e+00, 1e+01]  
 Objective range [1e+00, 1e+01]  
 Bounds range [0e+00, 0e+00]  
 RHS range [2e+01, 3e+01]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	8.3297685e+00	3.701343e-01	0.000000e+00	0s
1	8.9196232e+00	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 8.919623169e+00

master problem is optimal.

opt\_obj=8.92

opt\_g=0.00

Finish solving master problem.

-----  
 Bounds: lb=8.92, ub=14.25

dual subproblem objective updated!

-----  
 Start solving dual subproblem.

dual subproblem is optimal.

opt\_obj=6.12

Finish solving dual subproblem.

-----  
 Bounds: lb=8.92, ub=14.25

Minimize

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]  
 + 9.0 y[8] + 3.0 y[9] + g

Subject To

R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +  
 -11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g  
 <= -28.1562

R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +  
 -7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]  
 + -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g  
 <= -16.4615

R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +  
 -12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996  
 y[9] + -1.0 g <= -25.5

R3: -3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5  
 y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g <= -18.25

R4: -0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] +  
 -6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] +  
 -9.200000000000001 y[9] + -1.0 g <= -18.4

None

Benders optimality cut added!

-----  
Start solving master problem.

Minimize

3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]  
+ 9.0 y[8] + 3.0 y[9] + g

Subject To

R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +  
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g  
    <= -28.1562

R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +  
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]  
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g  
    <= -16.4615

R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +  
-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996  
    y[9] + -1.0 g <= -25.5

R3: -3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5  
    y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g <= -18.25

R4: -0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] +  
-6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] +  
    -9.200000000000001 y[9] + -1.0 g <= -18.4

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 5 rows, 11 columns and 55 nonzeros

Coefficient statistics:

Matrix range [8e-01, 1e+01]

Objective range [1e+00, 1e+01]

Bounds range [0e+00, 0e+00]

RHS range [2e+01, 3e+01]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	8.9196232e+00	3.825374e-01	0.000000e+00	0s
1	9.5016530e+00	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 9.501652960e+00

master problem is optimal.

opt\_obj=9.50



```

    opt_g=0.00
Finish solving master problem.
-----
Bounds: lb=9.50, ub=14.25
dual subproblem objective updated!
-----
Start solving dual subproblem.
    dual subproblem is optimal.
    opt_obj=2.23
Finish solving dual subproblem.
-----
Bounds: lb=9.50, ub=11.73
Minimize
3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
    <= -28.1562
R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g
    <= -16.4615
R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +
-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996
    y[9] + -1.0 g <= -25.5
R3: -3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5
    y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g <= -18.25
R4: -0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] +
-6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] +
    -9.200000000000001 y[9] + -1.0 g <= -18.4
R5: -7.6000000000000005 y[0] + -2.4000000000000004 y[1] + -8.0 y[2] + -6.4 y[3] + -2.0
y[4] + -5.6000000000000005 y[5] + -8.0 y[6] + -7.2 y[7] + -7.6000000000000005 y[8] +
    -2.4000000000000004 y[9] + -1.0 g <= -15.6
None
Benders optimality cut added!
-----
Start solving master problem.
Minimize
3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +

```

-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g  
 <= -28.1562

R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +  
 -7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]  
 + -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g  
 <= -16.4615

R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +  
 -12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996  
 y[9] + -1.0 g <= -25.5

R3: -3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5  
 y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g <= -18.25

R4: -0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] +  
 -6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] +  
 -9.200000000000001 y[9] + -1.0 g <= -18.4

R5: -7.6000000000000005 y[0] + -2.4000000000000004 y[1] + -8.0 y[2] + -6.4 y[3] + -2.0  
 y[4] + -5.6000000000000005 y[5] + -8.0 y[6] + -7.2 y[7] + -7.6000000000000005 y[8] +  
 -2.4000000000000004 y[9] + -1.0 g <= -15.6

None

Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 6 rows, 11 columns and 66 nonzeros

Coefficient statistics:

Matrix range [8e-01, 1e+01]  
 Objective range [1e+00, 1e+01]  
 Bounds range [0e+00, 0e+00]  
 RHS range [2e+01, 3e+01]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	9.5016530e+00	2.782364e-01	0.000000e+00	0s
1	9.6700817e+00	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.01 seconds (0.00 work units)

Optimal objective 9.670081743e+00

master problem is optimal.

opt\_obj=9.67

opt\_g=0.00

Finish solving master problem.

-----  
 Bounds: lb=9.67, ub=11.73

dual subproblem objective updated!  
 -----

Start solving dual subproblem.  
dual subproblem is optimal.  
opt\_obj=2.23  
Finish solving dual subproblem.

-----  
Bounds: lb=9.67, ub=11.73

Minimize

$3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7] + 9.0 y[8] + 3.0 y[9] + g$

Subject To

R0:  $-8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] + -11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g \leq -28.1562$

R1:  $-8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] + -7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6] + -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g \leq -16.4615$

R2:  $-10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] + -12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996 y[9] + -1.0 g \leq -25.5$

R3:  $-3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5 y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g \leq -18.25$

R4:  $-0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] + -6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] + -9.200000000000001 y[9] + -1.0 g \leq -18.4$

R5:  $-7.6000000000000005 y[0] + -2.4000000000000004 y[1] + -8.0 y[2] + -6.4 y[3] + -2.0 y[4] + -5.6000000000000005 y[5] + -8.0 y[6] + -7.2 y[7] + -7.6000000000000005 y[8] + -2.4000000000000004 y[9] + -1.0 g \leq -15.6$

R6:  $-5.0 y[0] + -3.0 y[1] + -10.0 y[2] + -10.5 y[3] + -8.0 y[4] + -7.5 y[5] + -6.5 y[6] + -1.5 y[7] + -12.0 y[8] + -8.0 y[9] + -1.0 g \leq -17.5$

None

Benders optimality cut added!

-----  
Start solving master problem.

Minimize

$3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7] + 9.0 y[8] + 3.0 y[9] + g$

Subject To

R0:  $-8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] + -11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g \leq -28.1562$

R1:  $-8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] + -7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]$

$+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g$   
 $\leq -16.4615$   
R2:  $-10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +$   
 $-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.749999999999996$   
 $y[9] + -1.0 g \leq -25.5$   
R3:  $-3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5$   
 $y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g \leq -18.25$   
R4:  $-0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] +$   
 $-6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] +$   
 $-9.200000000000001 y[9] + -1.0 g \leq -18.4$   
R5:  $-7.6000000000000005 y[0] + -2.4000000000000004 y[1] + -8.0 y[2] + -6.4 y[3] + -2.0$   
 $y[4] + -5.6000000000000005 y[5] + -8.0 y[6] + -7.2 y[7] + -7.6000000000000005 y[8] +$   
 $-2.4000000000000004 y[9] + -1.0 g \leq -15.6$   
R6:  $-5.0 y[0] + -3.0 y[1] + -10.0 y[2] + -10.5 y[3] + -8.0 y[4] + -7.5 y[5] + -6.5 y[6]$   
 $+ -1.5 y[7] + -12.0 y[8] + -8.0 y[9] + -1.0 g \leq -17.5$   
None  
Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 7 rows, 11 columns and 77 nonzeros

Coefficient statistics:

Matrix range [8e-01, 1e+01]  
Objective range [1e+00, 1e+01]  
Bounds range [0e+00, 0e+00]  
RHS range [2e+01, 3e+01]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	9.6700817e+00	1.396581e-01	0.000000e+00	0s
1	9.8201416e+00	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 9.820141589e+00

master problem is optimal.

opt\_obj=9.82

opt\_g=0.00

Finish solving master problem.

-----  
Bounds: lb=9.82, ub=11.73

dual subproblem objective updated!

-----  
Start solving dual subproblem.

dual subproblem is optimal.

```

    opt_obj=1.40
Finish solving dual subproblem.
-----
Bounds: lb=9.82, ub=11.22
Minimize
3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
    <= -28.1562
R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +
-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]
+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g
    <= -16.4615
R2: -10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +
-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996
    y[9] + -1.0 g <= -25.5
R3: -3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5
    y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g <= -18.25
R4: -0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] +
-6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] +
    -9.200000000000001 y[9] + -1.0 g <= -18.4
R5: -7.6000000000000005 y[0] + -2.4000000000000004 y[1] + -8.0 y[2] + -6.4 y[3] + -2.0
    y[4] + -5.6000000000000005 y[5] + -8.0 y[6] + -7.2 y[7] + -7.6000000000000005 y[8] +
    -2.4000000000000004 y[9] + -1.0 g <= -15.6
R6: -5.0 y[0] + -3.0 y[1] + -10.0 y[2] + -10.5 y[3] + -8.0 y[4] + -7.5 y[5] + -6.5 y[6]
    + -1.5 y[7] + -12.0 y[8] + -8.0 y[9] + -1.0 g <= -17.5
R7: -1.2000000000000002 y[0] + -8.0 y[1] + -2.0 y[2] + -7.2 y[3] + -3.2 y[4] +
-7.6000000000000005 y[5] + -10.0 y[6] + -0.8 y[7] + -6.800000000000001 y[8] +
    -2.8000000000000003 y[9] + -1.0 g <= -11.2
None
Benders optimality cut added!
-----
Start solving master problem.
Minimize
3.0 y[0] + 6.0 y[1] + 8.0 y[2] + 12.0 y[3] + 3.0 y[4] + 5.0 y[5] + 4.0 y[6] + 4.0 y[7]
+ 9.0 y[8] + 3.0 y[9] + g
Subject To
R0: -8.5625 y[0] + -9.859375 y[1] + -9.5625 y[2] + -7.9375 y[3] + -12.125 y[4] +
-11.828125 y[5] + -11.21875 y[6] + -11.46875 y[7] + -10.21875 y[8] + -10.5 y[9] + -1.0 g
    <= -28.1562
R1: -8.76923076923077 y[0] + -6.153846153846153 y[1] + -8.307692307692307 y[2] +

```

$-7.692307692307692 y[3] + -2.0 y[4] + -8.923076923076923 y[5] + -6.769230769230769 y[6]$   
 $+ -8.307692307692307 y[7] + -4.153846153846153 y[8] + -6.461538461538462 y[9] + -1.0 g$   
 $\leq -16.4615$   
R2:  $-10.75 y[0] + -10.124999999999998 y[1] + -11.75 y[2] + -11.5 y[3] + -8.75 y[4] +$   
 $-12.874999999999998 y[5] + -10.25 y[6] + -8.25 y[7] + -5.5 y[8] + -3.7499999999999996$   
 $y[9] + -1.0 g \leq -25.5$   
R3:  $-3.0 y[0] + -8.75 y[1] + -2.75 y[2] + -10.25 y[3] + -5.5 y[4] + -10.0 y[5] + -11.5$   
 $y[6] + -6.0 y[7] + -8.75 y[8] + -7.25 y[9] + -1.0 g \leq -18.25$   
R4:  $-0.8 y[0] + -5.2 y[1] + -9.200000000000001 y[2] + -3.2 y[3] + -8.8 y[4] +$   
 $-6.800000000000001 y[5] + -4.0 y[6] + -9.600000000000001 y[7] + -8.0 y[8] +$   
 $-9.200000000000001 y[9] + -1.0 g \leq -18.4$   
R5:  $-7.6000000000000005 y[0] + -2.4000000000000004 y[1] + -8.0 y[2] + -6.4 y[3] + -2.0$   
 $y[4] + -5.6000000000000005 y[5] + -8.0 y[6] + -7.2 y[7] + -7.6000000000000005 y[8] +$   
 $-2.4000000000000004 y[9] + -1.0 g \leq -15.6$   
R6:  $-5.0 y[0] + -3.0 y[1] + -10.0 y[2] + -10.5 y[3] + -8.0 y[4] + -7.5 y[5] + -6.5 y[6]$   
 $+ -1.5 y[7] + -12.0 y[8] + -8.0 y[9] + -1.0 g \leq -17.5$   
R7:  $-1.2000000000000002 y[0] + -8.0 y[1] + -2.0 y[2] + -7.2 y[3] + -3.2 y[4] +$   
 $-7.6000000000000005 y[5] + -10.0 y[6] + -0.8 y[7] + -6.800000000000001 y[8] +$   
 $-2.8000000000000003 y[9] + -1.0 g \leq -11.2$   
None  
Gurobi Optimizer version 10.0.3 build v10.0.3rc0 (mac64[arm])

CPU model: Apple M1

Thread count: 8 physical cores, 8 logical processors, using up to 8 threads

Optimize a model with 8 rows, 11 columns and 88 nonzeros

Coefficient statistics:

Matrix range [8e-01, 1e+01]  
Objective range [1e+00, 1e+01]  
Bounds range [0e+00, 0e+00]  
RHS range [1e+01, 3e+01]

Iteration	Objective	Primal Inf.	Dual Inf.	Time
0	9.8201416e+00	8.763627e-02	0.000000e+00	0s
1	9.8617265e+00	0.000000e+00	0.000000e+00	0s

Solved in 1 iterations and 0.00 seconds (0.00 work units)

Optimal objective 9.861726459e+00

master problem is optimal.

opt\_obj=9.86

opt\_g=0.00

Finish solving master problem.

-----  
Bounds: lb=9.86, ub=11.22

```
dual subproblem objective updated!
```

```
-----  
Start solving dual subproblem.  
    dual subproblem is optimal.  
    opt_obj=0.00  
Finish solving dual subproblem.  
-----
```

```
Bounds: lb=9.86, ub=9.86
```

```
c
```

```
array([4, 5, 2, 4, 4, 5, 2, 2, 4, 3, 4, 4, 4, 4, 5, 2, 5, 5, 5, 4])
```

```
np.random.randint(1, 5, size=(2, 10))
```

```
array([[4, 1, 4, 2, 2, 3, 2, 1, 4, 4],  
       [4, 4, 2, 1, 1, 2, 2, 3, 4, 3]])
```

## 4.2.7 Implementation with callbacks

### 4.2.8 Implementation with SCIP

```
from pycscipopt import Model  
from pycscipopt import quicksum  
from pycscipopt import SCIP_PARAMSETTING  
  
# Create a model  
model = Model("simple_lp")  
  
# Define variables  
x1 = model.addVar(lb=0, vtype="C", name="x1")  
x2 = model.addVar(lb=0, vtype="C", name="x2")  
  
# Set objective function  
model.setObjective(x1 + x2, "maximize")  
  
# Add constraints  
# model.addCons(2 * x1 + x2 >= 1, "constraint1")  
model.addCons(x1 + x2 >= 2, "constraint2")
```

```

# Solve the model
model.setPresolve(SCIP_PARAMSETTING.OFF)
model.setHeuristics(SCIP_PARAMSETTING.OFF)
model.disablePropagation()
model.optimize()

# Print results
status = model.getStatus()
print(f'status = {status}')
if model.getStatus() == "optimal":
    print("Optimal solution found.")
    print(f"x1: {model.getVal(x1):.2f}")
    print(f"x2: {model.getVal(x2):.2f}")
    print(f"Objective value: {model.getObjVal():.2f}")
    hasRay = model.hasPrimaryRay()
    print(hasRay)
elif model.getStatus() == 'unbounded':
    hasRay = model.hasPrimalRay()
    print(f'hasRay={hasRay}')
    ray = model.getPrimalRay()
    print(f'ray={ray}')

else:
    print("Model could not be solved.")

status = unbounded
hasRay=True
ray=[0.5, 0.5]
presolving:
  (0.0s) symmetry computation started: requiring (bin +, int +, cont +), (fixed: bin -, int
  (0.0s) symmetry computation finished: 1 generators found (max: 1500, log10 of symmetry gr
  (0.0s) no symmetry on binary variables present.
presolving (0 rounds: 0 fast, 0 medium, 0 exhaustive):
  0 deleted vars, 0 deleted constraints, 0 added constraints, 0 tightened bounds, 0 added hol
  0 implications, 0 cliques
presolved problem has 2 variables (0 bin, 0 int, 0 impl, 2 cont) and 2 constraints
  2 constraints of type <linear>
Presolving Time: 0.00

time | node | left | LP iter|LP it/n|mem/heur|mdpt |vars |cons |rows |cuts |sepa|confs|str
* 0.0s|    1 |    0 |    2 |    - |    LP |    0 |    2 |    2 |    2 |    1 |    0 |    0 |

```



SCIP Status : problem is solved [unbounded]  
Solving Time (sec) : 0.00  
Solving Nodes : 1  
Primal Bound : +1.000000000000000e+20 (1 solutions)  
Dual Bound : +1.000000000000000e+20  
Gap : 0.00 %

## Testing

Knuth, Donald E. 1984. "Literate Programming." *Comput. J.* 27 (2): 97–111. <https://doi.org/10.1093/comjnl/27.2.97>.