

Code Style

General concepts

Explicit code

While any kind of black magic is possible with Python, the most explicit and straightforward manner is preferred.

Bad

```
def make_complex(*args):
    x, y = args
    return dict(**locals())
```

Good

```
def make_complex(x, y):
    return {'x': x, 'y': y}
```

In the good code above, `x` and `y` are explicitly received from the caller, and an explicit dictionary is returned. The developer using this function knows exactly what to do by reading the first and last lines, which is not the case with the bad example.

One statement per line

While some compound statements such as list comprehensions are allowed and appreciated for their brevity and their expressiveness, it is bad practice to have two disjointed statements on the same line of code.

Bad

```
print('one'); print('two')

if x == 1: print('one')

if <complex comparison> and <other complex comparison>:
    # do something
```

Good

```
print('one')
print('two')

if x == 1:
    print('one')

cond1 = <complex comparison>
cond2 = <other complex comparison>
if cond1 and cond2:
    # do something
```

Function arguments

Arguments can be passed to functions in four different ways.

1. **Positional arguments** are mandatory and have no default values. They are the simplest form of arguments and they can be used for the few function arguments that are fully part of the function's meaning and their order is natural. For instance, in `send(message, recipient)` or `point(x, y)` the user of the function has no difficulty remembering that those two functions require two arguments, and in which order.

In those two cases, it is possible to use argument names when calling the functions and, doing so, it is possible to switch the order of arguments, calling for instance `send(recipient='World', message='Hello')` and `point(y=2, x=1)` but this reduces readability and is unnecessarily verbose, compared to the more straightforward calls to `send('Hello', 'World')` and `point(1, 2)`.

2. **Keyword arguments** are not mandatory and have default values. They are often used for optional parameters sent to the function. When a function has more than two or three positional parameters, its signature is more difficult to remember and using keyword arguments with default values is helpful. For instance, a more complete `send` function could be defined as `send(message, to, cc=None, bcc=None)`. Here `cc` and `bcc` are optional, and evaluate to `None` when they are not passed another value.

Calling a function with keyword arguments can be done in multiple ways in Python; for example, it is possible to follow the order of arguments in the definition without explicitly naming the arguments, like in `send('Hello', 'World', 'Cthulhu', 'God')`, sending a blind carbon copy to God. It would also be possible to name arguments in another order, like in `send('Hello again', 'World', bcc='God', cc='Cthulhu')`. Those two possibilities are better avoided without any strong reason to not follow the syntax that is the closest to the function definition: `send('Hello', 'World', cc='Cthulhu', bcc='God')`.

As a side note, following the [YAGNI](#) principle, it is often harder to remove an optional argument (and its logic inside the function) that was added “just in case” and is seemingly never used, than to add a new optional argument and its logic when needed.

3. The **arbitrary argument list** is the third way to pass arguments to a function. If the function intention is better expressed by a signature with an extensible number of positional arguments, it can be defined with the `*args` constructs. In the function body, `args` will be a tuple of all the remaining positional arguments. For example, `send(message, *args)` can be called with each recipient as an argument: `send('Hello', 'God', 'Mom', 'Cthulhu')`, and in the function body `args` will be equal to `('God', 'Mom', 'Cthulhu')`.

However, this construct has some drawbacks and should be used with caution. If a function receives a list of arguments of the same nature, it is often more clear to define it as a function of one argument, that argument being a list or any sequence. Here, if `send` has multiple recipients, it is better to define it explicitly: `send(message, recipients)` and call it with `send('Hello', ['God', 'Mom', 'Cthulhu'])`. This way, the user of the function can manipulate the recipient list as a list beforehand, and it opens the possibility to pass any sequence, including iterators, that cannot be unpacked as other sequences.

4. The **arbitrary keyword argument dictionary** is the last way to pass arguments to functions. If the function requires an undetermined series of named arguments, it is possible to use the `**kwargs` construct. In the function body, `kwargs` will be a dictionary of all the passed named arguments that have not been caught by other keyword arguments in the function signature.

The same caution as in the case of *arbitrary argument list* is necessary, for similar reasons: these powerful techniques are to be used when there is a proven necessity to use them, and they should not be used if the simpler and clearer construct is sufficient to express the function’s intention.

It is up to the programmer writing the function to determine which arguments are positional arguments and which are optional keyword arguments, and to decide whether to use the advanced techniques of arbitrary argument passing. If the advice above is followed wisely, it is possible and enjoyable to write Python functions that are:

- easy to read (the name and arguments need no explanations)
- easy to change (adding a new keyword argument does not break other parts of the code)

Avoid the magical wand

A powerful tool for hackers, Python comes with a very rich set of hooks and tools allowing you to do almost any kind of tricky tricks. For instance, it is possible to do each of the following:

- change how objects are created and instantiated
- change how the Python interpreter imports modules
- It is even possible (and recommended if needed) to embed C routines in Python.

However, all these options have many drawbacks and it is always better to use the most straightforward way to achieve your goal. The main drawback is that readability suffers greatly when using these constructs. Many code analysis tools, such as `pylint` or `pyflakes`, will be unable to parse this “magic” code.

We consider that a Python developer should know about these nearly infinite possibilities, because it instills confidence that no impassable problem will be on the way. However, knowing how and particularly when **not** to use them is very important.

Like a kung fu master, a Pythonista knows how to kill with a single finger, and never to actually do it.

We are all responsible users

As seen above, Python allows many tricks, and some of them are potentially dangerous. A good example is that any client code can override an object’s properties and methods: there is no “private” keyword in Python. This philosophy, very different from highly defensive languages like Java, which give a lot of mechanisms to prevent any misuse, is expressed by the saying: “We are all responsible users”.

This doesn’t mean that, for example, no properties are considered private, and that no proper encapsulation is possible in Python. Rather, instead of relying on concrete walls erected by the developers between their code and others’, the Python community prefers to rely on a set of conventions indicating that these elements should not be accessed directly.

The main convention for private properties and implementation details is to prefix all “internals” with an underscore. If the client code breaks this rule and accesses these marked elements, any misbehavior or problems encountered if the code is modified is the responsibility of the client code.

Using this convention generously is encouraged: any method or property that is not intended to be used by client code should be prefixed with an underscore. This will guarantee a better separation of duties and easier modification of existing code; it will always be possible to publicize a private property, but making a public property private might be a much harder operation.

Returning values

When a function grows in complexity, it is not uncommon to use multiple return statements inside the function’s body. However, in order to keep a clear intent and a sustainable readability level, it is preferable to avoid returning meaningful values from many output points in the body.

There are two main cases for returning values in a function: the result of the function return when it has been processed normally, and the error cases that indicate a wrong input parameter or any other reason for the function to not be able to complete its computation or task.

If you do not wish to raise exceptions for the second case, then returning a value, such as `None` or `False`, indicating that the

function could not perform correctly might be needed. In this case, it is better to return as early as the incorrect context has been detected. It will help to flatten the structure of the function: all the code after the return-because-of-error statement can assume the condition is met to further compute the function's main result. Having multiple such return statements is often necessary.

However, when a function has multiple main exit points for its normal course, it becomes difficult to debug the returned result, so it may be preferable to keep a single exit point. This will also help factoring out some code paths, and the multiple exit points are a probable indication that such a refactoring is needed.

```
def complex_function(a, b, c):
    if not a:
        return None # Raising an exception might be better
    if not b:
        return None # Raising an exception might be better
    # Some complex code trying to compute x from a, b and c
    # Resist temptation to return x if succeeded
    if not x:
        # Some Plan-B computation of x
    return x # One single exit point for the returned value x will help
        # when maintaining the code.
```

Conventions

Here are some conventions you should follow to make your code easier to read.

Check if a variable equals a constant

You don't need to explicitly compare a value to True, or None, or 0 – you can just add it to the if statement. See [Truth Value Testing](#) for a list of what is considered false.

Bad:

```
if attr == True:
    print('True!')

if attr == None:
    print('attr is None!')
```

Good:

```
# Just check the value
if attr:
    print('attr is truthy!')

# or check for the opposite
if not attr:
    print('attr is falsey!')

# or, since None is considered false, explicitly check for it
if attr is None:
    print('attr is None!')
```

Access a Dictionary Element

Don't use the `dict.has_key()` method. Instead, use `x in d` syntax, or pass a default argument to `dict.get()`.

Bad:

```
d = {'hello': 'world'}
if d.has_key('hello'):
    print(d['hello']) # prints 'world'
else:
    print('default_value')
```

Good:

```
d = {'hello': 'world'}

print(d.get('hello', 'default_value')) # prints 'world'
print(d.get('thingy', 'default_value')) # prints 'default_value'

# Or:
if 'hello' in d:
    print(d['hello'])
```

Short Ways to Manipulate Lists

[List comprehensions](#) provides a powerful, concise way to work with lists.

[Generator expressions](#) follows almost the same syntax as list comprehensions but return a generator instead of a list.

Creating a new list requires more work and uses more memory. If you are just going to loop through the new list, prefer using an iterator instead.

Bad:

```
# needlessly allocates a list of all (gpa, name) entires in memory
valedictorian = max([(student.gpa, student.name) for student in graduates])
```

Good:

```
valedictorian = max((student.gpa, student.name) for student in graduates)
```

Use list comprehensions when you really need to create a second list, for example if you need to use the result multiple times.

If your logic is too complicated for a short list comprehension or generator expression, consider using a generator function instead of returning a list.

Good:

```
def make_batches(items, batch_size):
    """
    >>> list(make_batches([1, 2, 3, 4, 5], batch_size=3))
    [[1, 2, 3], [4, 5]]
    """
    current_batch = []
    for item in items:
        current_batch.append(item)
        if len(current_batch) == batch_size:
            yield current_batch
            current_batch = []
    yield current_batch
```

Never use a list comprehension just for its side effects.

Bad:

```
[print(x) for x in sequence]
```

Good:

```
for x in sequence:
    print(x)
```

Filtering a list

Bad:

Never remove items from a list while you are iterating through it.

```
# Filter elements greater than 4
a = [3, 4, 5]
for i in a:
    if i > 4:
        a.remove(i)
```

Don't make multiple passes through the list.

```
while i in a:
    a.remove(i)
```

Good:

Use a list comprehension or generator expression.

```
# comprehensions create a new list object
filtered_values = [value for value in sequence if value != x]

# generators don't create another list
filtered_values = (value for value in sequence if value != x)
```

Possible side effects of modifying the original list

Modifying the original list can be risky if there are other variables referencing it. But you can use *slice assignment* if you

really want to do that.

```
# replace the contents of the original list
sequence[:] = [value for value in sequence if value != x]
```

Modifying the values in a list

Bad:

Remember that assignment never creates a new object. If two or more variables refer to the same list, changing one of them changes them all.

```
# Add three to all list members.
a = [3, 4, 5]
b = a                # a and b refer to the same list object

for i in range(len(a)):
    a[i] += 3         # b[i] also changes
```

Good:

It's safer to create a new list object and leave the original alone.

```
a = [3, 4, 5]
b = a

# assign the variable "a" to a new list without changing "b"
a = [i + 3 for i in a]
```

Use `enumerate()` keep a count of your place in the list.

```
a = [3, 4, 5]
for i, item in enumerate(a):
    print(i, item)
# prints
# 0 3
# 1 4
# 2 5
```

The `enumerate()` function has better readability than handling a counter manually. Moreover, it is better optimized for iterators.

Read From a File

Use the `with open` syntax to read from files. This will automatically close files for you.

Bad:

```
f = open('file.txt')
a = f.read()
print(a)
f.close()
```

Good:

```
with open('file.txt') as f:
    for line in f:
        print(line)
```

The `with` statement is better because it will ensure you always close the file, even if an exception is raised inside the `with` block.

Line Continuations

When a logical line of code is longer than the accepted limit, you need to split it over multiple physical lines. The Python interpreter will join consecutive lines if the last character of the line is a backslash. This is helpful in some cases, but should usually be avoided because of its fragility: a white space added to the end of the line, after the backslash, will break the code and may have unexpected results.

A better solution is to use parentheses around your elements. Left with an unclosed parenthesis on an end-of-line, the Python interpreter will join the next line until the parentheses are closed. The same behavior holds for curly and square braces.

Bad:

```
my_very_big_string = """For a long time I used to go to bed early. Sometimes, \
when I had put out my candle, my eyes would close so quickly that I had not even \
time to say "I'm going to sleep."""
```

```
from some.deep.module.inside.a.module import a_nice_function, another_nice_function, \
yet_another_nice_function
```

Good:

```
my_very_big_string = (
    "For a long time I used to go to bed early. Sometimes, "
    "when I had put out my candle, my eyes would close so quickly "
    "that I had not even time to say "I'm going to sleep.""
)

from some.deep.module.inside.a.module import (
    a_nice_function, another_nice_function, yet_another_nice_function)
```

However, more often than not, having to split a long logical line is a sign that you are trying to do too many things at the same time, which may hinder readability.