

Code Style

General concepts

Explicit code

While any kind of black magic is possible with Python, the most explicit and straightforward manner is preferred.

Bad

```
def make_complex(*args):
    x, y = args
    return dict(**locals())
```

Good

```
def make_complex(x, y):
    return {'x': x, 'y': y}
```

In the good code above, `x` and `y` are explicitly received from the caller, and an explicit dictionary is returned. The developer using this function knows exactly what to do by reading the first and last lines, which is not the case with the bad example.

One statement per line

While some compound statements such as list comprehensions are allowed and appreciated for their brevity and their expressiveness, it is bad practice to have two disjointed statements on the same line of code.

Bad

```
print('one'); print('two')

if x == 1: print('one')

if <complex comparison> and <other complex comparison>:
    # do something
```

Good

```
print('one')
print('two')

if x == 1:
    print('one')

cond1 = <complex comparison>
cond2 = <other complex comparison>
if cond1 and cond2:
    # do something
```

Function arguments

Arguments can be passed to functions in four different ways.

1. **Positional arguments** are mandatory and have no default values. They are the simplest form of arguments and they can be used for the few function arguments that are fully part of the function's meaning and their order is natural. For instance, in `send(message, recipient)` or `point(x, y)` the user of the function has no difficulty remembering that those two functions require two arguments, and in which order.

In those two cases, it is possible to use argument names when calling the functions and, doing so, it is possible to switch the order of arguments, calling for instance `send(recipient='World', message='Hello')` and `point(y=2, x=1)` but this reduces readability and is unnecessarily verbose, compared to the more straightforward calls to `send('Hello', 'World')` and `point(1, 2)`.

2. **Keyword arguments** are not mandatory and have default values. They are often used for optional parameters sent to the function. When a function has more than two or three positional parameters, its signature is more difficult to remember and using keyword arguments with default values is helpful. For instance, a more complete `send` function could be defined as `send(message, to, cc=None, bcc=None)`. Here `cc` and `bcc` are optional, and evaluate to `None` when they are not passed another value.

Calling a function with keyword arguments can be done in multiple ways in Python; for example, it is possible to follow the order of arguments in the definition without explicitly naming the arguments, like in `send('Hello', 'World', 'Cthulhu', 'God')`, sending a blind carbon copy to God. It would also be possible to name arguments in another order, like in `send('Hello again', 'World', bcc='God', cc='Cthulhu')`. Those two possibilities are better avoided without any strong reason to not follow the syntax that is the closest to the function definition: `send('Hello', 'World', cc='Cthulhu', bcc='God')`.

function could not perform correctly might be needed. In this case, it is better to return as early as the incorrect context has been detected. It will help to flatten the structure of the function: all the code after the return-because-of-error statement can assume the condition is met to further compute the function's main result. Having multiple such return statements is often necessary.

However, when a function has multiple main exit points for its normal course, it becomes difficult to debug the returned result, so it may be preferable to keep a single exit point. This will also help factoring out some code paths, and the multiple exit points are a probable indication that such a refactoring is needed.

```
def complex_function(a, b, c):
    if not a:
        return None # Raising an exception might be better
    if not b:
        return None # Raising an exception might be better
    # Some complex code trying to compute x from a, b and c
    # Resist temptation to return x if succeeded
    if not x:
        # Some Plan-B computation of x
    return x # One single exit point for the returned value x will help
        # when maintaining the code.
```

Conventions

Here are some conventions you should follow to make your code easier to read.

Check if a variable equals a constant

You don't need to explicitly compare a value to True, or None, or 0 – you can just add it to the if statement. See [Truth Value Testing](#) for a list of what is considered false.

Bad:

```
if attr == True:
    print('True!')

if attr == None:
    print('attr is None!')
```

Good:

```
# Just check the value
if attr:
    print('attr is truthy!')

# or check for the opposite
if not attr:
    print('attr is falsey!')

# or, since None is considered false, explicitly check for it
if attr is None:
    print('attr is None!')
```

Access a Dictionary Element

Don't use the `dict.has_key()` method. Instead, use `x in d` syntax, or pass a default argument to `dict.get()`.

Bad:

```
d = {'hello': 'world'}
if d.has_key('hello'):
    print(d['hello']) # prints 'world'
else:
    print('default_value')
```

Good:

```
d = {'hello': 'world'}

print(d.get('hello', 'default_value')) # prints 'world'
print(d.get('thingy', 'default_value')) # prints 'default_value'

# Or:
if 'hello' in d:
    print(d['hello'])
```

Short Ways to Manipulate Lists


```
from some.deep.module.inside.a.module import a_nice_function, another_nice_function, \
yet_another_nice_function
```

Good:

```
my_very_big_string = (
    "For a long time I used to go to bed early. Sometimes, "
    "when I had put out my candle, my eyes would close so quickly "
    "that I had not even time to say "I'm going to sleep.""
)

from some.deep.module.inside.a.module import (
    a_nice_function, another_nice_function, yet_another_nice_function)
```

However, more often than not, having to split a long logical line is a sign that you are trying to do too many things at the same time, which may hinder readability.