

WBET API INTEGRATION

Customer Copy

Version 2.6

30 April 2026

Contents

Revision Control	3
Create Member	5
Get Balance	7
New Deposit.....	9
New Withdrawal	11
Check Tran Status	13
Launch Sports.....	15
Launch Sports New.....	17
Get Bet List.....	19
Mark Fetch Bet List.....	21
Get Parlay Bet List	23
Mark Fetch Parlay Bet List	25
Get Parlay Details	27
Get Result	29
Set Bet Limit.....	32
Set HDP Package	36
Mark Fetch Result	38
Get Bonus Result	40
Mark Fetch Bonus Result	43
Appendix.....	45

Revision Control

Version	Revised On	Status	Revised By	Revision Description
1.0	15 Jun 2020	Final	Jason Lam / Eddie Chan	First Release
1.2	24 Mar 2021	Final	Jason Lam / Eddie Chan	Updated new deposit & withdrawal Check transaction function
1.3	16 Mar 2022	Final	Jason Lam / Eddie Chan	Updated appendix
1.4	20 April 2022	Final	Jason Lam / Eddie Chan	Updated appendix
1.5	21 July 2022	Final	Jason Lam / Eddie Chan	Include match time in parlay detail
1.6	11 Aug 2022	Final	Jason Lam / Eddie Chan	Updated appendix
1.7	29 Aug 2022	Final	Jason Lam / Eddie Chan	Updated appendix
1.8	9 Feb 2023	Final	Jason Lam / Eddie Chan	Updated appendix
1.9	11 Feb 2023	Final	Jason Lam / Eddie Chan	Updated appendix
2.0	30 Jun 2023	Final	Jason Lam / Eddie Chan	Add Get Bonus Result & Mark Fetch Bonus Result functions
2.1	04 April 2024	Final	Jason Lam / Eddie Chan	Updated getresult & getbonusresult function
2.2	09 May 2024	Final	Jason Lam / Eddie Chan	Setbetlimit function Include new parameters
2.3	07 Aug 2024	Final	Jason Lam / Eddie Chan	Added sethdppackages function
2.4	08 Sep 2025	Final	Jason Lam / Eddie Chan	Updated appendix
2.5	21 Oct 2025	Final	Jason Lam / Eddie Chan	Updated appendix
2.6	30 Apr 2026	Final	Jason Lam / Eddie Chan	Add Launch Sports New functions

Primary Input

Document Use:	External
Document Title:	WBET API Integration

Intended Audience:	Project Leaders, Developers, Others
Document Overview/Structure:	This is WBET Service Web API defines general guide lines.
Production Deployment Date:	

Create Member

Method = POST

Format = JSON

Method Name = createmember

SAMPLE API URL = https:xxxx.com/api/createmember

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

*** If existing members don't have any activity within 3 months, that member will be deleted from WBET system.**

Operator can recreate same member using same account_id.

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No	*only allow 4 – 20 character *alphanumeric	* jacky863 - system will add a suffix after successful create the member jacky863_tas3
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
full_name	varchar	No	* player name	No		* Jacky Leong

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "account_id":"jason8788",
  "signature":"d990c05e65f2f181cbca2b1120e8ea73",
  "full_name":"jason",
  "operator_id":"indoindo",
  "ukey":"aabbcc1122"
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

Get Balance

Method = POST

Format = JSON

Method Name = getbalance

SAMPLE API URL = https:xxxxx.com/api/getbalance

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No		
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
value	Json Object	No	available_balance = money frozen_balance = money currency_code = varchar * available_balance = member's current balance available for betting in wbet * frozen_balance = member already bet but the result not yet settle. * both balance will return in 4 decimal if any * once the result of match was settle the frozen_balance will auto cleared and reflected to the available balance accordingly depends on member's winlose

Example:

Request:

```
{
  "account_id": "jason87",
  "signature": "c796f0cd1525564ffc99339670618842",
  "operator_id": "indoindo",
  "ukey": "aabbcc1122"
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK",
  "value": [
    {
      "available_balance": 100,
      "frozen_balance": 0,
      "currency_code": "IDR"
    }
  ]
}
```


New Deposit

Method = POST

Format = JSON

Method Name = newdeposit

SAMPLE API URL = https:xxxxx.com/api/newdeposit

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No		
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
amount	money	Yes				5.50
transaction_id	varchar	Yes	* transaction id is a global unique key between newdeposit and newwithdrawal function	No	*only allow 4 – 20 character *alphanumeric	Example: T0000001

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "account_id":"kennkennkennkennkenn",
  "signature":"e0d25ac0fec54dffffb73f56e0718b008",
  "operator_id":"mqmqmqmq",
  "ukey":"aabbcc1122",
  "amount":5000,
  "transaction_id":"T00000001"
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

New Withdrawal

Method = POST

Format = JSON

Method Name = newwithdrawal

SAMPLE API URL = https:xxxxx.com/api/newwithdrawal

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No		
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
amount	money	Yes				3.80
transaction_id	varchar	Yes	* transaction id is a global unique key between newdeposit and newwithdrawal function	No	*only allow 4 – 20 character *alphanumeric	Example: T0000002

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "account_id":"kennkennkennkennkenn",
  "signature":"e0d25ac0fec54dffffb73f56e0718b008",
  "operator_id":"mqmqmqmq",
  "ukey":"aabbcc1122",
  "amount":5000,
  "transaction_id":"T00000002"
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

Check Tran Status

Method = POST

Format = JSON

Method Name = checktranstatus

SAMPLE API URL = https:xxxxx.com/api/checktranstatus

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
transaction_id	varchar	Yes	* transaction id is a global unique key between newdeposit and newwithdrawal function	No	*only allow 4 – 20 character *alphanumeric	Example: T0000002 transaction_id pass in from newdeposit or newwithdrawal function.

* signature = md5(operator_id + ukey + ukey + secret_key)

Response:

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
success	int	Yes	1 = transaction_id processed successfully 0 = transaction_id failed to process

Example:

Request:

```
{
  "transaction_id": "Tt000002",
  "signature": "e4ce40d37e1e61a67c87ee7515bafdc5",
  "operator_id": "mqmqmqmq",
  "ukey": "aabbcc1122"
}
```

Response:

```
{
  "success": 0,
  "status": 1,
  "statusdesc": "OK"
}
```

Launch Sports

Method = POST

Format = JSON

Method Name = launchsports

SAMPLE API URL = https:xxxxx.com/api/launchsports

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No		
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
lang	varchar	Yes	Supported language: en,cn,id,vi,kr,th	Yes	*default language when launch game	* if pass wrong parameter system will default to en
type	varchar	Yes	1 = Desktop View 2 = Mobile View	Yes		* if pass wrong parameter system will default to desktop view

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
url	varchar	No	* launch game url will return if successful call

Default odds during launch game:

MY = Malay Odds, HK = Hong Kong Odds, ID = Indonesia Odds, DEC = Decimal Odds

Example: https://galaticdragon.com?a=in/6s5XMtd +DmcA+ ==&lang=kr&ot=MY

Example:

Request:

```
{
  "account_id": "jason87",
  "signature": "c796f0cd1525564ffc99339670618842",
  "operator_id": "indoindo",
  "ukey": "aabbcc1122",
  "lang": "kr",
  "type": "1"
}
```

Response:

```
{
  "url": "https://galaticdragon.com?a=in/6s5XMtd +DmcA+ ==&lang=kr",
  "status": 1,
  "statusdesc": "OK"
}
```


Launch Sports New

Method = POST

Format = JSON

Method Name = launchsportsnew

SAMPLE API URL = https:xxxxx.com/api/launchsportsnew

Remark : This function is to get WBET game link of new interface.

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No		
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
lang	varchar	Yes	Supported language: en,cn,id,vi,kr,th	Yes	*default language when launch game	* if pass wrong parameter system will default to en
type	varchar	Yes	1 = Desktop View 2 = Mobile View	Yes		* if pass wrong parameter system will default to desktop view

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
url	varchar	No	* launch game url will return if successful call

Default odds during launch game:

MY = Malay Odds, HK = Hong Kong Odds, ID = Indonesia Odds, DEC = Decimal Odds

Example: https://galaticdragon.com?a=in/6s5XMtd +DmcA+ ==&lang=kr&ot=MY

Example:

Request:

```
{
  "account_id": "jason87",
  "signature": "c796f0cd1525564ffc99339670618842",
  "operator_id": "indoindo",
  "ukey": "aabbcc1122",
  "lang": "kr",
  "type": "1"
}
```

Response:

```
{
  "url": "https://dv2.galaticdragon.com?a=in/6s5XMtd +DmcA+ ==&lang=kr",
  "status": 1,
  "statusdesc": "OK"
}
```

Get Bet List

Method = POST

Format = JSON

Method Name = getbetlist

SAMPLE API URL = https:xxxxx.com/api/getbetlist

Remark : This function is to get outstanding bets which after player place bet and the result not yet settle.

- * Staging / production URL and API secretkey will supply after commercial term was agreed.
- * Bet List are bet ticket after player place betting, but the result of match not yet settle.
- * Bet List got 4 status which is Pending, Accepted, Rejected or Cancel
- * Cancel = Match Cancel
- * Rejected = Rejected by company's trader
- * For both Cancel and Rejected bet system will auto credit back the bet amount to player's wallet.
- * For each calling system will return 100 bet list record
- * Only allow call twice in 1 minutes which is 30 sec gap per request
- * After operator side has retrieve the first 100 bet list record please proceed to call mark fetch bet list, if not system will return the same 100 record on next call. After system receive the mark fetch bet list, system will mark fetch those bet id and return the new 100 record for next request.
- * Once operator mark fetch the bet list system will not return the same record again on next request, please make sure operator's side had successful store the record only proceed to call mark fetch bet list function.

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
value	Json object	No	

Example:

Request:

```
{
  "signature": "842d4306dc7c7500514dcc3a0b973d7e",
  "operator_id": "indoindo",
  "ukey": "aabbcc1122"
}
```

Response:

```
{
  "value": [
    {
      "bet_id": 12055,
      "bet_status": "Accepted",
      "league_name": "FANTASY MATCH - OLD",
      "home_team_name": "test a",
      "away_team_name": "test b",
      "bet_type": "HDP",
      "sports_type": 1,
      "sports_category": "SOCCER",
      "game_type_name": "SOCCER",
      "market_type": "LIVE",
      "bet_amount": 1,
      "currency": "MYR",
      "rate": 1,
      "odds_display": 0.97,
      "bet_hand": "H 1.5",
      "bet_time": "2020-05-21T10:49:01.003",
      "match_time": "2020-05-15T12:09:00",
      "working_date": "2020-05-15T00:00:00",
      "odds_type": 1, // 1 – Malay Odds, 2 – HK Odds, 3 – Indo Odds, 4 – Euro Odds
      "actual_bet_amount": 0.97
      "member_id": "jasontest",
      "int_ref": "HDP",
      "int_ref2": null
    }
  ],
  "status": 1,
  "statusdesc": "OK"
}
```

Mark Fetch Bet List

Method = POST

Format = JSON

Method Name = markfetchbetlist

SAMPLE API URL = https:xxxxx.com/api/markfetchbetlist

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

*** Maximum mark fetch bet list will be same as get bet list maximum will be 100 record per request to mark fetch**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
bet_list	Json object	Yes	*Take note Please refer to the example for the right format			Parameter a inside bet_list : a = {bet_id} on getbetlist

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "signature":"842d4306dc7c7500514dcc3a0b973d7e",
  "operator_id":"indoindo",
  "ukey":"aabbcc1122",
  "bet_list": [
    {
      "a": 11924
    },
    {
      "a": 11914
    }
  ]
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

Get Parlay Bet List

Method = POST

Format = JSON

Method Name = getparlaybetlist

SAMPLE API URL = https:xxxxx.com/api/getparlaybetlist

Remark : This function is to get outstanding parlay bets which is after player place bet and the result not yet settle.

- * Staging / production URL and API secretkey will supply after commercial term was agreed.
- * Parlay Bet List are bet ticket after player place betting, but the result of match not yet settle.
- * Parlay Bet List got 4 status which is Pending, Accepted, Rejected or Cancel
- * Cancel = Match Cancel
- * Rejected = Rejected by company's trader
- * For both Cancel and Rejected bet system will auto credit back the bet amount to player's wallet.
- * For each calling system will return 100 bet list record
- * Only allow call twice in 1 minutes which is 30 sec gap per request
- * After operator side has retrieve the first 100 bet list record please proceed to call mark fetch parlay bet list, if not system will return the same 100 record on next call. After system receive the mark fetch parlay bet list, system will mark fetch those bet id and return the new 100 record for next request.
- * Once operator mark fetch the bet list system will not return the same record again on next request, please make sure operator's side had successful store the record only proceed to call mark fetch parlay bet list function.
- * For Get Parlay Bet List, system will only return the Parlay Bet List Header, if need to get the details of each bet include on the parlay need to call get parlay details.

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
value	Json object	No	

Example:

Request:

```
{
  "signature":"842d4306dc7c7500514dcc3a0b973d7e",
  "operator_id":"indoindo",
  "ukey":"aabbcc1122"
}
```

Response:

```
{
  "value": [
    {
      "bet_id": 14774,
      "bet_status": "Accepted",
      "bet_time": "2020-06-08T19:28:32.963",
      "member_id": "jasontest",
      "bet_amount": 1,
      "odds_display": 4.305,
      "currency": "MYR",
      "rate": 1,
      "total_match": 2,
      "result_status": true,
      "int_ref": "PARLAY"
    },
    {
      "bet_id": 14775,
      "bet_status": "Accepted",
      "bet_time": "2020-06-08T19:28:34.38",
      "member_id": "jasontest",
      "bet_amount": 1,
      "odds_display": 4.614,
      "currency": "MYR",
      "rate": 1,
      "total_match": 2,
      "result_status": true,
      "int_ref": "PARLAY"
    }
  ],
  "status": 1,
  "statusdesc": "OK"
}
```


Mark Fetch Parlay Bet List

Method = POST

Format = JSON

Method Name = markfetchparlaybetlist

SAMPLE API URL = https:xxxxx.com/api/markfetchparlaybetlist

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

*** Maximum mark fetch parlay bet list will be same as get parlay bet list maximum will be 100 record per request to mark fetch**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommended alphanumeric between 6-8 character	* 2aaxdf22
bet_list_parlay	Json object	Yes	*Take note Please refer to the example for the right format			Parameter a inside bet_list_parlay : a = {bet_id} on getparlaybetlist

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "signature":"842d4306dc7c7500514dcc3a0b973d7e",
  "operator_id":"indoindo",
  "ukey":"aabbcc1122",
  "bet_list_parlay": [
    {
      "a": 14774
    },
    {
      "a": 14775
    }
  ]
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

Get Parlay Details

Method = POST

Format = JSON

Method Name = `getparlaydetails`

SAMPLE API URL = `https:xxxxx.com/api/getparlaydetails`

Remark : This function is to get outstanding parlay bets detail which is after player place bet and the result not yet settle.

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

*** For this function only allow to query the parlay bet detail by each single bet_id on parlay bet, system will return the details of the particular bet parlay.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22
bet_id	Int64	Yes	bet_id from get parlay bet list function / result_id from get result function	No		46

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
value	Json object	No	* please refer the example of return value

Example:

Request:

```
{
  "bet_id":46,
  "signature":"842d4306dc7c7500514dcc3a0b973d7e",
  "operator_id":"indoindo",
  "ukey":"aabbcc1122"
}
```

Response:

```
{
  "value": [
    {
      "bet_id": 46,
      "league_name": "TEST - 001",
      "home_team_name": "Test A",
      "away_team_name": "Test B",
      "bet_type": "HDP",
      "sports_type": 1,
      "game_type_name": "SOCCER",
      "market_type": "TODAY",
      "odds_display": 9.3,
      "bet_hand": "A 2",
      "created_on": "2020-04-05T16:32:51.543",
      "match_time": "2020-04-05T17:00:00 "
    },
    {
      "bet_id": 46,
      "league_name": "TEST - 001",
      "home_team_name": "Shakhtyor Soligorsk",
      "away_team_name": "Kalmar (n)",
      "bet_type": "HDP",
      "sports_type": 1,
      "game_type_name": "SOCCER",
      "market_type": "TODAY",
      "odds_display": 1.95,
      "bet_hand": "A 1.5",
      "created_on": "2020-04-05T16:32:51.543",
      "match_time": "2020-04-05T17:00:00 "
    }
  ],
  "status": 1,
  "statusdesc": "OK"
}
```

Get Result

Method = POST

Format = JSON

Method Name = getresult

SAMPLE API URL = https:xxxxx.com/api/getresult

Remark : This function is to get settled bets which the match was settled.

* Staging / production URL and API secretkey will supply after commercial term was agreed.

* Result got 2 status which is END, REOPEN.

* If result_status = END means the match result is out and match has been settled. Winlose will be calculated and auto debit/credit to player's wallet according to their winlose.

* In some special condition, company's trader will REOPEN the settled match if found the match result on market was wrong info or any others issue.

* If operator receive record with result_status = REOPEN, please follow below steps to handle record.

1. Delete the record based on result_id from your side (database).
2. After company's trader re-settled the match, system will return a record of result_status = END with same result_id to allow pulling the record again.
3. After done process and store the record, operator can proceed to call mark fetch result api.

* Record's result_status possible change from END to REOPEN, and then back to END.

* if operator's receive the record with result_status = END, please follow below steps to handle the record.

1. Check the existence of current record in operator's database based on record's result_id.
2. If record didn't found in operator's database, operator can process and store the record then proceed to call mark fetch result api.
3. If record did found in operator's database, operator need to cross check and update the whole record based on result_id, especially latest winlose and payout amount, and call mark fetch result api.

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK
value	Json object	No	* please refer the example of return value

Example:

Request:

```
{
  "signature": "842d4306dc7c7500514dcc3a0b973d7e",
  "operator_id": "indoindo",
  "ukey": "aabbcc1122"
}
```

Response:

```
{
  "value": [
    {
      "result_id": 293,
      "result_status": "END",
      "member_id": "jasontest",
      "league_name": "LEAGUE OF LEGENDS - CHALLENGERS KOREA SPRING",
      "sports_type": 20,
      "sports_category": "ESPORTS",
      "game_type_name": null,
      "bet_amount": 50,
      "currency": "MYR",
      "rate": 1,
      "bet_type": "OE",
      "bet_hand": "O",
      "home_team_name": "Team Dynamics",
      "away_team_name": "Element Mystic",
      "payout": 0,
      "winlose": -50,
      "home_running_score": null,
      "away_running_score": null,
      "working_date": "2020-04-30T00:00:00",
      "bet_time": "2020-04-17T12:51:12.07",
      "result_time": "2020-05-08T16:06:46.287",
      "home_score": 0,
      "away_score": 0,
      "match_time": "2020-04-14T16:44:00",
      "odds_type": 1, // 1 – Malay Odds, 2 – HK Odds, 3 – Indo Odds, 4 – Euro Odds
      "odds_display": 0.97,
      "odds_display_bet": null,
      "ip": "172.12.1.2",
      "wl_status": "LA",
      "int_ref": "HDP",
      "int_ref2": null,
      "valid_bet_amount": 50
    }
  ],
}
```

```

{
  "result_id": 304,
  "result_status": "REOPEN",
  "member_id": "jasontest",
  "league_name": "TEST-LEAGUE-001",
  "sports_type": 1,
  "sports_category": "SOCCER",
  "game_type_name": null,
  "bet_amount": 1,
  "currency": "MYR",
  "rate": 1,
  "bet_type": "HDP",
  "bet_hand": "A 2.5",
  "home_team_name": "Dinamo Brest",
  "away_team_name": "FC Gorodeya",
  "payout": 1.95,
  "winlose": 0.95,
  "home_running_score": 0,
  "away_running_score": 0,
  "working_date": "2020-04-17T00:00:00",
  "bet_time": "2020-04-17T16:51:15.657",
  "result_time": "2020-05-08T14:54:25.447",
  "home_score": 0,
  "away_score": 0,
  "match_time": "2020-04-17T16:23:00",
  "odds_type": 1, , // 1 – Malay Odds, 2 – HK Odds, 3 – Indo Odds, 4 – Euro Odds
  "odds_display": 0.95,
  "odds_display_bet": null,
  "ip": "172.12.9.32",
  "wl_status": "WA",
  "int_ref": "HDP",
  "int_ref2": null,
  "valid_bet_amount": 1
}
],
"status": 1,
"statusdesc": "OK"
}

```

Set Bet Limit

Method = POST

Format = JSON

Method Name = setbetlimit

SAMPLE API URL = https:xxxxx.com/api/setbetlimit

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No		
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommended alphanumeric between 6-8 character	* 2aaxdf22
soccer_min_bet	int	Yes				500
soccer_max_bet	int	Yes				1000
soccer_max_per_match	int	Yes				10000
basketball_min_bet	int	Yes				500
basketball_max_bet	int	Yes				1000
basketball_max_per_match	int	Yes				10000
tennis_min_bet	int	Yes				500
tennis_max_bet	int	Yes				1000
tennis_max_per_match	int	Yes				10000
baseball_min_bet	int	Yes				500
baseball_max_bet	int	Yes				1000
baseball_max_per_match	int	Yes				10000
parlay_min_bet	int	Yes				500
parlay_max_bet	int	Yes				1000
parlay_max_per_match	int	Yes				10000
esports_min_bet	int	Yes				500
esports_max_bet	int	Yes				1000
esports_max_per_match	int	Yes				10000
others_min_bet	int	Yes				500
others_max_bet	int	Yes				1000
others_max_per_match	int	Yes				10000
cs_min_bet	int	Yes				500
cs_max_bet	int	Yes				1000
cs_max_per_match	int	Yes				10000

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

* For same player call set bet limit must have 2 minutes of gap.

* cs_min_bet must be equal or more than soccer_min_bet.

* cs_max_bet must be equal or less than soccer_max_bet.

* cs_max_per_match must be equal or less than soccer_max_per_match.

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "account_id":"jasonlam",
  "signature":"058353682cc317b464652e99ba13e8f8",
  "operator_id":"ipipip",
  "ukey":"aabbcc1122",

  "soccer_min_bet":508,
  "soccer_max_bet":588,
  "soccer_max_per_match":15000,

  "basketball_min_bet":508,
  "basketball_max_bet":880,
  "basketball_max_per_match":15500,

  "tennis_min_bet":575,
  "tennis_max_bet":750,
  "tennis_max_per_match":17500,

  "baseball_min_bet":545,
  "baseball_max_bet":5450,
  "baseball_max_per_match":14500,

  "parlay_min_bet":535,
  "parlay_max_bet":3550,
  "parlay_max_per_match":13500,

  "esports_min_bet":525,
  "esports_max_bet":2550,
  "esports_max_per_match":12500,

  "others_min_bet":5115,
  "others_max_bet":5150,
  "others_max_per_match":11500,

  "cs_min_bet":535,
  "cs_max_bet":588,
  "cs_max_per_match":15000
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

}

Set HDP Package

Method = POST

Format = JSON

Method Name = sethdppackages

SAMPLE API URL = https:xxxxx.com/api/sethdppackages

*** Staging / production URL and API secretkey will supply after commercial term was agreed.**

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
account_id	varchar	Yes	*player id	No		
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommended alphanumeric between 6-8 character	* 2aaxdf22
hdp_package	varchar	Yes	Supported package: a,b,c,d,e,f		Always lower case	

* signature = md5(operator_id + ukey + account_id + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "account_id": "jasonlam",
  "signature": "058353682cc317b464652e99ba13e8f8",
  "operator_id": "ipipipip",
  "ukey": "aabbcc1122",
  "hdp_package": "a"
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

Mark Fetch Result

Method = POST

Format = JSON

Method Name = markfetchresult

SAMPLE API URL = https:xxxxx.com/api/markfetchresult

* Staging / production URL and API secretkey will supply after commercial term was agreed.

* Maximum mark fetch result will be same as get result maximum will be 100 record per request to mark fetch

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommended alphanumeric between 6-8 character	* 2aaxdf22
result_list	Json object	Yes	*Take note Please refer to the example for the right format			Parameter a inside result_list : a = {result_id} on getresult function

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "signature":"842d4306dc7c7500514dcc3a0b973d7e",
  "operator_id":"indoindo",
  "ukey":"aabbcc1122",
  "result_list": [
    {
      "a": 143
    },
    {
      "a": 12279
    }
  ]
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

Get Bonus Result

Method = POST

Format = JSON

Method Name = getbonusresult

SAMPLE API URL = https:xxxxx.com/api/getbonusresult

Remark : This function is to get bonus which the match was settled.

- * Staging / production URL and API secretkey will supply after commercial term was agreed.
- * Result got 3 room types which can refer to room_type = PUBLIC / PRIVATE / PUBLIC FREE.
- * Result got 3 result types which can refer to result_type = CREATEROOM / JOINROOM / RESULT.
- * Result got 3 result status which can refer to result_status = END / REOPEN / REFUND.
- * Position field is the member's ranking after result confirmed.
- * If result_status = END and result_type = CREATEROOM / JOINROOM, means the member wallet balance already got deducted according to **bet_amount**.
- * If result_status = REFUND and result_type = CREATEROOM / JOINROOM, means the room has been closed and refund will be auto credit to player's wallet according to **bet_amount**.
- * If operator receive record with result_status = REOPEN and result_type = RESULT, means settled match was reopened and previous payout which credited to member will be auto debit. Operator just need to call mark fetch bonus result api.
- * Record's result_status possible change from END to REOPEN, and then back to END.
- * if operator's receive the record with result_status = END and result_type= RESULT, please follow below steps to handle the record.
 1. Check the existence of current record in operator's database based on record's result_id.
 2. If record didn't found in operator's database, operator can process and store the record then proceed to call mark fetch bonus result api.
 3. If record did found in operator's database, operator need to cross check and update the whole record based on result_id, especially latest winlose and payout amount, and call mark fetch bonus result api.

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommend alphanumeric between 6-8 character	* 2aaxdf22

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

value	Json object	No	* please refer the example of return value
-------	-------------	----	--

Example:

Request:

```
{
  "signature": "3950d38179da31a82ee76e453e9ae17c",
  "operator_id": "umumumum",
  "ukey": "aabbcc1122"
}
```

Response:

```
{
  "value": [
    {
      "result_id": "2138_CREATEROOM",
      "result_status": "REFUND",
      "member_id": "umeddie",
      "bet_amount": 23.8663,
      "payout": 0,
      "result_on": "2023-03-04T00:36:19.16",
      "position": null,
      "room_type": "PRIVATE",
      "winlose": -23.8663,
      "result_type": "CREATEROOM",
      "room_id": 123
    },
    {
      "result_id": "2139_JOINROOM",
      "result_status": "REFUND",
      "member_id": "umkenny",
      "bet_amount": 23.8663,
      "payout": 0,
      "result_on": "2023-03-04T00:36:59.227",
      "position": null,
      "room_type": "PRIVATE",
      "winlose": -23.8663,
      "result_type": "JOINROOM",
      "room_id": 123
    },
    {
      "result_id": "4103_RESULT",
      "result_status": "END",
      "member_id": "whmbm03",
      "bet_amount": 0,
      "payout": 11.4558,
      "result_on": "2023-06-12T17:11:21.313",
    }
  ]
}
```

```
"position": 3,  
"room_type": "PRIVATE",  
"winlose": 11.4558,  
"result_type": "RESULT",  
"room_id": 200  
}  
],  
"status": 1,  
"statusdesc": "OK"  
}
```

Mark Fetch Bonus Result

Method = POST

Format = JSON

Method Name = markfetchbonusresult

SAMPLE API URL = https:xxxxx.com/api/markfetchbonusresult

* Staging / production URL and API secretkey will supply after commercial term was agreed.

* Maximum mark fetch bonus result will be same as get bonus result maximum will be 100 record per request to mark fetch

Parameter	Data Type	Required	Description	Case Sensitive	Criteria	Sample Data
signature	varchar	Yes	*authentication key to recognize between operator and provider	No	Always lower case after hashing	c796f0cd15aswv3ffc99339670618842
operator_id	varchar	Yes		No		
ukey	varchar	Yes	* random key for each request for signature md5 hashing	No	*recommended alphanumeric between 6-8 character	* 2aaxdf22
bonus_list	Json object	Yes	*Take note Please refer to the example for the right format			Parameter a inside bonus_list : a = {result_id} on getbonusresult function

* signature = md5(operator_id + ukey + ukey + secret_key)

Response

Parameter	Data Type	Required	Description
status	int	Yes	1 = Success
statusdesc	varchar	Yes	If error, will return error message. If success will return = OK

Example:

Request:

```
{
  "signature": "3950d38179da31a82ee76e453e9ae17c",
  "operator_id": "umumumum",
  "ukey": "aabbcc1122",
  "bonus_list": [
    {
      "a": "3055_CREATEROOM"
    },
    {
      "a": "3056_CREATEROOM"
    },
    {
      "a": "2151_JOINROOM"
    },
    {
      "a": "3067_CREATEROOM"
    }
  ]
}
```

Response:

```
{
  "status": 1,
  "statusdesc": "OK"
}
```

Appendix

Error Code	Description
2	No row
3	No Changes
100	accountIdRequired
101	parentIdRequired
102	passwordRequired
103	amountRequired
104	ipAddressRequired
105	transactionIdRequired
110	soccerMinBetRequired
111	soccerMaxBetRequired
112	soccerMaxPerMatchRequired
120	basketballMinBetRequired
121	basketballMaxBetRequired
122	basketballMaxPerMatchRequired
130	tennisMinBetRequired
131	tennisMaxBetRequired
132	tennisMaxPerMatchRequired
140	baseballMinBetRequired
141	baseballMaxBetRequired
142	baseballMaxPerMatchRequired
150	parlayMinBetRequired
151	parlayMaxBetRequired
152	parlayMaxPerMatchRequired
160	esportsMinBetRequired
161	esportsMaxBetRequired
162	esportsMaxPerMatchRequired
170	othersMinBetRequired
171	othersMaxBetRequired
172	othersMaxPerMatchRequired
180	csMinBetRequired
181	csMaxBetRequired
182	csMaxPerMatchRequired
183	hdpPackageRequired
200	accountNotExists
201	parentNotExists
202	keyNotExists
203	defaultSettingNotExists
210	soccerBetLimitSettingNotExists
211	soccerParentBetLimitSettingNotExists
220	basketballBetLimitSettingNotExists
221	basketballParentBetLimitSettingNotExists
230	tennisBetLimitSettingNotExists

231	tennisParentBetLimitSettingNotExists
240	baseballBetLimitSettingNotExists
241	baseballParentBetLimitSettingNotExists
250	parlayBetLimitSettingNotExists
251	parlayParentBetLimitSettingNotExists
260	esportsBetLimitSettingNotExists
261	esportsParentBetLimitSettingNotExists
270	othersBetLimitSettingNotExists
271	othersParentBetLimitSettingNotExists
300	accountExists
301	positionSettingExists
302	commissionSettingExists
303	betLimitSettingExists
304	accountSettingExists
305	transactionExists
400	accountInactive
401	invalidPassword
402	invalidAmount
403	permissionDenied
404	insufficientBalance
405	unauthorizedIpAddress
406	unauthenticatedUser
407	sessionExpired
408	invalidHdpPackage
410	soccerMinBetGtMaxBet
411	soccerMaxBetGtMaxPerMatch
412	soccerMinBetLtParent
413	soccerMaxBetGtParent
414	soccerMaxPerMatchGtParent
420	basketballMinBetGtMaxBet
421	basketballMaxBetGtMaxPerMatch
422	basketballMinBetLtParent
423	basketballMaxBetGtParent
424	basketballMaxPerMatchGtParent
430	tennisMinBetGtMaxBet
431	tennisMaxBetGtMaxPerMatch
432	tennisMinBetLtParent
433	tennisMaxBetGtParent
434	tennisMaxPerMatchGtParent
440	baseballMinBetGtMaxBet
441	baseballMaxBetGtMaxPerMatch
442	baseballMinBetLtParent
443	baseballMaxBetGtParent
444	baseballMaxPerMatchGtParent
450	parlayMinBetGtMaxBet
451	parlayMaxBetGtMaxPerMatch

452	parlayMinBetLtParent
453	parlayMaxBetGtParent
454	parlayMaxPerMatchGtParent
460	esportsMinBetGtMaxBet
461	esportsMaxBetGtMaxPerMatch
462	esportsMinBetLtParent
463	esportsMaxBetGtParent
464	esportsMaxPerMatchGtParent
470	othersMinBetGtMaxBet
471	othersMaxBetGtMaxPerMatch
472	othersMinBetLtParent
473	othersMaxBetGtParent
474	othersMaxPerMatchGtParent
480	csMinBetGtMaxBet
481	csMaxBetGtMaxPerMatch
482	csMinBetLtParent
483	csMaxBetGtParent
484	csMaxPermatchGtParent
485	csMinBetLtSoccer
486	csMaxBetGtSoccer
487	csMaxPerMatchGtSoccer

sports_type	Description
1	SOCCER
2	BASKETBALL
3	BADMINTON
4	TABLE TENNIS
5	SNOOKER
6	US FOOTBALL
7	TENNIS
8	BASEBALL
9	ICE HOCKEY
10	GOLF
11	VOLLEYBALL
12	CRICKET
13	RUGBY
14	MOTORSPORTS
15	MUAY THAI
16	DARTS
17	BEACH SOCCER
18	HANDBALL
19	BOXING
20	ESPORTS
21	SQUASH
22	DOTA
23	BANDY
24	ARCHERY
25	AUSSIE RULES FOOTBALL
26	HURLING
27	GAELIC FOOTBALL
28	WATER POLO
29	WINTER SPORTS
30	FIELD HOCKEY
31	CYCLING
32	SPECIAL
34	ATHLETICS
35	MIXED MARTIAL ARTS
36	OLYMPIC
37	OTHERS
38	WINTER OLYMPICS
39	FINANCE
40	4D SPECIALS
41	STREET FIGHTER V

42	UFC 3
43	KING OF FIGHTERS
44	MORTAL KOMBAT
45	GREYHOUND
46	MOTORBIKE RACING
47	TEKKEN 8
48	BEACHVOLLEYBALL
49	MARBLE RUNS
50	MARBLE CLASH
51	MARBLE SURVIVAL
52	DRAGON BALL
53	NARUTO
54	MARBLE RAFTING
55	MARIO PARTY
56	COCK FIGHT

bet_type	Description
1X2	1X2
1X2H	1X2 Half
1X2HDP	3 Way Handicap
1X2HDPH	3 Way Handicap Half
ANB	Away No Bet
BS	Both To Score
CL	Clean Sheet
CS	Correct Score
CSH	Correct Score Half
DC	Double Chance
DCH	Double Chance Half
DNB	Draw No Bet
FGLG	First Goal/Last Goal
FGLGH	First Goal/Last Goal Half
HDP	Handicap
HDPH	Handicap Half
HNB	Home No Bet
HTFT	Half Time/Full Time
ML	Money Line
MLH	Money Line Half
OE	Odd/Even
OEH	Odd/Even Half
OR	Outright
OU	Over/Under

OUH	Over/Under Half
TG	Total Goal
TGH	Total Goal Half
TWTN	To Win To Nil
CSHTFT	Correct Score Half Time/Full Time
ETGHTFT	Exact Total Goal Half Time/Full Time
DCOU	Double Chance Over/Under
DNBH	Draw No Bet Half
EATG	Exact Away Total Goal
EATGH	Exact Away Total Goal Half
HTG	Exact Home Total Goal
HTGH	Exact Home Total Goal Half
ETG	Exact Total Goal
ETGH	Exact Total Goal Half
HTFTOE	Half Time/Full Time Odd/Even
OEAW	Away Odd/Even
OEAWH	Away Odd/Even Half
OEHM	Home Odd/Even
OEHMH	Home Odd/Even Half
OUOE	Over/Under Odd/Even
WM	Winning Margin
1X2OU	1X2 Over/Under

odds_type	Description
1	Malay Odds
2	Hong Kong Odds
3	Indo Odds
4	Decimal Odds

wl_status	Description
D	Draw
WA	Win All
WH	Win Half
LA	Lose All
LH	Lose Half

bet_status	Description
Accepted	Ticket is accepted
Cancel	Match is cancel
Pending	Ticket is pending
Rejected	Ticket is rejected

result_status	Description
END	Ticket is settled
REOPEN	Settled ticket is reopen

sports_category	Description
BASEBALL	Baseball
BASKETBALL	Basketball
ESPORTS	Esports
OTHERS	Other sports
PARLAY	Parlay
SOCCER	Soccer
TENNIS	Tennis

market_type	Description
EARLY	Early Market
LIVE	Live Market
TODAY	Today Market

Currency	Description
UST	USDT

attribute	Description
actual_bet_amount	Actual deduct amount when member place bet
away_running_score	Away team running score
away_score	Away team final score
away_team_name	Away team full name
bet_amount	Member's bet amount of bet transaction
bet_hand	Member's bet overview
bet_id	Unique ID of bet transaction
bet_list	List which contains bet transaction(s)
bet_list_parlay	List which contains parlay bet transaction(s)
bet_status	Current status of bet transaction
bet_time	Datetime which member place bet
bet_type	Type of bet transaction
created_on	Datetime which bet transaction create in WBET system
currency	Bet amount's currency of bet transaction
game_type_name	Full name of game type
home_running_score	Home team running score
home_score	Home team final score
home_team_name	Home team full name
ip	IP address
int_ref	Internal reference

int_ref2	Internal reference 2
league_name	League full name
market_type	Type of market
match_time	Datetime which match begin
member_id	Unique ID of member
odds_col_criteria	Full Time Criteria
odds_display	Odds display on UI
odds_display_bet	Odds when member place bet
odds_type	Type of odds
payout	Member winning amount
rate	Currency rate
result_id	Unique ID of result record
result_list	List which contains result record(s)
result_status	Current status of result record
result_time	Datetime which result is finalized
sports_category	Category of sports
sports_type	Unique ID of sports
ticket_id	Unique ID of bet transaction
total_match	Total match count in single parlay ticket
transaction id	Unique ID of bet transaction
valid_bet_amount	Member's valid bet amount of bet transaction
winlose	Member winlose
wl_status	Winlose status of bet transaction
working_date	Winlose date of bet transaction

function	attribute	type	length	nullable
getbetlist	bet_id	bigint	-	Not Null
	bet_status	varchar	30	Not Null
	league_name	varchar	100	Null
	home_team_name	varchar	100	Not Null
	away_team_name	varchar	100	Not Null
	bet_type	varchar	50	Not Null
	sports_type	Int	-	Not Null
	sports_category	varchar	50	Not Null
	game_type_name	varchar	100	Not Null
	market_type	varchar	50	Not Null
	bet_amount	money	-	Not Null
	currency	varchar	3	Not Null
	rate	money	-	Not Null
	odds_display	money	-	Not Null
	bet_hand	varchar	50	Not Null
	bet_time	datetime	-	Not Null
	match_time	datetime	-	Not Null
	working_date	date	-	Not Null
	odds_type	int	-	Not Null

	actual_bet_amount	money	-	Not Null
	member_id	varchar	50	Not Null
	int_ref	varchar	50	Not Null
	int_ref2	varchar	20	Null
	odds_col_criteria	varchar	1000	Null
getparlaybetlist	bet_id	bigint	-	Not Null
	bet_status	varchar	30	Not Null
	bet_time	datetime	-	Not Null
	member_id	varchar	50	Not Null
	bet_amount	money	-	Not Null
	odds_display	money	-	Not Null
	currency	varchar	3	Not Null
	rate	money	-	Not Null
	total_match	int	-	Null
	result_status	bit	-	Not Null
	int_ref	varchar	50	Not Null
getparlaydetails	bet_id	bigint	-	Not Null
	league_name	varchar	100	Null
	home_team_name	varchar	100	Null
	away_team_name	varchar	100	Null
	bet_type	varchar	10	Not Null
	sports_type	int	-	Not Null
	game_type_name	varchar	100	Null
	market_type	varchar	50	Not Null
	odds_display	money	-	Not Null
	bet_hand	varchar	50	Not Null
	created_on	datetime	-	Not Null
	match_time	datetime	-	Null
getresult	result_id	bigint	-	Not Null
	result_status	varchar	30	Not Null
	member_id	varchar	50	Not Null
	league_name	varchar	100	Null
	sports_type	int	-	Not Null
	sports_category	varchar	50	Not Null
	game_type_name	varchar	100	Null
	bet_amount	money	-	Not Null
	currency	varchar	3	Not Null
	rate	money	-	Not Null
	bet_type	varchar	50	Not Null
	bet_hand	varchar	50	Not Null
	home_team_name	varchar	100	Null
	away_team_name	varchar	100	Null
	payout	money	-	Not Null
	winlose	money	-	Not Null
	home_running_score	int	-	Null
	away_running_score	int	-	Null

	working_date	date	-	Not Null
	bet_time	datetime	-	Not Null
	result_time	datetime	-	Not Null
	home_score	int	-	Null
	away_score	Int	-	Null
	match_time	datetime	-	Null
	odds_type	int	-	Not Null
	odds_display	money	-	Not Null
	odds_display_bet	money	-	Null
	ip	varchar	500	Null
	wl_status	varchar	10	Not Null
	int_ref	varchar	50	Not Null
	int_ref2	varchar	20	Null
	valid_bet_amount	money	-	Not Null
	odds_col_criteria	varchar	1000	Null