P1

```cpp
#include <bits/stdc++.h>
using namespace std;

int main() {
    cout << "Total seconds: " << 4*60*60 + 22*60 + 53 << endl;
    return 0;
}
```

```
PS C:\Users\kuole\Desktop\cpp\HW_1> ./P1.exe
Total seconds: 15773
```

P2

```cpp
#include <bits/stdc++.h>
using namespace std;

int main() {
    cout << "Enter the length of a side: ";
    int len;
    cin >> len;

    cout << "The area is: " << len * len << endl;
    cout << "The perimeter is: " << len * 4 << endl;

    return 0;
}
```

```
PS C:\Users\kuole\Desktop\cpp\HW_1> ./P2.exe
Enter the length of a side: 10
The area is: 100
The perimeter is: 40
```

P3

```cpp
#include <iostream>
using namespace std;

int main() {
    const double tax = 0.09;
```

```
    double sale_amount;

    cout << "Enter sale amount: ";
    cin >> sale_amount;
    cout << "Sale amount: " << sale_amount << endl;
    cout << "Tax amount: " << sale_amount * tax << endl;
    cout << "Total amount due: " << sale_amount + sale_amount * tax << endl;

    return 0;
}
```

```
PS C:\Users\kuole\Desktop\cpp\HW_1> ./P3.exe
Enter sale amount: 100
Sale amount: 100
Tax amount: 9
Total amount due: 109
```

P4

```
#include <iostream>
#include <string>
using namespace std;

int main() {
    string street_no, street_name, city, state, zip_code;

    cout << "Enter your street No: ";
    cin >> street_no;

    cout << "Enter your street Name: ";
    cin >> street_name;

    cout << "Enter your city: ";
    cin >> city;

    cout << "Enter your state: ";
    cin >> state;

    cout << "Enter your zip code: ";
    cin >> zip_code;

    cout << "Your address is: " << street_no << " " << street_name << ", " << city
<< ", " << state << " " << zip_code << endl;

    return 0;
}
```

```
PS C:\Users\kuole\Desktop\cpp\HW_1> ./P4.exe
Enter your street No: 200
Enter your street Name: Main
Enter your city: Houston
Enter your state: Texas
Enter your zip code: 100
Your address is: 200 Main, Houston, Texas 100
```