

# Event Discovery for Kubernetes Applications

Christoph Stäbler (@creydr)  
Senior Software Engineer, Red Hat

Pierangelo Di Pilato (@pierDipi)  
Principal Software Engineer, Red Hat



# Agenda



Why Event Discovery?



Event Discovery in Knative Eventing



Demo and Q&A

# Knative Eventing

## Source


- Way to get events into the system / event-mesh
- Service in the system, which emits events

## Broker & Triggers

- Routing of events

## Sink


- Way to get events out of the system / event-mesh to an external destination
- Service in the system, which accepts events



---

# Why Event Discovery?

## Why Event Discovery?



What are the  
available events I  
can consume?

What is their  
schema?

Knative Sources

↑ Back to top

Name	Status	Maintainer	Description
APIServerSource	Stable	Knative	Brings Kubernetes API server events into Knative. The APIServerSource fires a new event each time a Kubernetes resource is created, updated or deleted.
Apache CouchDB	Alpha	Knative	Brings Apache CouchDB messages into
Apache Kafka			
CephSource			notifications from Ceph format into CloudEvents format, and inject them into Knative. Conversion logic follow the one described for AWS S3 bucket notifications.
ContainerSource	Stable	Knative	The ContainerSource instantiates container

Third-Party Sources

Name	Status	Maintainer	Description
Apache Camel	Stable	Apache Software Foundation	Enables use of Apache Camel components for pushing events into Knative. Camel sources are now provided via Kamelets as part of the Apache Camel K project.

There is no information about the available types or schemas

## What can I do next?

I'm using Knative Eventing with the Apache Camel (Kamelets) and I need to know the event types and schemas that I can consume from AWS DynamoDB Stream



ChatGPT



When you're using **Knative Eventing** with **Apache Camel K (Kamelets)** to consume events from AWS services like DynamoDB Streams, the Kamelets handle the integration between the Knative event-driven architecture and the external system, such as DynamoDB.

For AWS DynamoDB Streams, which captures data modifications in your DynamoDB tables, the event types and schema depend on how the stream is configured and the data it captures (e.g., "New image" or "Old image" of the modified items).

Here's an overview of the event types and schemas you can expect when consuming DynamoDB Streams using Knative Eventing with Camel K:

### Event Types

Knative Eventing uses **CloudEvents** to wrap the event payloads coming from external systems like DynamoDB Streams. The CloudEvent will include certain metadata, including the type of the event.

For DynamoDB Streams, you'll typically encounter these event types:

1. `aws.dynamodb.insert` : An item was inserted into the DynamoDB table.
2. `aws.dynamodb.modify` : An existing item was modified in the DynamoDB table.
3. `aws.dynamodb.remove` : An item was deleted from the DynamoDB table.

These types directly map to DynamoDB Streams record types:

- **INSERT**: Represents a new item added to the table.
- **MODIFY**: Represents a modified item.
- **REMOVE**: Represents a deleted item.



ChatGPT




## Example Event Schema

For an `INSERT` event, the CloudEvent `data` payload might look like this:

```
json Copy code
{
  "eventID": "1",
  "eventName": "INSERT",
  "eventVersion": "1.1",
  "eventSource": "aws:dynamodb",
  "awsRegion": "us-east-1",
  "dynamodb": {
    "Keys": {
      "PrimaryKey": {
        "S": "PrimaryKeyValue"
      }
    },
    "NewImage": {
      "AttributeName1": {
        "S": "AttributeValue1"
      },
      "AttributeName2": {
        "N": "123"
      }
    },
    "StreamViewType": "NEW_AND_OLD_IMAGES",
    "SequenceNumber": "111",
    "SizeBytes": 26
  }
}
```



ChatGPT




What about the internal systems and services?

Trial and error is the only solution today



```
function handler(event) {  
  console.log(event.data)  
}
```



```
$ oc logs -l=app=my-application -f
```

```
{ "Records": [{ "eventID": "78dfd1ba7a17", "eventName": "INSERT", "eventVersion": "1.1",  
  "eventSource": "aws:dynamodb", "awsRegion": "ap-southeast-2", "dynamodb": [{ "id": { "S": "xxx" },  
  "type": { "S": "xxx" } }], "NewImage": { }, "OldImage": { } } ] }
```

---

# Event Discovery in Knative Eventing



# EventType API

```
apiVersion: eventing.knative.dev/v1beta3
kind: EventType
metadata:
  ...
spec:
  reference:
    apiVersion: camel.apache.org/v1
    kind: Kamelet
    name: github-event-source
  attributes:
    - name: type
      value: com.github.pull_request.opened
    - name: source
      value: "https://github.com/cloudevents/spec/pull/{id}"
    - name: dataschema
      value: "https:// ... "
```

Reference to the  
emitting resource

Attributes of the  
emitted event

## How are EventType catalogs populated?

- ▶ Manual Registration
- ▶ Automatic Registration (e.g. via Brokers)

# Automatic Registration

```
{
  "specversion" : "1.0",
  "type" : "com.github.pull_request.opened",
  "source" : "https://github.com/cloudevents/spec/pull",
  "subject" : "123",
  "id" : "A234-1234-1234",
  "time" : "2018-04-05T17:31:00Z",
  "dataschema" : "https:// ... ",
  ...
}
```




```
apiVersion: eventing.knative.dev/v1beta3
kind: EventType
metadata:
  ...
spec:
  reference:
    apiVersion: eventing.knative.dev/v1
    kind: Broker
    name: my-broker
  attributes:
    - name: type
      value: com.github.pull_request.opened
    - name: source
      value: "https://github.com/cloudevents/spec/pull"
    - name: dataschema
      value: "https:// ... "
```

---

# Demo







---

# Thank you



Feedback Form

