

From Sensors to Servers: Efficient Edge Computing with Akri and WebAssembly

Exploring an Open-Source Toolkit for Wasm and the Edge



Kate Goldenring
Senior Software Engineer
Fermion
Co-chair IoT Edge WG



Yu Jin Kim
Product Manager
Microsoft

Kubernetes on the Edge

Challenges with Edge Computing

Imagine a bustling ecosystem filled with diverse devices working together:

Thousands of edge sensors publish data, each speaking its own protocol.

Servers need to discover these devices and continually process data to harness valuable insights from the edge.



Open Source Tools for Running Serverless Kubernetes on the Edge

Akri + SpinKube: Toolkit for Serverless WebAssembly Applications on the Edge



Akri

CNCF project for dynamically bridging IoT
leaf devices to your edge Kubernetes cluster



SpinKube

Open Source project for efficiently running
Wasm applications on Kubernetes

Tiny Edge

IoT leaf devices (sensors, actuators, etc.) have many challenges:

Different protocols, topologies and authentication requirements.

May have intermittent availability and downtime.

Too small, too old and too locked down to run Kubernetes today.

Manual configuration required to make IoT devices available to Kubernetes workloads.



**Kubernetes
Nodes**



**Leaf Devices
(Tiny Edge)**

What is Akri?



1K GITHUB ★

300+ SLACK MEMBERS

github.com/project-akri/akri



Discovers non-Kubernetes devices exposed on protocols and stores node-attach information



Devices are registered as Kubernetes extended resources that can be requested by Pods




Standardizes method for storing and passing in secrets for authentication



Easily extend Akri to discover more devices by creating a new Discovery Handler (in any language)

Akri Architecture



Consuming Akri Resources

```
apiVersion: v1
kind: Pod
metadata:
  name: app
  namespace: default
spec:
  containers:
  - name: app
    image: app:latest
    resources:
      requests:
        akri.sh/mqtt-sound-sensor: 1
      limits:
        akri.sh/mqtt-sound-sensor: 1
```

Request IoT devices just as you would CPU and memory.

Consuming Akri Resources

```
apiVersion: v1
kind: Pod
metadata:
  name: app
  namespace: default
spec:
  containers:
  - name: app
    image: app:latest
  resources:
    requests:
      akri.sh/mqtt-sound-sensor: 1
    limits:
      akri.sh/mqtt-sound-sensor: 1
```

Request IoT devices just as you would CPU and memory.


PAIN POINT

Containers + Kubernetes = heavy

Containers are bloated with operational dependencies dependencies

They are slow to scale up and down

More than 80 percent of container spend is wasted on idle resources - Datadog 2024 State of Cloud Costs



WebAssembly



Why WebAssembly?




Portable

You can swap out the underlying node OS and architecture (x64/arm, linux/windows) without having to produce separate pipelines and deploy artifacts.




Small package sizes

A hello-world WebAssembly application written in Rust is a 284kB OCI Artifact.



Sandboxed

WebAssembly components are sandboxed and are by default denied access to resources on the system.



Startup time

A Spin WebAssembly component will start in < 1ms




Spin is an open source project, built with open standards like WASI, Wagi and the WebAssembly Component Model.

Developer tool for building and running event-driven serverless WebAssembly applications

5K GITHUB ★

80+ CONTRIBUTORS

github.com/fermyon/spin



Spin Triggers - Beyond HTTP



Redis

Redis message



SQS

SQS message



Command

Way to invoke
sidecars



MQTT

MQTT topic message




DIY

You can build your
own trigger too!

spin app

Oh, the places Spin goes





SpinKube

👤 68 followers 🔗 <https://spinkube.dev> 🐙 @SpinKube@mastodon.social

Follow

Popular repositories

spin-operator

Public

Spin Operator is a Kubernetes operator that empowers platform engineers to deploy Spin applications as custom resources to their Kubernetes clusters

● Go ★ 96 🦋 11

containerd-shim-spin

Public

A ContainerD shim for running Spin Applications.

● Rust ★ 35 🦋 7

runtime-class-manager

Public

A Kubernetes operator to manage Runtime Classes

● Go ★ 14 🦋 5

spin-plugin-kube

Public

A Spin plugin for interacting with Kubernetes.

● Go ★ 11 🦋 1

👁 View as: Public ▼


You are viewing the README and pinned repositories as a public user.

You can [create a README file](#) visible to anyone.

People



Demo: Measuring Crowd Engagement with an MQTT-based IoT App



Running SpinApps on K8s

Spin Wasm OCI artifact

```
apiVersion: core.spinoperator.dev/v1alpha1
kind: SpinApp
metadata:
  name: mqtt-booth-volume
spec:
  image: "ghcr.io/mqtt-booth-volume:v1"
  executor: containerd-shim-spin
  replicas: 1
  resources:
    requests:
      akri.sh/mqtt-sound-sensor: 1
    limits:
      akri.sh/mqtt-sound-sensor: 1
```

Request Akri resources just as you would in a Pod

Demo Time

Continue to Make Some Noise! for Wasm on Kubernetes



Check out the SpinKube booth volume demo at the Fermion, Microsoft, Ampere, and Akamai booths.

Dive deeper into the demo at the Microsoft booth demo (11/13, 2-3PM) and SUSE booth demo (11/14, 2:45-3:30PM).



Visit the Akri booth at the Project Pavilion on Thursday 11/14 from 10:30AM-12PM.



Join **#spinkube** in Cloud Native Computing Foundation and **#akri** in Kubernetes on Slack!

Resources



SpinKube Docs

spinkube.dev



Akri

docs.akri.sh



@kate-goldenring @KateGoldenring



@yujinkim-msft