

# Contribfest: Kickstart Your eBPF Journey with Tetragon

Joe Stringer, Mahé Tardy, Kornilios Kourtis, John Fastabend

#### Plan




- Architecture overview
- 2. Core concepts
  - a. Events
  - b. TracingPolicy
- 3. Internals
  - a. Kernel/User split
  - b. Policy handling
  - c. Sensors
  - d. Life of a TracingPolicy
- 4. How to contribute





# Architecture - High-level View








#### Architecture - More Details










# Core Concepts





rpc GetEvents(GetEventsRequest) returns (stream GetEventsResponse) {}

Configure event stream,
e.g,. Filters (allow, deny,
fields)

Event:
- event
- node\_name
- cluster\_name
- time



```
The state of the s
```

```
oneof event {
        ProcessExec process exec = 1;
                                               Base events
        ProcessExit process exit = 5;
        ProcessKprobe process kprobe = 9;
        ProcessTracepoint process_tracepoint = 10;
        ProcessLoader process loader = 11;
                                                         Configurable
        ProcessUprobe process uprobe = 12;
                                                         events
        ProcessThrottle process_throttle = 27;
        ProcessLsm process 1sm = 28;
```

#### Exec event



```
message ProcessExec {
    Process process = 1;
    Process parent = 2;
Message Process {
    string exec_id = 1;
    string binary = 5;
    string arguments = 6;
    Pod pod = 10;
```



#### Exec event



```
"process_exec": {
  'process": {
    "binary": "/usr/bin/find",
    "arguments": "-name pizza",
    "pod": {
      "namespace": "default",
      "name": "test",
      "container": {
        "id": "docker://acddc67175a09036565f34b796b191f68dc770cad50197fc43b23fc354254502",
        "name": "test",
        "image": {
          "id": "docker-pullable://debian@sha256:27586f4609433f2f49a9157405b473c62c3cb28a581c413393975b4e8496d0ab",
          "name": "debian:latest"
        ,,
"start_time": "2024-10-02T10:41:14Z",
       'pod_labels": {
        "run": "test"
      .
"workload": "test",
      "workload_kind": "Pod"
"node_name": "minikube",
"time": "2024-10-02T10:42:19.860322547Z"
```



#### Exit event



```
A COSENSO
```

```
message ProcessExit {
    Process process = 1;
    Process parent = 2;
    string signal = 3;
    uint32 status = 4;
}
```

All events have .process and .parent

.process.exec\_id can be used to match events of the same process



```
oneof event {
    ProcessExec process_exec = 1;
    ProcessExit process_exit = 5;
```

Tetragon can be configured via TracingPolicies to generate events beyond exec/exit




```
ProcessKprobe process_kprobe = 9;
ProcessTracepoint process_tracepoint = 10;
ProcessLoader process_loader = 11;
ProcessUprobe process_uprobe = 12;
ProcessThrottle process_throttle = 27;
ProcessLsm process_lsm = 28;
```

Configurable events

### **Tracing Policies**





# Policies and events




Policy section	Event type	
spec.kprobes	ProcessKprobe	generic kprobe hooks
spec.tracepoints	ProcessTracepoint	generic tracepoint hooks
spec.uprobes	ProcessUprobe	generic uprobe hook
spec.1smhooks	ProcessLsm	generic LSM hook
spec.loader	ProcessLoader	Shared library / binary loading



# Internals


# Kernel/user split





# **Policy Handling**










A sensor is a collection of BPF programs and map that is managed as a single unit

- The "exec" (or base) sensor is always loaded
- Other sensors are loaded dynamically by tracing policies

# Life of a TracingPolicy
















# Let's contribute!

#### Contribution Guide







#### Contribution Guide





- Development setup
- Making changes and running the codegen
- Running the tests
- Modify the documentation
- Submit your pull request containing your signed patch
- Write release and upgrade notes



# Good first issues





