

P Configuration DHCP	
Static	
Pv4 Address	192.168.0.1
Subnet Mask	255.255.255.0
IP Configuration	
O DHCP Static	
IPv4 Address	192.168.0.2
Subnet Mask	255,255,255.0
IP Configuration	
IPv4 Address	192.168.0.100
Subnet Mask	255.255.255.0
IP Configuration	
IPv4 Address	100.10.10.1
Subnet Mask	255.0.0.0

```
Router(config) #ip route 0.0.0.0 0.0.0.0 100.10.10.2

Router(config) #int fa0/0

Router(config-if) #ip nat inside

Router(config-if) #int fa0/1

Router(config-if) #ip nat outside

Router(config-if) #exit

Router(config) #ip nat inside source static 192.168.0.1 100.10.11.1

Router(config) #ip nat inside source static 192.168.0.1 100.10.11.2
```

```
Pinging 100.10.10.2 with 32 bytes of data:

Request timed out.

Request timed out.

Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Ping statistics for 100.10.10.2:

Packets: Sent = 4, Received = 2, Lost = 2 (50% loss)

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms
```