Практическая работа 20












GLOBAL
Settings
Algorithm Settings
INTERFACE
Wireless0
Bluetooth
Wireless0
Port Status
Bandwidth
24 Mbps
MAC Address
0090.2B67.96C9
SSID
it
Authentication
Disabled
WEP
WEP Key
WPA-PSK
WPA2-PSK
PSK Pass Phrase
User ID
WPA
WPA2
Password
802.1X
Method:
MD5
User Name
Password
Encryption Type
Disabled
IP Configuration
DHCP
Static
IPv4 Address
192.168.2.1
Subnet Mask
255.255.255.0


2811
Router0
PC-PT
PC0
AccessPoint-PT
Access Point1
PC-PT
PC2
AccessPoint-PT
Access Point2


Router0
Physical
Config
CLI
Attributes
GLOBAL
Settings
Algorithm Settings
ROUTING
Static
RIP
SWITCHING
VLAN Database
INTERFACE
FastEthernet0/0
FastEthernet0/0
Port Status
Bandwidth
Duplex
MAC Address
0006.2A34.3401
IP Configuration
IPv4 Address
192.168.1.100
Subnet Mask
255.255.255.0


Physical
Config
CLI
Attributes
GLOBAL
Settings
Algorithm Settings
ROUTING
Static
RIP
SWITCHING
VLAN Database
INTERFACE
FastEthernet0/0
FastEthernet0/1
FastEthernet0/1
Port Status
Bandwidth
Duplex
Half
MAC Address
0006.2A34.3402
IP Configuration
IPv4 Address
191.168.2.100
Subnet Mask
255.255.0.0
Tx Ring Limit
10




```
C:\>ping 192.168.2.1

Pinging 192.168.2.1 with 32 bytes of data:

Reply from 192.168.2.1: bytes=32 time<1ms TTL=128
Reply from 192.168.2.1: bytes=32 time=18ms TTL=128
Reply from 192.168.2.1: bytes=32 time=18ms TTL=128
Reply from 192.168.2.1: bytes=32 time=1ms TTL=128

Ping statistics for 192.168.2.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 18ms, Average = 9ms
```








Access Point2
Physical
Config
Attributes
GLOBAL
Settings
INTERFACE
Port 0
Port 1
Port 1
Port Status
SSID
it
2.4 GHz Channel
6
Coverage Range (meters)
140,00
Authentication
Disabled
WEP
WEP Key
WPA-PSK
WPA2-PSK
PSK Pass Phrase
12345678


PC-PT
PC2
AccessPoint-PT
Access Point2

Laptop-PT
Laptop2