Практическая 23

IP Configuration

IPv4 Address	192.168.0.100
Subnet Mask	255.255.255.0

IP Configuration

IPv4 Address	100.10.10.2
Subnet Mask	255.0.0.0

```
Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#ip address 100.10.10.1 255.0.0.0
Router(config-if)#
Router(config-if)#exit
Router(config)#access-list 1 permit 192.168.0.0 0.0.0.255
Router(config)#ip nat pool white-address 100.10.11.77 100.10.11.99 netmask 255.255.255.0
Router(config)#ip nat inside source list 1 pool white-address
Router(config)#int fa0/0
Router(config-if)#int nat inside
                        ^
% Invalid input detected at '^' marker.

Router(config-if)#ip nat inside
Router(config-if)#int fa0/1
Router(config-if)#ip nat outside
Router(config-if)#exit
```

```
C:\>ping 100.10.10.2

Pinging 100.10.10.2 with 32 bytes of data:

Request timed out.
Request timed out.
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Ping statistics for 100.10.10.2:
    Packets: Sent = 4, Received = 2, Lost = 2 (50% los
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

```
C:\>ping 100.10.10.2

Pinging 100.10.10.2 with 32 bytes of data:

Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Ping statistics for 100.10.10.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms
```