

Deep Learning Audio

Lecture 7

Pavel Severilov

Moscow Institute of Physics and Technology

2022


Outline

1. Neural Vocoder
2. WaveNet
3. Parallel WaveGAN
4. DiffWave

Outline

1. Neural Vocoder
2. WaveNet
3. Parallel WaveGAN
4. DiffWave

Neural Vocoders



Neural Vocoders

Model type	Model	MOS on LJ Speech
Autoregressive	WaveNet	3.68
	WaveRNN	3.96
GAN	MelGAN	3.73
	Parallel WaveGAN	3.99
Diffusion	WaveGrad	3.85
	DiffWave	4.07
	Griffin-Lim	3.68
	Ground Truth	4.10

Outline

1. Neural Vocoder
2. WaveNet
3. Parallel WaveGAN
4. DiffWave

WaveNet




Figure: WaveNet architecture: uses **causal** dilated convolutions

- ▶ The joint probability of a waveform $x = \{x_1, \dots, x_T\}$:
$$p(\mathbf{x}) = \prod_{t=1}^T p(x_t \mid x_{1:t-1})$$
- ▶ Each conditional $p(x_t \mid x_{1:t-1})$ models the distribution for the timestamp t

Causal Convolution




Figure: Standard vs causal convolutions. Causal makes convs autoregressive

Dilated Convolution





Figure: Non-dilated vs dilated causal convolutions. Dilated convs increase receptive fields

Conditional gated units




Gated activation unit as used in the gated PixelCNN + condition \mathbf{y}

$$\mathbf{z} = \tanh(W_{f,k} * \mathbf{x} + V_{f,k} * \mathbf{y}) \odot \sigma(W_{g,k} * \mathbf{x} + V_{g,k} * \mathbf{y}).$$

$*$ – convolution, \odot – element-wise multiplication, $\sigma(\cdot)$ – sigmoid function, f and g – filter and gate, respectively, W – learnable convolution filter, V – learnable linear projection

Mu Law Encoding



- ▶ Raw audio \sim 16-bit integer values \Rightarrow softmax layer need to output 65,536 probabilities per timestep
- ▶ Solution: apply a μ -law transformation to the data, and then quantize it to 256 possible values:

$$f(x_t) = \text{sign}(x_t) \frac{\ln(1 + \mu |x_t|)}{\ln(1 + \mu)}, \quad -1 < x_t < 1, \mu = 255$$

Outline

1. Neural Vocoders
2. WaveNet
3. Parallel WaveGAN
4. DiffWave

Parallel WaveGAN





Figure: Parallel WaveGAN

Yamamoto et al., *Parallel Wavegan: A Fast Waveform Generation Model Based on Generative Adversarial Networks with Multi-Resolution Spectrogram*, IEEE ICASSP, 2020

STFT Loss



$$\mathcal{L}_s(G) = \mathbb{E}_{\mathbf{z} \sim p(\mathbf{z}), \mathbf{x} \sim p_{data}} [\mathcal{L}_{sc}(\mathbf{x}, \hat{\mathbf{x}}) + \mathcal{L}_{mag}(\mathbf{x}, \hat{\mathbf{x}})]$$

$$\mathcal{L}_{sc}(\mathbf{x}, \hat{\mathbf{x}}) = \frac{\| |STFT(\mathbf{x})| - |STFT^T(\hat{\mathbf{x}})| \|}{\| |STFT(\mathbf{x})| \|_F}$$

$$\mathcal{L}_{mag}(\mathbf{x}, \hat{\mathbf{x}}) = \frac{1}{N} \|\log |STFT(\mathbf{x})| - \log |STFT(\hat{\mathbf{x}})|\|_1$$

$$\mathcal{L}_{aux}(G) = \frac{1}{M} \sum_{m=1}^M \mathcal{L}_s^{(m)}(G), M - \text{number of STFT losses}$$

Takaki et al., *STFT Spectral Loss for Training a Neural Speech Waveform Model*,
IEEE ICASSP, 2019

GAN Loss

- ▶ Discriminator Loss:

$$\mathcal{L}_D(G, D) = \mathbb{E}_{\mathbf{x} \sim p_{\text{data}}} [(1 - D(\mathbf{x}))^2] + \mathbb{E}_{\mathbf{z} \sim N(0, I)} [D(G(\mathbf{z}))^2]$$

- ▶ Generator Loss


$$L_{\text{adv}}(G, D) = \mathbb{E}_{\mathbf{z} \sim N(0, I)} [(1 - D(G(\mathbf{z})))^2]$$

$$L_G(G, D) = L_{\text{aux}}(G) + \lambda_{\text{adv}} L_{\text{adv}}(G, D)$$

Outline

1. Neural Vocoder
2. WaveNet
3. Parallel WaveGAN
4. DiffWave

Diffusion models idea




- **Diffusion probabilistic model:** parameterized Markov chain from data x_0 to the latent variable x_T

$$q(x_1, \dots, x_T | x_0) = \prod_{t=1}^T q(x_t | x_{t-1})$$

- **Reverse process:** Markov chain from x_T to x_0 parameterized by θ :

$$p_{\text{latent}}(x_T) = \mathcal{N}(0, I), \quad p_{\theta}(x_0, \dots, x_{T-1} | x_T) = \prod_{t=1}^T p_{\theta}(x_{t-1} | x_t)$$

DiffWave



- **Sampling:** reverse process $x_T \sim \mathcal{N}(0, I)$, $x_{t-1} \sim p_\theta(x_{t-1}|x_t)$ for $t = T, T-1, \dots, 1$. x_0 – sampled data.
- **Training:** $p_\theta(x_0) = \int p_\theta(x_0, \dots, x_{T-1}|x_T) \cdot p_{\text{latent}}(x_T) \mathbf{d}x_{1:T}$ (likelihood) is intractable to calculate \Rightarrow model trained by maximizing its variational lower bound (ELBO):

$$\begin{aligned} \mathbb{E}_{q_{\text{data}}(x_0)} \log p_\theta(x_0) &\geq \\ &\geq \mathbb{E}_{q(x_0, \dots, x_T)} \log \frac{p_\theta(x_0, \dots, x_{T-1}|x_T) \cdot p_{\text{latent}}(x_T)}{q(x_1, \dots, x_T|x_0)} := \text{ELBO} \end{aligned}$$

DiffWave: advantages

- ▶ **Non-autoregressive**: much faster than WaveNet
- ▶ **Compact model**: smaller footprint than flow-based models
- ▶ No auxiliary losses in training (e.g., spectrogram-based losses): **no mode collapse** like in GANs/VAEs