

Graphs in ML Project Defence

Recommender system with serendipity

Clémence Réda

École Normale Supérieure Paris-Saclay

January 17th, 2019

Introduction Field of research



**This might be a
useful
recommender
system!**

Comic from artist Piccolo

Introduction Field of research



This might be a useless recommender system!

(Adapted) comic from artist Piccolo

Outlines

- 1 Introduction
 - Field of research
 - Goal
- 2 Problem of Serendipity
 - State-of-the-art
 - Formalization of the problem
 - Method
- 3 Results
 - Datasets
 - Setting
 - Quantitative Results
 - Qualitative Results
- 4 Conclusion

1 Introduction

- Field of research
- Goal

2 Problem of Serendipity

- State-of-the-art
- Formalization of the problem
- Method

3 Results

- Datasets
- Setting
- Quantitative Results
- Qualitative Results

4 Conclusion

Introduction Field of research

Accuracy \neq Usefulness!

[Abbassi et al., 2009, Kunaver and Požrl, 2017], ...

Regular recommender problem

Input:

- A user u
- A set of objects V in which the recommended item must belong
- Access to the histories of the user(s): $\{(\text{object}_k, \text{reward}_k)\}_k$

Goal:

Return a recommended item
that maximizes the reward for the seller
(price, probability of buying, ...)

Introduction Field of research

Accuracy \neq Usefulness!

[Abbassi et al., 2009, Kunaver and Požrl, 2017], ...

Recommender problem **with serendipity**

Input:

- A user u
- A set of objects V in which the recommended item must belong
- Access to the histories of the user(s): $\{(\text{object}_k, \text{reward}_k)\}_k$

Goal:

Return a recommended item
that maximizes **both the reward**
and the novelty.

Introduction Field of research

~ *diversity-accuracy dilemma* [Zhou et al., 2010]
→ *exploration-exploitation dilemma* in bandits

Bandits are popular tools to tackle the recommender problem
[Koutrika, 2018, Mary et al., 2015, Guillou et al., 2016].

Multi-Armed Bandit

- 1: Initialize scores associated with each action (*eg* movie)
 - 2: Repeat
 - 3: Compute the score of each action
 - 4: Select the arm/action which maximizes the score
 - 5: Receive the reward and improve the computation of the score
 - 6: **return** the arm associated with the highest score
-

Introduction Objectives of this project

Goals

- 1 Formalize the problem of **recommendation with serendipity**

Introduction Objectives of this project

Goals

- 1 Formalize the problem of **recommendation with serendipity**
- 2 Find a method to tackle this problem

Introduction Objectives of this project

Goals

- 1 Formalize the problem of **recommendation with serendipity**
- 2 Find a method to tackle this problem
- 3 Compare it with other bandit methods

1 Introduction

- Field of research
- Goal

2 Problem of Serendipity

- State-of-the-art
- Formalization of the problem
- Method

3 Results

- Datasets
- Setting
- Quantitative Results
- Qualitative Results

4 Conclusion

State-of-the-art

Several definitions of *serendipity*

[Abbassi et al., 2009, Murakami et al., 2007, laquinta et al., 2008,
Kotkov et al., 2016]

State-of-the-art

Several definitions of *serendipity*

[Abbassi et al., 2009, Murakami et al., 2007, laquinta et al., 2008, Kotkov et al., 2016]

What one would need:

- A flexible definition
- Easy to understand and grasp
- Should fit as much as possible the concept of serendipity

Formalization

- $G(V, E)$ unweighted, undirected object similarity graph
- Histories of the user $\{(\text{object}_k, \text{reward}_k)\}_k$

$f_u^{(k)}$ = explored objects up to time k
 $r_u^{(k)}$ = associated reward received up to time k
 (*random variables*)

Serendipity value

serendipity value of an unexplored object v (of *normalized* reward variable $\tilde{r}_{v,u}^{(k)}$) at time $k > 0$ with respect to user u

$$s(v, u, k) = \mathbb{E}_{(f_u^{(k)}, \tilde{r}_u^{(k)})} [\tilde{r}_{v,u}^{(k)} \times d_e(v, \text{explored}) | (f_u^{(t)}, \tilde{r}_u^{(t)})_{t < k}]$$

Formalization

Serendipity value

serendipity value of an unexplored object v (of *normalized* reward variable $\tilde{r}_{v,u}^{(k)}$) at time $k > 0$ with respect to user u

$$s(v, u, k) = \mathbb{E}_{(f_u^{(k)}, \tilde{r}_u^{(k)})} [\tilde{r}_{v,u}^{(k)} \times d_e(v, \text{explored}) | (f_u^{(t)}, \tilde{r}_u^{(t)})_{t < k}]$$

Thus the set of potential serendipities at time $k > 0$ for user u is denoted S_u

Potential Serendipities

$$S_u = \arg \max \{v \text{ unexplored} : s(v, u, k)\}$$

Method Adapting from Influence Maximization



To whom should products
be given in order to
become viral?

`richardkim.me/
influencemaximization`

Method Adapting from Influence Maximization



To whom should products
be given in order to
become viral?

Online: Learning while
running the marketing
campaign

`richardkim.me/
influencemaximization`

Method Adapting from Influence Maximization



`richardkim.me/
influencemaximization`

To whom should products be given in order to become viral?

Online: Learning while running the marketing campaign

Persistent: Once a node is explored, it does not yield a reward anymore

Method Algorithm from [Lagrée et al., 2017]

Score:

$$b_k(t) = \hat{R}_k(t) + \left(1 + \sqrt{2}\right) \sqrt{\frac{\hat{\lambda}_k(t) \log(4t)}{n_k(t)}} + \frac{\log(4t)}{3n_k(t)}$$

Require: Set of candidates $[K]$, time budget N

- 1: **Initialization:** play each candidate $k \in [K]$ once, observe the spread $S_{k,1}$, set $n_k = 1$
 - 2: For each $k \in [K]$: update the reward $W = W \cup S_{k,1}$
 - 3: **for** $t = K + 1, \dots, N$ **do**
 - 4: Compute $b_k(t)$ for every candidate k
 - 5: Choose $k(t) = \arg \max_{k \in [K]} b_k(t)$
 - 6: Play candidate $k(t)$ and observe spread $S(t)$
 - 7: Update cumulative reward: $W = W \cup S(t)$
 - 8: Update statistics of candidate $k(t)$: $n_{k(t)}(t+1) = n_{k(t)}(t) + 1$ and $S_{k,n_{k(t)}} = S(t)$.
 - 9: **end for**
 - 10: **return** W
-

Method Adapted algorithm

Apply the serendipity constraint on the set of candidates (and their supports) selected in [Lagrée et al., 2017]'s algorithm, parametrized by value s .

- 1: $S \leftarrow \text{Supp}(f_u^{(t)}) \cap \{c \in V : \exists i, 1 \leq i \leq s, W^i[c, \text{Supp}(f_u^{(t)})] \mathbf{1} > 0\}$
- 2: $\text{centroids} \leftarrow \text{Kmeans}(\text{data} = F[S, :], \text{nclusters} = K)$
- 3: $\text{candidates} \leftarrow \emptyset$
- 4: **for** $c \in \text{centroids}$ **do**
- 5: Append $\arg \min_{v \in S} \|F[v, :] - F[c, :]\|_2^2$ to candidates
- 6: **end for**
- 7: $\text{supports} \leftarrow \emptyset$
- 8: **for** $v \in \text{candidates}$ **do**
- 9: Append $\{v' \in S : W[v, v'] > 0\}$ to supports
- 10: **end for**
- 11: **return** candidates, supports

1 Introduction

- Field of research
- Goal

2 Problem of Serendipity

- State-of-the-art
- Formalization of the problem
- Method

3 Results

- Datasets
- Setting
- Quantitative Results
- Qualitative Results

4 Conclusion

Movie recommendation! data on users, movies, and ratings

[illegible]

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ▶ ↺ 🔍 ↻

MovieLens (ml-1m, ml-20m)



- **MovieLens 1M Dataset (ml-1m)**

#movies	#users	average #ratings/user
4,000	6,000	165

- **MovieLens 20M Dataset (ml-20m)**

#movies	#users	average #ratings/user
27,000	138,000	144

Benchmark on *MovieLens* (ml-1m, ml-20m)

Evaluation on 100 iterations and at horizon 100

Cumulative regret

$a^{(t)}$ is the recommended item at time t :

$$R_T = \sum_{t \leq T} \max\{a^* \text{ explored} : r(a^*) - r(a^{(t)})\}$$

Benchmark on *MovieLens* (ml-1m, ml-20m)

Evaluation on 100 iterations and at horizon 100

Cumulative regret

$a^{(t)}$ is the recommended item at time t :

$$R_T = \sum_{t \leq T} \max\{a^* \text{ explored} : r(a^*) - r(a^{(t)})\}$$

Diversity measure ([Vie, 2016])

t is the number of rounds, $V^{(t)}$ is the feature matrix of explored objects up to time t

$$D(V^{(t)}) = \sqrt{|V^{(t)} \cdot t(V^{(t)})|}$$

Benchmark on *MovieLens* (ml-1m, ml-20m)

Algorithms

Tested bandit methods

- 1 Random strategy

Benchmark on *MovieLens* (ml-1m, ml-20m)

Algorithms

Tested bandit methods

- 1 Random strategy
- 2 ϵ -greedy strategy (w.r.t. diversity measure)

Benchmark on *MovieLens* (ml-1m, ml-20m)

Algorithms

Tested bandit methods

- 1 Random strategy
- 2 ϵ -greedy strategy (w.r.t. diversity measure)
- 3 LinUCB (described in [Chu et al., 2011])

Benchmark on *MovieLens* (ml-1m, ml-20m)







Algorithms

Tested bandit methods

- 1 Random strategy
- 2 ϵ -greedy strategy (w.r.t. diversity measure)
- 3 LinUCB (described in [Chu et al., 2011])
- 4 The adapted method from [Lagrée et al., 2017]







Results Regret, diversity, serendipity curves

ml-20m dataset, random (*top*) and ϵ -greedy methods






Results Regret, diversity, serendipity curves

ml-20m dataset, adapted method (*top*) and LinUCB methods






Results Variation of parameter s



Remarks:

- When s increases (up to some point), diversity increases and regret decreases




Results Variation of parameter s



Remarks:

- When s increases (up to some point), diversity increases and regret decreases
- From some value of s , regret increases again

Results Variation of parameter s



Remarks:

- When s increases (up to some point), diversity increases and regret decreases
- From some value of s , regret increases again
- Little influence of s on the (cumulative) serendipity value...

1 Introduction

- Field of research
- Goal

2 Problem of Serendipity

- State-of-the-art
- Formalization of the problem
- Method

3 Results

- Datasets
- Setting
- Quantitative Results
- Qualitative Results

4 Conclusion

Outlook

- 1 A measure for serendipity

Outlook

- 1 A measure for serendipity
- 2 A method that tackles the problem of recommendation with serendipity

Outlook

- 1 A measure for serendipity
- 2 A method that tackles the problem of recommendation with serendipity
- 3 Benchmark with classic/naive methods of recommendation

Outlook

- 1 A measure for serendipity
- 2 A method that tackles the problem of recommendation with serendipity
- 3 Benchmark with classic/naive methods of recommendation

What remains to be done

- Testing with methods that might be more relevant: Rotting Bandits [Seznec et al., 2018], Outside-The-Box recommendation [Abbassi et al., 2009]

Outlook

- 1 A measure for serendipity
- 2 A method that tackles the problem of recommendation with serendipity
- 3 Benchmark with classic/naive methods of recommendation

What remains to be done

- Testing with methods that might be more relevant: Rotting Bandits [Seznec et al., 2018], Outside-The-Box recommendation [Abbassi et al., 2009]
- User similarity has been ignored here




Outlook

- 1 A measure for serendipity
- 2 A method that tackles the problem of recommendation with serendipity
- 3 Benchmark with classic/naive methods of recommendation

What remains to be done

- Testing with methods that might be more relevant: Rotting Bandits [Seznec et al., 2018], Outside-The-Box recommendation [Abbassi et al., 2009]
- User similarity has been ignored here
- The parametrization with the serendipity threshold s has an influence on regret and diversity, but not so much on the serendipity measure!!

References I

-  Abbassi, Z., Amer-Yahia, S., Lakshmanan, L. V., Vassilvitskii, S., and Yu, C. (2009).
Getting recommender systems to think outside the box.
In Proceedings of the third ACM conference on Recommender systems, pages 285–288. ACM.
-  Chu, W., Li, L., Reyzin, L., and Schapire, R. (2011).
Contextual bandits with linear payoff functions.
In Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, pages 208–214.
-  Guillou, F., Gaudel, R., and Preux, P. (2016).
Large-scale bandit recommender system.
In International Workshop on Machine Learning, Optimization and Big Data, pages 204–215. Springer.

References II



Iaquinta, L., De Gemmis, M., Lops, P., Semeraro, G., Filannino, M., and Molino, P. (2008).

Introducing serendipity in a content-based recommender system.

In Hybrid Intelligent Systems, 2008. HIS'08. Eighth International Conference on, pages 168–173. IEEE.



Kotkov, D., Wang, S., and Veijalainen, J. (2016).

A survey of serendipity in recommender systems.




Knowledge-Based Systems, 111:180–192.



Koutrika, G. (2018).

Recent advances in recommender systems: Matrices, bandits, and blenders.

References III

-  Kunaver, M. and Požrl, T. (2017).
Diversity in recommender systems—a survey.
Knowledge-Based Systems, 123:154–162.
-  Lagrée, P., Cappé, O., Cautis, B., and Maniu, S. (2017).
Effective large-scale online influence maximization.
In *Data Mining (ICDM), 2017 IEEE International Conference on*,
pages 937–942. IEEE.
-  Mary, J., Gaudel, R., and Preux, P. (2015).
Bandits and recommender systems.
In *International Workshop on Machine Learning, Optimization
and Big Data*, pages 325–336. Springer.

References IV



Murakami, T., Mori, K., and Orihara, R. (2007).

Metrics for evaluating the serendipity of recommendation lists.
In Annual conference of the Japanese society for artificial intelligence, pages 40–46. Springer.



Seznec, J., Locatelli, A., Carpentier, A., Lazaric, A., and Valko, M. (2018).

Rotting bandits are no harder than stochastic ones.
arXiv preprint arXiv:1811.11043.



Vie, J.-J. (2016).

Modèles de tests adaptatifs pour le diagnostic de connaissances dans un cadre d'apprentissage à grande échelle.
PhD thesis, Université Paris-Saclay.

References V



Zhou, T., Kuscsik, Z., Liu, J.-G., Medo, M., Wakeling, J. R., and Zhang, Y.-C. (2010).

Solving the apparent diversity-accuracy dilemma of recommender systems.

Proceedings of the National Academy of Sciences,
107(10):4511–4515.