



[Course](#) > [Week 7...](#) > [Compr...](#) > Quiz 7

Quiz 7

Problem 1

1/1 point (graded)

Suppose we use a basis expansion $\Phi(x)$ for the purposes of getting a quadratic decision boundary. For two-dimensional data, we can do this by expanding to five features. What decision boundary is represented by $w \cdot \Phi(x) + b = 0$ for $w = (2, 1, 2, -1, 0)$ and $b = -1$?

☐ $2x_1^2 + x_2^2 + 2x_1 - x_2 - 1 = 0$

☐ $2x_1^2 + x_1 + 2x_2^2 - x_2 - 1 = 0$

☒ $2x_1 + x_2 + 2x_1^2 - x_2^2 - 1 = 0$

☐ $2x_1 + x_1^2 + 2x_2 - x_2^2 - 1 = 0$



Submit

Problem 2

1/1 point (graded)

True or false: When using a basis expansion of $x \in \mathbb{R}^6$ to get a quadratic boundary, the expanded feature vector $\Phi(x)$ has 36 pairwise features of the form x_1x_6 or x_2x_4 .

Loading [MathJax]/jax/output/HTML-CSS/fonts/STIX/Variants/Regular/All.js

☐ True☒ False

Problem 3

1/1 point (graded)

We want to use basis expansion of two-dimensional inputs $x = (x_1, x_2)$ to get a quadratic boundary. If the target boundary is given by the equation

$(x_1 - 2)^2 + (x_2 - 1)^2 = 16$, what is the coefficient vector, w , and constant, b , such that the boundary has the form $w \cdot \Phi(x) + b = 0$?

☒ $w = (-4 \quad -2 \quad 1 \quad 1 \quad 0), b = -11$ ☐ $w = (-4 \quad -2 \quad 1 \quad 1 \quad 0), b = -16$ ☐ $w = (1 \quad 1 \quad -4 \quad -2 \quad 5), b = -11$ ☐ $w = (1 \quad -2 \quad 1 \quad -11 \quad 0), b = 16$ 

Problem 5

1/1 point (graded)

For 12-dimensional x , what is the dimension of the basis expansion $\Phi(x)$ that we use for getting a quadratic boundary?

Loading [MathJax]/jax/output/HTML-CSS/fonts/STIX/Variants/Regular/All.js

☐ 24☐ 57☒ 90☐ 144

Problem 6

1/1 point (graded)

Given a data set with n data points, each of d dimensions, what is the dimension of the vector, α , which is used in the dual form of the perceptron algorithm?

☐ d ☒ n ☐ d^2 ☐ n^2 

Problem 7

Loading [MathJax]/jax/output/HTML-CSS/fonts/STIX/Variants/Regular/All.js

Given vectors $\mathbf{v}_1, \mathbf{v}_2$, which of the following expressions can be used in place of \mathbf{v}_1 , where is the basis expansion used for a quadratic boundary?

☐ [Math Processing Error]

☐

☒

☐

✓

Submit

Problem 8

1/1 point (graded)

Which vector are we solving for when using the dual form of the SVM?

☐

w

☒

α

☐

x

☐

none of the above

✓

Submit

Problem 9

1/1 point (graded)

Loading [MathJax]/jax/output/HTML-CSS/fonts/STIX/Variants/Regular/All.js

Which expression(s) can be used to classify a new point with the kernel SVM? Select all that apply.



$$\text{sign} \left(\sum_{i=1}^n \alpha_i y^{(i)} (\Phi(x^{(i)}) \cdot \Phi(x)) + b \right)$$



$$\text{sign} \left(\sum_{i=1}^n w \cdot \Phi(x^{(i)}) + b \right)$$



$$\text{sign} (w \cdot \Phi(x) + b)$$



$$\text{sign} \left(\sum_{i=1}^n (\Phi(x^{(i)}) \cdot \Phi(x)) + b \right)$$



Submit

Problem 10

1/1 point (graded)

If you are finding a degree 4 decision boundary and if $x \in \mathbb{R}^7$, then the term $x_1 x_3 x_4 x_7^2$ is part of the expanded feature vector, $\Phi(x)$.

☐ True

☒ False



Submit

Problem 11

1/1 point (graded)

Which is/are the correct kernel function(s), $k(x, y)$, that is used to find a degree 3 polynomial decision boundary.

Loading [MathJax]/jax/output/HTML-CSS/fonts/STIX/Variants/Regular/All.js

Φ



$$k(x, z) = x \cdot z$$



$$k(x, z) = (1 + x \cdot z)^3$$



$$k(x, z) = \Phi(x) - \Phi(z)$$



$$k(x, z) = (1 + \Phi(x) \cdot \Phi(z))^3$$



Submit

Problem 12

1/1 point (graded)

Vectors that produce high values with the kernel function are more similar or less similar than vectors that produce low values?

☒ More similar

☐ Less similar

☐ Not a measure of similarity



Submit

Problem 13

1/1 point (graded)

True or false: Decision trees typically perform best when they are grown until the training error is .

Loading [MathJax]/jax/output/HTML-CSS/fonts/STIX/Variants/Regular/All.js

☐ True☒ False

Problem 14

1/1 point (graded)

Overfitting the data with a decision tree will result in which of the following?

☐ Training error going up☒ Training error going down☒ Test error going up☐ Test error going down

Problem 15

1/1 point (graded)

True or false: When decision stumps are used as weak classifiers for AdaBoost, the final decision boundary is linear.

☐ True

☒ False

© All Rights Reserved

Loading [MathJax]/jax/output/HTML-CSS/fonts/STIX/Variants/Regular/All.js