

## CREATING A KERNEL

1.

```
GNU nano 8.7.1 simplecommand.c
#include<stdio.h>
#include<unistd.h>
#include<string.h>

int main()
{
char command[100];
while(1)
{
printf("VISHNU_SHELLFORGES$");
fgets(command,sizeof(command),stdin);
command[strcspn(command, "\n")]='\0';

if(strcmp(command, "exit")==0)
break;

printf("you entered %s \n",command);
}

return 0;
}
```

[ Read 21 lines ]

|                |                     |                    |                 |                   |                      |                 |                     |
|----------------|---------------------|--------------------|-----------------|-------------------|----------------------|-----------------|---------------------|
| <b>^G</b> Help | <b>^O</b> Write Out | <b>^F</b> Where Is | <b>^K</b> Cut   | <b>^T</b> Execute | <b>^C</b> Location   | <b>M-U</b> Undo | <b>M-A</b> Set Mark |
| <b>^X</b> Exit | <b>^R</b> Read File | <b>^I</b> Replace  | <b>^U</b> Paste | <b>^J</b> Justify | <b>^_</b> Go To Line | <b>M-E</b> Redo | <b>M-6</b> Copy     |

Output:

```
bash: /usr/bin/nano: No such file or directory
vishnu@VISHNU:~$ nano simplecommand.c
vishnu@VISHNU:~$ gcc simplecommand.c -o simplecommand
vishnu@VISHNU:~$ ./simplecommand
VISHNU_SHELLFORGES$
```