

2520030199
K.VISHNU

```
vishnu@VISHNU: ~  
GNU nano 8.7.1 socketserver.c  
#include <stdio.h>  
#include <unistd.h>  
#include <sys/socket.h>  
#include <sys/un.h>  
#include <string.h>  
  
#define SOCKET_PATH "/tmp/my_socket"  
  
int main()  
{  
    int server_fd, client_fd;  
    struct sockaddr_un address;  
    char buffer[100];  
  
    // Create socket  
    server_fd = socket(AF_UNIX, SOCK_STREAM, 0);  
  
    // Set socket address  
    address.sun_family = AF_UNIX;  
    strcpy(address.sun_path, SOCKET_PATH);  
  
    // Remove old socket  
    unlink(SOCKET_PATH);  
  
    // Bind socket to path  
    bind(server_fd, (struct sockaddr *)&address, sizeof(address));  
  
    // Wait for client  
    listen(server_fd, 5);  
  
    printf("Server waiting...\n");  
  
    // Accept client  
    client_fd = accept(server_fd, NULL, NULL);  
  
    // Receive message  
    read(client_fd, buffer, sizeof(buffer));  
  
    printf("Message from client: %s\n", buffer);  
  
    close(client_fd);  
    close(server_fd);  
  
    unlink(SOCKET_PATH);  
}  
  
[ Read 47 lines ]  
^G Help      ^O Write Out  ^F Where Is   ^K Cut        ^T Execute  
^X Exit      ^R Read File  ^\ Replace    ^U Paste      ^J Justify  
vishnu@VISHNU:~$ ls -lt | grep socketserver  
-rwxr-xr-x 1 vishnu vishnu 16352 Sep  3 03:37 socketserver  
-rw-r--r-- 1 vishnu vishnu  922 Sep  3 03:34 socketserver.c  
vishnu@VISHNU:~$ ./socketserver  
Server waiting...  
Message from client: Hello Server  
vishnu@VISHNU:~$ |
```

2520030199
K.VISHNU

```
vishnu@VISHNU: ~  
GNU nano 8.7.1 socketclient.c  
#include <stdio.h>  
#include <unistd.h>  
#include <sys/socket.h>  
#include <sys/un.h>  
#include <string.h>  
  
#define SOCKET_PATH "/tmp/my_socket"  
  
int main()  
{  
    int client_fd;  
    struct sockaddr_un address;  
  
    // Create socket  
    client_fd = socket(AF_UNIX, SOCK_STREAM, 0);  
  
    // Set socket address  
    address.sun_family = AF_UNIX;  
    strcpy(address.sun_path, SOCKET_PATH);  
  
    // Connect to server  
    connect(client_fd,  
            (struct sockaddr *)&address,  
            sizeof(address));  
  
    // Send message  
    write(client_fd, "Hello Server", 12);  
    printf("Message sent to server.\n");  
  
    close(client_fd);  
  
    return 0;  
}  
  
[ Read 33 lines ]  
^G Help      ^O Write Out  ^F Where Is   ^K Cut        ^T Execute  
^X Exit      ^R Read File  ^\ Replace    ^U Paste      ^J Justify
```

```
vishnu@VISHNU: ~  
vishnu@VISHNU:~$ nano socketclient.c  
vishnu@VISHNU:~$ gcc socketclient.c -o socketclient  
vishnu@VISHNU:~$ ./socketclient  
Message sent to server.  
vishnu@VISHNU:~$ |
```