


You




→ Extra cost



→ No extra cost



→ Extra time → No extraction



## Automatic memory management & Garbage collector:



aaa.py ↴


$$a = 5$$

$$b = 6$$

bbb.py ↴

$$x = 2$$

$$y = 3$$




$$x = 2$$

$$y = 4$$

$$z = 2$$

$$p = 2$$



$\rightarrow a = \underline{2}$


$\rightarrow b = \underline{4}$

$\rightarrow \text{print}(\underline{a})$

$\rightarrow \text{print}(a, \underline{b})$


$\rightarrow \text{print}('abc' \underline{c})$

$\rightarrow$




Scf = '\_' end = '\n'

Comments in Python:-




#



Single line

Comment



Multi line comment

. " " " = " "

. " " " = " "

→

" " "

## Data type in Python:

### Number

int  $\rightarrow$  -n to +n

float  $\rightarrow$  -n.n to +n.n

complex  $\rightarrow$   $2+9j$   
 $\rightarrow$   
real imag

$j \rightarrow \sqrt{-1}$ .

String :

'2'  
"2"  
'''2'''  
""2""

collection of charact -

'abc' → strg

'a' → str

-3	-2	-1
a	b	c
0	1	2

x : 'abc'

x ↴


x[0] or x[-3])

↳ 'a'

x[-2] or x[1] ↴ b,

x[-1] or x[2] ↴ c,

$a = [2, 64, 25, 81, 'abc', \text{True}]$



$\ln[\underline{\text{start}} : \underline{\text{stop}} : \underline{\text{step}}]$

$a[-5 : -2 : 1]$

$[64, 25, 81]$

$$2 - 1 = (1,)$$
$$3 - 2 = (1,)$$

$$-4 + 5 = 1$$

$a[1 : 4 : ]$

$a[-5 : 4 : 1]$

$a[1 : -2 : 1]$



$-5$	$4$	$2$	$-2$	$-1$
$24$	$81$	$61$	$92$	$85$
$\div$				$4$

$$4 - 0 = \textcircled{4}$$

$[24, 85]$

$x[0:5:4]$

$x[-5:5:4]$



$$[28, 65, 24]$$

$$y[5:-6:-2]$$

$$y[-1:0:-2]$$

$$[28, 61]$$

$$y[5:-7:-5]$$

$$y[-1:-7:-5]$$

$$0 - 5 \rightarrow -5$$

Start

M:N:L

M

M

M

M

0

0

0

0

Stop

N-1

N-1

len(a) - 1

"

N-1

N-1

len(a)-1

"

Step

L

+1

+1

L

L

+1

L

+1

$$a = \boxed{2 \mid 8 \mid 4 \cdot 5 \mid 6 \cdot 1 \mid 2 \cdot 9} \quad \begin{matrix} \downarrow & \downarrow & \downarrow & \downarrow & \downarrow \\ 0 & 1 & 2 & 3 & 4 \end{matrix}$$

a[1:5:2]  $\rightarrow [8, 6]$

a[2:5]  $\rightarrow$

list-name [ start : stop : step ]


a =

-6	-5	-4	-3	-2	-1
2	8	9	27	67	25
0	1	2	3	4	5

[ 2, 8, 9 ]

a[0:3:1]

Slicing  $L \rightarrow R$



Start  $\rightarrow 0$

Stop  $\rightarrow -1$

Step  $\rightarrow +1$

Slicing  $R \rightarrow L$



start  $\rightarrow -1$

stop  $\rightarrow 0$

step  $\rightarrow -1$

$$a = \left[ \begin{array}{cccccc|c} 2 & -6 & -5 & -4 & -3 & -2 & -1 \\ 2 & | & 9 & 61 & 28 & 49 & 62 \\ \hline 0 & 1 & 2 & 3 & 4 & 5 & 6 \end{array} \right] \rightarrow$$

$$a[1:6:3] \rightarrow [9, 49]$$

$$a[1:6] \rightarrow [9, 61, 28, 49, 62] \\ \rightarrow$$

$$a[1:] \rightarrow [9, 61, 28, 49, 62, 40]$$

if step →  $\frac{+}{-}$   
 L to R

$\frac{-}{+}$   
 R to L

$a =$
$\begin{array}{ccccccc} -7 & -6 & -4 & -3 & -2 & -1 \\ \hline 6 & 81 & 26 & 49 & 82 & 83 & 45 \\ \hline 10 & 1 & 2 & 3 & 4 & 5 & 6 \end{array}$
$a[::] \rightarrow [4, 81, 26, 49, 82, 83, 45]$
$a[6:-2:-1] \Rightarrow [45, 83, 82, 49, 26, 81, 4]$
$a[5:1] \rightarrow []$
$a[5:] \rightarrow [83, 45]$

$89$

$a[:, :-1] \rightarrow [45, 83, 82, 49, 26, 81, 4]$

$a[2:89:-2] \rightarrow [26, 82, 45]$

$a[-24:-2] \rightarrow [45, 82, 26, 4]$

## Adding elements

append() → add one element at last of the list

insert() → add one element at your desired location

extend() → add more than one element at last of the list  
,

## Removing elements

pop() → remove one element by using index from list

remove() → remove one element ————— value from list

del → remove one or more than one

clear() → remove all —————


## other methods

- {
  - index() → accoring index value
  - count() → occur of any el
  - reverse() → give the element
  - sort() → sorting into ascend or descend <sup>ord</sup>
  - copy()

$$a = 2$$

$$b = 6$$

$$\begin{matrix} c \\ - \end{matrix} = 2$$




$a = [11, 22]$

$b = [33, 44]$

$c = a$

$a.append(22)$

$c = a.copy()$



Tuple : Collection of heterogeneous type of data,  
indexed, ordered, immutable (unchangeable).

$a[-1][1]$

$$a = (2, 2.5, \text{True}, 3+9j, [2, 5, 6])$$

$a[0:3:1]$

-5	-4	-3	-2	-1
2	2.5	True	$3+9j$	$[2, 5, 6]$
0	1	2	3	4
-3	-2	-1	0	1

$a[-1][::2] \rightarrow [2, 5]$

-4	2	-1
9	5	6
0	1	2

$a[0] \rightarrow 2$

$a[-5] \rightarrow 2$

$a[-3] \rightarrow a[2]$

$a[3].real \rightarrow 3.0$


$a[-2].imag \rightarrow 9.0$

Dictionary :- collection of heterogeneous type of  
data, unindexed, ordered, mutable...

Key : Value , Key Unique, -- , { }

```
Student = { name : 'Manoj',  
            age : 12,  
            sub : ['maths', 'chem', 'Python']  
        }
```

remove :

{ clear ()  
del  
popitem ()  
pop 

Nested dictionary :-

dictionary inside dictionary

Set :- Collection of immutable - like of data ,  
unique , mutable , { } , unordered , indexed

$$a = \{ 8, 2.5, \text{True}, 2+3j, (2,5,6) \}$$

$$a1 = \{ 2, 5, 6, 2, 8, 1 \} \quad \text{error X}$$

$$\{ 2, 5, 6, 8, 1 \}$$

Union

$$S_1 = \{1, 2, 3, 4\}$$

intersection

$$S_2 = \{3, 4, 5, 6\}$$


difference

symmetric

$$S_1 - S_2 = \{1, 2\}$$

$$S_2 - S_1 = \{5, 6\}$$

$$S_1 \cap S_2 = \{3, 4\}$$



$$S_1 \cup S_2$$

$$\{ \cancel{1}, \cancel{2}, \cancel{3}, 4, \cancel{3}, 4, 5, 6 \}$$

$$\{ \cancel{1}, \cancel{2}, \cancel{3}, 4, 5, 6 \}$$

adding element in set :

add → 1 element

update → more than 1 el.

del el.

discard()

remove()

pop()

del


$$a = \{1, 2, 3, 4\}$$

$$b = \{3, 4, 5, 6\}$$

$$a.\text{difference}(b) = \{1, 2\}$$

$$a = \{1, 2, 3, 4\}$$

$$b = \{3, 4, 5, 6\}$$



$$\begin{aligned} a.\text{diff\_update}(b) &= \{1, 2\} \\ \uparrow & \end{aligned}$$

$$a = \{1, 2\}$$

$$b = \{3, 4, 5, 6\}$$

Boolean :- True , False  
                  |            0

logical operator :- and, or, not, xor -----

$i_1$   $i_2$  and  $o$   $xor$   
0 0 0 0 0  
0 1 0 1 1  
1 0 0 1 1  
1 1 1 1 0


not 0  $\rightarrow$  1  
1  $\rightarrow$  0

and  $\rightarrow$  logical operators

$$a = 20$$

$$b = 4$$

$a \text{ and } b \Rightarrow 4$



$$\begin{array}{rcl} 20 & \rightarrow & 10100 \\ 4 & \rightarrow & 100 \end{array}$$

$$10100$$

$$\begin{array}{rcl} 2 & | & 4 \\ 2 & | & 20 \\ 2 & | & 20 \\ 1 & & \end{array}$$

$$\begin{array}{rcl} 2 & | & 20 \\ 2 & | & 100 \\ 2 & | & 50 \\ 2 & | & 21 \\ 2 & | & 10 \\ 1 & & \end{array}$$

$a = 2$

$b = 4$

$a+b \rightarrow 6$


input( )



string

str  $\rightarrow$  num

process of converting one data-type into  
another -type of data -



a = 'a'

$a: 'a' \rightarrow \text{int} \quad \text{str}$

`int(a)`

## Control Statement:

if

if - else

if - elif - else

nested if

  ↳

if True / false  
condition :

{  
==  
=  
=



if - elif - else :

if <sup>T/f</sup> condite :

{ == }

→ elif <sup>T/f</sup> condition :

{ == }

→ elif <sup>T/f</sup> condite :


{ == }

→ else :



Nested if.

if inside if



$a, b, c = 2, 5, 9$

if ( $a \geq b$  and  $a \geq c$ ):

print('a is greater than b and c')  
→

$2 \geq 5$  and  $2 \geq 9$

f and f → f

Project - I

Quiz Game

Loop :- Repetation of statement

While

for


While loop :-

→ abc  
ab c }  
ab c }  
ab c }  
ab c }

initialization  
condition  
iter/decy

$\rightarrow \text{print('abc')}$

$a = 1$



$a = 1$

$1 \leq 6 \ T$

$a = 2$

$2 \leq 6 \ T$

$a = 3$

$3 \leq 6 \ T$

$a = 4$


$4 \leq 6 \ T$

$a = 5$

$5 \leq 6 \ T$

$a = 6$

$6 \leq 6 \ F$



$\rightarrow .1:$   
 $\left. \begin{array}{c} +1 \\ 2+1 \\ 3+1 \end{array} \right\}$   
u.  
;  
;

$a = 1$   
While  $a < 11:$   
 $\left. \begin{array}{c} \text{print}(a) \\ a = a + 1 \quad \text{or} \quad a + 1 \end{array} \right\}$

$a = 1$   
 $1 < 11 \top$   
 $2 < 11 \top$   
 $3$

10  
12  
1

$\rightarrow 5 - 1$

$4 - 1$

$3 - 1$

$2 - 1$

!

$a = 5$

$\rightarrow$  While  $a > 0$ :

$\rightarrow \text{print}(a)$

$a = a - 1$  or  $a - 1$

$a = 5$

$5 > 0 \top$

$a = 4$

$4 > 0 \top$

$\overline{5}$

14

13

1

$$\rightarrow \begin{array}{r} 2 + 2 \\ - 4 + 2 \\ \hline 6 + 2 \end{array}$$

8

10

12

14

16

18

 $\Rightarrow 20$ 

$$a = 2 + 2$$

$$a <= 20 \top$$

$$a = 4$$

$$4 <= 20 \top$$

$$a = 6$$

.

,

/

$$a = 2$$

while  $a <= 20$  :

$\rightarrow \text{print}(a)$

$$a = a + 2$$

$$\begin{array}{r} 2 \\ | 4 \\ 1 \end{array}$$

$$2 \times 1 = 2$$

$$2 \times 2 = 4$$

$$2 \times 3 = 6$$

.

.

.

.

$$2 \times 10 = 20$$

$$a = 1$$

while  $a <= 10:$

print(  
a \* 2)

$$a = 1$$

$$L = 10T$$

$$a + 1$$

$$1 \times 2 = 2$$

$$a = 2$$

$$2 < 10 T$$

$$2 \times 2 = 4$$

1

2

3

4

5

6

7

8

9

10

1  
2  
3  
4

1  
2  
3  
4

1  
2  
3  
4

1  
2  
3  
4

Nested while loop:

while loop inside while loop

while

while

while —

—  
—


\* \* \* \*

\* \* \* \*

\* \* \* \*

-

\*  
\* \*  
\* \* \*  
\* \* \* \*

1 2 3 4  
1.  $\rightarrow$    $\rightarrow a = 1$

2.  $\ast \times \ast \ast$

3.  $\ast \ast \times \ast$

while  $a < 3 :$

$\rightarrow b = 1$

while  $b <= 4 :$

$\text{print}(\text{"*"}, \text{end}=\text{" "})$

$b += 1$

$\text{print}()$

$a = a + 1$

	1	2	3	4
$\rightarrow 1$	*			
$\rightarrow 2$	*	*		
$\rightarrow 3$	*	*	*	
$\rightarrow 4$	*	*	*	*

```

row = 1
while row <= 4:
    col = 1
    while row >= col:
        print("*", end="")
    col += 1
    row += 1

```

row	col
1	= 1
2	=> 1 2
3	=> 1 2 3
4	=> 1 2 3 4

$\text{print}()$   
 $\text{row} += 1$

{ \* \* \*  
\* \* \*  
\* \*  
\*

Try to do it by yourself

all the best



for loop :-

for var in Sequence :  
    range  
        membership  
        operator

Keyword      Variable      =

list  
tuple  
set

string

## Membership operator :-

in      }  
not in    }  
          } True  
          } False

$x = [2, 5, 'abc', 29]$

2 in x True

'abc' in x True

21 in x False

5 not in x False  
29 not in x True  
50 not in x True

Identity operator is  $\left\{ \begin{array}{l} \text{is} \\ \text{is not} \end{array} \right\}$  true  
false

$$a = 2$$

$$b = 5$$

$$c = 2$$

$a, c$	$b$
2 =	5 -

$a \text{ is } c$  True

$a \text{ is } b$  false

$$\rightarrow \text{id}(a) \neq \text{id}(b)$$

$\underline{a} \text{ is not } \underline{c}$  False

$a \text{ is not } b$  True

for  $x$  in  $[2, 8, 5, 'abc']$  :


{ point (' $xy2$ ')  $\Rightarrow$

$2$  in  $[2, 8, 5, 'abc']$  True

$8$  in " " True

$5$  in " " True

'abc' in " " True



`range( start, stop , step )`

0


x

+1 -1

`range( 0, 5, 1 )`

0 1 2 3 4

`range( 2, 10, 2 )`



( 2, 4, 6, 8 )

$\text{rang } \tau(10, 2, -1)$

10 9 8 7 6 5 4 3

1 X2

2

3 X5

4

.

,

;

10

for i in range(1, 11):

font(X)

1

2


3

4

;

10

Nested for loop :-

0  \* \* \* \*

1 \* \* \* \*

\* \* \* \*

for i in range(3) :

    \* \* \* \*

	0	1	2	3
0	*	*	*	*
1	*	*	*	*
2	*	*	*	*

for row in range(3):

    for col in range(4):

        print("\*", end="")

    ()

for row in range(1, 5) :

0	→	1	*
1	.	2	* *
2	.	3	* * *
3	.	4	* * *

for col in range(row) :

(n(\*, end))

both

\* \* \* \*

\* \* \*

\* \*

\*

## file Handling :-

Open()

Write()

Read()

close()

mode.

'r' → read

'w' → write / create

'a' → append


'rb'

'wb' =

## function in Python :-

Block of code , by which you can perform a specific task -

plumber →  2-3 years.



defining a function → { ≡ }


calling a funcn →

function -name( )


```
def name():
    print ('Hello')
    print ("My name is Malleka")
    print ('Bye')
```

```
name()
name()
Hello
|
|
```

# Types of function



user defined



Anonymous function:-

function without name

or

nameless fun<sup>t</sup>

[lambda]

def add(a,b):  
 print(a+b)

lambda a,b : a+b