

Tên: Thái Nguyên Quốc

MSSV: 079206015807

Câu 4:

Exercise 4: What is the purpose of the “def” keyword in Python?

- a) It is slang that means “the following code is really cool”
- b) It indicates the start of a function
- c) It indicates that the following indented section of code is to be stored for later
- d) b and c are both true
- e) None of the above

Câu trả lời là **d) b and c are both true.**

Câu 5:

Exercise 5: What will the following Python program print out?

4.14. EXERCISES

```
def fred():  
    print("Zap")
```

```
def jane():  
    print("ABC")
```

```
jane()  
fred()  
jane()
```

- a) Zap ABC jane fred jane
- b) Zap ABC Zap
- c) ABC Zap jane
- d) ABC Zap ABC
- e) Zap Zap Zap

Câu trả lời là **d) ABC Zap ABC**

Câu 6:

Exercise 6: Rewrite your pay computation with time-and-a-half for overtime and create a function called `compute_pay` which takes two parameters (`hours` and `rate`).


Enter Hours: 45
Enter Rate: 10
Pay: 475.0

Câu trả lời:

```
> def computepay(a, b):  
    c = (a-40)*(b*1.5)  
    if a<=40:  
        print('Pay: ',a*b)  
    else:  
        print('Pay:', 40*b+c)  
a=int(input('Enter Hours:'))  
b=int(input('Enter Rate:'))  
print('Enter Hours: ',a)  
print('Enter Rate: ',b)  
  
computepay(a, b)
```

[41]

```
... Enter Hours: 45  
Enter Rate: 10  
Pay: 475.0
```



Câu 7:

Exercise 7: Rewrite the grade program from the previous chapter using a function called `computegrade` that takes a score as its parameter and returns a grade as a string.

Score	Grade
> 0.9	A
> 0.8	B
> 0.7	C
> 0.6	D
<= 0.6	F

Program Execution:

```
Enter score: 0.95
A
```

```
Enter score: perfect
Bad score
```

```
Enter score: 10.0
Bad score
```

```
Enter score: 0.75
C
```

```
Enter score: 0.5
F
```

Run the program repeatedly to test the various different values for input.

Câu trả lời:

```
def computegrade(a):  
    if a < 0 or a > 1.0:  
        return('Bad score')  
    elif a > 0.9:  
        return('A')  
    elif a > 0.8:  
        return('B')  
    elif a > 0.7:  
        return('C')  
    elif a > 0.6:  
        return('D')  
    else:  
        return('F')  
  
try:  
    a=float(input())  
    print('Enter Score: ',a)  
    print(computegrade(a))  
except ValueError:  
    print('Error')
```

✓ 4.3s

Enter Score: 10.0
Bad score

```
def computegrade(a):  
    if a < 0 or a > 1.0:  
        return('Bad score')  
    elif a > 0.9:  
        return('A')  
    elif a > 0.8:  
        return('B')  
    elif a > 0.7:  
        return('C')  
    elif a > 0.6:  
        return('D')  
    else:  
        return('F')  
  
try:  
    a=float(input())  
    print('Enter Score: ',a)  
    print(computegrade(a))  
except ValueError:  
    print('Error')
```

1] ✓ 5.1s

• Error

```
def computegrade(a):  
    if a < 0 or a > 1.0:  
        return('Bad score')  
    elif a > 0.9:  
        return('A')  
    elif a > 0.8:  
        return('B')  
    elif a > 0.7:  
        return('C')  
    elif a > 0.6:  
        return('D')  
    else:  
        return('F')  
  
try:  
    a=float(input())  
    print('Enter Score: ',a)  
    print(computegrade(a))  
except ValueError:  
    print('Error')
```

✓ 2.8s

Enter Score: 0.91
A

```
def computegrade(a):  
    if a < 0 or a > 1.0:  
        return('Bad score')  
    elif a > 0.9:  
        return('A')  
    elif a > 0.8:  
        return('B')  
    elif a > 0.7:  
        return('C')  
    elif a > 0.6:  
        return('D')  
    else:  
        return('F')  
  
try:  
    a=float(input())  
    print('Enter Score: ',a)  
    print(computegrade(a))  
except ValueError:  
    print('Error')
```

✓ 3.9s

Enter Score: 0.89

B


```
def computegrade(a):  
    if a < 0 or a > 1.0:  
        return('Bad score')  
    elif a > 0.9:  
        return('A')  
    elif a > 0.8:  
        return('B')  
    elif a > 0.7:  
        return('C')  
    elif a > 0.6:  
        return('D')  
    else:  
        return('F')  
  
try:  
    a=float(input())  
    print('Enter Score: ',a)  
    print(computegrade(a))  
except ValueError:  
    print('Error')
```

5] ✓ 3.9s

Enter Score: 0.75

C

```
def computegrade(a):  
    if a < 0 or a > 1.0:  
        return('Bad score')  
    elif a > 0.9:  
        return('A')  
    elif a > 0.8:  
        return('B')  
    elif a > 0.7:  
        return('C')  
    elif a > 0.6:  
        return('D')  
    else:  
        return('F')  
  
try:  
    a=float(input())  
    print('Enter Score: ',a)  
    print(computegrade(a))  
except ValueError:  
    print('Error')
```

✓ 3.1s

Enter Score: 0.65

D


```
def computegrade(a):
    if a < 0 or a > 1.0:
        return('Bad score')
    elif a > 0.9:
        return('A')
    elif a > 0.8:
        return('B')
    elif a > 0.7:
        return('C')
    elif a > 0.6:
        return('D')
    else:
        return('F')

try:
    a=float(input())
    print('Enter Score: ',a)
    print(computegrade(a))
except ValueError:
    print('Error')
```

✓ 4.9s

Enter Score: 0.55

F



Lưu đồ giải thuật