


Differentiable Causal Discovery from Interventional Data (DCDI)



Philippe
Brouillard^{*1}



Sébastien
Lachapelle^{*1}



Alexandre
Lacoste²



Simon
Lacoste-Julien¹



Alexandre
Drouin²

¹ Mila & DIRO, Université de Montréal

² Element AI

^{*} Equal contribution

Differentiable Causal Discovery with Interventions (DCDI) is causal discovery algorithm that

- can leverage **perfect**, **imperfect** and **unknown-target** interventions;
- relies on **continuous-constrained optimization** and **neural networks**;
- does not make strong parametric assumptions about the causal mechanisms, thanks to expressive **normalizing flows**;
- is **theoretically grounded**;
- and **compares favorably** to SOTA methods.

Causal graphical models (CGM)


- Random vector $X = (X_1, \dots, X_d)$
- Let \mathcal{G} be a **directed acyclic graph** (DAG)
- \mathcal{G} describes causal relationships between variables.

Example: Kidney stone treatment

$T = \text{Treatment} \in \{A, B\}$

$S = \text{Stone size} \in \{\text{small}, \text{large}\}$

$R = \text{Patient recovered} \in \{0, 1\}$



$$p(S, T, R) = p(S)p(T | S)p(R | S, T)$$

Perfect and Imperfect Interventions

- CGM can model **interventions**, i.e. a localized change in a distribution.

Perfect and Imperfect Interventions

- CGM can model **interventions**, i.e. a localized change in a distribution.


Intervening on the treatment T

T = Treatment $\in \{A, B\}$

S = Stone size $\in \{\text{small}, \text{large}\}$


R = Patient recovered $\in \{0, 1\}$

Observations




$$p(S)p(T | S)p(R | S, T)$$

Perfect intervention



$$p(S)\tilde{p}(T)p(R | S, T)$$

Imperfect intervention



$$p(S)\tilde{p}(T | S)p(R | S, T)$$

Perfect and Imperfect Interventions

- CGM can model **interventions**, i.e. a localized change in a distribution.


Intervening on the treatment T

T = Treatment $\in \{A, B\}$

S = Stone size $\in \{\text{small}, \text{large}\}$


R = Patient recovered $\in \{0, 1\}$

Observations




$$p(S)p(T | S)p(R | S, T)$$

Perfect intervention



$$p(S)\tilde{p}(T)p(R | S, T)$$

Imperfect intervention




$$p(S)\tilde{p}(T | S)p(R | S, T)$$

The ability to model interventions is **crucial to predict the effect of actions/policies** and **requires the causal graph**.

Causal discovery from interventions

But the causal graph might be **unknown**...
Causal discovery = learn the causal graph!



Problem setting and notation

- We observe d variables which are *causally sufficient*, i.e. no hidden confounders.

Problem setting and notation

- We observe d variables which are *causally sufficient*, i.e. no hidden confounders.

$$\text{Causal DAG} = \underbrace{G}_{\text{Adjacency matrix}} = \begin{pmatrix} 0 & 0 & 1 \\ 1 & 0 & 1 \\ 0 & 0 & 0 \end{pmatrix} \in \{0, 1\}^{d \times d}$$

Problem setting and notation

- We observe d variables which are *causally sufficient*, i.e. no hidden confounders.

$$\text{Causal DAG} = \underbrace{G = \begin{pmatrix} 0 & 0 & 1 \\ 1 & 0 & 1 \\ 0 & 0 & 0 \end{pmatrix}}_{\text{Adjacency matrix}} \in \{0, 1\}^{d \times d}$$

- We have K , potentially **imperfect**, interventions which can target multiple variables simultaneously.

$$\underbrace{I = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & 1 \end{pmatrix}}_{\text{Intervention matrix}} \in \{0, 1\}^{K \times d}$$

Problem setting and notation

- We observe d variables which are *causally sufficient*, i.e. no hidden confounders.


$$\text{Causal DAG} = \underbrace{G = \begin{pmatrix} 0 & 0 & 1 \\ 1 & 0 & 1 \\ 0 & 0 & 0 \end{pmatrix}}_{\text{Adjacency matrix}} \in \{0, 1\}^{d \times d}$$

- We have K , potentially **imperfect**, interventions which can target multiple variables simultaneously.


$$\underbrace{I = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & 1 \end{pmatrix}}_{\text{Intervention matrix}} \in \{0, 1\}^{K \times d}$$

- G^* = ground truth causal graph.
- I^* = ground truth intervention matrix.

DCDI: The model




DCDI: The model




DCDI: The model

$$f^{(k)}(x; \mathbf{G}, \mathbf{I}, \phi) := \prod_{j=1}^d \tilde{f}(x_j; \text{NN}(\mathbf{G}_j \odot x; \underbrace{\phi_j^{(1)}}_{\text{Observational parameter}}))^{1-I_{kj}} \tilde{f}(x_j; \text{NN}(\mathbf{G}_j \odot x; \underbrace{\phi_j^{(k)}}_{\text{Interventional parameter}}))^{I_{kj}}$$



DCCI: The model

$$f^{(k)}(x; \mathbf{G}, \mathbf{I}, \phi) := \prod_{j=1}^d \tilde{f}(x_j; \text{NN}(\mathbf{G}_j \odot x; \underbrace{\phi_j^{(1)}}_{\text{Observational parameter}}))^{1-I_{kj}} \tilde{f}(x_j; \text{NN}(\mathbf{G}_j \odot x; \underbrace{\phi_j^{(k)}}_{\text{Interventional parameter}}))^{I_{kj}}$$



DCDI: The score (discrete form)

- We suggest maximizing this score over the space of DAGs G :

$$\mathcal{S}_{I^*}(G) := \sup_{\phi} \sum_{k=1}^K \underbrace{\mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I^*, \phi)}_{k\text{th ground truth intervention}} - \underbrace{\lambda \|G\|_0}_{\text{Sparsity regularization}}$$

- Here, we assume I^* is **known** (we relax this assumption later!).
- We will see later how to relax to a continuous constrained problem.

DCCI: Theoretical justification

- G^* = ground-truth DAG
- I^* = ground-truth intervention matrix

$\hat{G} \in \arg \max_{G \in \text{DAG}} \mathcal{S}_{I^*}(G)$ is the estimator.

Theorem (Identification via score maximization)

Suppose $I_{1,:}^* = 0$. Given that

- 1 Each variable is individually targeted by an intervention;
- 2 The model has enough capacity to express the ground truth;
- 3 The regularization coefficient $\lambda > 0$ is small enough;
- 4 And some more technical assumptions, e.g. I^* -faithfulness... (See paper)

then

$$\hat{G} = G^*.$$

¹We use the notion of I^* -Markov equivalence of [Yang et al., 2018].

DCCI: Theoretical justification

- G^* = ground-truth DAG
- I^* = ground-truth intervention matrix

$\hat{G} \in \arg \max_{G \in \text{DAG}} \mathcal{S}_{I^*}(G)$ is the estimator.

Theorem (Identification via score maximization)

Suppose $I_{1,:}^* = 0$. Given that

- 1 Each variable is individually targeted by an intervention;
- 2 The model has enough capacity to express the ground truth;
- 3 The regularization coefficient $\lambda > 0$ is small enough;
- 4 And some more technical assumptions, e.g. I^* -faithfulness... (See paper)

then

$$\hat{G} = G^*.$$

More general result

Without the first assumption, we can identify the I^* -Markov equivalence class¹ of G^* .

¹We use the notion of I^* -Markov equivalence of [Yang et al., 2018].

DCDI: Continuous-constrained formulation

$$\mathcal{S}_{I^*}(G) := \sup_{\phi} \sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I^*, \phi) - \lambda \|G\|_0$$



Relaxation where $G_{ij} \sim \text{Bernoulli}(\sigma(\Lambda_{ij}))$,
with $\sigma(\cdot) := \text{sigmoid function}$

$$\hat{\mathcal{S}}_{I^*}(\Lambda) := \sup_{\phi} \mathbb{E}_{G \sim \sigma(\Lambda)} \left[\sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I^*, \phi) - \lambda \|G\|_0 \right]$$

DCCI: Continuous-constrained formulation

$$\mathcal{S}_{I^*}(G) := \sup_{\phi} \sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I^*, \phi) - \lambda \|G\|_0$$



Relaxation where $G_{ij} \sim \text{Bernoulli}(\sigma(\Lambda_{ij}))$,
with $\sigma(\cdot) := \text{sigmoid function}$

$$\hat{\mathcal{S}}_{I^*}(\Lambda) := \sup_{\phi} \mathbb{E}_{G \sim \sigma(\Lambda)} \left[\sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I^*, \phi) - \lambda \|G\|_0 \right]$$



Optimize for Λ under acyclicity constraint

$$\sup_{\Lambda} \hat{\mathcal{S}}_{I^*}(\Lambda) \quad \text{s.t.} \quad \underbrace{\text{Tre}^{\sigma}(\Lambda)}_{\text{Acyclicity constraint}} - d = 0$$

[Zheng et al., 2018]

- Optimize jointly Λ and ϕ (NN parameters)

$$\max_{\phi, \Lambda} \mathbb{E}_{G \sim \sigma(\Lambda)} \left[\sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I^*, \phi) - \lambda \|G\|_0 \right] \text{ s.t. } \underbrace{\text{Tre}^{\sigma(\Lambda)} - d = 0}_{\text{Acyclicity constraint}}$$


- Optimized with **RMSprop + augmented Lagrangian method**.

- Optimize jointly Λ and ϕ (NN parameters)


$$\max_{\phi, \Lambda} \mathbb{E}_{G \sim \sigma(\Lambda)} \left[\sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I^*, \phi) - \lambda \|G\|_0 \right] \text{ s.t. } \underbrace{\text{Tre}^{\sigma(\Lambda)} - d = 0}_{\text{Acyclicity constraint}}$$

- Optimized with **RMSprop + augmented Lagrangian method**.
- Gradient w.r.t. Λ estimated via *Gumbel-Softmax Straight-Through estimator* [Jang et al., 2017, Maddison et al., 2017].
- Masks and/or the Gumbel-Softmax estimator were used before in causal discovery:
[Kalainathan et al., 2018, Ng et al., 2019, Bengio et al., 2019, Ke et al., 2019]

DCDI: Optimization



Choice of density function \tilde{f}



- Deep sigmoidal flow [Huang et al., 2018] = a specific kind of **normalizing flow**.
- Gaussian fails to recover the causal direction while the normalizing flow can (Not visible from the plot).

Support for interventions with **unknown targets**

- Up to now we assumed I^* is known, i.e. we knew which variables were targeted.
- What if it is **unknown**? Learn it!

Support for interventions with **unknown targets**

- Up to now we assumed I^* is known, i.e. we knew which variables were targeted.
- What if it is **unknown**? Learn it!

$$\mathcal{S}(\underset{\substack{\text{Intervention matrix} \\ \text{is learned}}}{\underset{\phi}{G}}, \underset{\substack{\text{Additional sparsity} \\ \text{regularizer}}}{I}) := \sup_{\phi} \sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; \underset{\phi}{G}, \underset{\substack{\text{Additional sparsity} \\ \text{regularizer}}}{I}, \phi) - \lambda \|\underset{\phi}{G}\|_0 - \underbrace{\lambda_I \|\underset{\substack{\text{Additional sparsity} \\ \text{regularizer}}}{I}\|_0}_{\text{Additional sparsity regularizer}}$$

Support for interventions with **unknown targets**

- Up to now we assumed I^* is known, i.e. we knew which variables were targeted.
- What if it is **unknown**? Learn it!

$$\mathcal{S}(\underset{\substack{\text{Intervention matrix} \\ \text{is learned}}}{G}, \underset{\substack{\text{Intervention matrix} \\ \text{is learned}}}{I}) := \sup_{\phi} \sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I, \phi) - \lambda \|G\|_0 - \underbrace{\lambda_I \|I\|_0}_{\substack{\text{Additional sparsity} \\ \text{regularizer}}}$$

- We showed the same **theoretical guarantee** holds for this score!

Support for interventions with **unknown targets**

- Up to now we assumed I^* is known, i.e. we knew which variables were targeted.
- What if it is **unknown**? Learn it!


$$\mathcal{S}(\underset{\substack{\text{Intervention matrix} \\ \text{is learned}}}{G}, \underset{\substack{\text{Additional sparsity} \\ \text{regularizer}}}{I}) := \sup_{\phi} \sum_{k=1}^K \mathbb{E}_{X \sim p^{(k)}} \log f^{(k)}(X; G, I, \phi) - \lambda \|G\|_0 - \underbrace{\lambda_I \|I\|_0}_{\text{Additional sparsity regularizer}}$$

- We showed the same **theoretical guarantee** holds for this score!
- Can do the same relaxation $I_{kj} \sim \text{Bernoulli}(\sigma(\beta_{kj}))$.
- Optimize jointly for ϕ , Λ and β .


Experiment summary (lower is better)

DCDI-G = DCDI with Gaussian density
DCDI-DSF = DCDI with deep sigmoidal flow

ANM = nonlinear with additive noise
NN = nonlinear (no additive noise)
e = average number of parents



Known target interventions (20 nodes)



Unknown target interventions (20 nodes)

Conclusion & Future Work

We proposed DCDI, a causal discovery algorithm that:

- is **theoretically grounded**;
- supports **perfect**, **imperfect** and **unknown-target** interventions;
- **scales well with sample size** compared to methods using kernel-based independence tests; and
- **works better for denser graphs** compared to other greedy search methods.

Conclusion & Future Work

We proposed DCDI, a causal discovery algorithm that:

- is **theoretically grounded**;
- supports **perfect**, **imperfect** and **unknown-target** interventions;
- **scales well with sample size** compared to methods using kernel-based independence tests; and
- **works better for denser graphs** compared to other greedy search methods.

Future work:

- Relax **causal sufficiency**, i.e. allow for hidden confounders;
- **Scaling up to larger graphs** (> 100 nodes):
The matrix exponential from the acyclicity constraint costs $\mathcal{O}(d^3)$.

If you want to know more about DCDI:

- Check our paper
- Check our github repo: <https://github.com/slachapelle/dcdi>
- Come talk to us!

References

Bengio, Y., Deleu, T., Rahaman, N., Ke, R., Lachapelle, S., Bilaniuk, O., Goyal, A., & Pal, C. (2019). A meta-transfer objective for learning to disentangle causal mechanisms. *arXiv preprint arXiv:1901.10912*.

Huang, C.-W., Krueger, D., Lacoste, A., & Courville, A. (2018). Neural autoregressive flows.

Jang, E., Gu, S., & Poole, B. (2017). Categorical reparameterization with gumbel-softmax. *Proceedings of the 34th International Conference on Machine Learning*.

Kalainathan, D., Goudet, O., Guyon, I., Lopez-Paz, D., & Sebag, M. (2018). Sam: Structural agnostic model, causal discovery and penalized adversarial learning. *arXiv preprint arXiv:1803.04929*.

Ke, N. R., Bilaniuk, O., Goyal, A., Bauer, S., Larochelle, H., Pal, C., & Bengio, Y. (2019). Learning neural causal models from unknown interventions. *arXiv preprint arXiv:1910.01075*.

Maddison, C. J., Mnih, A., & Teh, Y. W. (2017). The concrete distribution: A continuous relaxation of discrete random variables. *Proceedings of the 34th International Conference on Machine Learning*.

Ng, I., Fang, Z., Zhu, S., Chen, Z., & Wang, J. (2019). Masked gradient-based causal structure learning. *arXiv preprint arXiv:1910.08527*.

Yang, K. D., Katcoff, A., & Uhler, C. (2018). Characterizing and learning equivalence classes of causal DAGs under interventions. *Proceedings of the 35th International Conference on Machine Learning*.

Zheng, X., Aragam, B., Ravikumar, P., & Xing, E. (2018). Dags with no tears: Continuous optimization for structure learning. In *Advances in Neural Information Processing Systems* 31.



Mila

Université
de Montréal

ELEMENT^{AI}